



Defence and Strategic Goods List

made under paragraph 112 (2A) (aa) of the

Customs Act 1901

Compilation No. 6

Compilation date:	8 April 2015
Includes amendments up to:	Defence and Strategic Goods List Amendment Instrument 2015
Registered:	10 April 2015

Prepared by the Office of Parliamentary Counsel, Canberra

About this compilation

This compilation

This is a compilation of the *Defence and Strategic Goods List* that shows the text of the law as amended and in force on 8 April 2015 (the **compilation date**).

This compilation was prepared on 9 April 2015.

The notes at the end of this compilation (the **endnotes**) include information about amending laws and the amendment history of provisions of the compiled law.

Uncommenced amendments

The effect of uncommenced amendments is not shown in the text of the compiled law. Any uncommenced amendments affecting the law are accessible on ComLaw (www.comlaw.gov.au). The details of amendments made up to, but not commenced at, the compilation date are underlined in the endnotes. For more information on any uncommenced amendments, see the series page on ComLaw for the compiled law.

Application, saving and transitional provisions for provisions and amendments

If the operation of a provision or amendment of the compiled law is affected by an application, saving or transitional provision that is not included in this compilation, details are included in the endnotes.

Modifications

If the compiled law is modified by another law, the compiled law operates as modified but the modification does not amend the text of the law. Accordingly, this compilation does not show the text of the compiled law as modified. For more information on any modifications, see the series page on ComLaw for the compiled law.

Self-repealing provisions

If a provision of the compiled law has been repealed in accordance with a provision of the law, details are included in the endnotes.

Contents

Part 1A—Preliminary	1
Division 1—Preliminary	1
1 Name.....	1
2 Authority.....	1
Division 2—Preface	2
Division 3—Notes	3
Division 4—Definitions	5
Division 5—Acronyms and abbreviations	26
Part 1—Munitions list	29
Part 2—Dual-use list	62
Category 0—Nuclear materials, facilities and equipment	64
Category 1—Materials, chemicals, microorganisms and toxins	78
Category 2—Materials processing	126
Category 3—Electronics	164
Category 4—Computers	196
Category 5—Telecommunications and “information security”	202
Category 6—Sensors and lasers	219
Category 7—Navigation and avionics	264
Category 8—Marine	277
Category 9—Aerospace and propulsion	285
Sensitive list of dual-use goods and technologies	304
Very sensitive list of dual-use goods and technologies	319
Part 3—Index	326
Endnotes	421
Endnote 1—About the endnotes	421
Endnote 2—Abbreviation key	422
Endnote 3—Legislation history	423
Endnote 4—Amendment history	424

Part 1A—Preliminary

Division 1—Preliminary

1 Name

This is the *Defence and Strategic Goods List 1996*.

Note: This instrument is the document referred to in the definition of ***defence and strategic goods list*** in subregulation 13E(1) of the *Customs (Prohibited Exports) Regulations 1958*.

2 Authority

This instrument is made under paragraph 112(2A)(aa) of the *Customs Act 1901*.

Division 2—Preface

Goods and technology included in the list may not be exported or supplied from Australia unless a licence or permission has been granted by the Minister or an authorised delegate of the Minister. Brokering of items on the list is also a regulated activity for which a permit must be obtained.

Licences or permissions authorising the exportation of prohibited goods and technology must be produced to a Collector of Customs before exportation: regulation 13E of the *Customs (Prohibited Exports) Regulations 1958*.

Permits authorising the supply of intangible technology and the brokering of listed items are given in accordance with the provisions of the *Defence Trade Controls Act 2012*.

The DSGL was first published in 1996 when the *Customs (Prohibited Exports) Regulations 1958* were consolidated and revised as a result of an Australian National Audit Office review of the Defence export control activity.

The DSGL includes equipment, assemblies and components, associated test, inspection and production equipment, materials, software and technology and is divided into two parts.

PART 1 covers defence and related goods — those goods and technologies designed or adapted for use by armed forces or goods that are inherently lethal. These goods include:

- *Military Goods* — those goods or technology that is designed or adapted for military purposes including parts and accessories thereof.
- *Non Military Lethal Goods (NMLG)* — that equipment that is inherently lethal, incapacitating or destructive such as non-military firearms, non-military ammunition and commercial explosives and initiators.

PART 2 covers those goods that have a dual use. Dual-use goods comprise equipment and technologies developed to meet commercial needs but which may be used either as military components or for the development or production of military systems or weapons of mass destruction. This part is further subdivided into and is made up of the following 10 categories:

- *Category 0* — Nuclear Materials;
- *Category 1* — Materials, Chemicals, Microorganisms and Toxins;
- *Category 2* — Materials Processing;
- *Category 3* — Electronics;
- *Category 4* — Computers;
- *Category 5* — Telecommunications and Information Security;
- *Category 6* — Sensors and Lasers;
- *Category 7* — Navigation and Avionics;
- *Category 8* — Marine;
- *Category 9* — Aerospace and Propulsion.

The DSGL is amended from time to time to reflect changes in the various multilateral non-proliferation and export control regimes of which Australia is a member.

Division 3—Notes

GENERAL NOTES

1. The Notes, Technical Notes and Nota Bene (N.B.) appearing in the Defence and Strategic Goods List form an integral part of the control text.
2. The index at the end of the Defence and Strategic Goods List is provided for guidance only and does not form part of the control text.
3. The object of the controls contained in the Defence and Strategic Goods List should not be defeated by the export of any non-controlled goods (including plant) containing one or more controlled components when the controlled component or components are the principal element of the goods and can feasibly be removed or used for other purposes.
N.B.: In judging whether the controlled component or components are to be considered the principal element, it is necessary to weigh the factors of quantity, value and technological know-how involved and other special circumstances which might establish the controlled component or components as the principal element of the goods being procured.
4. Goods specified in the Defence and Strategic Goods List include both new and used goods.
5. Terms in “quotations” are defined terms. Refer to the “Definitions of Terms” section of the Defence and Strategic Goods List. Words and terms appearing under “Definitions of Terms”, if used in their undefined forms, take their common or dictionary meanings.

PART 1 — MUNITIONS LIST

ML 8

Specially formulated pharmaceutical products containing ML8 materials are not controlled.

ML 10

Absence of items from the Munitions List and absence of configuration for military use would mean that an aircraft would not be considered military.

PART 2 — DUAL-USE GOODS AND TECHNOLOGIES

General Technology Note

The transfer of “technology” according to the General Technology Note, for “production” or “development” of items on this list shall be treated with vigilance.

General Technology Note

Controls on intangible “technology” are to be exercised as far as the scope of legislation† will allow.

General Software Note

The transfer of “software”, for “production” or “development” of items on this list shall be treated with vigilance.

Source Code

Taking into account national practices and legislation[†], Participating States agree that “source code” items are controlled either by “software” or by “software” and “technology” controls, except when such “source code” items are explicitly decontrolled.

Medical equipment

Equipment specially designed for medical end-use that incorporates an item controlled in the Dual-Use List is not controlled.

Category 9

“Development” or “production” “technology” controlled by 9E for gas turbine engines remains controlled when the “technology” is used for repair, rebuild and overhaul. Excluded from control are: technical data, drawings or documentation for maintenance activities directly associated with calibration, removal or replacement of damaged or unserviceable line replaceable units, including replacement of whole engines or engine modules.

[†] *Australia’s export control legislation regulating intangible supplies of “technology” and “software” is the Defence Trade Controls Act 2012 (DTC Act).*

The DTC Act asserts controls over the supply of intangible “technology” to prevent unauthorised supplies from Australia. Controls on the brokering of intangible “technology” are also provided by this legislation.

The Weapons of Mass Destruction (Prevention of Proliferation) Act 1995 captures the supply of intangible technology and the provision of services in circumstances where the technology will or may be used in, or the services will or may assist a Weapons of Mass Destruction (WMD) program.

A WMD program means a plan or program for the development, production, acquisition or stockpiling of nuclear, biological or chemical weapons or missiles capable of delivering such weapons.

The provision of services includes doing anything that confers a benefit on, grants a right or privilege to, provides a facility for, or otherwise assists, someone.

Division 4—Definitions

Definitions of terms between ‘single quotation marks’ are given in a Technical Note to the relevant item.

Definitions of terms between “double quotation marks” are as follows:

Note: Category references are given in brackets after the defined term.

“Accuracy” (2 6), usually measured in terms of inaccuracy, means the maximum deviation, positive or negative, of an indicated value from an accepted standard or true value.

“Active flight control systems” (7) are systems that function to prevent undesirable “aircraft” and missile motions or structural loads by autonomously processing outputs from multiple sensors and then providing necessary preventive commands to effect automatic control.

“Active pixel” (6 8) is a minimum (single) element of the solid state array which has a photoelectric transfer function when exposed to light (electromagnetic) radiation.

“Adapted for use in war” (1 ML7) means any modification or selection (such as altering purity, shelf life, virulence, dissemination characteristics, or resistance to UV radiation) designed to increase the effectiveness in producing casualties in humans or animals, degrading equipment or damaging crops or the environment.

“Adjusted Peak Performance” (4) is an adjusted peak rate at which “digital computers” perform 64-bit or larger floating point additions and multiplications, and is expressed in Weighted TeraFLOPS (WT) with units of 10^{12} adjusted floating point operations per second.

Note: See Category 4, Technical Note.

“Additives” (ML8) means substances used in explosive formulations to improve their properties.

“Aircraft” (1 7 9 ML8 ML9 ML10) means a fixed wing, swivel wing, rotary wing (helicopter), tilt rotor or tilt-wing airborne vehicle.

Note: See also “civil aircraft”.

“All compensations available” (2) means after all feasible measures available to the manufacturer to minimise all systematic positioning errors for the particular machine-tool model are considered.

“Allocated by the ITU” (3 5) means the allocation of frequency bands according to the current edition of the ITU Radio Regulations for primary, permitted and secondary services.

Note: Additional and alternative allocations are not included.

“Angle random walk” (7) means the angular error build up with time that is due to white noise in angular rate. (IEEE STD 528-2001)

“APP” (4) is equivalent to “Adjusted Peak Performance”.

“Asymmetric algorithm” (5) means a cryptographic algorithm using different, mathematically related keys for encryption and decryption.

Note: A common use of “asymmetric algorithms” is key management.

“Automated Command and Control Systems” (ML11) means electronic systems, through which information essential to the effective operation of the grouping, major formation, tactical formation, unit, ship, subunit or weapons under command is entered, processed and transmitted. This is achieved by the use of computer and other specialised hardware designed to support the functions of a military command and control organisation. The main functions of an automated command and control system are: the efficient automated collection, accumulation, storage and processing of information; the display of the situation and the circumstances affecting the preparation and conduct of combat operations; operational and tactical calculations for the allocation of resources among force groupings or elements of the operational order of battle or battle deployment according to the mission or stage of the operation; the preparation of data for appreciation of the situation and decision-making at any point during operation or battle; computer simulation of operations.

“Automatic target tracking” (6) means a processing technique that automatically determines and provides as output an extrapolated value of the most probable position of the target in real time.

“Average output power” (6) means the total “laser” output energy in joules divided by the “laser duration” in seconds.

“Basic gate propagation delay time” (3) means the propagation delay time value corresponding to the basic gate used in a “monolithic integrated circuit”. For a ‘family’ of “monolithic integrated circuits”, this may be specified either as the propagation delay time per typical gate within the given ‘family’ or as the typical propagation delay time per gate within the given ‘family’.

Note 1: “Basic gate propagation delay time” is not to be confused with the input/output delay time of a complex “monolithic integrated circuit”.

Note 2: ‘Family’ consists of all integrated circuits to which all of the following are applied as their manufacturing methodology and specifications except their respective functions:

- a. The common hardware and software architecture;*
- b. The common design and process technology; and*
- c. The common basic characteristics.*

“Basic scientific research” (GTN NTN ML22) means experimental or theoretical work undertaken principally to acquire new knowledge of the fundamental principles of phenomena or observable facts, not primarily directed towards a specific practical aim or objective.

“Bias” (accelerometer) (7) means the average over a specified time of accelerometer output measured at specified operating conditions that has no correlation with input acceleration or rotation. “Bias” is expressed in g or in metres per second squared (g or m/s²). (IEEE STD 528-2001) (Micro g equals 1x10⁻⁶ g).

“Bias” (gyro) (7) means the average over a specified time of gyro output measured at specified operating conditions that has no correlation with input rotation or acceleration. “Bias” is typically expressed in degrees per hour (deg/hr). (IEEE STD 528-2001).

“Biocatalysts” (ML7 ML22) means enzymes for specific chemical or biochemical reactions or other biological compounds which bind to and accelerate the degradation of CW agents.

Technical Note:

‘Enzymes’ means “biocatalysts” for specific chemical or biochemical reactions.

“Biopolymers” (ML7 ML22) means biological macromolecules as follows:

- a. Enzymes for specific chemical or biochemical reactions;
- b. Antibodies, monoclonal, polyclonal or anti-idiotypic;
- c. Specially designed or specially processed receptors;

Technical Notes:

1. *‘Anti-idiotypic antibodies’ means antibodies which bind to the specific antigen binding sites of other antibodies;*
2. *‘Monoclonal antibodies’ means proteins which bind to one antigenic site and are produced by a single clone of cells;*
3. *‘Polyclonal antibodies’ means a mixture of proteins which bind to the specific antigen and are produced by more than one clone of cells;*
4. *‘Receptors’ means biological macromolecular structures capable of binding ligands, the binding of which affects physiological functions.*

“Camming” (2) means axial displacement in one revolution of the main spindle measured in a plane perpendicular to the spindle faceplate, at a point next to the circumference of the spindle faceplate (Reference: ISO 230/1 1986, paragraph 5.63).

“Carbon fibre preforms” (1) means an ordered arrangement of uncoated or coated fibres intended to constitute a framework of a part before the “matrix” is introduced to form a “composite”.

“CE” (4) is equivalent to “computing element”.

“CEP” (circle of equal probability) (7) is a measure of accuracy; the radius of the circle centred at the target, at a specific range, in which 50% of the payloads impact.

“Chemical laser” (6) means a “laser” in which the excited species is produced by the output energy from a chemical reaction.

“Chemical mixture” (1) means a solid, liquid or gaseous product made up of two or more components which do not react together under the conditions under which the mixture is stored.

“Circulation-controlled anti-torque or circulation controlled direction control systems” (7) are systems that use air blown over aerodynamic surfaces to increase or control the forces generated by the surfaces.

“Civil aircraft” (1 7 9 ML10) means those “aircraft” listed by designation in published airworthiness certification lists by the civil aviation authorities to fly commercial civil internal and external routes or for legitimate civil, private or business use.

Note: See also “aircraft”.

“Commingled” (1) means filament to filament blending of thermoplastic fibres and reinforcement fibres in order to produce a fibre reinforcement “matrix” mix in total fibre form.

“Comminution” (1) means a process to reduce a material to particles by crushing or grinding.

“Common channel signalling” (5) is a signalling method in which a single channel between exchanges conveys, by means of labelled messages, signalling information relating to a multiplicity of circuits or calls and other information such as that used for network management.

“Communications channel controller” (4) means the physical interface which controls the flow of synchronous or asynchronous digital information. It is an assembly that can be integrated into computer or telecommunications equipment to provide communications access.

“Compensation systems” (6) consist of the primary scalar sensor, one or more reference sensors (e.g., vector magnetometers) together with software that permit reduction of rigid body rotation noise of the platform.

“Composite” (1 2 6 8 9) means a “matrix” and an additional phase or additional phases consisting of particles, whiskers, fibres or any combination thereof, present for a specific purpose or purposes.

“Compound rotary table” (2) means a table allowing the workpiece to rotate and tilt about two non-parallel axes, which can be coordinated simultaneously for “contouring control”.

“III/V compounds” (3) means polycrystalline or binary or complex monocrystalline products consisting of elements of groups IIIA and VA of Mendeleyev’s periodic classification table (e.g., gallium arsenide, gallium-aluminium arsenide, indium phosphide).

“Computing element” (“CE”) (4) means the smallest computational unit that produces an arithmetic or logic result.

“Contouring control” (2) means two or more “numerically controlled” motions operating in accordance with instructions that specify the next required position and the required feed rates to that position. These feed rates are varied in relation to each other so that a desired contour is generated (ref. ISO/DIS 2806 - 1980).

“Critical temperature” (1 3 6) (sometimes referred to as the transition temperature) of a specific “superconductive” material means the temperature at which the material loses all resistance to the flow of direct electrical current.

“Cryptographic activation” (5) means any technique that activates or enables cryptographic capability, via a secure mechanism that is implemented by the manufacturer of the item and is uniquely bound to the item or customer for which the cryptographic capability is being activated or enabled (e.g., a serial number-based licence key or an authentication instrument such as a digitally signed certificate).

Technical Note:

"Cryptographic activation" techniques and mechanisms may be implemented as hardware, "software" or "technology".

“Cryptography” (5) means the discipline which embodies principles, means and methods for the transformation of data in order to hide its information content, prevent its undetected modification or prevent its unauthorised use. “Cryptography” is limited to the transformation of information using one or more ‘secret parameters’ (e.g., crypto variables) or associated key management.

Note: “Cryptography” does not include fixed data compression or coding techniques.

Technical Note:

‘Secret parameter’: a constant or key kept from the knowledge of others or shared only within a group.

“CW laser” (6) means a “laser” that produces a nominally constant output energy for greater than 0.25 seconds.

“Data-Based Referenced Navigation” (“DBRN”) (7) Systems means systems which use various sources of previously measured geo-mapping data integrated to provide accurate navigation information under dynamic conditions. Data sources include bathymetric maps, stellar maps, gravity maps, magnetic maps or 3-D digital terrain maps.

“Deformable mirrors” (6) (also known as adaptive optic mirrors) means mirrors having:

- a. A single continuous optical reflecting surface which is dynamically deformed by the application of individual torques or forces to compensate for distortions in the optical waveform incident upon the mirror; or
- b. Multiple optical reflecting elements that can be individually and dynamically repositioned by the application of torques or forces to compensate for distortions in the optical waveform incident upon the mirror.

“Depleted uranium” (0) means uranium depleted in the isotope 235 below that occurring in nature.

“Development” (GTN NTN All) is related to all stages prior to serial production, such as: design, design research, design analyses, design concepts, assembly and testing of prototypes, pilot production schemes, design data, process of transforming design data into a product, configuration design, integration design, layouts.

“Diffusion bonding” (1 2 9) means a solid state molecular joining of at least two separate metals into a single piece with a joint strength equivalent to that of the weakest material, wherein the principal mechanism is interdiffusion of atoms across the interface.

“Digital computer” (4 5) means equipment which can, in the form of one or more discrete variables, perform all of the following:

- a. Accept data;
- b. Store data or instructions in fixed or alterable (writable) storage devices;
- c. Process data by means of a stored sequence of instructions which is modifiable; and
- d. Provide output of data.

Note.: Modifications of a stored sequence of instructions include replacement of fixed storage devices, but not a physical change in wiring or interconnections.

“Digital transfer rate” (5) means the total bit rate of the information that is directly transferred on any type of medium.

Note: See also “total digital transfer rate”.

“Direct-acting hydraulic pressing” (2) means a deformation process which uses a fluid-filled flexible bladder in direct contact with the workpiece.

“Discrete component” means a separately packaged “circuit element” with its own external connections.

“Dynamic adaptive routing” (5) means automatic rerouting of traffic based on sensing and analysis of current actual network conditions.

Note: This does not include cases of routing decisions taken on predefined information.

“Effective gram” (1) of “special fissile material” means:

- a. For plutonium isotopes and uranium-233, the isotope weight in grams;
- b. For uranium enriched 1 per cent or greater in the isotope uranium-235, the element weight in grams multiplied by the square of its enrichment expressed as a decimal weight fraction;
- c. For uranium enriched below 1 per cent in the isotope uranium-235, the element weight in grams multiplied by 0.0001

“Electronic assembly” (2 3 4 5) means a number of electronic components (i.e., ‘circuit elements’, ‘discrete components’, integrated circuits, etc.) connected together to perform (a) specific function(s), replaceable as an entity and normally capable of being disassembled.

Note 1: ‘Circuit element’: a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

Note 2: ‘Discrete component’: a separately packaged ‘circuit element’ with its own external connections.

“Electronically steerable phased array antenna” (5 6) means an antenna which forms a beam by means of phase coupling, (i.e., the beam direction is controlled by the complex excitation coefficients of the radiating elements) and the direction of that beam can be varied (both in transmission and reception) in azimuth or in elevation, or both, by application of an electrical signal.

“End-effectors” (2 ML17) means grippers, ‘active tooling units’ and any other tooling that is attached to the baseplate on the end of a “robot” manipulator arm.

Note: ‘Active tooling units’ are devices for applying motive power, process energy or sensing to the workpiece.

“Energetic materials” (ML 4 ML8 ML908 ML909) mean substances or mixtures that react chemically to release energy required for their intended application. “Explosives”, “pyrotechnics” and “propellants” are subclasses of energetic materials.

“Equivalent Density” (6) means the mass of an optic per unit optical area projected onto the optical surface.

“Explosives” (ML8 ML18 ML909) mean solid, liquid or gaseous substances or mixtures of substances which, in their application as primary, booster, or main charges in warheads, demolition and other applications, are required to detonate.

“Expression Vectors” (ML7) mean carriers (e.g., plasmid or virus) used to introduce genetic material into host cells.

“FADEC” is equivalent to “full authority digital engine control”.

“Fault tolerance” (4) is the capability of a computer system, after any malfunction of any of its hardware or “software” components, to continue to operate without human intervention, at a given level of service that provides: continuity of operation, data integrity and recovery of service within a given time.

“Fibrous or filamentary materials” (0 1 2 8) include:

- a. Continuous “monofilaments”;
- b. Continuous “yarns” and “rovings”;
- c. “Tapes”, fabrics, random mats and braids;
- d. Chopped fibres, staple fibres and coherent fibre blankets;
- e. Whiskers, either monocrystalline or polycrystalline, of any length;
- f. Aromatic polyamide pulp.

“Film type integrated circuit” (3) means an array of ‘circuit elements’ and metallic interconnections formed by deposition of a thick or thin film on an insulating “substrate”.

Note: ‘Circuit element’ is a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

“First generation image intensifier tubes” (ML15) means electrostatically focused tubes, employing input and output fibre optic or glass face plates, multi-alkali photocathodes (S-20 or S-25), but not microchannel plate amplifiers.

“Fixed” (5) means that the coding or compression algorithm cannot accept externally supplied parameters (e.g., cryptographic or key variables) and cannot be modified by the user.

“Flight control optical sensor array” (7) is a network of distributed optical sensors, using “laser” beams, to provide real-time flight control data for on-board processing.

“Flight path optimisation” (7) is a procedure that minimises deviations from a four-dimensional (space and time) desired trajectory based on maximising performance or effectiveness for mission tasks.

“Focal plane array” (6) means a linear or two-dimensional planar layer, or combination of planar layers, of individual detector elements, with or without readout electronics, which work in the focal plane.

Note: This definition does not include a stack of single detector elements or any two, three or four element detectors provided time delay and integration is not performed within the element.

“Fractional bandwidth” (3) means the “instantaneous bandwidth” divided by the centre frequency, expressed as a percentage.

“Frequency hopping” (5) means a form of “spread spectrum” in which the transmission frequency of a single communication channel is made to change by a random or pseudo-random sequence of discrete steps.

“Frequency mask trigger” (3), for “signal analysers”, means a mechanism where the trigger function is able to select a frequency range to be triggered on as a subset of the acquisition bandwidth while ignoring other signals that may also be present within the same acquisition bandwidth. A “frequency mask trigger” may contain more than one independent set of limits.

“Frequency switching time” (3) means the time (i.e., delay) taken by a signal when switched from an initial specified output frequency, to arrive at or within $\pm 0.05\%$ of a final specified output frequency. Items having a specified frequency range of less than $\pm 0.05\%$ around their centre frequency are defined to be incapable of frequency switching.

“Frequency synthesiser” (3) means any kind of frequency source or signal generator, regardless of the actual technique used, providing a multiplicity of simultaneous or alternative output frequencies, from one or more outputs, controlled by, derived from or disciplined by a lesser number of standard (or master) frequencies.

“Fuel cell” (8 ML17) means an electrochemical device that converts chemical energy directly into Direct Current (DC) electricity by consuming fuel from an external source.

“Full Authority Digital Engine Control” (“FADEC”) (7 9) means an electronic control system for gas turbine or combined cycle engines utilising a digital computer to control the variables required to regulate engine thrust or shaft power output throughout the engine operating range from the beginning of fuel metering to fuel shutoff.

“Fusible” (1) means capable of being cross-linked or polymerised further (cured) by the use of heat, radiation, catalysts, etc., or that can be melted without pyrolysis (charring).

“Gas Atomisation” (1) means a process to reduce a molten stream of metal alloy to droplets of 500 μm diameter or less by a high pressure gas stream.

“Geographically dispersed” (6) is where each location is distant from any other more than 1,500 m in any direction. Mobile sensors are always considered “geographically dispersed”.

“Guidance set” (7) means systems that integrate the process of measuring and computing a vehicle’s position and velocity (i.e. navigation) with that of computing and sending commands to the vehicle’s flight control systems to correct the trajectory.

“Hot isostatic densification” (2) means the process of pressurising a casting at temperatures exceeding 375 K (102 °C) in a closed cavity through various media (gas, liquid, solid particles, etc.) to create equal force in all directions to reduce or eliminate internal voids in the casting.

“Hybrid computer” (4) means equipment which can perform all of the following:

- a. Accept data;
- b. Process data, in both analogue and digital representations; and
- c. Provide output of data.

“Hybrid integrated circuit” (3) means any combination of integrated circuit(s), or integrated circuit with ‘circuit elements’ or ‘discrete components’ connected together to perform (a) specific function(s), and having all of the following characteristics:

- a. Containing at least one unencapsulated device;

-
- b. Connected together using typical IC production methods;
 - c. Replaceable as an entity; and
 - d. Not normally capable of being disassembled.

Note 1: 'Circuit element': a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

Note 2: 'Discrete component': a separately packaged 'circuit element' with its own external connections.

“Image enhancement” (4) means the processing of externally derived information-bearing images by algorithms such as time compression, filtering, extraction, selection, correlation, convolution or transformations between domains (e.g., fast Fourier transform or Walsh transform). This does not include algorithms using only linear or rotational transformation of a single image, such as translation, feature extraction, registration or false coloration.

“Immunotoxin” (1) is a conjugate of one cell specific monoclonal antibody and a “toxin” or “sub-unit of toxin”, that selectively affects diseased cells.

“In the public domain” (GTN NTN GSN ML22), as it applies herein, means “technology” or “software” which has been made available without restrictions upon its further dissemination (copyright restrictions do not remove “technology” or “software” from being “in the public domain”).

“Information security” (4 5) is all the means and functions ensuring the accessibility, confidentiality or integrity of information or communications, excluding the means and functions intended to safeguard against malfunctions. This includes “cryptography”, ‘cryptanalysis’, protection against compromising emanations and computer security.

Note: 'Cryptanalysis' is the analysis of a cryptographic system or its inputs and outputs to derive confidential variables or sensitive data, including clear text.

“Instantaneous bandwidth” (3 5 7) means the bandwidth over which output power remains constant within 3 dB without adjustment of other operating parameters.

“Instrumented range” (6) means the specified unambiguous display range of a radar.

“Insulation” (9) is applied to the components of a rocket motor, i.e. the case, nozzle, inlets, case closures, and includes cured or semi-cured compounded rubber sheet stock containing an insulating or refractory material. It may also be incorporated as stress relief boots or flaps.

“Interconnected radar sensors” (6) means two or more radar sensors are interconnected when they mutually exchange data in real time.

“Interior lining” (9) is suited for the bond interface between the solid propellant and the case or insulating liner. Usually a liquid polymer based dispersion of refractory or insulating materials, e.g. carbon filled hydroxyl terminated polybutadiene (HTPB) or other polymer with added curing agents sprayed or screeded over a case interior.

“Intrinsic Magnetic Gradiometer” (6) is a single magnetic field gradient sensing element and associated electronics the output of which is a measure of magnetic field gradient.

Note: See also “magnetic gradiometer”.

“Intrusion software” (4) “Software” specially designed or modified to avoid detection by ‘monitoring tools’, or to defeat ‘protective countermeasures’, of a computer or network-capable device, and performing any of the following:

- a. The extraction of data or information, from a computer or network-capable device, or the modification of system or user data; or
- b. The modification of the standard execution path of a program or process in order to allow the execution of externally provided instructions.

Note 1: “Intrusion software” does not include any of the following:

- a. *Hypervisors, debuggers or Software Reverse Engineering (SRE) tools;*
- b. *Digital Rights Management (DRM) “software”; or*
- c. *“Software” designed to be installed by manufacturers, administrators or users, for the purposes of asset tracking or recovery.*

Note 2: Network-capable devices include mobile devices and smart meters.

Technical Notes:

1. *‘Monitoring tools’: “software” or hardware devices, that monitor system behaviours or processes running on a device. This includes antivirus (AV) products, end point security products, Personal Security Products (PSP), Intrusion Detection Systems (IDS), Intrusion Prevention Systems (IPS) or firewalls.*
2. *‘Protective countermeasures’: techniques designed to ensure the safe execution of code, such as Data Execution Prevention (DEP), Address Space Layout Randomisation (ASLR) or sandboxing.*

“Isolated live cultures” (1) includes live cultures in dormant form and in dried preparations.

“Isostatic presses” (2) mean equipment capable of pressurising a closed cavity through various media (gas, liquid, solid particles, etc.) to create equal pressure in all directions within the cavity upon a workpiece or material.

“Laser” (0 2 3 5 6 7 8 9 ML5 ML9 ML19) is an assembly of components which produce both spatially and temporally coherent light that is amplified by stimulated emission of radiation.

*Note: See also: “Chemical laser”;
“Q-switched laser”;
“Super High Power Laser”;
“Transfer laser”.*

“Laser duration” (6) means the time over which a “laser” emits “laser” radiation, which for “pulsed lasers” corresponds to the time over which a single pulse or series of consecutive pulses is emitted.

“Lighter-than-air vehicles” (ML10) mean balloons and airships that rely on hot air or on lighter-than-air gases such as helium or hydrogen for their lift.

“Linearity” (2) (usually measured in terms of non-linearity) means the maximum deviation of the actual characteristic (average of upscale and downscale readings), positive or negative, from a straight line so positioned as to equalise and minimise the maximum deviations.

“Local area network” (4) is a data communication system having all of the following characteristics:

- a. Allows an arbitrary number of independent ‘data devices’ to communicate directly with each other; and
- b. Is confined to a geographical area of moderate size (e.g., office building, plant, campus, warehouse).

Note.: ‘Data device’ means equipment capable of transmitting or receiving sequences of digital information.

“Magnetic Gradiometers” (6) are instruments designed to detect the spatial variation of magnetic fields from sources external to the instrument. They consist of multiple “magnetometers” and associated electronics the output of which is a measure of magnetic field gradient.

Note: See also “intrinsic magnetic gradiometer”.

“Magnetometers” (6) are instruments designed to detect magnetic fields from sources external to the instrument. They consist of a single magnetic field sensing element and associated electronics the output of which is a measure of the magnetic field.

“Main storage” (4) means the primary storage for data or instructions for rapid access by a central processing unit. It consists of the internal storage of a “digital computer” and any hierarchical extension thereto, such as cache storage or non-sequentially accessed extended storage.

“Materials resistant to corrosion by UF₆” (0) may be copper, stainless steel, aluminium, aluminium oxide, aluminium alloys, nickel or alloy containing 60 weight percent or more nickel and UF₆-resistant fluorinated hydrocarbon polymers, as appropriate for the type of separation process.

“Matrix” (1 2 8 9) means a substantially continuous phase that fills the space between particles, whiskers or fibres.

“Measurement uncertainty” (2) is the characteristic parameter which specifies in what range around the output value the correct value of the measurable variable lies with a confidence level of 95 %. It includes the uncorrected systematic deviations, the uncorrected backlash and the random deviations (Reference: ISO 10360-2).

“Mechanical Alloying” (1) means an alloying process resulting from the bonding, fracturing and rebonding of elemental and master alloy powders by mechanical impact. Non-metallic particles may be incorporated in the alloy by addition of the appropriate powders.

“Melt Extraction” (1) means a process to ‘solidify rapidly’ and extract a ribbon-like alloy product by the insertion of a short segment of a rotating chilled block into a bath of a molten metal alloy.

Note: ‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.

“Melt Spinning” (1) means a process to ‘solidify rapidly’ a molten metal stream impinging upon a rotating chilled block, forming a flake, ribbon or rod-like product.

Note: ‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.

“Microcomputer microcircuit” (3) means a “monolithic integrated circuit” or “multichip integrated circuit” containing an arithmetic logic unit (ALU) capable of executing general purpose instructions from an internal storage, on data contained in the internal storage.

Note: The internal storage may be augmented by an external storage.

“Microprocessor microcircuit” (3) means a “monolithic integrated circuit” or “multichip integrated circuit” containing an arithmetic logic unit (ALU) capable of executing a series of general purpose instructions from an external storage.

Note 1: The “microprocessor microcircuit” normally does not contain integral user-accessible storage, although storage present on-the-chip may be used in performing its logic function.

Note 2: This includes chip sets which are designed to operate together to provide the function of a “microprocessor microcircuit”.

“Microprogramme” means a sequence of elementary instructions maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction register.

“Microorganisms” (1 2) means bacteria, viruses, mycoplasmas, rickettsiae, chlamydiae or fungi, whether natural, enhanced or modified, either in the form of isolated live cultures or as material including living material which has been deliberately inoculated or contaminated with such cultures.

“Missiles” (1 3 6 7 9) means complete rocket systems and unmanned aerial vehicle systems, capable of delivering at least 500 kg payload to a range of at least 300 km.

“Monofilament” (1) or filament is the smallest increment of fibre, usually several micrometres in diameter.

“Monolithic integrated circuit” (3) means a combination of passive or active ‘circuit elements’ or both which:

- a. Are formed by means of diffusion processes, implantation processes or deposition processes in or on a single semiconducting piece of material, a so-called ‘chip’;
- b. Can be considered as indivisibly associated; and
- c. Perform the function(s) of a circuit.

Note: ‘Circuit element’ is a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

“Monospectral imaging sensors” (6) are capable of acquisition of imaging data from one discrete spectral band.

“Multichip integrated circuit” (3) means two or more “monolithic integrated circuits” bonded to a common “substrate”.

“Multispectral imaging sensors” (6) are capable of simultaneous or serial acquisition of imaging data from two or more discrete spectral bands. Sensors having more than twenty discrete spectral bands are sometimes referred to as hyperspectral imaging sensors.

“Natural uranium” (0) means uranium containing the mixtures of isotopes occurring in nature.

“Network access controller” (4) means a physical interface to a distributed switching network. It uses a common medium which operates throughout at the same “digital transfer rate” using arbitration (e.g., token or carrier sense) for transmission. Independently from any other, it selects data packets or data groups (e.g., IEEE 802) addressed to it. It is an assembly that can be integrated into computer or telecommunications equipment to provide communications access.

“Neural computer” (4) means a computational device designed or modified to mimic the behaviour of a neuron or a collection of neurons, i.e., a computational device which is distinguished by its hardware capability to modulate the weights and numbers of the interconnections of a multiplicity of computational components based on previous data.

“Nuclear reactor” (0 ML17) means the items within or attached directly to the reactor vessel, the equipment which controls the level of power in the core, and the components which normally contain, come into direct contact with or control the primary coolant of the reactor core.

“Numerical control” (2) means the automatic control of a process performed by a device that makes use of numeric data usually introduced as the operation is in progress (ref. ISO 2382).

“Object code” (GSN) means an equipment executable form of a convenient expression of one or more processes (“source code” (source language)) which has been converted by programming system.

“Optical amplification” (5), in optical communications, means an amplification technique that introduces a gain of optical signals that have been generated by a separate optical source, without conversion to electrical signals, i.e., using semiconductor optical amplifiers, optical fibre luminescent amplifiers.

“Optical computer” (4) means a computer designed or modified to use light to represent data and whose computational logic elements are based on directly coupled optical devices.

“Optical integrated circuit” (3) means a “monolithic integrated circuit” or a “hybrid integrated circuit”, containing one or more parts designed to function as a photosensor or photoemitter or to perform (an) optical or (an) electro-optical function(s).

“Optical switching” (5) means the routing of or switching of signals in optical form without conversion to electrical signals.

“Overall current density” (3) means the total number of ampere-turns in the coil (i.e., the sum of the number of turns multiplied by the maximum current carried by each turn) divided by the total cross-section of the coil (comprising the superconducting filaments, the metallic matrix in which the superconducting filaments are embedded, the encapsulating material, any cooling channels, etc.).

“Peak power” (6), means the highest level of power attained in the “laser duration”.

“Personal area network” (5) means a data communication system having all of the following characteristics:

- a. Allows an arbitrary number of independent or interconnected ‘data devices’ to communicate directly with each other; and

-
- b. Is confined to the communication between devices within the immediate vicinity of an individual person or device controller (e.g., single room, office, or automobile, and their nearby surrounding spaces).

Technical Note:

'Data device' means equipment capable of transmitting or receiving sequences of digital information.

“Personalised smart card” (5) means a smart card containing a microcircuit which has been programmed for a specific application and cannot be reprogrammed for any other application by the user.

“Power management” (7) means changing the transmitted power of the altimeter signal so that received power at the “aircraft” altitude is always at the minimum necessary to determine the altitude.

“Precursors” (ML8) means specialty chemicals used in the manufacture of military explosives.

“Pressure transducers” (2) are devices that convert pressure measurements into an electrical signal.

“Previously separated” (0 1) means the application of any process intended to increase the concentration of the controlled isotope.

“Primary flight control” (7) means an “aircraft” stability or manoeuvring control using force/moment generators, i.e., aerodynamic control surfaces or propulsive thrust vectoring.

“Principal element” (4), as it applies in Category 4, is a “principal element” when its replacement value is more than 35% of the total value of the system of which it is an element. Element value is the price paid for the element by the manufacturer of the system, or by the system integrator. Total value is the normal international selling price to unrelated parties at the point of manufacture or consolidation of shipment.

“Production” (GTN NTN All) means all production phases, such as: construction, production engineering, manufacture, integration, assembly (mounting), inspection, testing, quality assurance.

“Production equipment” (1 7 9) means tooling, templates, jigs, mandrels, moulds, dies, fixtures, alignment mechanisms, test equipment, other machinery and components therefor, limited to those specially designed or modified for “development” or for one or more phases of “production”.

“Production facilities” (7 9) means equipment and specially designed software therefor integrated into installations for “development” or for one or more phases of “production”.

“Program(s)” (2 4 5 6) means a sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer.

“Propellants” (ML8) Substances or mixtures that react chemically to produce large volumes of hot gases at controlled rates to perform mechanical work.

“Pulse compression” (6) means the coding and processing of a radar signal pulse of long time duration to one of short time duration, while maintaining the benefits of high pulse energy.

“Pulse duration” (6) is the duration of a “laser” pulse measured at Full Width Half Intensity (FWHI) levels.

“Pulsed laser” (6) means a “laser” having a “pulse duration” that is less than or equal to 0.25 seconds.

“Pyrotechnic(s)” (ML4 ML8 ML909) means mixtures of solid or liquid fuels and oxidisers which, when ignited, undergo an energetic chemical reaction at a controlled rate intended to produce specific time delays, or quantities of heat, noise, smoke, visible light or infrared radiation. Pyrophorics are a subclass of pyrotechnics, which contain no oxidisers but ignite spontaneously on contact with air.

“Quantum cryptography” (5) means a family of techniques for the establishment of a shared key for “cryptography” by measuring the quantum-mechanical properties of a physical system (including those physical properties explicitly governed by quantum optics, quantum field theory, or quantum electrodynamics).

“Q-switched laser” (6) means a “laser” in which the energy is stored in the population inversion or in the optical resonator and subsequently emitted in a pulse.

“Radar frequency agility” (6) means any technique which changes, in a pseudo-random sequence, the carrier frequency of a pulsed radar transmitter between pulses or between groups of pulses by an amount equal to or larger than the pulse bandwidth.

“Radar spread spectrum” (6) means any modulation technique for spreading energy originating from a signal with a relatively narrow frequency band, over a much wider band of frequencies, by using random or pseudo-random coding.

“Radiant sensitivity” (6) Radiant sensitivity (mA/W) = 0.807 x (wavelength in nm) x Quantum Efficiency (QE)

Technical Note:

QE is usually expressed as a percentage; however, for the purposes of this formula QE is expressed as a decimal number less than one, e.g., 78% is 0.78.

“Real-time bandwidth” (3) for “signal analysers” is the widest frequency range for which the analyser can continuously transform time-domain data entirely into frequency-domain results, using a Fourier or other discrete time transform that processes every incoming time point without gaps or windowing effects that causes a reduction of measured amplitude of more than 3 dB below the actual signal amplitude, while outputting or displaying the transformed data.

“Real time processing” (6 7) means the processing of data by a computer system providing a required level of service, as a function of available resources, within a guaranteed response time, regardless of the load of the system, when stimulated by an external event.

“Repeatability” (7) means the closeness of agreement among repeated measurements of the same variable under the same operating conditions when changes in conditions or non-operating periods occur between measurements. (Reference: IEEE STD 528-2001 (one sigma standard deviation)).

“Required” (GTN 1 9 ML22), as applied to “technology”, refers to only that portion of “technology” which is peculiarly responsible for achieving or extending the controlled performance levels, characteristics or functions. Such “required” “technology” may be shared by different goods.

“Resolution” (2) means the least increment of a measuring device; on digital instruments, the least significant bit (ref. ANSI B-89.1.12).

“Riot control agents” (ML7) mean substances which, under the expected conditions of use for riot control purposes, rapidly produce in humans sensory irritation or disabling physical effects which disappear within a short time following termination of exposure. (Tear gases are a subset of “riot control agents”.)

Technical Note:

Tear gases are a subset of “riot control agents”.

“Robot” (2 8 ML17) means a manipulation mechanism, which may be of the continuous path or of the point-to-point variety, may use sensors, and has all the following characteristics:

- a. Is multifunctional;
- b. Is capable of positioning or orienting material, parts, tools or special devices through variable movements in three dimensional space;
- c. Incorporates three or more closed or open loop servo-devices which may include stepping motors; and
- d. Has “user-accessible programmability” by means of teach/playback method or by means of an electronic computer which may be a programmable logic controller, i.e., without mechanical intervention.

Note: The above definition does not include the following devices:

1. Manipulation mechanisms which are only manually / teleoperator controllable;
2. Fixed sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed stops, such as pins or cams. The sequence of motions and the selection of paths or angles are not variable or changeable by mechanical, electronic or electrical means;
3. Mechanically controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed, but adjustable stops, such as pins or cams. The sequence of motions and the selection of paths or angles are variable within the fixed program pattern. Variations or modifications of the program pattern (e.g., changes of pins or exchanges of cams) in one or more motion axes are accomplished only through mechanical operations;

-
4. *Non-servo-controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is variable but the sequence proceeds only by the binary signal from mechanically fixed electrical binary devices or adjustable stops;*
 5. *Stacker cranes defined as Cartesian coordinate manipulator systems manufactured as an integral part of a vertical array of storage bins and designed to access the contents of those bins for storage or retrieval.*

“Rotary atomisation” (1) means a process to reduce a stream or pool of molten metal to droplets to a diameter of 500 µm or less by centrifugal force.

“Roving” (1) is a bundle (typically 12–120) of approximately parallel ‘strands’.

Note: ‘Strand’ is a bundle of “monofilaments” (typically over 200) arranged approximately parallel.

“Run-out” (2) (out-of-true running) means radial displacement in one revolution of the main spindle measured in a plane perpendicular to the spindle axis at a point on the external or internal revolving surface to be tested (Reference: ISO 230/1-1986, paragraph 5.61).

“Scale factor” (gyro or accelerometer) (7) means the ratio of change in output to a change in the input intended to be measured. Scale factor is generally evaluated as the slope of the straight line that can be fitted by the method of least squares to input-output data obtained by varying the input cyclically over the input range.

“Settling time” (3) means the time required for the output to come within one-half bit of the final value when switching between any two levels of the converter.

“SHPL” (6) is equivalent to “super high power laser”.

“Signal analysers” (3) mean apparatus capable of measuring and displaying basic properties of the single-frequency components of multi-frequency signals.

“Signal processing” (3 4 5 6) means the processing of externally derived information-bearing signals by algorithms such as time compression, filtering, extraction, selection, correlation, convolution or transformations between domains (e.g., fast Fourier transform or Walsh transform).

“Software” (GSN All) means a collection of one or more “programs” or ‘microprograms’ fixed in any tangible medium of expression.

Note: ‘Microprogram’ means a sequence of elementary instructions, maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction into an instruction register.

“Source code” (or source language) (4 6 7 9) is a convenient expression of one or more processes which may be turned by a programming system into equipment executable form (“object code” (or object language)).

“Spacecraft” (7 9) means active and passive satellites and space probes.

“Space qualified” (3 6 7 ML19) refers to products designed, manufactured, or qualified through successful testing, for operation at altitudes greater than 100 km above the surface of the Earth.

Note: A determination that a specific item is “space-qualified” by virtue of testing does not mean that other items in the same production run or model series are “space-qualified” if not individually tested.

“Special fissile material” (0) means plutonium-239, uranium-233, “uranium enriched in the isotopes 235 or 233”, and any material containing the foregoing.

“Specific modulus” (0 1 9) is Young’s modulus in pascals, equivalent to N/m^2 divided by specific weight in N/m^3 , measured at a temperature of $(296 \pm 2) \text{ K}$ ($(23 \pm 2)^\circ\text{C}$) and a relative humidity of $(50 \pm 5)\%$.

“Specific tensile strength” (0 1 9) is ultimate tensile strength in pascals, equivalent to N/m^2 divided by specific weight in N/m^3 , measured at a temperature of $(296 \pm 2) \text{ K}$ ($(23 \pm 2)^\circ\text{C}$) and a relative humidity of $(50 \pm 5)\%$.

“Spinning mass gyros” (7) “Spinning mass gyros” are gyros which use a continually rotating mass to sense angular motion.

“Splat Quenching” (1) means a process to ‘solidify rapidly’ a molten metal stream impinging upon a chilled block, forming a flake-like product.

Note: ‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.

“Spread spectrum” (5) means the technique whereby energy in a relatively narrow-band communication channel is spread over a much wider energy spectrum.

“Spread spectrum” radar (6) — see “Radar spread spectrum”.

“Stability” (7) means the standard deviation (1 sigma) of the variation of a particular parameter from its calibrated value measured under stable temperature conditions. This can be expressed as a function of time.

“States (not) Party to the Chemical Weapon Convention” (1) are those states for which the Convention on the Prohibition of the Development, Production, Stockpiling and Use of Chemical Weapons has (not) entered into force. (See www.opcw.org)

“Substrate” (3) means a sheet of base material with or without an interconnection pattern and on which or within which ‘discrete components’ or integrated circuits or both can be located.

Note 1: ‘Discrete component’: a separately packaged ‘circuit element’ with its own external connections.

Note 2: ‘Circuit element’: a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

“Substrate blanks” (3 6) means monolithic compounds with dimensions suitable for the production of optical elements such as mirrors or optical windows.

“Sub-unit of toxin” (1) is a structurally and functionally discrete component of a whole “toxin”.

“Superalloys” (2 9) mean nickel-, cobalt- or iron-base alloys having strengths superior to any alloys in the AISI 300 series at temperatures over 922 K (649°C) under severe environmental and operating conditions.

“Superconductive” (1 3 6 8 ML18 ML20) means materials, i.e., metals, alloys or compounds, which can lose all electrical resistance, i.e., which can attain infinite electrical conductivity and carry very large electrical currents without Joule heating.

Note: The “superconductive” state of a material is individually characterised by a “critical temperature”, a critical magnetic field, which is a function of temperature, and a critical current density which is, however, a function of both magnetic field and temperature.

“Super High Power Laser” (“SHPL”) (6) means a “laser” capable of delivering (the total or any portion of) the output energy exceeding 1 kJ within 50 ms or having an average or CW power exceeding 20 kW.

“Superplastic forming” (1 2) means a deformation process using heat for metals that are normally characterised by low values of elongation (less than 20%) at the breaking point as determined at room temperature by conventional tensile strength testing, in order to achieve elongations during processing which are at least 2 times those values.

“Symmetric algorithm” (5) means a cryptographic algorithm using an identical key for both encryption and decryption.

Note: A common use of “symmetric algorithms” is confidentiality of data.

“System tracks” (6) means processed, correlated (fusion of radar target data to flight plan position) and updated aircraft flight position report available to the Air Traffic Control centre controllers.

“Systolic array computer” (4) means a computer where the flow and modification of the data is dynamically controllable at the logic gate level by the user.

“Tape” (1) is a material constructed of interlaced or unidirectional “monofilaments”, ‘strands’, ‘rovings’, ‘tows’, or ‘yarns’, etc., usually preimpregnated with resin.

Note: ‘Strand’ is a bundle of “monofilaments” (typically over 200) arranged approximately parallel.

“Technology” (GTN NTN All) means specific information necessary for the “development”, “production” or “use” of a product. This information takes the form of ‘technical data’ or ‘technical assistance’. Controlled “technology” for the Dual-Use List is defined in the General Technology Note and in the Dual-Use List. Controlled “technology” for the Munitions List is specified in ML22.

Note 1: ‘Technical assistance’ may take forms such as instruction, skills, training, working knowledge and consulting services and may involve the transfer of ‘technical data’.

Note 2: ‘Technical data’ may take forms such as blueprints, plans, diagrams, models, formulae, tables, engineering designs and specifications, manuals and instructions written or recorded on other media or devices such as disk, tape, read-only memories.

“Three dimensional integrated circuit” (3) A collection of semiconductor die, integrated together, and having vias passing completely through at least one die to establish interconnections between die.

“Tilting spindle” (2) means a tool-holding spindle which alters, during the machining process, the angular position of its centre line with respect to any other axis.

“Time constant” (6) is the time taken from the application of a light stimulus for the current increment to reach a value of $1-1/e$ times the final value (i.e., 63% of the final value).

“Tip shroud” (9) means a stationary ring component (solid or segmented) attached to the inner surface of the engine turbine casing or a feature at the outer tip of the turbine blade, which primarily provides a gas seal between the stationary and rotating components.

“Total control of flight” (7) means an automated control of “aircraft” state variables and flight path to meet mission objectives responding to real time changes in data regarding objectives, hazards or other “aircraft”.

“Total digital transfer rate” (5) means the number of bits, including line coding, overhead and so forth per unit time passing between corresponding equipment in a digital transmission system.

Note: See also “digital transfer rate”.

“Tow” (1) is a bundle of “monofilaments”, usually approximately parallel.

“Toxins” (1 2) means toxins in the form of deliberately isolated preparations or mixtures, no matter how produced, other than toxins present as contaminants of other materials such as pathological specimens, crops, foodstuffs or seed stocks of “microorganisms”.

“Transfer laser” (6) means a “laser” in which the lasing species is excited through the transfer of energy by collision of a non-lasing atom or molecule with a lasing atom or molecule species.

“Tunable” (6) means the ability of a “laser” to produce a continuous output at all wavelengths over a range of several “laser” transitions. A line selectable “laser” produces discrete wavelengths within one “laser” transition and is not considered “tunable”.

“Unmanned aerial vehicle” (“UAV”) (9) means any “aircraft” capable of initiating flight and sustaining controlled flight and navigation without any human presence on board.

“Uranium enriched in the isotopes 235 or 233” (0) means uranium containing the isotopes 235 or 233, or both, in an amount such that the abundance ratio of the sum of these isotopes to the isotope 238 is more than the ratio of the isotope 235 to the isotope 238 occurring in nature (isotopic ratio 0.71 per cent).

“Use” (GTN NTN All) means operation, installation (including on-site installation), maintenance (checking), repair, overhaul and refurbishing.

“User-accessible programmability” (6) means the facility allowing a user to insert, modify or replace “programs” by means other than:

- a. A physical change in wiring or interconnections; or
- b. The setting of function controls including entry of parameters.

“Vaccine” (1) is a medicinal product in a pharmaceutical formulation licensed by, or having marketing or clinical trial authorisation from, the regulatory authorities of either the country of manufacture or of use, which is intended to stimulate a protective immunological response in humans or animals in order to prevent disease in those to whom or to which it is administered.

“Vacuum Atomisation” (1) means a process to reduce a molten stream of metal to droplets of a diameter of 500 micrometre or less by the rapid evolution of a dissolved gas upon exposure to a vacuum.

“Variable geometry airfoils” (7) means the use of trailing edge flaps or tabs, or leading edge slats or pivoted nose droop, the position of which can be controlled in flight.

“Yarn” (1) is a bundle of twisted ‘strands’.

Note: ‘Strand’ is a bundle of “monofilaments” (typically over 200) arranged approximately parallel.

Division 5—Acronyms and abbreviations

An acronym or abbreviation, when used as a defined term, will be found in the ‘Definitions of Terms’ section.

Acronym or abbreviation	Meaning
ABEC	Annular Bearing Engineers Committee
AGMA	American Gear Manufacturers’ Association
AHRS	attitude and heading reference systems
AISI	American Iron and Steel Institute
ALU	arithmetic logic unit
ANSI	American National Standards Institute
ASNO	Australian Safeguards and Non-proliferation Office
ASTM	the American Society for Testing and Materials
ATC	air traffic control
AVLIS	atomic vapour laser isotope separation
CAD	computer-aided-design
CAS	Chemical Abstracts Service
CASA	Civil Aviation Safety Authority
CCITT	International Telegraph and Telephone Consultative Committee
CDU	control and display unit
CEP	circular error probable
CNTD	controlled nucleation thermal deposition
CRISLA	chemical reaction by isotope selective laser activation.
CVD	chemical vapour deposition
CW	chemical warfare
CW (for lasers)	continuous wave
DEW	directed energy weapon systems
DME	distance measuring equipment
DS	directionally solidified
EB-PVD	electron beam physical vapour deposition
EBU	European Broadcasting Union
ECM	electro-chemical machining
ECR	electron cyclotron resonance
EDM	electrical discharge machines
EEPROMS	electrically erasable programmable read only memory

Acronym or abbreviation	Meaning
EIA	Electronic Industries Association
EMC	electromagnetic compatibility
EMCDB	elastomer modified cast double based propellants
FFT	Fast Fourier Transform
GLONASS	global navigation satellite system
GNSS	global navigation satellite system
GPS	global positioning system
HBT	hetero-bipolar transistors
HDDR	high density digital recording
HEMT	high electron mobility transistors
ICAO	International Civil Aviation Organisation
IEC	International Electro-technical Commission
IEEE	Institute of Electrical and Electronic Engineers
IFOV	instantaneous-field-of-view
ILS	instrument landing system
IRIG	inter-range instrumentation group
ISA	international standard atmosphere
ISAR	inverse synthetic aperture radar
ISO	International Organization for Standardization
ITU	International Telecommunication Union
JIS	Japanese Industrial Standard
JT	Joule-Thomson
LIDAR	light detection and ranging
LRU	line replaceable unit
MAC	message authentication code
Mach	ratio of speed of an object to speed of sound (after Ernst Mach)
MLIS	molecular laser isotopic separation
MLS	microwave landing systems
MOCVD	metal organic chemical vapour deposition
MPEG	Moving Picture Experts Group (ISO/IEC JTC1/SC29/WG11)
MRI	magnetic resonance imaging
MTBF	mean-time-between-failures
MTTF	mean-time-to-failure

Part 1A Preliminary

Division 5 Acronyms and abbreviations

Acronym or abbreviation	Meaning
NBC	Nuclear, Biological and Chemical
NDT	non-destructive test
PAR	precision approach radar
PIN	personal identification number
ppm	parts per million
PSD	power spectral density
QAM	quadrature-amplitude-modulation
RF	radio frequency
RPV	remotely piloted air vehicle
SACMA	Suppliers of Advanced Composite Materials Association
SAR	synthetic aperture radar
SC	single crystal
SLAR	sidelooking airborne radar
SMPTE	Society of Motion Picture and Television Engineers
SRA	shop replaceable assembly
SRAM	static random access memory
SRM	SACMA Recommended Methods
SSB	single sideband
SSR	secondary surveillance radar
TCSEC	trusted computer system evaluation criteria
TIR	total indicated reading
UAV	unmanned aerial vehicle
UTS	ultimate tensile strength
UV	ultraviolet
VOR	very high frequency omni-directional range
YAG	yttrium/aluminium garnet

Part 1—Munitions list

Note 1: Terms in “quotations” are defined terms. Refer to ‘Definitions of Terms used in these Lists’ annexed to this List.

Note 2: In some instances chemicals are listed by name and CAS number. The list applies to chemicals of the same structural formula (including hydrates) regardless of name or CAS number. CAS numbers are shown to assist in identifying a particular chemical or mixture, irrespective of nomenclature. CAS numbers cannot be used as unique identifiers because some forms of the listed chemical have different CAS numbers, and mixtures containing a listed chemical may also have different CAS numbers.

ML1. Smooth-bore weapons with a calibre of less than 20 mm, other arms and automatic weapons with a calibre of 12.7 mm (calibre 0.50 inches) or less and accessories, as follows, and specially designed components therefor:

Note: ML1. does not apply to:

- a. *Firearms specially designed for dummy ammunition and which are incapable of discharging a projectile;*
- b. *Firearms specially designed to launch tethered projectiles having no high explosive charge or communications link, to a range of less than or equal to 500 m.;*
- c. *Weapons using non-centre fire cased ammunition and which are not of the fully automatic firing type.*

- a. Rifles and combination guns, handguns, machine, sub-machine and volley guns;

Note: ML1.a. does not apply to the following:

- a. *Rifles and combination guns, manufactured earlier than 1938;*
- b. *Reproductions of rifles and combination guns the originals of which were manufactured earlier than 1890;*
- c. *Handguns, volley guns and machine guns, manufactured earlier than 1890, and their reproductions.*
- d. *Rifles or handguns, specially designed to discharge an inert projectile by compressed air or CO₂.*

- b. Smooth-bore weapons as follows:

1. Smooth-bore weapons specially designed for military use;
2. Other smooth-bore weapons as follows:
 - a. Fully automatic type weapons;
 - b. Semi-automatic or pump-action type weapons;

Note: ML1.b.2. does not apply to weapons specially designed to discharge an inert projectile by compressed air or CO₂.

Note: ML1.b. does not apply to the following:

- a. *Smooth-bore weapons manufactured earlier than 1938;*
- b. *Reproductions of smooth-bore weapons, the originals of which were manufactured earlier than 1890.*

	<ul style="list-style-type: none"> c. <i>Smooth-bore weapons used for hunting or sporting purposes. These weapons must not be specially designed for military use or of the fully automatic firing type;</i> d. <i>Smooth-bore weapons specially designed for any of the following:</i> <ul style="list-style-type: none"> 1. <i>Slaughtering of domestic animals;</i> 2. <i>Tranquilizing of animals;</i> 3. <i>Seismic testing;</i> 4. <i>Firing of industrial projectiles; or</i> 5. <i>Disrupting Improvised Explosive Devices (IEDs).</i> <p style="margin-left: 40px;"><i>N.B.: For disruptors, see ML4. and 1A006. on the Dual-Use List.</i></p>
	<ul style="list-style-type: none"> c. Weapons using caseless ammunition; d. Detachable cartridge magazines, sound suppressors or moderators, special gun-mountings, optical weapons sights and flash suppressors for arms specified by ML1.a., ML1.b. or ML1.c. <p style="margin-left: 40px;"><i>Note: ML1.d. does not apply to optical weapon sights without electronic image processing, with a magnification of 9 times or less, provided they are not specially designed or modified for military use, or incorporate any reticles specially designed for military use.</i></p>
ML2.	<p>Smooth-bore weapons with a calibre of 20 mm or more, other weapons or armament with a calibre greater than 12.7 mm (calibre 0.50 inches), projectors and accessories, as follows, and specially designed components therefor:</p> <ul style="list-style-type: none"> a. Guns, howitzers, cannon, mortars, anti-tank weapons, projectile launchers, military flame throwers, rifles, recoilless rifles, smooth-bore weapons and signature reduction devices therefor; <p style="margin-left: 40px;"><i>Note 1: ML2.a. includes injectors, metering devices, storage tanks and other specially designed components for use with liquid propelling charges for any of the equipment specified by ML2.a.</i></p> <p style="margin-left: 40px;"><i>Note 2: ML2.a. does not apply to weapons as follows:</i></p> <ul style="list-style-type: none"> a. <i>Rifles, smooth-bore weapons and combination guns, manufactured earlier than 1938;</i> b. <i>Reproductions of rifles, smooth-bore weapons and combination guns, the originals of which were manufactured earlier than 1890;</i> c. <i>Guns, howitzers, cannons, mortars, manufactured earlier than 1890;</i> d. <i>Smooth-bore weapons used for hunting or sporting purposes. These weapons must not be specially designed for military use or of the fully automatic firing type;</i> e. <i>Smooth-bore weapons specially designed for any of the following:</i> <ul style="list-style-type: none"> 1. <i>Slaughtering of domestic animals;</i> 2. <i>Tranquilizing of animals;</i> 3. <i>Seismic testing;</i> 4. <i>Firing of industrial projectiles; or</i>

-
5. *Disrupting Improvised Explosive Devices (IEDs);*
N.B. For disruptors, see ML4. and 1A006. on the Dual-Use List.
- f. *Hand-held projectile launchers specially designed to launch tethered projectiles having no high explosive charge or communications link, to a range of less than or equal to 500 m.*
- b. Smoke, gas and pyrotechnic projectors or generators, specially designed or modified for military use;
Note: ML2.b. does not apply to signal pistols.
- c. Weapons sights and weapon sight mounts, having all of the following:
1. Specially designed for military use; and
 2. Specially designed for weapons specified in ML2.a.;
- d. Mountings specially designed for the weapons specified in ML2.a.
- ML3. Ammunition and fuze setting devices, as follows, and specially designed components therefor:
- a. Ammunition for weapons specified by ML1., ML2. or ML12.;
 - b. Fuze setting devices specially designed for ammunition specified by ML3.a.
- Note 1: Specially designed components specified by ML3. include:*
- a. *Metal or plastic fabrications such as primer anvils, bullet cups, cartridge links, rotating bands and munitions metal parts;*
 - b. *Safing and arming devices, fuzes, sensors and initiation devices;*
 - c. *Power supplies with high one-time operational output;*
 - d. *Combustible cases for charges;*
 - e. *Submunitions including bomblets, minelets and terminally guided projectiles.*
- Note 2: ML3.a. does not apply to any of the following:*
- a. *Ammunition crimped without a projectile (blank star);*
 - b. *Dummy ammunition with a pierced powder chamber;*
 - c. *Other blank and dummy ammunition, not incorporating components designed for live ammunition; or*
 - d. *Components specially designed for blank or dummy ammunition, specified in this Note 2.a., b. or c.*
- Note 3: ML3.a. does not apply to cartridges specially designed for any of the following purposes:*
- a. *Signalling;*
 - b. *Bird scaring; or*
 - c. *Lighting of gas flares at oil wells.*
- ML4. Bombs, torpedoes, rockets, missiles, other explosive devices and charges and related equipment and accessories, as follows, and specially designed components therefor:
- N.B. 1: For guidance and navigation equipment, see ML11.*
- N.B. 2: For Aircraft Missile Protection Systems (AMPS), see ML4.c.*
-

-
- a. Bombs, torpedoes, grenades, smoke canisters, rockets, mines, missiles, depth charges, demolition-charges, demolition-devices, demolition-kits, “pyrotechnic” devices, cartridges and simulators (i.e., equipment simulating the characteristics of any of these items), specially designed for military use;

Note: ML4.a. includes:

- a. Smoke grenades, fire bombs, incendiary bombs and explosive devices;
- b. Missile rocket nozzles and re-entry vehicle nosetips.

- b. Equipment having all of the following:

1. Specially designed for military use; and
2. Specially designed for ‘activities’ relating to any of the following:
 - a. Items specified by ML4.a.; or
 - b. Improvised Explosive Devices (IEDs).

Technical Note:

For the purpose of ML4.b.2., ‘activities’ applies to handling, launching, laying, controlling, discharging, detonating, activating, powering with one-time operational output, decoying, jamming, sweeping, detecting, disrupting or disposing.

Note 1: ML4.b. includes:

- a. Mobile gas liquefying equipment capable of producing 1,000 kg or more per day of gas in liquid form;
- b. Buoyant electric conducting cable suitable for sweeping magnetic mines.

Note 2: ML4.b. does not apply to hand-held devices limited by design solely to the detection of metal objects and incapable of distinguishing between mines and other metal objects.

- c. Aircraft Missile Protection Systems (AMPS).

Note: ML4.c. does not apply to AMPS having all of the following:

- a. Any of the following missile warning sensors:
 1. Passive sensors having peak response between 100-400 nm; or
 2. Active pulsed Doppler missile warning sensors;
- b. Countermeasures dispensing systems;
- c. Flares, which exhibit both a visible signature and an infrared signature, for decoying surface-to-air missiles; and
- d. Installed on “civil aircraft” and having all of the following:
 1. The AMPS is only operable in a specific “civil aircraft” in which the specific AMPS is installed and for which any of the following has been issued:
 - a. A civil Type Certificate; or
 - b. An equivalent document recognised by the International Civil Aviation Organisation (ICAO);
 2. The AMPS employs protection to prevent unauthorised access to “software”; and

-
3. *The AMPS incorporates an active mechanism that forces the system not to function when it is removed from the “civil aircraft” in which it was installed.*

ML5. Fire control, and related alerting and warning equipment, and related systems, test and alignment and countermeasure equipment, as follows, specially designed for military use, and specially designed components and accessories therefor:

- a. Weapon sights, bombing computers, gun laying equipment and weapon control systems;
- b. Target acquisition, designation, range-finding, surveillance or tracking systems; detection, data fusion, recognition or identification equipment; and sensor integration equipment;
- c. Countermeasure equipment for items specified by ML5.a. or ML5.b.;

Note: For the purposes of ML5.c., countermeasure equipment includes detection equipment.

- d. Field test or alignment equipment, specially designed for items specified by ML5.a., ML5.b. or ML5.c.

ML6. Ground vehicles and components, as follows:

N.B.: For guidance and navigation equipment, see ML11.

- a. Ground vehicles and components therefor, specially designed or modified for military use;

Technical Note:

For the purposes of ML6.a. the term ground vehicles includes trailers.

- b. Other ground vehicles and components, as follows:
 - 1. Vehicles having all of the following:
 - a. Manufactured or fitted with materials or components to provide ballistic protection to level III (NIJ 0108.01, September 1985, or comparable national standard) or better;
 - b. A transmission to provide drive to both front and rear wheels simultaneously, including those vehicles having additional wheels for load bearing purposes whether driven or not;
 - c. Gross Vehicle Weight Rating (GVWR) greater than 4,500 kg; and
 - d. Designed or modified for off-road use;
 - 2. Components having all of the following:
 - a. Specially designed for vehicles specified in ML6.b.1.; and
 - b. Providing ballistic protection to level III (NIJ 0108.01, September 1985, or comparable national standard) or better.

N.B. See also ML13.a.

Note 1: ML6.a. includes:

- a. *Tanks and other military armed vehicles and military vehicles fitted with mountings for arms or equipment for mine laying or the launching of munitions specified by ML4;*
 - b. *Armoured vehicles;*
-

-
- c. *Amphibious and deep water fording vehicles;*
 - d. *Recovery vehicles and vehicles for towing or transporting ammunition or weapon systems and associated load handling equipment.*

Note 2: Modification of a ground vehicle for military use specified by ML6.a. entails a structural, electrical or mechanical change involving one or more components that are specially designed for military use. Such components include:

- a. *Pneumatic tyre casings of a kind specially designed to be bullet-proof;*
- b. *Armoured protection of vital parts, (e.g. fuel tanks or vehicle cabs);*
- c. *Special reinforcements or mountings for weapons;*
- d. *Black-out lighting.*

Note 3: ML6. does not apply to civil vehicles designed or modified for transporting money or valuables.

Note 4: ML6. does not apply to vehicles that meet all of the following:

- a. *Were manufactured before 1946;*
- b. *Do not have items specified by the Munitions List and manufactured after 1945, except for reproductions of original components or accessories for the vehicle; and*
- c. *Do not incorporate weapons specified in ML1., ML2. or ML4. unless they are inoperable and incapable of discharging a projectile.*

ML7. Chemical or biological toxic agents, “riot control agents”, radioactive materials, related equipment, components and materials, as follows:

- a. Biological agents and radioactive materials “adapted for use in war” to produce casualties in humans or animals, degrade equipment or damage crops or the environment;
- b. Chemical warfare (CW) agents, including:
 - 1. CW nerve agents:
 - a. O-Alkyl (equal to or less than C₁₀, including cycloalkyl) alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) - phosphonofluoridates, such as:
 - 1. Sarin (GB):O-Isopropyl methylphosphonofluoridate (CAS 107-44-8); and
 - 2. Soman (GD):O-Pinacolyl methylphosphonofluoridate (CAS 96-64-0);
 - b. O-Alkyl (equal to or less than C₁₀, including cycloalkyl) N,N-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphoramidocyanidates, such as:
 - 1. Tabun (GA):O-Ethyl N,N-dimethylphosphoramidocyanidate (CAS 77-81-6);

-
- c. O-Alkyl (H or equal to or less than C₁₀, including cycloalkyl) S-2-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-aminoethyl alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphonothiolates and corresponding alkylated and protonated salts, such as:
 - 1. VX: O-Ethyl S-2-diisopropylaminoethyl methyl phosphonothiolate (CAS 50782-69-9);
 - 2. CW vesicant agents:
 - a. Sulphur mustards, such as:
 - 1. 2-Chloroethylchloromethylsulphide (CAS 2625-76-5);
 - 2. Bis(2-chloroethyl) sulphide (CAS 505-60-2);
 - 3. Bis(2-chloroethylthio) methane (CAS 63869-13-6);
 - 4. 1,2-bis (2-chloroethylthio) ethane (CAS 3563-36-8);
 - 5. 1,3-bis (2-chloroethylthio) -n-propane (CAS 63905-10-2);
 - 6. 1,4-bis (2-chloroethylthio) -n-butane (CAS 142868-93-7);
 - 7. 1,5-bis (2-chloroethylthio) -n-pentane (CAS 142868-94-8);
 - 8. Bis (2-chloroethylthiomethyl) ether (CAS 63918-90-1);
 - 9. Bis (2-chloroethylthioethyl) ether (CAS 63918-89-8);
 - b. Lewisites, such as:
 - 1. 2-chlorovinylchloroarsine (CAS 541-25-3);
 - 2. Tris (2-chlorovinyl) arsine (CAS 40334-70-1);
 - 3. Bis (2-chlorovinyl) chloroarsine (CAS 40334-69-8);
 - c. Nitrogen mustards, such as:
 - 1. HN1: bis (2-chloroethyl) ethylamine (CAS 538-07-8);
 - 2. HN2: bis (2-chloroethyl) methylamine (CAS 51-75-2);
 - 3. HN3: tris (2-chloroethyl) amine (CAS 555-77-1);
 - 3. CW incapacitating agents, such as:
 - a. 3-Quinuclidinyl benzilate (BZ) (CAS 6581-06-2);
 - 4. CW defoliants, such as:
 - a. Butyl 2-chloro-4-fluorophenoxyacetate (LNF);
 - b. 2,4,5-trichlorophenoxyacetic acid (CAS 93-76-5) mixed with 2,4-dichlorophenoxyacetic acid (CAS 94-75-7) (Agent Orange (CAS 39277-47-9));
 - c. CW binary precursors and key precursors, as follows:
 - 1. Alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) Phosphonyl Difluorides, such as: DF: Methyl Phosphonyldifluoride (CAS 676-99-3);
 - 2. O-Alkyl (H or equal to or less than C₁₀, including cycloalkyl) O-2-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-aminoethyl alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphonites and corresponding alkylated and protonated salts, such as:
 - QL: O-Ethyl O-2-di-isopropylaminoethyl methylphosphonite (CAS 57856-11-8);
 - 3. Chlorosarin: O-Isopropyl methylphosphonochloridate (CAS 1445-76-7);
 - 4. Chlorosoman: O-Pinacolyl methylphosphonochloridate (CAS 7040-57-5);
-

-
- d. “Riot control agents”, active constituent chemicals and combinations thereof, including:
1. α -Bromobenzeneacetonitrile, (Bromobenzyl cyanide) (CA) (CAS 5798-79-8);
 2. [(2-chlorophenyl) methylene] propanedinitrile, (o-Chlorobenzylidenemalononitrile) (CS) (CAS 2698-41-1);
 3. 2-Chloro-1-phenylethanone, Phenylacetyl chloride (ω -chloroacetophenone) (CN) (CAS 532-27-4);
 4. Dibenz-(b,f)-1,4-oxazepine, (CR) (CAS 257-07-8);
 5. 10-Chloro-5,10-dihydrophenarsazine, (Phenarsazine chloride), (Adamsite), (DM) (CAS 578-94-9);
 6. N-Nonanoylmorpholine, (MPA) (CAS 5299-64-9);
- Note 1: ML7.d. does not apply to “riot control agents” individually packaged for personal self defence purposes.*
- Note 2: ML7.d. does not apply to active constituent chemicals, and combinations thereof, identified and packaged for food production or medical purposes.*
- e. Equipment, specially designed or modified for military use, designed or modified for the dissemination of any of the following, and specially designed components therefor:
1. Materials or agents specified by ML7.a., ML7.b. or ML7.d.; or
 2. CW agents made up of precursors specified by ML7.c.;
- f. Protective and decontamination equipment, specially designed or modified for military use, components and chemical mixtures, as follows:
1. Equipment designed or modified for defence against materials specified by ML7.a., ML7.b. or d., and specially designed components therefor;
 2. Equipment designed or modified for decontamination of objects contaminated with materials specified by ML7.a. or ML7.b., and specially designed components therefor;
 3. Chemical mixtures specially developed or formulated for the decontamination of objects contaminated with materials specified by ML7.a. or ML7.b.;
- Note: ML7.f.1. includes:*
- a. *Air conditioning units specially designed or modified for nuclear, biological or chemical filtration;*
 - b. *Protective clothing.*
- N.B.: For civil gas masks, protective and decontamination equipment, see also I.A.4. on the Dual-Use List.*
- g. Equipment, specially designed or modified for military use designed or modified for the detection or identification of materials specified by ML7.a., ML7.b. or ML7.d., and specially designed components therefor;
- Note: ML7.g. does not apply to personal radiation monitoring dosimeters.*
-

N.B.: See also 1A004 on the Dual-Use List.

- h. “Biopolymers” specially designed or processed for the detection or identification of CW agents specified by ML7.b., and the cultures of specific cells used to produce them;
- i. “Biocatalysts” for the decontamination or degradation of CW agents, and biological systems therefor, as follows:
 - 1. “Biocatalysts” specially designed for the decontamination or degradation of CW agents specified by ML7.b., and resulting from directed laboratory selection or genetic manipulation of biological systems;
 - 2. Biological systems containing the genetic information specific to the production of “biocatalysts” specified by ML7.i.1., as follows:
 - a. “Expression vectors”;
 - b. Viruses;
 - c. Cultures of cells.

Note 1: ML7.b. and ML7.d. do not apply to the following:

- a. Cyanogen chloride (CAS 506-77-4);
- b. Hydrocyanic acid (CAS 74-90-8);
- c. Chlorine (CAS 7782-50-5);
- d. Carbonyl chloride (phosgene) (CAS 75-44-5);
- e. Diphosgene (trichloromethyl-chloroformate) (CAS 503-38-8);
- f. Not used since 2004
- g. Xylyl bromide, ortho: (CAS 89-92-9), meta: (CAS 620-13-3), para: (CAS 104-81-4);
- h. Benzyl bromide (CAS 100-39-0);
- i. Benzyl iodide (CAS 620-05-3);
- j. Bromo acetone (CAS 598-31-2);
- k. Cyanogen bromide (CAS 506-68-3);
- l. Bromo methylethylketone (CAS 816-40-0);
- m. Chloro acetone (CAS 78-95-5);
- n. Ethyl iodoacetate (CAS 623-48-3);
- o. Iodo acetone (CAS 3019-04-3);
- p. Chloropicrin (CAS 76-06-2).

Note 2: The cultures of cells and biological systems specified by ML7.h. and ML7.i.2. are exclusive and these sub-items do not apply to cells or biological systems for civil purposes, such as agricultural, pharmaceutical, medical, veterinary, environmental, waste management, or in the food industry.

ML8. “Energetic materials” and related substances, as follows:

N.B. 1: See also 1C011 on the Dual-Use List.

N.B. 2: For charges and devices, see ML4 and 1A008 on the Dual-Use List.

Technical Notes:

- 1. *For the purposes of ML8., mixture refers to a composition of two or more substances with at least one substance being listed in the ML8 sub-items.*

-
2. *Any substance listed in the ML8 sub-items is subject to this list, even when utilised in an application other than that indicated. (e.g., TAGN is predominantly used as an explosive but can also be used either as a fuel or an oxidiser.)*
 3. *For the purposes of ML8, particle size is the mean particle diameter on a weight or volume basis. International or equivalent national standards will be used in sampling and determining particle size.*
 - a. “Explosives” as follows, and mixtures thereof:
 1. ADNBF (aminodinitrobenzofuroxan or 7-amino-4,6-dinitrobenzofurazane-1-oxide) (CAS 97096-78-1);
 2. BNCP (cis-bis (5-nitrotetrazolato) tetra amine-cobalt (III) perchlorate) (CAS 117412-28-9);
 3. CL-14 (diamino dinitrobenzofuroxan or 5,7-diamino-4,6-dinitrobenzofurazane-1-oxide) (CAS 117907-74-1);
 4. CL-20 (HNIW or Hexanitrohexaazaisowurtzitane) (CAS 135285-90-4); chlathrates of CL-20 (see also ML8.g.3. and g.4. for its “precursors”);
 5. CP (2-(5-cyanotetrazolato) penta amine-cobalt (III) perchlorate) (CAS 70247-32-4);
 6. DADE (1,1-diamino-2,2-dinitroethylene, FOX7) (CAS 145250-81-3);
 7. DATB (diaminotrinitrobenzene) (CAS 1630-08-6);
 8. DDFP (1,4-dinitrodifurazanopiperazine);
 9. DDPO (2,6-diamino-3,5-dinitropyrazine-1-oxide, PZO) (CAS 194486-77-6);
 10. DIPAM (3,3'-diamino-2,2',4,4',6,6'-hexanitrobiphenyl or dipicramide) (CAS 17215-44-0);
 11. DNGU (DINGU or dinitroglycoluril) (CAS 55510-04-8);
 12. Furazans as follows:
 - a. DAAOF (diaminoazoxyfurazan);
 - b. DAAzF (diaminoazofurazan) (CAS 78644-90-3);
 13. HMX and derivatives (see also ML8.g.5. for its “precursors”), as follows:
 - a. HMX (Cyclotetramethylenetetranitramine, octahydro-1,3,5,7-tetranitro-1,3,5,7-tetrazine, 1,3,5,7-tetranitro-1,3,5,7-tetraza-cyclooctane, octogen or octogene) (CAS 2691-41-0);
 - b. difluoroaminated analogs of HMX;
 - c. K-55 (2,4,6,8-tetranitro-2,4,6,8-tetraazabicyclo [3,3,0]-octanone-3, tetranitrosemiglycouril or keto-bicyclic HMX) (CAS 130256-72-3);
 14. HNAD (hexanitroadamantane) (CAS 143850-71-9);
 15. HNS (hexanitrostilbene) (CAS 20062-22-0);
 16. Imidazoles as follows:
 - a. BNNII (Octahydro-2,5-bis(nitroimino)imidazo [4,5-d]imidazole);
 - b. DNI (2,4-dinitroimidazole) (CAS 5213-49-0);
-

-
- c. FDIA (1-fluoro-2,4-dinitroimidazole);
 - d. NTDNIA (N-(2-nitrotriazolo)-2,4-dinitroimidazole);
 - e. PTIA (1-picryl-2,4,5-trinitroimidazole);
 - 17. NTNMH (1-(2-nitrotriazolo)-2-dinitromethylene hydrazine);
 - 18. NTO (ONTA or 3-nitro-1,2,4-triazol-5-one) (CAS 932-64-9);
 - 19. Polynitrocubanes with more than four nitro groups;
 - 20. PYX (2,6-Bis(picrylamino)-3,5-dinitropyridine) (CAS 38082-89-2);
 - 21. RDX and derivatives, as follows:
 - a. RDX (cyclotrimethylenetrinitramine, cyclonite, T4, hexahydro-1,3,5-trinitro-1,3,5-triazine, 1,3,5-trinitro-1,3,5-triaza-cyclohexane, hexogen or hexogene) (CAS 121-82-4);
 - b. Keto-RDX (K-6 or 2,4,6-trinitro-2,4,6-triazacyclohexanone) (CAS 115029-35-1);
 - 22. TAGN (triaminoguanidinenitrate) (CAS 4000-16-2);
 - 23. TATB (triaminotrinitrobenzene) (CAS 3058-38-6) (see also ML8.g.7 for its “precursors”);
 - 24. TEDDZ (3,3,7,7-tetrakis(difluoroamine) octahydro-1,5-dinitro-1,5-diazocine);
 - 25. Tetrazoles as follows:
 - a. NTAT (nitrotriazol aminotetrazole);
 - b. NTNT (1-N-(2-nitrotriazolo)-4-nitrotetrazole);
 - 26. Tetryl (trinitrophenylmethylnitramine) (CAS 479-45-8);
 - 27. TNAD (1,4,5,8-tetranitro-1,4,5,8-tetraazadecalin) (CAS 135877-16-6) (see also ML8.g.6. for its “precursors”);
 - 28. TNAZ (1,3,3-trinitroazetidine) (CAS 97645-24-4) (see also ML8.g.2. for its “precursors”);
 - 29. TNGU (SORGUYL or tetranitroglycoluril) (CAS 55510-03-7);
 - 30. TNP (1,4,5,8-tetranitro-pyridazino[4,5-d]pyridazine) (CAS 229176-04-9);
 - 31. Triazines as follows:
 - a. DNAM (2-oxy-4,6-dinitroamino-s-triazine) (CAS 19899-80-0);
 - b. NNHT (2-nitroimino-5-nitro-hexahydro-1,3,5-triazine) (CAS 130400-13-4);
 - 32. Triazoles as follows:
 - a. 5-azido-2-nitrotriazole;
 - b. ADHTDN (4-amino-3,5-dihydrazino-1,2,4-triazole dinitramide) (CAS 1614-08-0);
 - c. ADNT (1-amino-3,5-dinitro-1,2,4-triazole);
 - d. BDNTA ([bis-dinitrotriazole]amine);
 - e. DBT (3,3'-dinitro-5,5-bi-1,2,4-triazole) (CAS 30003-46-4);
 - f. DNBT (dinitrobistriazole) (CAS 70890-46-9);
 - g. NTDNA (2-nitrotriazole 5-dinitramide) (CAS 75393-84-9);
 - h. NTDNT (1-N-(2-nitrotriazolo) 3,5-dinitrotriazole);
 - i. PDNT (1-picryl-3,5-dinitrotriazole);
-

-
- j. TACOT (tetranitrobenzotriazolobenzotriazole) (CAS 25243-36-1);
 - 33. Explosives not listed elsewhere in ML8.a. and having any of the following:
 - a. Detonation velocity exceeding 8,700 m/s, at maximum density; or
 - b. Detonation pressure exceeding 34 GPa (340 kbar);
 - 34. Not used;
 - 35. DNAN (2,4-dinitroanisole) (CAS 119-27-7);
 - 36. TEX (4,10-Dinitro-2,6,8,12-tetraoxa-4,10-diazaisowurtzitane)
 - 37. GUDN (Guanylurea dinitramide) FOX-12 (CAS 217464-38-5)
 - 38. Tetrazines as follows:
 - a. BTAT (Bis(2,2,2-trinitroethyl)-3,6-diaminotetrazine);
 - b. LAX-112 (3,6-diamino-1,2,4,5-tetrazine-1,4-dioxide);
 - 39. Energetic ionic materials melting between 343 K (70°C) and 373 K (100°C) and with detonation velocity exceeding 6,800 m/s or detonation pressure exceeding 18 GPa (180 kbar);
 - b. "Propellants" as follows:
 - 1. Any solid "propellant" with a theoretical specific impulse (under standard conditions) of more than:
 - a. 240 seconds for non-metallized, non-halogenized "propellant";
 - b. 250 seconds for non-metallized, halogenized "propellant"; or
 - c. 260 seconds for metallized "propellant";
 - 2. Not used;
 - 3. "Propellants" having a force constant of more than 1,200 kJ/kg;
 - 4. "Propellants" that can sustain a steady-state linear burning rate of more than 38 mm/s under standard conditions (as measured in the form of an inhibited single strand) of 6.89 MPa (68.9 bar) pressure and 294K (21°C);
 - 5. Elastomer Modified Cast Double Base (EMCDB) "propellants" with extensibility at maximum stress of more than 5% at 233K (-40°C);
 - 6. Any "propellant" containing substances specified by ML8.a.;
 - 7. "Propellants", not specified elsewhere in the Munitions List, specially designed for military use;
 - c. "Pyrotechnics", fuels and related substances, as follows, and mixtures thereof:
 - 1. Aircraft fuels specially formulated for military purposes;

Note: Aircraft fuels specified by ML8.c.1. are finished products, not their constituents.
 - 2. Alane (aluminum hydride) (CAS 7784-21-6);
 - 3. Carboranes; decaborane (CAS 17702-41-9); pentaboranes (CAS 19624-22-7 and 18433-84-6) and their derivatives;
 - 4. Hydrazine and derivatives, as follows (see also ML8.d.8. and d.9. for oxidising hydrazine derivatives):
 - a. Hydrazine (CAS 302-01-2) in concentrations of 70% or more;
-

- b. Monomethyl hydrazine (CAS 60-34-4);
- c. Symmetrical dimethyl hydrazine (CAS 540-73-8);
- d. Unsymmetrical dimethyl hydrazine (CAS 57-14-7);

Note: ML8.c.4.a. does not apply to hydrazine 'mixtures' specially formulated for corrosion control.

5. Metal fuels, fuel mixtures or "pyrotechnic" mixtures, in particle form whether spherical, atomized, spheroidal, flaked or ground, manufactured from material consisting of 99 % or more of any of the following:
 - a. Metals as follows and mixtures thereof:
 1. Beryllium (CAS 7440-41-7) in particle sizes of less than 60 µm;
 2. Iron powder (CAS 7439-89-6) with particle size of 3 µm or less produced by reduction of iron oxide with hydrogen;
 - b. Mixtures containing any of the following:
 1. Zirconium (CAS 7440-67-7), magnesium (CAS 7439-95-4) or alloys of these in particle sizes of less than 60 µm; or
 2. Boron (CAS 7440-42-8) or boron carbide (CAS 12069-32-8) fuels of 85% purity or higher and particle sizes of less than 60 µm;

Note 1: ML8.c.5 applies to explosives and fuels, whether or not the metals or alloys are encapsulated in aluminium, magnesium, zirconium, or beryllium.

Note 2: ML8.c.5.b. only applies to metal fuels in particle form when they are mixed with other substances to form a mixture formulated for military purposes such as liquid propellant slurries, solid propellants, or pyrotechnic mixtures.

Note 3: ML8.c.5.b.2. does not apply to boron and boron carbide enriched with boron-10 (20% or more of total boron-10 content.)

6. Military materials, containing thickeners for hydrocarbon fuels, specially formulated for use in flame throwers or incendiary munitions, such as metal stearates (e.g., octal (CAS 637-12-7)) or palmitates;
7. Perchlorates, chlorates and chromates, composited with powdered metal or other high energy fuel components;
8. Spherical aluminium powder (CAS 7429-90-5) with a particle size of 60 µm or less, manufactured from material with an aluminium content of 99% or more;
9. Titanium subhydride (TiH_n) of stoichiometry equivalent to $n=0.65-1.68$;
10. Liquid high energy density fuels not specified in ML8.c.1., as follows:
 - a. Mixed fuels, that incorporate both solid and liquid fuels (e.g., boron slurry), having a mass-based energy density of 40 MJ/kg or greater;

-
- b. Other high energy density fuels and fuel additives (e.g., cubane, ionic solutions, JP-7, JP-10), having a volume-based energy density of 37.5 GJ per cubic meter or greater, measured at 293 K (20°C) and one atmosphere (101.325 kPa) pressure;
 - Note: ML8.c.10.b. does not apply to JP-4, JP-8, fossil refined fuels or biofuels, or fuels for engines certified for use in civil aviation.*
 - 11. “Pyrotechnic” and pyrophoric materials as follows:
 - a. “Pyrotechnic” or pyrophoric materials specifically formulated to enhance or control the production of radiated energy in any part of the IR spectrum;
 - b. Mixtures of magnesium, polytetrafluoroethylene (PTFE) and a vinylidene difluoride-hexafluoropropylene copolymer (e.g., MTV);
 - 12. Fuel mixtures, “pyrotechnic” mixtures or “energetic materials”, not specified elsewhere in ML8, having all of the following:
 - a. Containing greater than 0.5% of particles of any of the following:
 - 1. Aluminium;
 - 2. Beryllium;
 - 3. Boron;
 - 4. Zirconium;
 - 5. Magnesium; or
 - 6. Titanium;
 - b. Particles specified by ML8.c.12.a. with a size less than 200 nm in any direction; and
 - c. Particles specified by ML8.c.12.a. with a metal content of 60% or greater;
 - d. Oxidisers as follows, and mixtures thereof:
 - 1. ADN (ammonium dinitramide or SR 12) (CAS 140456-78-6);
 - 2. AP (ammonium perchlorate) (CAS 7790-98-9);
 - 3. Compounds composed of fluorine and any of the following:
 - a. Other halogens;
 - b. Oxygen; or
 - c. Nitrogen;

Note 1: ML8.d.3. does not apply to chlorine trifluoride (CAS 7790-91-2).

Note 2: ML8.d.3. does not apply to nitrogen trifluoride (CAS 7783-54-2) in its gaseous state.

 - 4. DNAD (1,3-dinitro-1,3-diazetidine) (CAS 78246-06-7);
 - 5. HAN (hydroxylammonium nitrate) (CAS 13465-08-2);
 - 6. HAP (hydroxylammonium perchlorate) (CAS 15588-62-2);
 - 7. HNF (hydrazinium nitroformate) (CAS 20773-28-8);
 - 8. Hydrazine nitrate (CAS 37836-27-4);
 - 9. Hydrazine perchlorate (CAS 27978-54-7);
-

-
10. Liquid oxidisers comprised of or containing inhibited red fuming nitric acid (IRFNA) (CAS 8007-58-7);
Note: ML8.d.10. does not apply to non-inhibited fuming nitric acid.
 - e. Binders, plasticisers, monomers and polymers, as follows:
 1. AMMO (azidomethylmethyloxetane and its polymers) (CAS 90683-29-7) (see also ML8.g.1. for its “precursors”);
 2. BAMO (bisazidomethyloxetane and its polymers) (CAS 17607-20-4) (see also ML8.g.1. for its “precursors”);
 3. BDNPA (bis (2,2-dinitropropyl)acetal) (CAS 5108-69-0);
 4. BDNPF (bis (2,2-dinitropropyl)formal) (CAS 5917-61-3);
 5. BTTN (butanetrioltrinitrate) (CAS 6659-60-5) (see also ML8.g.8. for its “precursors”);
 6. Energetic monomers, plasticisers or polymers, specially formulated for military use and containing any of the following:
 - a. Nitro groups;
 - b. Azido groups;
 - c. Nitrate groups;
 - d. Nitro groups; or
 - e. Difluoroamino groups;
 7. FAMAO (3-difluoroaminomethyl-3-azidomethyl oxetane) and its polymers;
 8. FEFO (bis-(2-fluoro-2,2-dinitroethyl) formal) (CAS 17003-79-1);
 9. FPF-1 (poly-2,2,3,3,4,4-hexafluoropentane-1,5-diol formal) (CAS 376-90-9);
 10. FPF-3
 (poly-2,4,4,5,5,6,6-heptafluoro-2-tri-fluoromethyl-3-oxaheptane-1,7-diol formal);
 11. GAP (glycidylazide polymer) (CAS 143178-24-9) and its derivatives;
 12. HTPB (hydroxyl terminated polybutadiene) with a hydroxyl functionality equal to or greater than 2.2 and less than or equal to 2.4, a hydroxyl value of less than 0.77 meq/g, and a viscosity at 30°C of less than 47 poise (CAS 69102-90-5);
 13. Alcohol functionalised poly(epichlorohydrin) with a molecular weight less than 10,000, as follows:
 - a. Poly(epichlorohydrindiol);
 - b. Poly(epichlorohydrintriol);
 14. NENAs (nitroethylnitramine compounds) (CAS 17096-47-8, 85068-73-1, 82486-83-7, 82486-82-6 and 85954-06-9);
 15. PGN (poly-GLYN, polyglycidynitrate or poly(nitratomethyl oxirane) (CAS 27814-48-8);
 16. Poly-NIMMO (poly nitratomethylmethyloxetane) or poly-NMMO (poly[3-Nitratomethyl-3-methyloxetane]) (CAS 84051-81-0);
 17. Polynitroorthocarbonates;
-

-
18. TVOPA (1,2,3-tris[1,2-bis(difluoroamino)ethoxy] propane or tris vinoxyl propane adduct) (CAS 53159-39-0);
 - f. "Additives" as follows:
 1. Basic copper salicylate (CAS 62320-94-9);
 2. BHEGA (bis-(2-hydroxyethyl) glycolamide) (CAS 17409-41-5);
 3. BNO (butadienenitrileoxide) (CAS 9003-18-3);
 4. Ferrocene derivatives as follows:
 - a. Butacene (CAS 125856-62-4);
 - b. Catocene (2,2-bis-ethylferrocenyl propane) (CAS 37206-42-1);
 - c. Ferrocene carboxylic acids;
 - d. n-butyl-ferrocene (CAS 31904-29-7);
 - e. Other adducted polymer ferrocene derivatives;
 - f. Ethyl ferrocene (CAS 1273-89-8);
 - g. Propyl ferrocene;
 - h. Pentyl ferrocene (CAS 1274-00-6);
 - i. Dicyclopentyl ferrocene;
 - j. Dicyclohexyl ferrocene;
 - k. Diethyl ferrocene (CAS 1273-97-8);
 - l. Dipropyl ferrocene;
 - m. Dibutyl ferrocene (CAS 1274-08-4);
 - n. Dihexyl ferrocene (CAS 93894-59-8);
 - o. Acetyl ferrocene (CAS 1271-55-2)/1,1'-diacetyl ferrocene (CAS 1273-94-5);
 5. Lead beta-resorcyate (CAS 20936-32-7);
 6. Lead citrate (CAS 14450-60-3);
 7. Lead-copper chelates of beta-resorcyate or salicylates (CAS 68411-07-4);
 8. Lead maleate (CAS 19136-34-6);
 9. Lead salicylate (CAS 15748-73-9);
 10. Lead stannate (CAS 12036-31-6);
 11. MAPO (tris-1-(2-methyl)aziridinyl phosphine oxide) (CAS 57-39-6); BOBBA 8 (bis(2-methyl aziridinyl) 2-(2-hydroxypropanoxy) propylamino phosphine oxide); and other MAPO derivatives;
 12. Methyl BAPO (bis(2-methyl aziridinyl) methylamino phosphine oxide) (CAS 85068-72-0);
 13. N-methyl-p-nitroaniline (CAS 100-15-2);
 14. 3-Nitrazo-1,5-pentane diisocyanate (CAS 7406-61-9);
 15. Organo-metallic coupling agents as follows:
 - a. Neopentyl[diallyl]oxy, tri[diethyl]phosphato-titanate (CAS 103850-22-2); also known as titanium IV, 2,2[bis 2-propenolato-methyl, butanolato, tris (diethyl) phosphato] (CAS 110438-25-0); or LICA 12 (CAS 103850-22-2);
 - b. Titanium IV, [(2-propenolato-1) methyl, n-propanolatomethyl] butanolato-1, tris[diethyl] pyrophosphate or KR3538;
 - c. Titanium IV, [(2-propenolato-1)methyl, n-propanolatomethyl] butanolato-1, tris(diethyl)phosphate;
-

-
16. Polycyanodifluoroaminoethyleneoxide;
 17. Bonding agents as follows:
 - a. 1,1R,1S-trimesoyl-tris(2-ethylaziridine) (HX-868, BITA) (CAS 7722-73-8);
 - b. Polyfunctional aziridine amides with isophthalic, trimesic, isocyanuric or trimethyladipic backbone also having a 2-methyl or 2-ethyl aziridine group;

Note: Item ML.8.f.17.b. includes:

 - a. 1,1H-Isophthaloyl-bis(2-methylaziridine) (HX-752) (CAS 7652-64-4);
 - b. 2,4,6-tris(2-ethyl-1-aziridinyl)-1,3,5-triazine (HX-874) (CAS 18924-91-9);
 - c. 1,1'-trimethyladipoyl-bis(2-ethylaziridine) (HX-877) (CAS 71463-62-2).
 18. Propyleneimine (2-methylaziridine) (CAS 75-55-8);
 19. Superfine iron oxide (Fe₂O₃) (CAS 1317-60-8) with a specific surface area more than 250 m²/g and an average particle size of 3.0 nm or less;
 20. TEPAN (tetraethylenepentaamineacrylonitrile) (CAS 68412-45-3); cyanoethylated polyamines and their salts;
 21. TEPANOL (tetraethylenepentaamineacrylonitrileglycidol) (CAS 68412-46-4); cyanoethylated polyamines adducted with glycidol and their salts;
 22. TPB (triphenyl bismuth) (CAS 603-33-8);
 23. TEPB (Tris (ethoxyphenyl) bismuth) (CAS 90591-48-3);
 - g. "Precursors" as follows:

N.B.: In ML8.g. the references are to specified "Energetic Materials" manufactured from these substances.

 1. BCMO (bischloromethyloxetane) (CAS 142173-26-0) (see also ML8.e.1. and e.2.);
 2. Dinitroazetidine-t-butyl salt (CAS 125735-38-8) (see also ML8.a.28.);
 3. HBIW (hexabenzylhexaazaisowurtzitane) (CAS 124782-15-6) (see also ML8.a.4.);
 4. Not used;
 5. TAT (1,3,5,7 tetraacetyl-1,3,5,7-tetraaza cyclo-octane) (CAS 41378-98-7) (see also ML8.a.13.);
 6. 1,4,5,8-tetraazadecalin (CAS 5409-42-7) (see also ML8.a.27.);
 7. 1,3,5-trichlorobenzene (CAS 108-70-3) (see also ML8.a.23.);
-

8. 1,2,4-trihydroxybutane (1,2,4-butanetriol) (CAS 3068-00-6) (see also ML8.e.5.);
9. DADN (1,5-diacetyl-3,7-dinitro-1, 3, 5, 7-tetraaza-cyclooctane) (see also ML8.a.13).

Note 1: ML8. does not apply to the following substances unless they are compounded or mixed with the “energetic material” specified by ML8.a. or powdered metals specified by ML8.c.:

- a. Ammonium picrate (CAS 131-74-8);
 - b. Black powder;
 - c. Hexanitrodiphenylamine (CAS 131-73-7);
 - d. Difluoroamine (CAS 10405-27-3);
 - e. Nitrostarch (CAS 9056-38-6);
 - f. Potassium nitrate (CAS 7757-79-1);
 - g. Tetranitronaphthalene;
 - h. Trinitroanisol;
 - i. Trinitronaphthalene;
 - j. Trinitroxylene;
 - k. N-pyrrolidinone; 1-methyl-2-pyrrolidinone (CAS 872-50-4);
 - l. Dioctylmaleate (CAS 142-16-5);
 - m. Ethylhexylacrylate (CAS 103-11-7);
 - n. Triethylaluminium (TEA) (CAS 97-93-8), trimethylaluminium (TMA) (CAS 75-24-1), and other pyrophoric metal alkyls and aryls of lithium, sodium, magnesium, zinc or boron;
 - o. Nitrocellulose (CAS 9004-70-0);
 - p. Nitroglycerin (or glyceroltrinitrate, trinitroglycerine) (NG) (CAS 55-63-0);
 - q. 2,4,6-trinitrotoluene (TNT) (CAS 118-96-7);
 - r. Ethylenediaminedinitrate (EDDN) (CAS 20829-66-7);
 - s. Pentaerythritoltetranitrate (PETN) (CAS 78-11-5);
 - t. Lead azide (CAS 13424-46-9), normal lead styphnate (CAS 15245-44-0) and basic lead styphnate (CAS 12403-82-6), and primary explosives or priming compositions containing azides or azide complexes;
 - u. Triethyleneglycoldinitrate (TEGDN) (CAS 111-22-8);
 - v. 2,4,6-trinitroresorcinol (styphnic acid) (CAS 82-71-3);
 - w. Diethyldiphenylurea; (CAS 85-98-3); dimethyldiphenylurea; (CAS 611-92-7), methylethyldiphenylurea; [Centralites]
 - x. N,N-diphenylurea (unsymmetrical diphenylurea) (CAS 603-54-3);
 - y. Methyl-N,N-diphenylurea (methyl unsymmetrical diphenylurea) (CAS 13114-72-2);
 - z. Ethyl-N,N-diphenylurea (ethyl unsymmetrical diphenylurea) (CAS 64544-71-4);
 - aa. 2-Nitrodiphenylamine (2-NDPA) (CAS 119-75-5);
 - bb. 4-Nitrodiphenylamine (4-NDPA) (CAS 836-30-6);
 - cc. 2,2-dinitropropanol (CAS 918-52-5);
 - dd. Nitroguanidine (CAS 556-88-7) (see I.C.11.d. on the Dual-Use List).
- N.B.: See also ML908.

Note 2: ML8. does not apply to ammonium perchlorate (ML8.d.2.), NTO (ML8.a.18.) or catocene (ML8.f.4.b.), and meeting all of the following:

- a. Specially shaped and formulated for civil-use gas generation devices;*
- b. Compounded or mixed, with non-active thermoset binders or plasticizers, and having a mass of less than 250 g;*
- c. Having a maximum of 80% ammonium perchlorate (ML8.d.2.) in mass of active material;*
- d. Having less than or equal to 4 g of NTO (ML8.a.18.); and*
- e. Having less than or equal to 1 g of catocene (ML8.f.4.b.).*

Note 3: Former note 5 was deleted in 2008. Remaining Notes 6 and 7 were renumbered Notes 1 and 2 in 2012.

ML9. Vessels of war (surface or underwater), special naval equipment, accessories, components and other surface vessels, as follows:

N.B.: For guidance and navigation equipment, see ML11.

a. Vessels and components, as follows:

1. Vessels (surface or underwater) specially designed or modified for military use, regardless of current state of repair or operating condition, and whether or not they contain weapon delivery systems or armour, and hulls or parts of hulls for such vessels, and components therefor specially designed for military use;
2. Surface vessels, other than those specified in ML9.a.1., having any of the following, fixed or integrated into the vessel:
 - a. Automatic weapons having a calibre of 12.7 mm or greater specified in ML1., or weapons specified in ML2., ML4., ML12. or ML19., or 'mountings' or hard points for such weapons;

Technical Note:

'Mountings' refers to weapon mounts or structural strengthening for the purpose of installing weapons.

- b. Fire control systems specified in ML5.;
- c. Having all of the following:
 1. 'Chemical, Biological, Radiological and Nuclear (CBRN) protection'; and
 2. 'Pre-wet or wash down system' designed for decontamination purposes; or

Technical Notes:

1. *'CBRN protection' is a self contained interior space containing features such as over-pressurisation, isolation of ventilation systems, limited ventilation openings with CBRN filters and limited personnel access points incorporating air-locks.*
 2. *'Pre-wet or wash down system' is a seawater spray system capable of simultaneously wetting the exterior superstructure and decks of a vessel.*
-

-
- d. Active weapon countermeasure systems specified in ML4.b., ML5.c. or ML11.a. and having any of the following:
 - 1. 'CBRN protection';
 - 2. Hull and superstructure, specially designed to reduce the radar cross section;
 - 3. Thermal signature reduction devices, (e.g., an exhaust gas cooling system), excluding those specially designed to increase overall power plant efficiency or to reduce the environmental impact; or
 - 4. A degaussing system designed to reduce the magnetic signature of the whole vessel;
 - b. Engines and propulsion systems, as follows, specially designed for military use and components therefor specially designed for military use:
 - 1. Diesel engines specially designed for submarines and having all of the following:
 - a. Power output of 1.12 MW (1,500 hp) or more; and
 - b. Rotary speed of 700 rpm or more;
 - 2. Electric motors specially designed for submarines and having all of the following:
 - a. Power output of more than 0.75 MW (1,000 hp);
 - b. Quick reversing;
 - c. Liquid cooled; and
 - d. Totally enclosed;
 - 3. Non-magnetic diesel engines having all of the following:
 - a. Power output of 37.3 kW (50 hp) or more; and
 - b. Non-magnetic content in excess of 75% of total mass;
 - 4. 'Air Independent Propulsion' (AIP) systems specially designed for submarines;

Technical Note:

'Air Independent Propulsion' (AIP) allows a submerged submarine to operate its propulsion system, without access to atmospheric oxygen, for a longer time than the batteries would have otherwise allowed. For the purposes of ML9.b.4., AIP does not include nuclear power.

- c. Underwater detection devices, specially designed for military use, controls therefor and components therefor specially designed for military use;
- d. Anti-submarine nets and anti-torpedo nets, specially designed for military use;
- e. Not used since 2003;

-
- f. Hull penetrators and connectors, specially designed for military use, that enable interaction with equipment external to a vessel, and components therefor specially designed for military use;

Note: ML9.f. includes connectors for vessels which are of the single-conductor, multi-conductor, coaxial or waveguide type, and hull penetrators for vessels, both of which are capable of remaining impervious to leakage from without and of retaining required characteristics at marine depths exceeding 100 m; and fibre-optic connectors and optical hull penetrators, specially designed for "laser" beam transmission, regardless of depth. ML9.f. does not apply to ordinary propulsive shaft and hydrodynamic control-rod hull penetrators.

- g. Silent bearings having any of the following, components therefor and equipment containing those bearings, specially designed for military use:
1. Gas or magnetic suspension;
 2. Active signature controls; or
 3. Vibration suppression controls.

ML10. "Aircraft", "lighter-than-air vehicles", "Unmanned Aerial Vehicles" ("UAVs"), aero-engines and "aircraft" equipment, related equipment, and components, as follows, specially designed or modified for military use:

N.B. For guidance and navigation equipment, see ML11.

- a. Manned "aircraft" and "lighter-than-air vehicles", and specially designed components therefor;
- b. Not used;
- c. Unmanned aircraft and related equipment, as follows, and specially designed components therefor:
 1. "UAVs", Remotely Piloted Air Vehicles (RPVs), autonomous programmable vehicles and unmanned "lighter-than-air vehicles";
 2. Launchers, recovery equipment and ground support equipment;
 3. Equipment designed for command or control;
- d. Propulsion aero-engines and specially designed components therefor;
- e. Airborne refuelling equipment specially designed or modified for any of the following, and specially designed components therefor:
 1. "Aircraft" specified by ML10.a.; or
 2. Unmanned aircraft specified by ML10.c.;
- f. 'Ground equipment' specially designed for aircraft specified by ML10.a. or aero-engines specified by ML10.d.;

Technical Note:

'Ground equipment' includes pressure refuelling equipment and equipment designed to facilitate operations in confined areas.

-
- g. Aircrew life support equipment, aircrew safety equipment and other devices for emergency escape, not specified in ML10.a., designed for “aircraft” specified by ML10.a.;

Note: ML10.g. does not control aircrew helmets that do not incorporate, or have mountings or fittings for, equipment specified in the Munitions List.

N.B.: For helmets see also ML13.c.

- h. Parachutes, paragliders and related equipment, as follows, and specially designed components therefor:
1. Parachutes not specified elsewhere in the Munitions List;
 2. Paragliders;
 3. Equipment specially designed for high altitude parachutists (e.g. suits, special helmets, breathing systems, navigation equipment);
- i. Controlled opening equipment or automatic piloting systems, designed for parachuted loads.

Note 1: ML10.a. does not apply to “aircraft” and “lighter-than-air vehicles” or variants of those “aircraft”, specially designed for military use and which are all of the following:

- a. Not a combat aircraft;
- b. Not configured for military use and not fitted with equipment or attachments specially designed or modified for military use; and
- c. Certified for civil use by the civil aviation authority in a Wassenaar Arrangement Participating State.

Note 2: ML10.d. does not apply to:

- a. Aero-engines designed or modified for military use which have been certified by civil aviation authorities in a Wassenaar Arrangement Participating State for use in “civil aircraft”, or specially designed components therefor;
- b. Reciprocating engines or specially designed components therefor, except those specially designed for “UAVs”.

Note 3: For the purposes of ML10.a. and ML10.d., specially designed components and related equipment for non-military “aircraft” or aero-engines modified for military use applies only to those military components and to military related equipment required for the modification to military use.

Note 4: For the purposes of ML10.a., military use includes combat, military reconnaissance, assault, military training, logistics support, and transporting and airdropping troops or military equipment.

Note 5: ML10.a. does not apply to “aircraft” that meet all of the following:

- a. Were first manufactured before 1946;
 - b. Do not incorporate items specified by the Munitions List, unless the items are required to meet safety or airworthiness standards of a participating state; and
 - c. Do not incorporate weapons specified by the Munitions List, unless inoperable and incapable of being returned to operation.
-

ML11. Electronic equipment, not specified elsewhere on the Munitions List, as follows, and specially designed components therefor:

- a. Electronic equipment specially designed for military use;

Note: ML11.a. includes:

- a. *Electronic countermeasure and electronic counter-countermeasure equipment (i.e., equipment designed to introduce extraneous or erroneous signals into radar or radio communication receivers or otherwise hinder the reception, operation or effectiveness of adversary electronic receivers including their countermeasure equipment), including jamming and counter-jamming equipment;*
- b. *Frequency agile tubes;*
- c. *Electronic systems or equipment, designed either for surveillance and monitoring of the electro-magnetic spectrum for military intelligence or security purposes or for counteracting such surveillance and monitoring;*
- d. *Underwater countermeasures, including acoustic and magnetic jamming and decoy, equipment designed to introduce extraneous or erroneous signals into sonar receivers;*
- e. *Data processing security equipment, data security equipment and transmission and signalling line security equipment, using ciphering processes;*
- f. *Identification, authentication and keyloader equipment and key management, manufacturing and distribution equipment;*
- g. *Guidance and navigation equipment;*
- h. *Digital troposcatter-radio communications transmission equipment;*
- i. *Digital demodulators specially designed for signals intelligence;*
- j. *“Automated Command and Control Systems”.*

N.B.: For “software” associated with military “Software” Defined Radio (SDR), see ML21.

- b. Global Navigation Satellite Systems (GNSS) jamming equipment.
- c. “Spacecraft” specially designed or modified for military use, and “spacecraft” components specially designed for military use.

ML12. High velocity kinetic energy weapon systems and related equipment, as follows, and specially designed components therefor:

- a. Kinetic energy weapon systems specially designed for destruction or effecting mission-abort of a target;
- b. Specially designed test and evaluation facilities and test models, including diagnostic instrumentation and targets, for dynamic testing of kinetic energy projectiles and systems.

N.B.: For weapon systems using sub-calibre ammunition or employing solely chemical propulsion, and ammunition therefor, see ML1. to ML4.

Note 1: ML12. includes the following when specially designed for kinetic energy weapon systems:

- a. Launch propulsion systems capable of accelerating masses larger than 0.1 g to velocities in excess of 1.6 km/s, in single or rapid fire modes;*
- b. Prime power generation, electric armour, energy storage (e.g., high energy storage capacitors), thermal management, conditioning, switching or fuel-handling equipment; and electrical interfaces between power supply, gun and other turret electric drive functions;*
N.B.: See also 3A001.e.2. on the Dual-Use List for high energy storage capacitors.
- c. Target acquisition, tracking, fire control or damage assessment systems;*
- d. Homing seeker, guidance or divert propulsion (lateral acceleration) systems for projectiles.*

Note 2: ML12. applies to weapon systems using any of the following methods of propulsion:

- a. Electromagnetic;*
- b. Electrothermal;*
- c. Plasma;*
- d. Light gas; or*
- e. Chemical (when used in combination with any of the above).*

ML13. Armoured or protective equipment, constructions and components, as follows:

- a. Armoured plate, having any of the following:
 1. Manufactured to comply with a military standard or specification; or
 2. Suitable for military use;

N.B.: For body armour plate, see ML13.d.2.
- b. Constructions of metallic or non-metallic materials, or combinations thereof, specially designed to provide ballistic protection for military systems, and specially designed components therefor;
- c. Helmets manufactured according to military standards or specifications, or comparable national standards, and specially designed components therefor (i.e. helmet shell, liner and comfort pads);
- d. Body armour or protective garments, and components therefor, as follows:
 1. Soft body armour or protective garments, manufactured to military standards or specifications, or to their equivalents, and specially designed components therefor;

Note: For the purposes of ML13.d.1., military standards or specifications include, at a minimum, specifications for fragmentation protection.
 2. Hard body armour plates providing ballistic protection equal to or greater than level III (NIJ 0101.06, July 2008) or national equivalents.

Note 1: ML13.b. includes materials specially designed to form explosive reactive armour or to construct military shelters.

Note 2: ML13.c. does not apply to conventional steel helmets, neither modified or designed to accept, nor equipped with any type of accessory device.

Note 3: ML13.c. and ML13.d. do not apply to helmets, body armour or protective garments, when accompanying their user for the user's own personal protection.

Note 4: The only helmets specially designed for bomb disposal personnel that are specified by ML13. are those specially designed for military use.

N.B. 1: See also 1A005 on the Dual-Use List.

N.B. 2: For "fibrous or filamentary materials" used in the manufacture of body armour and helmets, see 1C010 on the Dual-Use List.

ML14. 'Specialised equipment for military training' or for simulating military scenarios, simulators specially designed for training in the use of any firearm or weapon specified by ML1. or ML2., and specially designed components and accessories therefor.

Technical Note:

The term 'specialised equipment for military training' includes military types of attack trainers, operational flight trainers, radar target trainers, radar target generators, gunnery training devices, anti-submarine warfare trainers, flight simulators (including human-rated centrifuges for pilot/astronaut training), radar trainers, instrument flight trainers, navigation trainers, missile launch trainers, target equipment, drone "aircraft", armament trainers, pilotless "aircraft" trainers, mobile training units and training equipment for ground military operations.

Note 1: ML14. includes image generating and interactive environment systems for simulators, when specially designed or modified for military use.

Note 2: ML14. does not apply to equipment specially designed for training in the use of hunting or sporting weapons.

ML15. Imaging or countermeasure equipment, as follows, specially designed for military use, and specially designed components and accessories therefor:

- a. Recorders and image processing equipment;
- b. Cameras, photographic equipment and film processing equipment;
- c. Image intensifier equipment;
- d. Infrared or thermal imaging equipment;
- e. Imaging radar sensor equipment;
- f. Countermeasure or counter-countermeasure equipment, for the equipment specified by ML15.a. to ML15.e.

Note: ML15.f. includes equipment designed to degrade the operation or effectiveness of military imaging systems or to minimise such degrading effects.

-
- Note 1: In ML15., the term specially designed components includes the following, when *specially designed for military use*:
- a. *Infrared image converter tubes*;
 - b. *Image intensifier tubes (other than first generation)*;
 - c. *Microchannel plates*;
 - d. *Low-light-level television camera tubes*;
 - e. *Detector arrays (including electronic interconnection or read out systems)*;
 - f. *Pyroelectric television camera tubes*;
 - g. *Cooling systems for imaging systems*;
 - h. *Electrically triggered shutters of the photochromic or electro-optical type having a shutter speed of less than 100 μ s, except in the case of shutters which are an essential part of a high speed camera*;
 - i. *Fibre optic image inverters*;
 - j. *Compound semiconductor photocathodes*.

Note 2: *ML15. does not apply to “first generation image intensifier tubes” or equipment specially designed to incorporate “first generation image intensifier tubes”.*

N.B.: *For the classification of weapons sights incorporating “first generation image intensifier tubes” see ML1., ML2. and ML5.a.*

N.B.: *See also 6A002.a.2. and 6A002.b. on the Dual-Use List.*

ML16. Forgings, castings and other unfinished products, specially designed for items specified by ML1. to ML4., ML6., ML9., ML10., ML12. or ML19.

Note: *ML16. applies to unfinished products when they are identifiable by material composition, geometry or function.*

ML17. Miscellaneous equipment, materials and ‘libraries’, as follows, and specially designed components therefor:

- a. Self-contained diving and underwater swimming apparatus, as follows:
 1. Closed or semi-closed circuit (rebreathing) apparatus, specially designed for military use (i.e., specially designed to be non magnetic);
 2. Specially designed components for use in the conversion of open-circuit apparatus to military use;
 3. Articles designed exclusively for military use with self-contained diving and underwater swimming apparatus;

N.B.: *See also 8A002.q. on the Dual-Use List.*
- b. Construction equipment specially designed for military use;
- c. Fittings, coatings and treatments, for signature suppression, specially designed for military use;
- d. Field engineer equipment specially designed for use in a combat zone;
- e. “Robots”, “robot” controllers and “robot” “end-effectors”, having any of the following characteristics:
 1. Specially designed for military use;

-
2. Incorporating means of protecting hydraulic lines against externally induced punctures caused by ballistic fragments (e.g., incorporating self-sealing lines) and designed to use hydraulic fluids with flash points higher than 839 K (566°C); or
 3. Specially designed or rated for operating in an electro-magnetic pulse (EMP) environment;

Technical Note:

Electro-magnetic pulse does not refer to unintentional interference caused by electromagnetic radiation from nearby equipment (e.g., machinery, appliances or electronics) or lightning.

- f. ‘Libraries’ (parametric technical databases) specially designed for military use with equipment specified by the Munitions List;
- g. Nuclear power generating equipment or propulsion equipment, including “nuclear reactors”, specially designed for military use and components therefor specially designed or ‘modified’ for military use;
- h. Equipment and material, coated or treated for signature suppression, specially designed for military use, other than those specified elsewhere in the Munitions List;
- i. Simulators specially designed for military “nuclear reactors”;
- j. Mobile repair shops specially designed or ‘modified’ to service military equipment;
- k. Field generators specially designed or ‘modified’ for military use;
- l. Containers specially designed or ‘modified’ for military use;
- m. Ferries, other than those specified elsewhere in the Munitions List, bridges and pontoons, specially designed for military use;
- n. Test models specially designed for the “development” of items specified by ML4., ML6., ML9. or ML10.;
- o. Laser protection equipment (e.g., eye and sensor protection) specially designed for military use;
- p. “Fuel cells”, other than those specified elsewhere in the Munitions List, specially designed or ‘modified’ for military use.

Technical Notes:

1. *For the purpose of ML17., the term ‘library’ (parametric technical database) means a collection of technical information of a military nature, reference to which may enhance the performance of military equipment or systems.*
2. *For the purpose of ML17., ‘modified’ means any structural, electrical, mechanical, or other change that provides a non-military item with military capabilities equivalent to an item which is specially designed for military use.*

ML18. Production equipment and components, as follows:

- a. Specially designed or modified ‘production’ equipment for the ‘production’ of products specified by the Munitions List, and specially designed components therefor;
-

-
- b. Specially designed environmental test facilities and specially designed equipment therefor, for the certification, qualification or testing of products specified by the Munitions List.

Technical Note:

For the purposes of ML18., the term 'production' includes design, examination, manufacture, testing and checking.

Note: ML18.a. and ML18.b. include the following equipment:

- a. Continuous nitrators;*
- b. Centrifugal testing apparatus or equipment, having any of the following:*
 - 1. Driven by a motor or motors having a total rated horsepower of more than 298 kW (400 hp);*
 - 2. Capable of carrying a payload of 113 kg or more; or*
 - 3. Capable of exerting a centrifugal acceleration of 8 g or more on a payload of 91 kg or more;*
- c. Dehydration presses;*
- d. Screw extruders specially designed or modified for military explosive extrusion;*
- e. Cutting machines for the sizing of extruded propellants;*
- f. Sweetie barrels (tumblers) 1.85 m or more in diameter and having over 227 kg product capacity;*
- g. Continuous mixers for solid propellants;*
- h. Fluid energy mills for grinding or milling the ingredients of military explosives;*
- i. Equipment to achieve both sphericity and uniform particle size in metal powder listed in ML8.c.8.;*
- j. Convection current converters for the conversion of materials listed in ML8.c.3.*

ML19. Directed Energy Weapon (DEW) systems, related or countermeasure equipment and test models, as follows, and specially designed components therefor:

- a. "Laser" systems specially designed for destruction or effecting mission-abort of a target;
- b. Particle beam systems capable of destruction or effecting mission-abort of a target;
- c. High power Radio-Frequency (RF) systems capable of destruction or effecting mission-abort of a target;
- d. Equipment specially designed for the detection or identification of, or defence against, systems specified by ML19.a. to ML19.c.;
- e. Physical test models for the systems, equipment and components, specified by ML19.;
- f. "Laser" systems specially designed to cause permanent blindness to unenhanced vision, i.e. to the naked eye or to the eye with corrective eyesight devices.

Note 1: DEW systems specified by ML19. include systems whose capability is derived from the controlled application of:

- a. “Lasers” of sufficient power to effect destruction similar to the manner of conventional ammunition;*
- b. Particle accelerators which project a charged or neutral particle beam with destructive power;*
- c. High pulsed power or high average power radio frequency beam transmitters, which produce fields sufficiently intense to disable electronic circuitry at a distant target.*

Note 2: ML19. includes the following when specially designed for DEW systems:

- a. Prime power generation, energy storage, switching, power conditioning or fuel-handling equipment;*
- b. Target acquisition or tracking systems;*
- c. Systems capable of assessing target damage, destruction or mission-abort;*
- d. Beam-handling, propagation or pointing equipment;*
- e. Equipment with rapid beam slew capability for rapid multiple target operations;*
- f. Adaptive optics and phase conjugators;*
- g. Current injectors for negative hydrogen ion beams;*
- h. “Space-qualified” accelerator components;*
- i. Negative ion beam funnelling equipment;*
- j. Equipment for controlling and slewing a high energy ion beam;*
- k. “Space qualified” foils for neutralising negative hydrogen isotope beams.*

ML20. Cryogenic and “superconductive” equipment, as follows, and specially designed components and accessories therefor:

- a. Equipment specially designed or configured to be installed in a vehicle for military ground, marine, airborne or space applications, capable of operating while in motion and of producing or maintaining temperatures below 103 K (-170°C);

Note: ML20.a. includes mobile systems incorporating or employing accessories or components manufactured from non-metallic or non-electrical conductive materials, such as plastics or epoxy-impregnated materials.

- b. “Superconductive” electrical equipment (rotating machinery and transformers) specially designed or configured to be installed in a vehicle for military ground, marine, airborne or space applications and capable of operating while in motion.

Note: ML20.b. does not apply to direct-current hybrid homopolar generators that have single-pole normal metal armatures which rotate in a magnetic field produced by superconducting windings, provided those windings are the only superconducting components in the generator.

ML21. “Software” as follows:

- a. “Software” specially designed or modified for the “development”, “production” or “use” of equipment, materials or “software”, specified by the Munitions List;
- b. Specific “software”, other than that specified by ML21.a., as follows:
 1. “Software” specially designed for military use and specially designed for modelling, simulating or evaluating military weapon systems;
 2. “Software” specially designed for military use and specially designed for modelling or simulating military operational scenarios;
 3. “Software” for determining the effects of conventional, nuclear, chemical or biological weapons;
 4. “Software” specially designed for military use and specially designed for Command, Communications, Control and Intelligence (C³I) or Command, Communications, Control, Computer and Intelligence (C⁴I) applications;
- c. “Software”, not specified by ML21.a., or b., specially designed or modified to enable equipment not specified by the Munitions List to perform the military functions of equipment specified by the Munitions List.

ML22. “Technology” as follows:

- a. “Technology”, other than specified in ML22.b., which is “required” for the “development”, “production”, operation, installation, maintenance (checking), repair, overhaul or refurbishing of items specified by the Munitions List;
- b. “Technology” as follows:
 1. “Technology” “required” for the design of, the assembly of components into, and the operation, maintenance and repair of, complete production installations for items specified by the Munitions List, even if the components of such production installations are not specified;
 2. “Technology” “required” for the “development” and “production” of small arms, even if used to produce reproductions of antique small arms;
 3. Not used;
N.B.: See ML22.a. for “technology” previously specified by ML22.b.3.
 4. Not used;
N.B.: See ML22.a. for “technology” previously specified by ML22.b.4.
 5. “Technology” “required” exclusively for the incorporation of “biocatalysts”, specified by ML7.i.1., into military carrier substances or military material.

Note 1: “Technology” “required” for the “development”, “production”, operation, installation, maintenance (checking), repair, overhaul or refurbishing of items specified by the Munitions List remains under control even when applicable to any item not specified by the Munitions List.

Note 2: ML22 does not apply to:

- a. *“Technology” that is the minimum necessary for the installation, operation, maintenance (checking) and repair, of those items which are not controlled or whose export has been authorised;*
- b. *“Technology” that is “in the public domain”, “basic scientific research” or the minimum necessary information for patent applications;*
- c. *“Technology” for magnetic induction for continuous propulsion of civil transport devices.*

Note 3: ML22 does not control “technology” “required” for the operation, installation, maintenance (checking), repair, overhaul or refurbishing of items specified in ML901 to ML905.

ML901. Firearms, other than those specified in ML1 or ML2, including rifles, carbines, muskets, pistols, revolvers, shotguns and smooth-bore weapons, and specially designed components therefor.

ML902. Ammunition, projectiles, and specially designed components therefor, for the firearms specified in ML901.

Technical Note:

Specially designed components for the products controlled by ML901 and ML902 include forgings, castings and other unfinished products the use of which in a controlled product is identifiable by material composition, geometry or function.

ML903. Deleted.

ML904. Accessories, including silencers, special gun-mountings, magazines, weapon sights and flash suppressors, for the firearms specified in ML901.

ML905. Air guns having any of the following characteristics and specially designed components therefor:

- a. muzzle velocity exceeding 152.4 m/s (500 feet per second);
- b. designed for competition target shooting; or
- c. capable of fully automatic operation.

Technical Note:

Air guns discharge a projectile by the use of compressed air or gas and not by the explosive force of propellant combustion. Air guns include any air pistol or air rifle.

Note: ML905 does not include air gun accessories, air gun pellets or other air gun projectiles.

ML908. “Energetic materials” other than “energetic materials” specified in ML8, including high explosives specified in 1C239, but excluding those specially formulated for toys, novelty goods and fireworks.

ML909. Detonators or other equipment, other than those specified in ML4 or 1A007, for the initiation of “energetic materials” specified in ML908.

ML910. Charges and devices, other than those specified in ML4 or 1A008, containing “energetic materials” specified in ML908.

Note: ML901 to ML910 do not include any of the following:

- a. nailing or stapling guns;
- b. explosive powered fixing tools;
- c. starting pistols, flare guns or other signalling devices designed for emergency or life-saving purposes;
- d. line throwers;
- e. tranquilliser guns;
- f. guns that operate a captive bolt for the slaughter of animals;
- g. devices for the casting of weighted nets;
- h. underwater power-heads;
- i. fire extinguisher cartridges;
- j. hand-operated devices that use blank cartridges to propel objects for retrieval in connection with the training of dogs;
- k. paintball guns;
- l. air-soft guns (6mm or 8mm calibre);
- m. air bag and life raft inflation gas generators;
- n. thermite welding charges and associated igniters;
- o. sidewall core guns designed for geological or mining purposes;
- p. expandable casing perforation guns designed for geological or mining purposes;
- q. oil well gas flare igniters;
- r. bird-fright cartridges;
- s. improvised explosive device disposal (IEDD) disruptor cartridges;
or

-
- t. other cartridges or “explosive”/”pyrotechnic” charges specially designed for use with the items listed in this Note.*

Part 2—Dual-use list

Note 1: Terms in “quotations” are defined terms. Refer to the ‘Definitions of Terms’ section.

Note 2: Chemicals are listed by name and CAS number. Chemicals of the same structural formula (including hydrates) are controlled regardless of name or CAS number. CAS numbers are shown to assist in identifying whether a particular chemical or mixture is controlled, irrespective of nomenclature. CAS numbers cannot be used as unique identifiers because some forms of the listed chemical have different CAS numbers, and mixtures containing a listed chemical may also have different CAS numbers.

NUCLEAR TECHNOLOGY NOTE (NTN)

(To be read in conjunction with section E of Category 0.)

1. The “technology” directly associated with any goods controlled in Category 0 is controlled according to the provisions of Category 0.
2. “Technology” for the “development”, “production” or “use” of goods under control remains under control even when applicable to non-controlled goods.
3. The approval of goods for export also authorises the export to the same end-user of the minimum “technology” required for the installation, operation, maintenance and repair of the goods.
4. Controls on “technology” transfer do not apply to information “in the public domain” or to “basic scientific research”.

GENERAL TECHNOLOGY NOTE (GTN)

(This note applies to all technology controls in Categories 1 to 9.)

1. The export of “technology” which is “required” for the “development”, “production” or “use” of goods controlled in Categories 1 to 9, is controlled according to the provisions of Categories 1 to 9.
2. “Technology” “required” for the “development”, “production” or “use” of goods under control remains under control even when applicable to non-controlled goods.
3. Controls do not apply to that “technology” which is the minimum necessary for the installation, operation, maintenance (checking) and repair of those goods which are not controlled or whose export has been authorised.

Note: This does not release such “technology” specified in 1E002.e., 1E002.f., 8E002.a. and 8E002.b.

4. Controls on “technology” transfer do not apply to information “in the public domain”, to “basic scientific research” or to the minimum necessary information for patent applications.

GENERAL SOFTWARE NOTE (GSN)

(This note applies to all software controls within Categories 0 to 9.)

Categories 0 to 9 of this list do not control “software” which is any of the following:

1. Generally available to the public by being:
 - a. Sold from stock at retail selling points, without restriction, by means of:
 1. Over-the-counter transactions;
 2. Mail order transactions;
 3. Electronic transactions; or
 4. Telephone order transactions; and
 - b. Designed for installation by the user without further substantial support by the supplier;

Note: Entry 1. of the General Software Note does not release “software” specified in Category 5 — Part 2 (“Information Security”).

2. “In the public domain”; or
3. The minimum necessary “object code” for the installation, operation, maintenance (checking) or repair of those items whose export has been authorised.

Note: Entry 3 of the General Software Note does not release “software” controlled by Category 5 — Part 2 (“Information Security”).

Category 0—Nuclear materials, facilities and equipment

0A Systems, Equipment and Components

- 0A001 “Nuclear reactors” and specially designed or prepared equipment and components therefor, as follows:
- a. “Nuclear reactors” capable of operation so as to maintain a controlled self-sustaining fission chain reaction;
 - b. Metal vessels, or major shop-fabricated parts therefor, including the reactor vessel head for a reactor pressure vessel, specially designed or prepared to contain the core of a “nuclear reactor” specified by 0A001.a;
 - c. Manipulative equipment specially designed or prepared for inserting or removing fuel in a “nuclear reactor” specified by 0A001.a;
 - d. Control rods specially designed or prepared for the control of the fission process in a “nuclear reactor” specified by 0A001.a, support or suspension structures therefor, rod drive mechanisms and rod guide tubes;
 - e. Tubes which are specially designed or prepared to contain both fuel elements and the primary coolant in a “nuclear reactor” specified by 0A001.a.;
 - f. Zirconium metal tubes or zirconium alloy tubes (or assemblies of tubes), specially designed or prepared for use as fuel cladding in a “nuclear reactor” specified by 0A001.a, and in quantities exceeding 10 kg;
N.B.1: For zirconium pressure tubes see 0A001.e.
N.B.2: For calandria tubes see 0A001.h.
 - g. Pumps or circulators specially designed or prepared for circulating the primary coolant of “nuclear reactors” specified by 0A001.a.;
 - h. ‘Nuclear reactor internals’ specially designed or prepared for use in a “nuclear reactor” specified by 0A001.a., including, for example, support columns for the core, fuel channels, calandria tubes, thermal shields, baffles, core grid plates, and diffuser plates;
Note: In 0A001.h. ‘nuclear reactor internals’ means any major structure within a reactor vessel which has one or more functions such as supporting the core, maintaining fuel alignment, directing primary coolant flow, providing radiation shields for the reactor vessel, and guiding in-core instrumentation.
 - i. Heat exchangers as follows:
 1. Steam generators specially designed or prepared for the primary, or intermediate, coolant circuit of a “nuclear reactor” specified by 0A001.a;
 2. Other heat exchangers specially designed or prepared for use in the primary coolant circuit of a “nuclear reactor” specified by 0A001.a.

Note: 0A001.i. does not control heat exchangers for the supporting systems of the reactor e.g. the emergency cooling system or the decay heat cooling system.

- j. Neutron detectors specially designed or prepared for determining neutron flux levels within the core of a “nuclear reactor” specified by 0A001.a..
- k. ‘External thermal shields’ specially designed or prepared for use in a “nuclear reactor” specified by 0A001.a. for reduction of heat loss and also for containment vessel protection.

Note: In 0A001.k. ‘external thermal shields’ means major structures placed over the reactor vessel which reduce heat loss from the reactor and reduce temperature within the containment vessel.

0B Test, Inspection and Production Equipment

0B001 Plant for the separation of isotopes of “natural uranium”, “depleted uranium” and “special fissile materials”, and specially designed or prepared equipment and components therefor, other than analytical instruments, as follows:

- a. Plant specially designed for separating isotopes of “natural uranium”, “depleted uranium”, and “special fissile materials”, as follows:
 - 1. Gas centrifuge separation plant;
 - 2. Gaseous diffusion separation plant;
 - 3. Aerodynamic separation plant;
 - 4. Chemical exchange separation plant;
 - 5. Ion-exchange separation plant;
 - 6. Atomic vapour “laser” isotope separation (AVLIS) plant;
 - 7. Molecular “laser” isotope separation (MLIS) plant;
 - 8. Plasma separation plant;
 - 9. Electro magnetic separation plant;
- b. Gas centrifuges and assemblies and components, specially designed or prepared for gas centrifuge separation process, as follows:

Note: In 0B001.b. ‘high strength-to-density ratio material’ means any material with a high strength-to-density ratio, including any of the following:

- a. *Maraging steel capable of an ultimate tensile strength of 1.95 GPa or more;*
 - b. *Aluminium alloys capable of an ultimate tensile strength of 0.46 GPa or more; or*
 - c. *Filamentary materials suitable for use in composite structures and having a “specific modulus” of 3.18×10^6 m or greater and a “specific tensile strength” of 7.62×10^4 m or greater;*
- 1. Gas centrifuges;
 - 2. Complete rotor assemblies;

-
3. Rotor tube cylinders with a wall thickness of 12 mm or less, a diameter of between 75 mm and 650 mm, made from 'high strength-to-density ratio materials';
 4. Rings or bellows with a wall thickness of 3 mm or less and a diameter of between 75 mm and 650 mm and designed to give local support to a rotor tube or to join a number together, made from 'high strength-to-density ratio materials';
 5. Baffles of between 75 mm and 650 mm diameter for mounting inside a rotor tube, made from 'high strength-to-density ratio materials';
 6. Top or bottom caps of between 75 mm and 650 mm diameter to fit the ends of a rotor tube, made from 'high strength-to-density ratio materials';
 7. Magnetic suspension bearings as follows:
 - a. Magnetic suspension bearings, specially designed or prepared, consisting of an annular magnet suspended within a housing made of or protected by "materials resistant to corrosion by UF₆" containing a damping medium and having the magnet coupling with a pole piece or second magnet fitted to the top cap of the rotor;
 - b. Active magnetic bearings specially designed or prepared for use with gas centrifuges.

Note: Bearings specified in 0B001.b.7.b. usually have the following characteristics:

 1. *Designed to keep centered a rotor spinning at 600 Hz or more; and*
 2. *Associated to a reliable electrical power supply and/or to an uninterruptible power supply (UPS) unit in order to function for more than one hour.*
 8. Specially designed or prepared bearings comprising a pivot-cup assembly mounted on a damper;
 9. Specially designed or prepared molecular pumps comprised of cylinders having internally machined or extruded helical grooves and internally machined bores;
 10. Specially designed or prepared ring-shaped motor stators for multiphase AC hysteresis (or reluctance) motors for synchronous operation within a vacuum at a frequency of 600 Hz or greater and a power of 40 VA or greater;
 11. Centrifuge housing/containers to contain the rotor tube assembly of a gas centrifuge, consisting of a rigid cylinder of wall thickness up to 30 mm with precision machined ends to locate the bearings and with one or more flanges for mounting;
-

-
12. Specially designed or prepared tubes for the extraction of UF₆ gas from within a centrifuge rotor tube by a Pitot tube action (that is, with an aperture facing into the circumferential gas flow within the rotor tube, for example by bending the end of a radially disposed tube) and capable of being fixed to the central gas extraction system;
 13. Not used;
 14. Not used;
- c. Equipment and components, specially designed or prepared for gaseous diffusion separation process, made of or protected by “materials resistant to corrosion by UF₆”, as follows:
1. Specially designed or prepared gaseous diffusion barriers, being thin, porous filters, with a pore size of 10 – 100 nm, a thickness of 5 mm or less, and for tubular forms, a diameter of 25 mm or less, made of metallic, polymer or ceramic “materials resistant to corrosion by UF₆”;
 2. Specially designed or prepared hermetically sealed vessels for containing the gaseous diffusion barrier, made of or protected by “materials resistant to corrosion by UF₆”;
 3. Specially designed or prepared compressors or gas blowers with a suction volume capacity of 1 m³ per minute or more of UF₆ and with a discharge pressure of up to 500 kPa and a pressure ratio of 10:1 or less, designed for long-term operation in the UF₆ environment, as well as separate assemblies of such compressors and gas blowers, made of or protected by “materials resistant to corrosion by UF₆”;
 4. Specially designed or prepared rotary shaft seals for compressors or blowers specified in 0B001.c.3. and designed for a buffer gas in-leakage rate of less than 1,000 cm³ per minute.;
 5. Specially designed or prepared heat exchangers made of or protected with “materials resistant to corrosion by UF₆”, and intended for a leakage pressure change rate of less than 10 Pa per hour under a pressure difference of 100 kPa.
 6. Not used;
- d. Equipment and components, specially designed or prepared for aerodynamic separation process, as follows:
1. Specially designed or prepared separation nozzles and assemblies thereof, consisting of slit-shaped, curved channels having a radius of curvature less than 1 mm, resistant to corrosion by UF₆, and having a knife-edge contained within the nozzle which separates the gas flowing through the nozzle into two streams;
 2. Specially designed or prepared vortex tubes and assemblies thereof, which are cylindrical or tapered, made of or protected by “materials resistant to corrosion by UF₆” and with one or more tangential inlets;
-

Note: Vortex tubes may be equipped with nozzle-type appendages at either or both ends. The feed gas enters the vortex tube tangentially at one end or through swirl vanes or at numerous tangential positions along the periphery of the tube.

3. Specially designed or prepared compressors or gas blowers made of or protected by “materials resistant to corrosion by UF₆” / materials resistant to corrosion by carrier gas (hydrogen or helium) mixture.
 4. Heat exchangers made of or protected by “materials resistant to corrosion by UF₆”;
 5. Specially designed or prepared separation element housings, made of or protected by “materials resistant to corrosion by UF₆” to contain vortex tubes or separation nozzles;
 6. Not used;
 7. Process systems for separating UF₆ from carrier gas (hydrogen or helium) to 1 ppm UF₆ content or less, including:
 - a. Cryogenic heat exchangers and cryoseparators capable freezing out UF₆;
 - b. Cryogenic refrigeration units capable freezing out UF₆;
 - c. Separation nozzle or vortex tube units for the separation of UF₆ from carrier gas;
 - d. UF₆ cold traps capable of temperatures of 253 K (-20°C) or less;
 8. Specially designed or prepared rotary shaft seals, with seal feed and seal exhaust connections, for sealing the shaft connecting compressors or gas blowers specified by 1B001.d.3. with the driver motor so as to ensure a reliable seal against out-leakage of process gas or in-leakage of air or seal gas into the inner chamber of the compressor or gas blower which is filled with a UF₆/carrier gas mixture.
- e. Equipment and components, specially designed or prepared for uranium enrichment using the chemical exchange separation process, as follows:
1. Countercurrent liquid-liquid exchange columns having mechanical power input with stage residence time of 30 seconds or less and resistant to concentrated hydrochloric acid (e.g. made of or protected by suitable plastic materials such as fluorocarbon polymers or glass);
 2. Liquid-liquid centrifugal contactors with stage residence time of 30 seconds or less and resistant to concentrated hydrochloric acid (e.g. made of or protected by suitable plastic materials such as fluorocarbon polymers or glass);
 3. Electrochemical reduction cells resistant to concentrated hydrochloric acid solutions, for reduction of uranium from one valence state to another;
-

-
4. Specially designed or prepared systems at the product end of the cascade for taking the U^{+4} out of the organic, stream, adjusting the acid concentration and feeding to the electrochemical reduction cells and, for those parts in contact with the process stream, made of or protected by suitable materials (e.g. glass, fluorocarbon polymers, polyphenyl sulphate, polyether sulfone and resin-impregnated graphite);
 5. Feed preparation systems for producing high purity uranium chloride solution consisting of dissolution, solvent extraction and/or ion exchange equipment for purification and electrolytic cells for reducing the uranium U^{+6} or U^{+4} to U^{+3} ;
 6. Uranium oxidation systems for oxidation of U^{+3} to U^{+4} for return to the uranium isotope separation cascade;
- f. Equipment and components, specially designed or prepared for ion-exchange separation process, as follows:
1. Fast reacting ion-exchange resins, pellicular or porous macro-reticulated resins in which the active chemical exchange groups are limited to a coating on the surface of an inactive porous support structure, and other composite structures in any suitable form, including particles or fibres, with diameters of 0.2 mm or less, resistant to concentrated hydrochloric acid and designed to have an exchange rate half-time of less than 10 seconds and capable of operating at temperatures in the range of 373 K (100°C) to 473 K (200°C);
 2. Ion exchange columns (cylindrical) with a diameter greater than 1,000 mm, made of or protected by materials resistant to concentrated hydrochloric acid (e.g. titanium or fluorocarbon plastics) and capable of operating at temperatures in the range of 373 K (100°C) to 473 K (200°C) and pressures above 0.7 MPa;
 3. Ion exchange reflux systems (chemical or electrochemical oxidation or reduction systems) for regeneration of the chemical reducing or oxidising agents used in ion exchange enrichment cascades;
- g. Equipment and components, specially designed or prepared for atomic vapour “laser” isotope separation process (AVLIS), as follows:
1. Uranium metal vaporisation systems for use in laser enrichment;
Note: These systems may contain electron beam guns and are designed to achieve a delivered power (1kW or greater) on the target sufficient to generate uranium metal vapour at a rate required for the laser enrichment function
 2. Liquid or vapour uranium metal handling systems for molten uranium, molten uranium alloys or uranium metal vapour, and specially designed or prepared components thereof;
-

Note: Liquid uranium metal handling systems may consist of crucibles, made of or protected by suitable corrosion and heat resistant materials (e.g. tantalum, yttria-coated graphite, graphite coated with other rare earth oxides or mixtures thereof), and cooling equipment for the crucibles.

N.B.: SEE ALSO 2A225.

3. Uranium metal product and tails collector systems made of or lined with materials resistant to the heat and corrosion of uranium metal vapour or liquid, such as yttria-coated graphite or tantalum;
4. Separator module housings (cylindrical or rectangular vessels) for containing the uranium metal vapour source, the electron beam gun and the product and tails collectors;
5. "Lasers" or "laser" systems for the separation of uranium isotopes with a spectrum frequency stabiliser for operation over extended periods of time;

N.B.: SEE ALSO 6A005 AND 6A205.

- h. Equipment and components, specially designed or prepared for molecular "laser" isotope separation process (MLIS) or chemical reaction by isotope selective "laser" activation (CRISLA), as follows:

1. Supersonic expansion nozzles for cooling mixtures of UF_6 and carrier gas to 150 K (-123°C) or less and made from "materials resistant to corrosion by UF_6 ";
2. Components or devices for collecting uranium product material or uranium tails material following illumination with laser light, and made of or protected by "materials resistant to corrosion by UF_5/UF_6 ";
3. Compressors for UF_6 /carrier gas mixtures, made of or protected by "materials resistant to corrosion by UF_6 ";
4. Equipment for fluorinating UF_5 (solid) to UF_6 (gas);
5. Process systems for separating UF_6 from carrier gas (e.g. nitrogen, argon or other gas) including:
 - a. Cryogenic heat exchangers and cryoseparators capable of temperatures of 153 K (-120°C) or less;
 - b. Cryogenic refrigeration units capable of temperatures of 153 K (-120°C) or less;
 - c. UF_6 cold traps capable of freezing out UF_6 ;
6. "Lasers" or "laser" systems for the separation of uranium isotopes with a spectrum frequency stabiliser for operation over extended periods of time;

N.B.: SEE ALSO 6A005 AND 6A205.

-
7. Specially designed or prepared rotary shaft seals, with seal feed and seal exhaust connections, for sealing the shaft connecting compressors specified by 1B001.h.3. with the driver motor so as to ensure a reliable seal against out-leakage of process gas or in-leakage of air or seal gas into the inner chamber of the compressor which is filled with a UF₆/carrier gas mixture
- i. Equipment and components, specially designed or prepared for plasma separation process, as follows:
 1. Microwave power sources and antennae for producing or accelerating ions, with an output frequency greater than 30 GHz and mean power output for ion production greater than 50 kW;
 2. Radio frequency ion excitation coils for frequencies of more than 100 kHz and capable of handling more than 40 kW mean power;
 3. Uranium plasma generation systems for use in plasma separation plants;
 4. Not used;
 5. Uranium metal product and tails collectors made of or protected by materials resistant to the heat and corrosion of uranium vapour such as yttria-coated graphite or tantalum;
 6. Separator module housings (cylindrical) for containing the uranium plasma source, radio-frequency drive coil and the product and tails collectors and made of a suitable non-magnetic material (e.g. stainless steel);
 - j. Equipment and components, specially designed or prepared for electromagnetic separation process, as follows:
 1. Ion sources, single or multiple, consisting of a vapour source, ioniser, and beam accelerator made of suitable non-magnetic materials (e.g. graphite, stainless steel, or copper) and capable of providing a total ion beam current of 50 mA or greater;
 2. Ion collector plates for collection of enriched or depleted uranium ion beams, consisting of two or more slits and pockets and made of suitable non-magnetic materials (e.g. graphite or stainless steel);
 3. Vacuum housings for uranium electromagnetic separators made of non-magnetic materials (e.g. stainless steel) and designed to operate at pressures of 0.1 Pa or lower;
 4. Magnet pole pieces with a diameter greater than 2 m;
 5. High voltage power supplies for ion sources, having all of the following characteristics:
 - a. Capable of continuous operation;
 - b. Output voltage of 20,000 V or greater;
 - c. Output current of 1 A or greater; and
 - d. Voltage regulation of better than 0.01% over a period of 8 hours;

N.B.: SEE ALSO 3A227.

-
6. Magnet power supplies (high power, direct current) having all of the following characteristics:
 - a. Capable of continuous operation with a current output of 500 A or greater at a voltage of 100 V or greater; and
 - b. Current or voltage regulation better than 0.01% over a period of 8 hours.

N.B.: SEE ALSO 3A226.

0B002 Specially designed or prepared auxiliary systems, equipment and components, as follows, for isotope separation plant specified in 0B001, made of or protected by “materials resistant to corrosion by UF₆”:

- a. Feed autoclaves, ovens or systems used for passing UF₆ to the enrichment process;
 - b. Desublimers or cold traps, used to remove UF₆ from the enrichment process for subsequent transfer upon heating;
 - c. Solidification or liquefaction stations used to remove UF₆ from the enrichment process by compressing and converting UF₆ to a liquid or solid form;
 - d. Product or tails stations used for transferring UF₆ into containers;
 - e. Piping systems and header systems specially designed for handling UF₆ within gaseous diffusion, centrifuge or aerodynamic cascades;
 - f. Vacuum systems and pumps as follows:
 1. Specially designed or prepared vacuum manifolds, vacuum headers and vacuum pumps having a suction capacity of 5 m³ per minute or more; or
 2. Vacuum pumps specially designed for use in UF₆-bearing atmospheres made of, or protected by, “materials resistant to corrosion by UF₆”.
- Note: Pumps specified by 0B002.f.2. may be either rotary or positive, may have displacement and fluorocarbon seals, and may have special working fluids present.*
- g. Specially designed or prepared bellows-sealed valves, manual or automated, shut-off or control, made of or protected by, “materials resistant to corrosion by UF₆”, for installation in main and auxiliary systems of gaseous diffusion enrichment plants.
 - h. Specially designed or prepared mass spectrometers capable of taking on-line samples from UF₆ gas streams and having all of the following:
 1. Capable of measuring ions of 320 atomic mass units or greater and having a resolution of better than 1 part in 320;
 2. Ion sources constructed of or protected by nickel, nickel-copper alloys with a nickel content of 60% or more by weight, or nickel-chrome alloys;
 3. Electron bombardment ionisation sources; and
-

-
4. Having a collector system suitable for isotopic analysis.
- 0B003 Plant for the conversion of uranium and equipment specially designed or prepared therefor, as follows:
- Systems for the conversion of uranium ore concentrates to UO_3 ;
 - Systems for the conversion of UO_3 to UF_6 ;
 - Systems for the conversion of UO_3 to UO_2 ;
 - Systems for the conversion of UO_2 to UF_4 ;
 - Systems for the conversion of UF_4 to UF_6 ;
 - Systems for the conversion of UF_4 to uranium metal;
 - Systems for the conversion of UF_6 to UO_2 ;
 - Systems for the conversion of UF_6 to UF_4 ;
 - Systems for the conversion of UO_2 to UCl_4 .
- 0B004 Plant for the production or concentration of heavy water, deuterium and deuterium compounds and specially designed or prepared equipment and components therefor, as follows:
- Plant for the production of heavy water, deuterium or deuterium compounds, as follows:
 - Water-hydrogen sulphide exchange plants;
 - Ammonia-hydrogen exchange plants;
 - Equipment and components, as follows:
 - Water-hydrogen sulphide exchange towers with diameters 1.5 m or greater and capable of operating at pressures greater than or equal to 2 MPa 300 psi;
 - Single stage, low head (i.e. 0.2 MPa or 30 psi) centrifugal blowers or compressors for hydrogen sulphide gas circulation (i.e. gas containing more than 70% H_2S) with a throughput capacity greater than or equal to $56 \text{ m}^3/\text{second}$ (120,000 SCFM) when operating at pressures greater than or equal to 1.8 MPa (260 psi) suction and having seals designed for wet H_2S service;
 - Ammonia-hydrogen exchange towers greater than or equal to 35 m (114.3 ft) in height with diameters of 1.5 m (4.9 ft) to 2.5 m (8.2 ft) capable of operating at pressures greater than 15 MPa (2225 psi);
 - Tower internals, including stage contactors, and stage pumps, including those which are submersible, for towers specified by 0B004.b.3;
 - Ammonia crackers with operating pressures greater than or equal to 3 MPa (450 psi) for heavy water production utilising the ammonia-hydrogen exchange process;

Part 2 Dual-use list

Category 0 Nuclear materials, facilities and equipment

	<ol style="list-style-type: none">6. Infrared absorption analysers capable of on-line hydrogen/deuterium ratio analysis where deuterium concentrations are equal to or greater than 90%;7. Catalytic burners for the conversion of enriched deuterium gas into heavy water utilising the ammonia-hydrogen exchange process;8. Complete heavy water upgrade systems, or columns therefor, for the upgrade of heavy water to reactor-grade deuterium concentration;9. Ammonia synthesis converters or ammonia synthesis units, in which the synthesis gas (nitrogen and hydrogen) is withdrawn from an ammonia/hydrogen high-pressure exchange column and the synthesised ammonia is returned to said column.
0B005	<p>Plant for the fabrication of “nuclear reactor” fuel elements and specially designed or prepared equipment therefor.</p> <p><i>Note: A plant for the fabrication of “nuclear reactor” fuel elements includes equipment which:</i></p> <ol style="list-style-type: none"><i>a. Normally comes into direct contact with or directly processes or controls the production flow of nuclear materials;</i><i>b. Seals the nuclear materials within the cladding;</i><i>c. Checks the integrity of the cladding or the seal;</i><i>d. Checks the finish treatment of the sealed fuel; or</i><i>e. Is used for assembling reactor fuel elements.</i>
0B006	<p>Plant for the reprocessing of irradiated “nuclear reactor” fuel elements, and specially designed or prepared equipment and components therefor.</p> <p><i>Note: 0B006 includes:</i></p> <ol style="list-style-type: none"><i>a. Plant for the reprocessing of irradiated “nuclear reactor” fuel elements including equipment and components which normally come into direct contact with and directly control the irradiated fuel and the major nuclear material and fission product processing streams;</i><i>b. Irradiated fuel element chopping machines, i.e. remotely operated equipment specially designed or prepared for use in a reprocessing plant specified by (a) above and intended to cut, chop, shred or shear irradiated “nuclear reactor” fuel assemblies, bundles or rods;</i><i>c. Dissolvers, i.e. critically safe tanks (e.g. small diameter, annular or slab tanks) specially designed or prepared for use in a reprocessing plant specified by (a) above, intended for the dissolution of irradiated “nuclear reactor” fuel, which are capable of withstanding hot, highly corrosive liquids, and which can be remotely loaded and maintained;</i>

-
- d. *Solvent extractors and solvent extraction equipment i.e. specially designed or prepared solvent extractors such as packed or pulse columns, miser settlers or centrifugal contactors for use in a plant for the reprocessing of irradiated fuel. Solvent extractors must be resistant to the corrosive effect of nitric acid. Solvent extractors are normally fabricated to extremely high standards (including special welding and inspection and quality assurance and quality control techniques) out of low carbon stainless steels, titanium, zirconium, or other high quality materials;*
- e. *Chemical holding or storage vessels, i.e. specially designed or prepared holding or storage vessels for use in a plant for the reprocessing of irradiated fuel. The holding or storage vessels must be resistant to the corrosive effects of nitric acid. The holding or storage vessels are normally fabricated of materials such as low carbon stainless steels, titanium or zirconium, or other high quality materials. Holding or storage vessels may be designed for remote operation and maintenance;*

Note: Holding or storage vessels may have the following features:

- 1. Walls or internal structures with a boron equivalent (calculated for all constituent elements as defined in Note 2 to 0C004) of at least two per cent;*
 - 2. A maximum diameter of 175 mm (7 in) for cylindrical vessels; or*
 - 3. A maximum width of 75 mm (3 in) for either a slab or annular vessel.*
- f. *Neutron measurement systems for process control, i.e. neutron measurement systems specially designed or prepared for the integration and use with automated process control systems in a plant for the reprocessing of irradiated fuel elements.*

Note: Note f does not include neutron detection and measurement instruments that are designed for nuclear material accountancy and safeguarding or any other application not related to integration and use with automated process control systems in a plant for the reprocessing of irradiated fuel elements.

- 0B007 Plant for the conversion of plutonium and equipment specially designed or prepared therefor, as follows:
- a. Specially designed or prepared systems for the conversion of plutonium nitrate to oxide;
 - b. Specially designed or prepared systems for plutonium metal production.

Part 2 Dual-use list

Category 0 Nuclear materials, facilities and equipment

0C	Materials
0C003	Deuterium, heavy water (deuterium oxide) or any other deuterium compounds, for use in a “nuclear reactor” specified by 0A001.a, in which the ratio of deuterium to hydrogen atoms exceeds 1:5,000.
0C004	<p>Graphite having a purity level of less than 5 parts per million ‘boron equivalent’ and with a density greater than 1.50 g/cm³ for use in a “nuclear reactor” specified by 0A001.a., in quantities exceeding 1 kilogram.</p> <p>N.B.: SEE ALSO 1C107</p> <p><i>Note 1: For the purpose of export control, the Government will determine whether or not the exports of graphite meeting the above specifications are for “nuclear reactor” use.</i></p> <p><i>Note 2: In 0C004, ‘boron equivalent’ (BE) may be determined experimentally or is calculated as the sum of BE_z for impurities (excluding BE_{carbon} since carbon is not considered an impurity) including boron, where:</i></p> <p><i>BE_z (ppm) = CF x concentration of element Z in ppm;</i></p> <p><i>where CF is the conversion factor:</i></p> $\frac{\sigma_z A_B}{\sigma_B A_z}$ <p><i>and σ_B and σ_z are the thermal neutron capture cross sections (in barns) for naturally occurring boron and element Z respectively; and A_B and A_z are the atomic masses of naturally occurring boron and element Z respectively.</i></p>
0C005	<p>Specially prepared compounds or powders for the manufacture of filters specified by 0B001.c.1.</p> <p><i>Note: Compounds and powders specified by 0C005 include nickel or alloys containing 60% or more nickel, aluminium oxide, or UF₆-resistant fully fluorinated hydrocarbon polymers have a purity of 99.9% by weight or more, a particle size less than 10 µm, and a high degree of particle size uniformity, which are specially prepared for the manufacture of gaseous diffusion barriers.</i></p>
0D	Software
0D001	“Software” specially designed or modified for the “development”, “production” or “use” of goods specified in this Category.

0E	Technology
0E001	“Technology” according to the Nuclear Technology Note for the “development”, “production” or “use” of goods specified in this Category.

Category 1—Materials, chemicals, microorganisms and toxins

1A Systems, Equipment and Components

1A001 Components made from fluorinated compounds, as follows:

- a. Seals, gaskets, sealants or fuel bladders, specially designed for “aircraft” or aerospace use, made from more than 50% by weight of any of the materials specified in 1C009.b. or 1C009.c.;
- b. Piezoelectric polymers and copolymers, made from vinylidene fluoride (CAS 75–38–7) materials, specified in 1C009.a., having all of the following:
 1. In sheet or film form; and
 2. With a thickness exceeding 200 µm.
- c. Seals, gaskets, valve seats, bladders or diaphragms, having all of the following:
 1. Made from fluoroelastomers containing at least one vinyl ether group as a constitutional unit; and
 2. Specially designed for “aircraft”, aerospace or ‘missile’ use.

Note: In 1A001.c., ‘missile’ means complete rocket systems and unmanned aerial vehicle systems.

1A002 “Composite” structures or laminates, having any of the following:

N.B.: SEE ALSO 1A202, 9A010 and 9A110

- a. Consisting of an organic “matrix” and materials specified in 1C010.c., 1C010.d. or 1C010.e.; or
- b. Consisting of a metal or carbon “matrix”, and any of the following:
 1. Carbon “fibrous or filamentary materials” having all of the following:
 - a. A “specific modulus” exceeding 10.15×10^6 m; and
 - b. A “specific tensile strength” exceeding 17.7×10^4 m; or
 2. Materials specified in 1C010.c.

Note 1: 1A002 does not control composite structures or laminates made from epoxy resin impregnated carbon “fibrous or filamentary materials” for the repair of “civil aircraft” structures or laminates, having all of the following:

- a. An area not exceeding 1 m²;
- b. A length not exceeding 2.5 m; and
- c. A width exceeding 15 mm.

Note 2: 1A002 does not control finished or semi-finished items, specially designed for purely civilian applications as follows:

- a. Sporting goods;*
- b. Automotive industry;*
- c. Machine tool industry;*
- d. Medical applications.*

Note 3: 1A002.b.1. does not control finished or semi-finished items containing a maximum of two dimensions of interwoven filaments and specially designed for applications as follows:

- a. Metal heat-treatment furnaces for tempering metals;*
- b. Silicon boule production equipment.*

Note 4: 1A002 does not control finished items specially designed for a specific application.

1A003 Manufactures of non-“fusible” aromatic polyimides in film, sheet, tape or ribbon form having any of the following :

- a. A thickness exceeding 0.254 mm; or
- b. Coated or laminated with carbon, graphite, metals or magnetic substances.

Note: 1A003 does not control manufactures when coated or laminated with copper and designed for the production of electronic printed circuit boards.

N.B.: For “fusible” aromatic polyimides in any form, see 1C008.a.3.

1A004 Protective and detection equipment and components, other than those specified in Munitions List, as follows:

N.B.: SEE ALSO 2B351 AND 2B352.

- a. Full face masks, filter canisters and decontamination equipment therefor, designed or modified for defence against any of the following, and specially designed components therefor:

Note: 1A004.a. includes Powered Air Purifying Respirators (PAPR) that are designed or modified for defence against agents or materials, listed in 1A004.a.

Technical Note:

For the purposes of 1A004.a., full face masks are also known as gas masks.

1. Biological agents “adapted for use in war”;
2. Radioactive materials “adapted for use in war”;
3. Chemical warfare (CW) agents; or
4. “Riot control agents”, including:
 - a. α -Bromobenzeneacetonitrile, (Bromobenzyl cyanide) (CA) (CAS 5798-79-8);

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
- b. [(2-chlorophenyl) methylene] propanedinitrile, (o-Chlorobenzylidenemalononitrile) (CS) (CAS 2698-41-1);
 - c. 2-Chloro-1-phenylethanone, Phenylacetyl chloride (o-chloroacetophenone) (CN) (CAS 532-27-4);
 - d. Dibenz-(b,f)-1,4-oxazepine (CR) (CAS 257-07-8);
 - e. 10-Chloro-5,10-dihydrophenarsazine, (Phenarsazine chloride), (Adamsite), (DM) (CAS 578-94-9);
 - f. N-Nonanoylmorpholine, (MPA) (CAS 5299-64-9);
- b. Protective suits, gloves and shoes, specially designed or modified for defence against any of the following:
- 1. Biological agents “adapted for use in war”;
 - 2. Radioactive materials “adapted for use in war”; or
 - 3. Chemical warfare (CW) agents;
- c. Nuclear, biological and chemical (NBC) detection systems, specially designed or modified for detection or identification of any of the following, and specially designed components therefor:
- 1. Biological agents “adapted for use in war”;
 - 2. Radioactive materials “adapted for use in war”; or
 - 3. Chemical warfare (CW) agents;
- d. Electronic equipment designed for automatically detecting or identifying the presence of “explosives” residues and utilising ‘trace detection’ techniques (e.g., surface acoustic wave, ion mobility spectrometry, differential mobility spectrometry, mass spectrometry).

Technical Note:

‘Trace detection’ is defined as the capability to detect less than 1 ppm vapour, or 1 mg solid or liquid.

Note 1: IA004.d. does not control equipment specially designed for laboratory use.

Note 2: IA004.d. does not control non-contact walk-through security portals.

Note: IA004 does not control:

- a. *Personal radiation monitoring dosimeters;*
 - b. *Occupational health or safety equipment limited by design or function to protect against hazards specific to residential safety or civil industries, including:*
 - 1. *mining;*
 - 2. *quarrying;*
 - 3. *agriculture;*
 - 4. *pharmaceutical;*
 - 5. *medical;*
 - 6. *veterinary;*
 - 7. *environmental;*
 - 8. *waste management;*
-

9. food industry.

Technical Notes:

1. 1A004 includes equipment and components that have been identified, successfully tested to national standards or otherwise proven effective, for the detection of or defence against radioactive materials “adapted for use in war”, biological agents “adapted for use in war”, chemical warfare agents, ‘simulants’ or “riot control agents”, even if such equipment or components are used in civil industries such as mining, quarrying, agriculture, pharmaceuticals, medical, veterinary, environmental, waste management, or the food industry.
2. ‘Simulant’: A substance or material that is used in place of toxic agent (chemical or biological) in training, research, testing or evaluation.

1A005 Body armour and components therefor, as follows:

- a. Soft body armour not manufactured to military standards or specifications, or to their equivalents, and specially designed components therefor;
- b. Hard body armour plates providing ballistic protection equal to or less than level IIIA (NIJ 0101.06, July 2008) or national equivalents.

N.B.1.: For “fibrous or filamentary materials” used in the manufacture of body armour, see 1C010.

N.B.2.: For body armour manufactured to military standards or specifications, see entry ML13.d.

Note 1: 1A005 does not control body armour or protective garments, when accompanying their user for the user’s own personal protection.

Note 2: 1A005 does not control body armour designed to provide frontal protection only from both fragment and blast from non-military explosive devices.

Note 3: 1A005 does not apply to body armour designed to provide protection only from knife, spike, needle or blunt trauma.

1A006 Equipment, specially designed or modified for the disposal of improvised explosive devices, as follows, and specially designed components and accessories therefor:

N.B.: SEE ALSO MUNITIONS LIST.

- a. Remotely operated vehicles;
- b. ‘Disruptors’.

Technical Note:

‘Disruptors’ are devices specially designed for the purpose of preventing the operation of an explosive device by projecting a liquid, solid or frangible projectile.

N.B.: For equipment specially designed for military use for the disposal of improvised explosive devices, see also ML4.

Note: 1A006 does not control equipment when accompanying its operator.

1A007 Equipment and devices, specially designed to initiate charges and devices containing energetic materials, by electrical means, as follows:

N.B.: SEE ALSO MUNITIONS LIST, 3A229 AND 3A232.

- a. Explosive detonator firing sets (initiation systems, firesets) including electronically-charged, explosively-driven and optically-driven firing sets designed to drive explosive detonators specified in 1A007.b.;
- b. Electrically driven explosive detonators as follows:
 1. Exploding bridge (EB);
 2. Exploding bridge wire (EBW);
 3. Slapper;
 4. Exploding foil initiators (EFI).

Technical Notes:

1. *The word initiator or igniter is sometimes used in place of the word detonator.*
2. *For the purpose of 1A007.b. the detonators of concern all utilise a small electrical conductor (bridge, bridge wire, or foil) that explosively vaporises when a fast, high-current electrical pulse is passed through it. In non-slapper types, the exploding conductor starts a chemical detonation in a contacting high explosive material such as PETN (pentaerythritoltetranitrate). In slapper detonators, the explosive vaporisation of the electrical conductor drives a flyer or slapper across a gap, and the impact of the slapper on an explosive starts a chemical detonation. The slapper in some designs is driven by magnetic force. The term exploding foil detonator may refer to either an EB or a slapper-type detonator.*

Note: Optically driven firing sets include both those employing laser initiation and laser charging. Explosively-driven firing sets include both explosive ferroelectric and explosive ferromagnetic firing set types.

1A008 Charges, devices and components, as follows:

- a. 'Shaped charges' having all of the following:
 1. Net Explosive Quantity (NEQ) greater than 90 g; and
 2. Outer casing diameter equal to or greater than 75 mm;
- b. Linear shaped cutting charges having all of the following, and specially designed components therefor:
 1. An explosive load greater than 40 g/m; and
 2. A width of 10 mm or more;
- c. Detonating cord with explosive core load greater than 64 g/m;

-
- d. Cutters, other than those specified in 1A008.b., and severing tools, having a Net Explosive Quantity (NEQ) greater than 3.5 kg.

Note: The only charges and devices specified in 1A008. are those containing “explosives” listed in the Annex to Category 1 and mixtures thereof.

Technical Note:

‘Shaped charges’ are explosive charges shaped to focus the effects of the explosive blast.

- 1A102 Resaturated pyrolysed carbon-carbon components designed for space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.

- 1A202 Composite structures, other than those specified in 1A002, in the form of tubes and having both of the following characteristics:

N.B.: SEE ALSO 9A010 AND 9A110.

- a. An inside diameter of between 75 mm and 400 mm; and
b. Made with any of the “fibrous or filamentary materials” specified in 1C010.a. or b. or 1C210.a. or with carbon prepreg materials specified in 1C210.c.

- 1A225 Platinised catalysts specially designed or prepared for promoting the hydrogen isotope exchange reaction between hydrogen and water for the recovery of tritium from heavy water or for the production of heavy water.

- 1A226 Specialised packings which may be used in separating heavy water from ordinary water, having both of the following characteristics:

- a. Made of phosphor bronze mesh chemically treated to improve wettability; and
b. Designed to be used in vacuum distillation towers.

- 1A227 High-density (lead glass or other) radiation shielding windows, having all of the following characteristics, and specially designed frames therefor:

- a. A ‘cold area’ greater than 0.09 m²;
b. A density greater than 3 g/cm³; and
c. A thickness of 100 mm or greater.

Technical Note:

In 1A227 the term ‘cold area’ means the viewing area of the window exposed to the lowest level of radiation in the design application.

1B Test, Inspection and Production Equipment

1B001 Equipment for the production of fibres, prepregs, preforms or “composites”, specified in 1A002 or 1C010, as follows, and specially designed components and accessories therefor:

N.B.: SEE ALSO 1B101 AND 1B201.

- a. Filament winding machines of which the motions for positioning, wrapping and winding fibres are coordinated and programmed in three or more axes, specially designed for the manufacture of “composite” structures or laminates, from “fibrous or filamentary materials”;
- b. ‘Tape-laying machines’, of which the motions for positioning and laying tape are coordinated and programmed in five or more ‘primary servo positioning’ axes, specially designed for the manufacture of “composite” airframe or missile structures;

Technical Note:

For the purposes of 1B001.b., ‘tape-laying machines’ have the ability to lay one or more ‘filament bands’ limited to widths greater than 25 mm and less than or equal to 305 mm, and to cut and restart individual ‘filament band’ courses during the laying process.

- c. Multidirectional, multidimensional weaving machines or interlacing machines, including adapters and modification kits, for weaving, interlacing or braiding fibres, to manufacture “composite” structures;

Technical Note:

For the purposes of 1B001.c., the technique of interlacing includes knitting.

- d. Equipment specially designed or adapted for the production of reinforcement fibres, as follows:
 1. Equipment for converting polymeric fibres (such as polyacrylonitrile, rayon, pitch or polycarbosilane) into carbon fibres or silicon carbide fibres, including special equipment to strain the fibre during heating;
 2. Equipment for the chemical vapour deposition of elements or compounds, on heated filamentary substrates, to manufacture silicon carbide fibres;
 3. Equipment for the wet-spinning of refractory ceramics (such as aluminium oxide);
 4. Equipment for converting aluminium containing precursor fibres into alumina fibres by heat treatment;
 - e. Equipment for producing prepregs specified in 1C010.e. by the hot melt method;
 - f. Non-destructive inspection equipment specially designed for “composite” materials, as follows:
 1. X-ray tomography systems for three dimensional defect inspection;
-

-
2. Numerically controlled ultrasonic testing machines of which the motions for positioning transmitters or receivers are simultaneously coordinated and programmed in four or more axes to follow the three dimensional contours of the component under inspection.
 - g. Tow-placement machines, of which the motions for positioning and laying tows or sheets are coordinated and programmed in two or more 'primary servo positioning' axes, specially designed for the manufacture of "composite" airframe or "missile" structures.

Technical Notes:

1. *For the purposes of 1B001., 'primary servo positioning' axes control, under computer program direction, the position of the end effector (i.e., head) in space relative to the work piece at the correct orientation and direction to achieve the desired process.*
2. *For the purposes of 1B001., a 'filament band' is a single continuous width of fully or partially resin-impregnated tape, tow or fibre.*

1B002 Equipment for producing metal alloys, metal alloy powder or alloyed materials, specially designed to avoid contamination and specially designed for use in one of the processes specified in 1C002.c.2.

N.B.: SEE ALSO 1B102.

1B003 Tools, dies, moulds or fixtures, for "superplastic forming" or "diffusion bonding" titanium, aluminium or their alloys, specially designed for the manufacture of any of the following:

- a. Airframe or aerospace structures;
- b. "Aircraft" or aerospace engines; or
- c. Specially designed components for structures specified in 1B003.a. or for engines specified in 1B003.b.

1B101 Equipment, other than that specified in 1B001, for the "production" of structural composites as follows; and specially designed components and accessories therefor:

N.B.: SEE ALSO 1B201.

Note: Components and accessories specified in 1B101 include moulds, mandrels, dies, fixtures and tooling for the preform pressing, curing, casting, sintering or bonding of composite structures, laminates and manufactures thereof.

- a. Filament winding machines or fibre placement machines, of which the motions for positioning, wrapping and winding fibres can be coordinated and programmed in three or more axes, designed to fabricate composite structures or laminates from fibrous or filamentary materials, and coordinating and programming controls;

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
- b. Tape-laying machines of which the motions for positioning and laying tape and sheets can be coordinated and programmed in two or more axes, designed for the manufacture of composite airframe and “missile” structures;
 - c. Equipment designed or modified for the “production” of “fibrous or filamentary materials” as follows:
 - 1. Equipment for converting polymeric fibres (such as polyacrylonitrile, rayon or polycarbosilane) including special provision to strain the fibre during heating;
 - 2. Equipment for the vapour deposition of elements or compounds on heated filament substrates;
 - 3. Equipment for the wet-spinning of refractory ceramics (such as aluminium oxide);
 - d. Equipment designed or modified for special fibre surface treatment or for producing prepreps and preforms specified in entry 9C110.

Note: 1B101.d. includes rollers, tension stretchers, coating equipment, cutting equipment and clicker dies.

1B102 Metal powder “production equipment”, other than that specified in 1B002, and components as follows:

N.B.: SEE ALSO 1B115.b.

- a. Metal powder “production equipment” usable for the “production”, in a controlled environment, of spherical, spheroidal or atomised materials specified in 1C011.a., 1C011.b., 1C111.a.1., 1C111.a.2. or in the Munitions List;
- b. Specially designed components for “production equipment” specified in 1B002 or 1B102.a.

Note: 1B102 includes:

- a. *Plasma generators (high frequency arc-jet) usable for obtaining sputtered or spherical metallic powders with organisation of the process in an argon-water environment;*
- b. *Electroburst equipment usable for obtaining sputtered or spherical metallic powders with organisation of the process in an argon-water environment;*
- c. *Equipment usable for the “production” of spherical aluminium powders by powdering a melt in an inert medium (e.g. nitrogen).*

1B115 Equipment, other than that specified in 1B002 or 1B102, for the production of propellant and propellant constituents, as follows, and specially designed components therefor:

- a. “Production equipment” for the “production”, handling or acceptance testing of liquid propellants or propellant constituents specified in 1C011.a., 1C011.b., 1C111 or in the Munitions List;

-
- b. “Production equipment” for the “production”, handling, mixing, curing, casting, pressing, machining, extruding or acceptance testing of solid propellants or propellant constituents specified in 1C011.a., 1C011.b., 1C111 or in the Munitions List.
- Note:* 1B115.b. does not control batch mixers, continuous mixers or fluid energy mills. For the control of batch mixers, continuous mixers and fluid energy mills see 1B117, 1B118 and 1B119.
- Note 1:* For equipment specially designed for the production of military goods, see the Munitions List.
- Note 2:* 1B115 does not control equipment for the “production”, handling and acceptance testing of boron carbide.
- 1B116 Specially designed nozzles for producing pyrolytically derived materials formed on a mould, mandrel or other substrate from precursor gases which decompose in the 1,573 K (1,300°C) to 3,173 K (2,900°C) temperature range at pressures of 130 Pa to 20 kPa.
- 1B117 Batch mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with temperature control capability of the mixing chamber and having all of the following, and specially designed components therefor:
- a. A total volumetric capacity of 110 litres or more; and
- b. At least one ‘mixing/kneading shaft’ mounted off centre.
- Technical Note:*
In 1B117.b, the term ‘mixing/kneading shaft’ does not refer to deagglomerators or knife-spindles.
- 1B118 Continuous mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with a temperature control capability of the mixing chamber having any of the following, and specially designed components therefor:
- a. Two or more mixing/kneading shafts; or
- b. A single rotating shaft which oscillates and having kneading teeth/pins on the shaft as well as inside the casing of the mixing chamber.
- 1B119 Fluid energy mills usable for grinding or milling substances specified in 1C011.a., 1C011.b., 1C111 or in the Munitions List, and specially designed components therefor.
- 1B201 Filament winding machines, other than those specified in 1B001 or 1B101, and related equipment, as follows:
- a. Filament winding machines having all of the following characteristics:
1. Having motions for positioning, wrapping, and winding fibres coordinated and programmed in two or more axes;
-

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

	<ul style="list-style-type: none">2. Specially designed to fabricate composite structures or laminates from “fibrous or filamentary materials”; and3. Capable of winding cylindrical tubes with an internal diameter between 75 and 650 mm and lengths of 300 mm or greater; <ul style="list-style-type: none">b. Coordinating and programming controls for the filament winding machines specified in 1B201.a.;c. Precision mandrels for the filament winding machines specified in 1B201.a.
1B225	Electrolytic cells for fluorine production with an output capacity greater than 250 g of fluorine per hour.
1B226	<p>Electromagnetic isotope separators designed for, or equipped with, single or multiple ion sources capable of providing a total ion beam current of 50 mA or greater.</p> <p><i>Note: 1B226 includes separators:</i></p> <ul style="list-style-type: none">a. Capable of enriching stable isotopes;b. With the ion sources and collectors both in the magnetic field and those configurations in which they are external to the field.
1B227	Not used.
1B228	<p>Hydrogen-cryogenic distillation columns having all of the following characteristics:</p> <ul style="list-style-type: none">a. Designed for operation with internal temperatures of 35 K (-238°C) or less;b. Designed for operation at an internal pressure of 0.5 to 5 MPa;c. Constructed of either:<ul style="list-style-type: none">1. Stainless steel of the 300 series with low sulphur content and with an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; or2. Equivalent materials which are both cryogenic and H₂-compatible; andd. With internal diameters of 30 cm or greater and ‘effective lengths’ of 4 m or greater. <p><i>Technical Note:</i></p> <p><i>The term ‘effective length’ means the active height of packing material in a packed-type column, or the active height of internal contactor plates in a plate-type column.</i></p>

-
- 1B229 Water-hydrogen sulphide exchange tray columns and ‘internal contactors’, as follows:
- N.B.: For columns which are specially designed or prepared for the production of heavy water, see 0B004.*
- a. Water-hydrogen sulphide exchange tray columns, having all of the following characteristics:
 1. Can operate at pressures of 2 MPa or greater;
 2. Constructed of carbon steel having an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; and
 3. With a diameter of 1.8 m or greater;
 - b. ‘Internal contactors’ for the water-hydrogen sulphide exchange tray columns specified in 1B229.a.
- Technical Note:*
‘Internal contactors’ of the columns are segmented trays which have an effective assembled diameter of 1.8 m or greater, are designed to facilitate countercurrent contacting and are constructed of stainless steels with a carbon content of 0.03% or less. These may be sieve trays, valve trays, bubble cap trays, or turbogrid trays.
- 1B230 Pumps capable of circulating solutions of concentrated or dilute potassium amide catalyst in liquid ammonia (KNH_2/NH_3), having all of the following characteristics:
- a. Airtight (i.e., hermetically sealed);
 - b. A capacity greater than 8.5 m³/h; and
 - c. Either of the following characteristics:
 1. For concentrated potassium amide solutions (1% or greater), an operating pressure of 1.5 to 60 MPa; or
 2. For dilute potassium amide solutions (less than 1%), an operating pressure of 20 to 60 MPa.
- 1B231 Tritium facilities or plants, and equipment therefor, as follows:
- a. Facilities or plants for the production, recovery, extraction, concentration, or handling of tritium;
 - b. Equipment for tritium facilities or plants, as follows:
 1. Hydrogen or helium refrigeration units capable of cooling to 23 K (-250°C) or less, with heat removal capacity greater than 150 W;
 2. Hydrogen isotope storage or purification systems using metal hydrides as the storage or purification medium.
-

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
- 1B232 Turboexpanders or turboexpander-compressor sets having both of the following characteristics:
- a. Designed for operation with an outlet temperature of 35 K (-238°C) or less; and
 - b. Designed for a throughput of hydrogen gas of 1000 kg/h or greater.
- 1B233 Lithium isotope separation facilities or plants, and systems and equipment therefor, as follows:
- a. Facilities or plants for the separation of lithium isotopes;
 - b. Equipment for the separation of lithium isotopes based on the lithium-mercury amalgam process, as follows:
 1. Packed liquid-liquid exchange columns specially designed for lithium amalgams;
 2. Mercury or lithium amalgam pumps;
 3. Lithium amalgam electrolysis cells;
 4. Evaporators for concentrated lithium hydroxide solution.
 - c. Ion exchange systems specially designed for lithium isotope separation, and specially designed component parts therefor;
 - d. Chemical exchange systems (employing crown ethers, cryptands, or lariat ethers) specially designed for lithium isotope separation, and specially designed component parts therefor.
- N.B.: SEE ALSO 0B001 FOR LITHIUM ISOTOPE SEPARATION EQUIPMENT AND COMPONENTS FOR THE PLASMA SEPARATION PROCESS THAT ARE DIRECTLY APPLICABLE TO URANIUM ISOTOPE SEPARATION**

1C Materials

Technical Note:

Metals and alloys:

Unless provision to the contrary is made, the words ‘metals’ and ‘alloys’ in 1C001 to 1C012 cover crude and semi-fabricated forms, as follows:

Crude forms:

Anodes, balls, bars (including notched bars and wire bars), billets, blocks, blooms, brickets, cakes, cathodes, crystals, cubes, dice, grains, granules, ingots, lumps, pellets, pigs, powder, rondelles, shot, slabs, slugs, sponge, sticks;

Semi-fabricated forms (whether or not coated, plated, drilled or punched):

- a. *Wrought or worked materials fabricated by rolling, drawing, extruding, forging, impact extruding, pressing, graining, atomising, and grinding, i.e.: angles, channels, circles, discs, dust, flakes, foils and leaf, forging, plate, powder, pressings and stampings, ribbons, rings, rods (including bare welding rods, wire rods, and rolled wire), sections, shapes, sheets, strip, pipe and tubes (including tube rounds, squares, and hollows), drawn or extruded wire;*
- b. *Cast material produced by casting in sand, die, metal, plaster or other types of moulds, including high pressure castings, sintered forms, and forms made by powder metallurgy.*

The object of the control should not be defeated by the export of non-listed forms alleged to be finished products but representing in reality crude forms or semi-fabricated forms.

1C001 Materials specially designed for use as absorbers of electromagnetic waves, or intrinsically conductive polymers, as follows:

N.B.: SEE ALSO 1C101.

- a. Materials for absorbing frequencies exceeding 2×10^8 Hz but less than 3×10^{12} Hz;

Note 1: 1C001.a. does not control:

- a. *Hair type absorbers, constructed of natural or synthetic fibres, with non-magnetic loading to provide absorption;*
- b. *Absorbers having no magnetic loss and whose incident surface is non-planar in shape, including pyramids, cones, wedges and convoluted surfaces;*
- c. *Planar absorbers, having all of the following:*
 - 1. *Made from any of the following:*
 - a. *Plastic foam materials (flexible or non-flexible) with carbon-loading, or organic materials, including binders, providing more than 5% echo compared with metal over a bandwidth exceeding $\pm 15\%$ of the centre frequency of the incident energy, and not capable of withstanding temperatures exceeding 450 K (177°C); or*
 - b. *Ceramic materials providing more than 20% echo compared with metal over a bandwidth exceeding $\pm 15\%$ of the centre frequency of the incident energy, and not capable of withstanding temperatures exceeding 800 K (527°C);*

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

Technical Note:

Absorption test samples for 1C001.a. Note: 1.c.1. should be a square at least 5 wavelengths of the centre frequency on a side and positioned in the far field of the radiating element.

2. *Tensile strength less than $7 \times 10^6 \text{ N/m}^2$; and*
3. *Compressive strength less than $14 \times 10^6 \text{ N/m}^2$;*
- d. *Planar absorbers made of sintered ferrite, having all of the following:*
 1. *A specific gravity exceeding 4.4; and*
 2. *A maximum operating temperature of 548 K (275°C).*

Note 2: Nothing in Note 1 to 1C001.a. releases magnetic materials to provide absorption when contained in paint.

- b. *Materials for absorbing frequencies exceeding $1.5 \times 10^{14} \text{ Hz}$ but less than $3.7 \times 10^{14} \text{ Hz}$ and not transparent to visible light;*

Note: 1C001.b. does not apply to materials, specially designed or formulated for any of the following applications:

- a. *Laser marking of polymers; or*
- b. *Laser welding of polymers.*

- c. *Intrinsically conductive polymeric materials with a 'bulk electrical conductivity' exceeding 10,000 S/m (Siemens per metre) or a 'sheet (surface) resistivity' of less than 100 ohms/square, based on any of the following polymers:*

1. *Polyaniline;*
2. *Polypyrrole;*
3. *Polythiophene;*
4. *Poly phenylene-vinylene; or*
5. *Poly thienylene-vinylene.*

Technical Note:

'Bulk electrical conductivity' and 'sheet (surface) resistivity' should be determined using ASTM D-257 or national equivalents.

Note: 1C001.c. does not apply to materials in a liquid form.

1C002 Metal alloys, metal alloy powder and alloyed materials, as follows:

N.B.: SEE ALSO 1C202.

Note: 1C002 does not control metal alloys, metal alloy powder and alloyed materials for coating substrates.

Technical Notes:

1. *The metal alloys in 1C002 are those containing a higher percentage by weight of the stated metal than of any other element.*

-
2. *'Stress-rupture life' should be measured in accordance with ASTM standard E-139 or national equivalents.*
 3. *'Low cycle fatigue life' should be measured in accordance with ASTM Standard E-606 'Recommended Practice for Constant-Amplitude Low-Cycle Fatigue Testing' or national equivalents. Testing should be axial with an average stress ratio equal to 1 and a stress-concentration factor (K_t) equal to 1. The average stress is defined as maximum stress minus minimum stress divided by maximum stress.*
 - a. Aluminides, as follows:
 1. Nickel aluminides containing a minimum of 15 % by weight aluminium, a maximum of 38 % by weight aluminium and at least one additional alloying element;
 2. Titanium aluminides containing 10 % by weight or more aluminium and at least one additional alloying element;
 - b. Metal alloys, as follows, made from the powder or particulate material specified in 1C002.c.:
 1. Nickel alloys having any of the following:
 - a. A 'stress-rupture life' of 10,000 hours or longer at 923 K (650°C) at a stress of 676 MPa; or
 - b. A 'low cycle fatigue life' of 10,000 cycles or more at 823 K (550°C) at a maximum stress of 1,095 MPa;
 2. Niobium alloys having any of the following:
 - a. A 'stress-rupture life' of 10,000 hours or longer at 1,073 K (800°C) at a stress of 400 MPa; or
 - b. A 'low cycle fatigue life' of 10,000 cycles or more at 973 K (700°C) at a maximum stress of 700 MPa;
 3. Titanium alloys having any of the following:
 - a. A 'stress-rupture life' of 10,000 hours or longer at 723 K (450°C) at a stress of 200 MPa; or
 - b. A 'low cycle fatigue life' of 10,000 cycles or more at 723 K (450°C) at a maximum stress of 400 MPa;
 4. Aluminium alloys having any of the following:
 - a. A tensile strength of 240 MPa or more at 473 K (200°C); or
 - b. A tensile strength of 415 MPa or more at 298 K (25°C);
 5. Magnesium alloys having all of the following:
 - a. A tensile strength of 345 MPa or more; and
 - b. A corrosion rate of less than 1 mm/year in 3% sodium chloride aqueous solution measured in accordance with ASTM standard G-31 or national equivalents;
 - c. Metal alloy powder or particulate material, having all of the following:
 1. Made from any of the following composition systems:

Technical Note:
X in the following equals one or more alloying elements.
-

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

	<ul style="list-style-type: none">a. Nickel alloys (Ni-Al-X, Ni-X-Al) qualified for turbine engine parts or components, i.e. with less than 3 non-metallic particles (introduced during the manufacturing process) larger than 100 µm in 10⁹ alloy particles;b. Niobium alloys (Nb-Al-X or Nb-X-Al, Nb-Si-X or Nb-X-Si, Nb-Ti-X or Nb-X-Ti);c. Titanium alloys (Ti-Al-X or Ti-X-Al);d. Aluminium alloys (Al-Mg-X or Al-X-Mg, Al-Zn-X or Al-X-Zn, Al-Fe-X or Al-X-Fe); ore. Magnesium alloys (Mg-Al-X or Mg-X-Al);
	<ul style="list-style-type: none">2. Made in a controlled environment by any of the following processes:<ul style="list-style-type: none">a. “Vacuum atomisation”;b. “Gas atomisation”;c. “Rotary atomisation”;d. “Splat quenching”;e. “Melt spinning” and “comminution”;f. “Melt extraction” and “comminution”; org. “Mechanical alloying”; and3. Capable of forming materials specified in 1C002.a. or 1C002.b.;
	<ul style="list-style-type: none">d. Alloyed materials having all of the following:<ul style="list-style-type: none">1. Made from any of the composition systems specified in 1C002.c.1.;2. In the form of uncomminuted flakes, ribbons or thin rods; and3. Produced in a controlled environment by any of the following:<ul style="list-style-type: none">a. “Splat quenching”;b. “Melt spinning”; orc. “Melt extraction”.
1C003	<p>Magnetic metals, of all types and of whatever form, having any of the following:</p> <ul style="list-style-type: none">a. Initial relative permeability of 120,000 or more and a thickness of 0.05 mm or less; <i>Technical Note:</i> <i>Measurement of initial permeability must be performed on fully annealed materials.</i>b. Magnetostrictive alloys having any of the following:<ul style="list-style-type: none">1. A saturation magnetostriction of more than 5×10^{-4}; or2. A magnetomechanical coupling factor (k) of more than 0.8; orc. Amorphous or ‘nanocrystalline’ alloy strips, having all of the following:<ul style="list-style-type: none">1. A composition having a minimum of 75 % by weight of iron, cobalt or nickel;

2. A saturation magnetic induction (B_S) of 1.6 T or more; and
3. Any of the following:
 - a. A strip thickness of 0.02 mm or less; or
 - b. An electrical resistivity of 2×10^{-4} ohm cm or more.

Technical Note:

'Nanocrystalline' materials in 1C003.c. are those materials having a crystal grain size of 50 nm or less, as determined by X-ray diffraction.

1C004 Uranium titanium alloys or tungsten alloys with a "matrix" based on iron, nickel or copper, having all of the following:

- a. A density exceeding 17.5 g/cm^3 ;
- b. An elastic limit exceeding 880 MPa;
- c. An ultimate tensile strength exceeding 1,270 MPa; and
- d. An elongation exceeding 8%.

1C005 "Superconductive" "composite" conductors in lengths exceeding 100 m or with a mass exceeding 100 g, as follows:

- a. "Superconductive" "composite" conductors containing one or more niobium-titanium 'filaments', having all of the following:
 1. Embedded in a "matrix" other than a copper or copper-based mixed "matrix"; and
 2. Having a cross-section area less than $0.28 \times 10^{-4} \text{ mm}^2$ ($6 \mu\text{m}$ in diameter for circular 'filaments');
- b. "Superconductive" "composite" conductors consisting of one or more "superconductive" 'filaments' other than niobium-titanium, having all of the following:
 1. A "critical temperature" at zero magnetic induction exceeding 9.85 K (-263.31°C); and
 2. Remaining in the "superconductive" state at a temperature of 4.2 K (-268.96°C) when exposed to a magnetic field oriented in any direction perpendicular to the longitudinal axis of conductor and corresponding to a magnetic induction of 12 T with critical current density exceeding $1,750 \text{ A/mm}^2$ on overall cross-section of the conductor;
- c. "Superconductive" "composite" conductors consisting of one or more "superconductive" 'filaments' which remain "superconductive" above 115 K (-158.16°C).

Technical Note:

For the purpose of 1C005 'filaments' may be in wire, cylinder, film, tape or ribbon form.

-
- 1C006 Fluids and lubricating materials, as follows:
- a. Hydraulic fluids containing, as their principal ingredients, any of the following:
 - 1. Synthetic 'silahydrocarbon oils' having all of the following:

Technical Note:
For the purpose of 1C006.a.1., 'silahydrocarbon oils' contain exclusively silicon, hydrogen and carbon.

 - a. A 'flash point' exceeding 477 K (204°C);
 - b. A 'pour point' at 239 K (-34°C) or less;
 - c. A 'viscosity index' of 75 or more; and
 - d. A 'thermal stability' at 616 K (343°C); or
 - 2. 'Chlorofluorocarbons' having all of the following:

Technical Note:
For the purpose of 1C006.a.2., 'chlorofluorocarbons' contain exclusively carbon, fluorine and chlorine.

 - a. No 'flash point';
 - b. An 'autogenous ignition temperature' exceeding 977 K (704°C);
 - c. A 'pour point' at 219 K (-54°C) or less;
 - d. A 'viscosity index' of 80 or more; and
 - e. A boiling point at 473 K (200°C) or higher;
 - b. Lubricating materials containing, as their principal ingredients, any of the following:
 - 1. Phenylene or alkylphenylene ethers or thio-ethers, or their mixtures, containing more than two ether or thio-ether functions or mixtures thereof; or
 - 2. Fluorinated silicone fluids with a kinematic viscosity of less than 5,000 mm²/s (5,000 centistokes) measured at 298 K (25°C);
 - c. Damping or flotation fluids having all of the following:
 - 1. Purity exceeding 99.8%;
 - 2. Containing less than 25 particles of 200 µm or larger in size per 100 ml; and
 - 3. Made from at least 85% of any of the following:
 - a. Dibromotetrafluoroethane (CAS 25497-30-7, 124-73-2, 27336-23-8);
 - b. Polychlorotrifluoroethylene (oily and waxy modifications only); or
 - c. Polybromotrifluoroethylene;
-

-
- d. Fluorocarbon electronic cooling fluids having all of the following:
1. Containing 85% by weight or more of any of the following, or mixtures thereof:
 - a. Monomeric forms of perfluoropolyalkylether-triazines or perfluoroaliphatic-ethers;
 - b. Perfluoroalkylamines;
 - c. Perfluorocycloalkanes; or
 - d. Perfluoroalkanes;
 2. Density at 298 K (25°C) of 1.5 g/ml or more;
 3. In a liquid state at 273 K (0°C); and
 4. Containing 60% or more by weight of fluorine.

Technical Note:

For the purpose of 1C006:

1. 'Flash point' is determined using the Cleveland Open Cup Method described in ASTM D-92 or national equivalents;
2. 'Pour point' is determined using the method described in ASTM D-97 or national equivalents;
3. 'Viscosity index' is determined using the method described in ASTM D-2270 or national equivalents;
4. 'Thermal stability' is determined by the following test procedure or national equivalents:

Twenty ml of the fluid under test is placed in a 46 ml type 317 stainless steel chamber containing one each of 12.5 mm (nominal) diameter balls of M-10 tool steel, 52100 steel and naval bronze (60% Cu, 39% Zn, 0.75% Sn);

The chamber is purged with nitrogen, sealed at atmospheric pressure and the temperature raised to and maintained at 644 ± 6 K ($371 \pm 6^\circ\text{C}$) for six hours;

The specimen will be considered thermally stable if, on completion of the above procedure, all of the following conditions are met:

- a. *The loss in weight of each ball is less than 10 mg/mm^2 of ball surface;*
 - b. *The change in original viscosity as determined at 311 K (38°C) is less than 25%; and*
 - c. *The total acid or base number is less than 0.40;*
5. 'Autogenous ignition' temperature is determined using the method described in ASTM E-659 or national equivalents.

-
- 1C007 Ceramic base materials, non-“composite” ceramic materials, ceramic-“matrix” “composite” materials and precursor materials, as follows:
- N.B.: SEE ALSO 1C107.**
- a. Base materials of single or complex borides of titanium, having total metallic impurities, excluding intentional additions, of less than 5,000 ppm, an average particle size equal to or less than 5 µm and no more than 10% of the particles larger than 10 µm;
 - b. Non-“composite” ceramic materials in crude or semi-fabricated form, composed of borides of titanium with a density of 98% or more of the theoretical density;
- Note: 1C007.b. does not control abrasives.*
- c. Ceramic-ceramic “composite” materials with a glass or oxide-“matrix” and reinforced with fibres having all of the following:
 1. Made from any of the following materials:
 - a. Si-N;
 - b. Si-C;
 - c. Si-Al-O-N; or
 - d. Si-O-N; and
 2. Having a “specific tensile strength” exceeding 12.7×10^3 m;
 - d. Ceramic-ceramic “composite” materials, with or without a continuous metallic phase, incorporating particles, whiskers or fibres, where carbides or nitrides of silicon, zirconium or boron form the “matrix”;
 - e. Precursor materials (i.e., special purpose polymeric or metallo-organic materials) for producing any phase or phases of the materials specified in 1C007.c., as follows:
 1. Polydiorganosilanes (for producing silicon carbide);
 2. Polysilazanes (for producing silicon nitride);
 3. Polycarbosilazanes (for producing ceramics with silicon, carbon and nitrogen components);
 - f. Ceramic-ceramic “composite” materials with an oxide or glass “matrix” reinforced with continuous fibres from any of the following systems:
 1. Al_2O_3 ; or
 2. Si-C-N.

Note: 1C007.f. does not control “composites” containing fibres from these systems with a fibre tensile strength of less than 700 MPa at 1,273 K (1,000°C) or fibre tensile creep resistance of more than 1% creep strain at 100 MPa load and 1,273 K (1,000°C) for 100 hours.
- 1C008 Non-fluorinated polymeric substances as follows:
- a. Imides as follows:
-

1. Bismaleimides;
2. Aromatic polyamide-imides (PAI) having a 'glass transition temperature (T_g)' exceeding 563 K (290°C);
3. Aromatic polyimides having a 'glass transition temperature (T_g)' exceeding 505 K (232°C);
4. Aromatic polyetherimides having a glass transition temperature (T_g) exceeding 513 K (240°C);

Note: IC008.a. controls substances in liquid or solid "fusible" form, including resin, powder, pellet, film, sheet, tape or ribbon.

N.B.: For non-"fusible" aromatic polyimides in film, sheet, tape or ribbon form, see 1A003.

- b. Thermoplastic liquid crystal copolymers having a heat distortion temperature exceeding 523 K (250°C) measured according to ISO 75-2 (2004), method A or national equivalents, with a load of 1.80 N/mm² and composed of:
 1. Any of the following compounds:
 - a. Phenylene, biphenylene or naphthalene; or
 - b. Methyl, tertiary-butyl or phenyl substituted phenylene, biphenylene or naphthalene; and
 2. Any of the following acids:
 - a. Terephthalic acid (CAS 100-21-0);
 - b. 6-hydroxy-2 naphthoic acid (CAS 16712-64-4); or
 - c. 4-hydroxybenzoic acid (CAS 99-96-7);
- c. Not used;
- d. Polyarylene ketones;
- e. Polyarylene sulphides, where the arylene group is biphenylene, triphenylene or combinations thereof;
- f. Polybiphenylenethersulphone having a 'glass transition temperature (T_g)' exceeding 563 K (290°C).

Technical Notes:

1. The 'glass transition temperature (T_g)' for IC008.a.2. thermoplastic materials and IC008.a.4. materials is determined using the method described in ISO 11357-2 (1999) or national equivalents.
2. The 'glass transition temperature (T_g)' for IC008.a.2. thermosetting materials and IC008.a.3. materials is determined using the 3-point bend method described in ASTM D 7028-07 or equivalent national standard. The test is to be performed using a dry test specimen which has attained a minimum of 90% degree of cure as specified by ASTM E 2160-04 or equivalent national standard, and was cured using the combination of standard- and post-cure processes that yield the highest T_g .

1C009	<p>Unprocessed fluorinated compounds as follows:</p> <ol style="list-style-type: none"> Copolymers of vinylidene fluoride having 75% or more beta crystalline structure without stretching; Fluorinated polyimides containing 10% by weight or more of combined fluorine; Fluorinated phosphazene elastomers containing 30% by weight or more of combined fluorine.
1C010	<p>“Fibrous or filamentary materials” as follows:</p> <p>N.B.: SEE ALSO 1C210 AND 9C110.</p> <p><i>Technical Notes:</i></p> <ol style="list-style-type: none"> <i>For the purpose of calculating “specific tensile strength”, “specific modulus” or specific weight of “fibrous or filamentary materials” in 1.C.10.a., 1.C.10.b., 1.C.10.c. or 1.C.10.e.1.b., the tensile strength and modulus should be determined by using Method A described in ISO 10618 (2004) or national equivalent.</i> <i>Assessing the “specific tensile strength”, “specific modulus” or specific weight of non-unidirectional “fibrous or filamentary materials” (e.g., fabrics, random mats or braids) in 1.C.10. is to be based on the mechanical properties of the constituent unidirectional monofilaments (e.g., monofilaments, yarns, rovings or tows) prior to processing into the non-unidirectional “fibrous or filamentary materials”.</i> <ol style="list-style-type: none"> Organic “fibrous or filamentary materials”, having all of the following: <ol style="list-style-type: none"> A “specific modulus” exceeding 12.7×10^6 m; and A “specific tensile strength” exceeding 23.5×10^4 m; <p><i>Note: 1C010.a. does not control polyethylene.</i></p> Carbon “fibrous or filamentary materials”, having all of the following: <ol style="list-style-type: none"> “Specific modulus” exceeding 14.65×10^6 m; and “Specific tensile strength” exceeding 26.82×10^4 m; <p><i>Note: 1C010.b. does not control:</i></p> <ol style="list-style-type: none"> <i>“Fibrous or filamentary materials”, for the repair of “civil aircraft” structures or laminates, having all of the following:</i> <ol style="list-style-type: none"> <i>An area not exceeding 1 m^2;</i> <i>A length not exceeding 2.5 m; and</i> <i>A width exceeding 15 mm.</i> <i>Mechanically chopped, milled or cut carbon “fibrous or filamentary materials” 25.0 mm or less in length.</i> Inorganic “fibrous or filamentary materials”, having all of the following: <ol style="list-style-type: none"> A “specific modulus” exceeding 2.54×10^6 m; and

-
2. A melting, softening, decomposition or sublimation point exceeding 1,922 K (1,649°C) in an inert environment;

Note: 1C010.c. does not control:

- a. *Discontinuous, multiphase, polycrystalline alumina fibres in chopped fibre or random mat form, containing 3 % by weight or more silica, with a “specific modulus” of less than 10×10^6 m;*
- b. *Molybdenum and molybdenum alloy fibres;*
- c. *Boron fibres;*
- d. *Discontinuous ceramic fibres with a melting, softening, decomposition or sublimation point lower than 2,043 K (1,770°C) in an inert environment.*

- d. “Fibrous or filamentary materials”, having any of the following:
 1. Composed of any of the following:
 - a. Polyetherimides specified in 1C008.a.; or
 - b. Materials specified in 1C008.b. to 1C008.f.; or
 2. Composed of materials specified in 1C010.d.1.a. or 1C010.d.1.b. and “commingled” with other fibres specified in 1C010.a., 1C010.b. or 1C010.c.;
- e. Fully or partially resin-impregnated or pitch-impregnated “fibrous or filamentary materials” (prepregs), metal or carbon-coated “fibrous or filamentary materials” (preforms) or “carbon fibre preforms”, having all of the following:
 1. Having any of the following:
 - a. Inorganic “fibrous or filamentary materials” specified in 1C010.c.; or
 - b. Organic or carbon “fibrous or filamentary materials”, having all of the following:
 1. “Specific modulus” exceeding 10.15×10^6 m; and
 2. “Specific tensile strength” exceeding 17.7×10^4 m; and
 2. Having any of the following:
 - a. Resin or pitch, specified in 1C008 or 1C009.b.;
 - b. ‘Dynamic Mechanical Analysis glass transition temperature (DMA T_g)’ equal to or exceeding 453 K (180°C) and having a phenolic resin; or
 - c. ‘Dynamic Mechanical Analysis glass transition temperature (DMA T_g)’ equal to or exceeding 505 K (232°C) and having a resin or pitch, not specified in 1C008 or 1C009.b., and not being a phenolic resin;

Note 1: Metal or carbon-coated “fibrous or filamentary materials” (preforms) or carbon fibre preforms, not impregnated with resin or pitch, are specified by “fibrous or filamentary materials” in 1C010.a., 1C010.b. or 1C010.c.

Note 2: 1C010.e. does not control:

-
- a. Epoxy resin “matrix” impregnated carbon “fibrous or filamentary materials” (prepregs) for the repair of “civil aircraft” structures or laminates, having all the following:
 - 1. An area not exceeding 1 m²;
 - 2. A length not exceeding 2.5 m; and
 - 3. A width exceeding 15 mm.
 - b. Fully or partially resin-impregnated or pitch-impregnated mechanically chopped, milled or cut carbon “fibrous or filamentary materials” 25.0 mm or less in length when using a resin or pitch other than those specified by 1C008. or 1C009.b.

Technical Note:

The ‘Dynamic Mechanical Analysis glass transition temperature (DMA T_g)’ for materials specified by 1C010.e. is determined using the method described in ASTM D 7028–07, or equivalent national standard, on a dry test specimen. In the case of thermoset materials, degree of cure of a dry test specimen shall be a minimum of 90% as defined by ASTM E 2160–04 or equivalent national standard.

1C011 Metals and compounds, as follows:

N.B.: SEE ALSO MUNITIONS LIST and 1C111.

- a. Metals in particle sizes of less than 60 µm whether spherical, atomised, spheroidal, flaked or ground, manufactured from material consisting of 99% or more of zirconium, magnesium and alloys thereof;

Technical Note:

The natural content of hafnium in the zirconium (typically 2% to 7%) is counted with the zirconium.

Note: The metals or alloys specified in 1C011.a. are controlled whether or not the metals or alloys are encapsulated in aluminium, magnesium, zirconium or beryllium.

- b. Boron or boron alloys, with a particle size of 60 µm or less, as follows:
 - 1. Boron with a purity of 85% by weight or more;
 - 2. Boron alloys with a boron content of 85% by weight or more;

Note: The metals or alloys specified in 1C011.b. are controlled whether or not the metals or alloys are encapsulated in aluminium, magnesium, zirconium or beryllium.

- c. Guanidine nitrate;
- d. Nitroguanidine (NQ) (CAS 556-88-7).

N.B.: SEE ALSO MUNITIONS LIST CONTROLS FOR METAL POWDERS MIXED WITH OTHER SUBSTANCES TO FORM A MIXTURE FORMULATED FOR MILITARY PURPOSES.

1C012	<p>Materials as follows:</p> <p><i>Technical Note:</i></p> <p><i>These materials are typically used for nuclear heat sources.</i></p> <p>a. Plutonium in any form with a plutonium isotopic assay of plutonium-238 of more than 50% by weight;</p> <p><i>Note:</i> 1C012.a. does not control:</p> <p style="margin-left: 40px;">a. Shipments with a plutonium content of 1 g or less;</p> <p style="margin-left: 40px;">b. Shipments of 3 “effective grammes” or less when contained in a sensing component in instruments.</p> <p>b. “Previously separated” neptunium-237 in any form.</p> <p><i>Note:</i> 1C012.b. does not control shipments with a neptunium-237 content of 1 g or less.</p>
1C101	<p>Materials and devices for reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures, other than those specified in 1C001, usable in ‘missiles’, ‘missile’ subsystems or unmanned aerial vehicles specified in 9A012.</p> <p><i>Note 1:</i> 1C101 includes:</p> <p style="margin-left: 40px;">a. Structural materials and coatings specially designed for reduced radar reflectivity;</p> <p style="margin-left: 40px;">b. Coatings, including paints, specially designed for reduced or tailored reflectivity or emissivity in the microwave, infrared or ultraviolet regions of the electromagnetic spectrum.</p> <p><i>Note 2:</i> 1C101 does not include coatings when specially used for the thermal control of satellites.</p> <p><i>Technical Note:</i></p> <p><i>In 1C101 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
1C102	<p>Resaturated pyrolysed carbon-carbon materials designed for space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.</p>
1C107	<p>Graphite and ceramic materials, other than those specified in 1C007, as follows:</p> <p>a. Fine grain graphites with a bulk density of 1.72 g/cm³ or greater, measured at 288 K (15°C), and having a grain size of 100 µm or less, usable for rocket nozzles and re-entry vehicle nose tips, which can be machined to any of the following products:</p> <ol style="list-style-type: none"> 1. Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater; 2. Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; or 3. Blocks having a size of 120 mm x 120 mm x 50 mm or greater;

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

N.B.: See also 0C004

- b. Pyrolytic or fibrous reinforced graphites, usable for rocket nozzles and reentry vehicle nose tips usable in “missiles”, space launch vehicles specified in 9A004 or sounding rockets specified in 9A104;

N.B.: See also 0C004

- c. Ceramic composite materials (dielectric constant less than 6 at any frequency from 100 MHz to 100 GHz) for use in radomes usable in “missiles”, space launch vehicles specified in 9A004 or sounding rockets specified in 9A104;
- d. Bulk machinable silicon-carbide reinforced unfired ceramic, usable for nose tips usable in “missiles”, space launch vehicles specified in 9A004 or sounding rockets specified in 9A104;
- e. Reinforced silicon-carbide ceramic composites, usable for nose tips, reentry vehicles and nozzle flaps usable in “missiles”, space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.

1C111 Propellants and constituent chemicals for propellants, other than those specified in 1C011, as follows:

- a. Propulsive substances:
 - 1. Spherical or spheroidal aluminium powder, other than that specified in the Munitions List, in particle size of less than 200 µm and an aluminium content of 97% by weight or more, if at least 10% of the total weight is made up of particles of less than 63 µm, according to ISO 2591:1988 or national equivalents;
Technical Note:
A particle size of 63 µm (ISO R-565) corresponds to 250 mesh (Tyler) or 230 mesh (ASTM standard E-11).
 - 2. Metal powders, other than that specified in the Munitions List, with at least 90% of the total particles by particle volume or weight made up of particles of less than 60 µm (determined by measurement techniques such as using a sieve, laser diffraction or optical scanning), whether spherical, atomised, spheroidal, flaked or ground, consisting of any of the following:
 - a. Zirconium (CAS 7440-67-7) or zirconium alloys consisting of 97% by weight or more of zirconium;
 - b. Beryllium (CAS 7440-41-7) or beryllium alloys consisting of 97% by weight or more of beryllium;
 - c. Magnesium (CAS 7439-95-4) magnesium alloys consisting of 97% by weight or more of magnesium; or
 - d. Boron (CAS 7440-42-8) or boron alloys consisting of 85% by weight or more of boron;

Note: In a multimodal particle distribution (e.g. mixtures of different grain sizes) in which one or more modes are controlled, the entire powder mixture is controlled.

Technical Note:

The natural content of hafnium in the zirconium (typically 2% to 7%) is counted with the zirconium.

3. Oxidiser substances usable in liquid propellant rocket engines as follows:

- a. Dinitrogen trioxide (CAS 10544-73-7);
- b. Nitrogen dioxide (CAS 10102-44-0)/dinitrogen tetroxide (CAS 10544-72-6);
- c. Dinitrogen pentoxide (CAS 10102-03-1);
- d. Mixed Oxides of Nitrogen (MON);

Technical Note:

Mixed Oxides of Nitrogen (MON) are solutions of Nitric Oxide (NO) in Dinitrogen Tetroxide/Nitrogen Dioxide (N_2O_4/NO_2) that can be used in missile systems. There are a range of compositions that can be denoted as MON_i or MON_{ij}, where i and j are integers representing the percentage of Nitric Oxide in the mixture (e.g., MON₃ contains 3% Nitric Oxide, MON₂₅ 25% Nitric Oxide. An upper limit is MON₄₀, 40% by weight).

- e. SEE MUNITIONS LIST FOR Inhibited Red Fuming Nitric Acid (IRFNA);
- f. SEE MUNITIONS LIST AND 1C238 FOR Compounds composed of fluorine and one or more of other halogens, oxygen or nitrogen;

4. Hydrazine derivatives as follows:

N.B.: SEE ALSO MUNITIONS LIST.

- a. Trimethylhydrazine (CAS 1741-01-1);
- b. Tetramethylhydrazine (CAS 6415-12-9);
- c. N,N diallylhydrazine;
- d. Allylhydrazine (CAS 7422-78-8);
- e. Ethylene dihydrazine;
- f. Monomethylhydrazine dinitrate;
- g. Unsymmetrical dimethylhydrazine nitrate;
- h. Hydrazinium azide (CAS 14546-44-2);
- i. Dimethylhydrazinium azide;
- j. Hydrazinium dinitrate;
- k. Diimido oxalic acid dihydrazine;
- l. 2-hydroxyethylhydrazine nitrate (HEHN);
- m. See Munitions List for Hydrazinium perchlorate;

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
- n. Hydrazinium diperchlorate (CAS 13812–39–0);
 - o. Methylhydrazine nitrate (MHN);
 - p. Diethylhydrazine nitrate (DEHN);
 - q. 3,6-dihydrazino tetrazine nitrate (1,4-dihydrazine nitrate) (DHTN);
5. High energy density materials, other than that specified in the Munitions List, usable in ‘missiles’ or unmanned aerial vehicles specified in 9A012:
- a. Mixed fuel that incorporates both solid and liquid fuels, such as boron slurry, having a mass-based energy density of 40×10^6 J/kg or greater;
 - b. Other high energy density fuels and fuel additives (e.g. cubane, ionic solutions, JP–10) having a volume-based energy density of 37.5×10^9 J/m³ or greater, measured at 20°C and one atmosphere (101.325 kPa) pressure;

Note: 1C111.a.5.b. does not control fossil refined fuels and biofuels produced from vegetables, including fuels for engines certified for use in civil aviation, unless specially formulated for ‘missiles’ or unmanned aerial vehicles specified in 9A012.

Technical Note:

In 1C111.a.5., ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.

- b. Polymeric substances:
 - 1. Carboxy-terminated polybutadiene (including carboxyl-terminated polybutadiene) (CTPB);
 - 2. Hydroxy-terminated polybutadiene (included hydroxyl-terminated polybutadiene) (HTPB), other than that specified in the Munitions List;
 - 3. Polybutadiene-acrylic acid (PBAA);
 - 4. Polybutadiene-acrylic acid-acrylonitrile (PBAN);
 - 5. Polytetrahydrofuran polyethylene glycol (TPEG);

Technical Note:

Polytetrahydrofuran polyethylene glycol (TPEG) is a block co-polymer of poly 1,4-Butanediol and polyethylene glycol (PEG).

- c. Other propellant additives and agents:
 - 1. SEE MUNITIONS LIST FOR Carboranes, decaboranes, pentaboranes and derivatives thereof;
 - 2. Triethylene glycol dinitrate (TEGDN) (CAS 111-22-8);
 - 3. 2-Nitrodiphenylamine (CAS 119-75-5);
 - 4. Trimethylolethane trinitrate (TMETN) (CAS 3032-55-1);
 - 5. Diethylene glycol dinitrate (DEGDN) (CAS 693-21-0);
-

6. Ferrocene derivatives as follows:
 - a. See Munitions List for catocene;
 - b. Ethyl ferrocene (CAS 1273-89-8);
 - c. Propyl ferrocene;
 - d. See Munitions List for n-butyl ferrocene;
 - e. Pentyl ferrocene (CAS 1274-00-6);
 - f. Dicyclopentyl ferrocene;
 - g. Dicyclohexyl ferrocene;
 - h. Diethyl ferrocene (CAS 1273-97-8);
 - i. Dipropyl ferrocene;
 - j. Dibutyl ferrocene (CAS 1274-08-4);
 - k. Dihexyl ferrocene (CAS 93894-59-8);
 - l. Acetyl ferrocene (CAS 1271-55-2) / 1,1'-diacetyl ferrocene (CAS 1273-94-5);
 - m. See Munitions List for ferrocene Carboxylic acids;
 - n. See Munitions List for butacene;
 - o. Other ferrocene derivatives usable as rocket propellant burning rate modifiers, other than those specified in the Military Goods Controls.

Note: 1C111.c.6.o. does not control ferrocene derivatives that contain a six carbon aromatic functional group attached to the ferrocene molecule.

7. 4,5 diazidomethyl-2-methyl-1,2,3-triazole (iso- DAMTR) , other than that specified in the Munitions List.

Note: For propellants and constituent chemicals for propellants not specified in 1C111, see the Munitions List.

1C116 Maraging steels having an ultimate tensile strength of 1,500 MPa or greater, measured at 293 K (20°C), in the form of sheet, plate or tubing with a wall or plate thickness equal to or less than 5 mm.

N.B.: SEE ALSO 1C216.

Technical Note:

Maraging steels are iron alloys generally characterised by high nickel, very low carbon content and the use of substitutional elements or precipitates to produce strengthening and age-hardening of the alloy.

1C117 Materials for the fabrication of 'missile' components as follows:

- a. Tungsten and alloys in particulate form with a tungsten content of 97% by weight or more and a particle size of 50×10^{-6} m (50 µm) or less;
- b. Molybdenum and alloys in particulate form with a molybdenum content of 97% by weight or more and a particle size of 50×10^{-6} m (50 µm) or less;
- c. Tungsten materials in solid form having all of the following:

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
1. Any of the following material compositions:
 - a. Tungsten and alloys containing 97% by weight or more of tungsten;
 - b. Copper infiltrated tungsten containing 80% by weight or more of tungsten; or
 - c. Silver infiltrated tungsten containing 80% by weight or more of tungsten; and
 2. Able to be machined to any of the following products:
 - a. Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater;
 - b. Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; or
 - c. Blocks having a size of 120 mm by 120 mm by 50 mm or greater.

Technical Note:

In 1C117, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.

1C118 Titanium-stabilised duplex stainless steel (Ti-DSS) having all of the following:

- a. Having all of the following characteristics:
 1. Containing 17.0 - 23.0 weight percent chromium and 4.5 - 7.0 weight percent nickel;
 2. Having a titanium content of greater than 0.10 weight percent; and
 3. A ferritic-austenitic microstructure (also referred to as a two-phase microstructure) of which at least 10 percent is austenite by volume (according to ASTM E-1181-87 or national equivalents); and
- b. Having any of the following forms:
 1. Ingots or bars having a size of 100 mm or more in each dimension;
 2. Sheets having a width of 600 mm or more and a thickness of 3 mm or less; or
 3. Tubes having an outer diameter of 600 mm or more and a wall thickness of 3 mm or less.

1C202 Alloys, other than those specified in 1C002.b.3. or .b.4., as follows:

- a. Aluminium alloys having both of the following characteristics:
 1. 'Capable of' an ultimate tensile strength of 460 MPa or more at 293 K (20°C); and
 2. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm;

-
- b. Titanium alloys having both of the following characteristics:
1. 'Capable of' an ultimate tensile strength of 900 MPa or more at 293 K (20°C); and
 2. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm.

Technical Note:

The phrase alloys 'capable of' encompasses alloys before or after heat treatment.

1C210 'Fibrous or filamentary materials' or preregs, other than those specified in 1C010.a., b. or e., as follows:

- a. Carbon or aramid 'fibrous or filamentary materials' having either of the following characteristics:

1. A "specific modulus" of 12.7×10^6 m or greater; or
2. A "specific tensile strength" of 235×10^3 m or greater;

Note: 1C210.a. does not control aramid 'fibrous or filamentary materials' having 0.25 percent or more by weight of an ester based fibre surface modifier.

- b. Glass 'fibrous or filamentary materials' having both of the following characteristics:

1. A "specific modulus" of 3.18×10^6 m or greater; and
2. A "specific tensile strength" of 76.2×10^3 m or greater;

- c. Thermoset resin impregnated continuous "yarns", "rovings", "tows" or "tapes" with a width of 15 mm or less (preregs), made from carbon or glass 'fibrous or filamentary materials' specified in 1C210.a. or b.

Technical Note:

The resin forms the matrix of the composite.

Note: In 1C210, 'fibrous or filamentary materials' is restricted to continuous "monofilaments", "yarns", "rovings", "tows" or "tapes".

1C216 Maraging steel, other than that specified in 1C116, 'capable of' an ultimate tensile strength of 1,950 MPa or more, at 293 K (20°C).

Note: 1C216 does not control forms in which all linear dimensions are 75 mm or less.

Technical Note:

The phrase maraging steel 'capable of' encompasses maraging steel before or after heat treatment.

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
- 1C225 Boron enriched in the boron-10 (^{10}B) isotope to greater than its natural isotopic abundance, as follows: elemental boron, compounds, mixtures containing boron, manufactures thereof, waste or scrap of any of the foregoing.
- Note:* In 1C225 mixtures containing boron include boron loaded materials.
- Technical Note:*
- The natural isotopic abundance of boron-10 is approximately 18.5 weight per cent (20 atom per cent).*
- 1C226 Tungsten, tungsten carbide, and alloys containing more than 90% tungsten by weight, having both of the following characteristics:
- In forms with a hollow cylindrical symmetry (including cylinder segments) with an inside diameter between 100 mm and 300 mm; and
 - A mass greater than 20 kg.
- Note:* 1C226 does not control manufactures specially designed as weights or gamma-ray collimators.
- 1C227 Calcium having both of the following characteristics:
- Containing less than 1,000 parts per million by weight of metallic impurities other than magnesium; and
 - Containing less than 10 parts per million by weight of boron.
- 1C228 Magnesium having both of the following characteristics:
- Containing less than 200 parts per million by weight of metallic impurities other than calcium; and
 - Containing less than 10 parts per million by weight of boron.
- 1C229 Bismuth having both of the following characteristics:
- A purity of 99.99% or greater by weight; and
 - Containing less than 10 ppm (parts per million) by weight of silver.
- 1C230 Beryllium metal, alloys containing more than 50% beryllium by weight, beryllium compounds, manufactures thereof, and waste or scrap of any of the foregoing, other than that specified in the Munitions List controls.
- N.B.: SEE ALSO MUNITIONS LIST CONTROLS.**
- 1C231 Hafnium metal, alloys containing more than 60% hafnium by weight, hafnium compounds containing more than 60% hafnium by weight, manufactures thereof, and waste or scrap of any of the foregoing.
-

-
- | | |
|-------|--|
| 1C232 | <p>Helium-3 (^3He), mixtures containing helium-3, and products or devices containing any of the foregoing.</p> <p><i>Note:</i> 1C232 does not control a product or device containing less than 1 g of helium-3.</p> |
| 1C233 | <p>Lithium enriched in the lithium-6 (^6Li) isotope to greater than its natural isotopic abundance, and products or devices containing enriched lithium, as follows: elemental lithium, alloys, compounds, mixtures containing lithium, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><i>Note:</i> 1C233 does not control thermoluminescent dosimeters.</p> <p><i>Technical Note:</i>
The natural isotopic abundance of lithium-6 is approximately 6.5 weight per cent (7.5 atom per cent).</p> |
| 1C234 | <p>Zirconium with a hafnium content of less than 1 part hafnium to 500 parts zirconium by weight, as follows: metal, alloys containing more than 50% zirconium by weight, compounds, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><i>Note:</i> 1C234 does not control zirconium in the form of foil having a thickness of 0.10 mm or less.</p> |
| 1C235 | <p>Tritium, tritium compounds, mixtures containing tritium in which the ratio of tritium to hydrogen atoms exceeds 1 part in 1000, and products or devices containing any of the foregoing.</p> <p><i>Note:</i> 1C235 does not control a product or device containing less than 1.48×10^3 GBq (40 Ci) of tritium.</p> |
| 1C236 | <p>Radionuclides appropriate for making neutron sources based on alpha-n reaction (Actinium 225, Actinium 227, Californium 253, Curium 240, Curium 241, Curium 242, Curium 243, Curium 244, Einsteinium 253, Einsteinium 254, Gadolinium 148, Plutonium 236, Plutonium 238, Polonium 208, Polonium 209, Polonium 210, Radium 223, Thorium 227, Thorium 228, Uranium 230 or Uranium 232) in the following forms:</p> <ol style="list-style-type: none"> a. Elemental; b. Compounds having a total activity of 37 GBq/kg (1 Ci/kg) or greater; c. Mixtures having a total activity of 37 GBq/kg (1 Ci/kg) or greater; d. Products or devices containing any of the foregoing. <p><i>Note:</i> 1C236 does not control a product or device containing less than 3.7 GBq (100 millicuries) of activity.</p> |
-

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
- 1C237 Radium-226 (^{226}Ra), radium-226 alloys, radium-226 compounds, mixtures containing radium-226, manufactures thereof, and products or devices containing any of the foregoing.
- Note:* 1C237 does not control the following:
- a. Medical applicators;
 - b. A product or device containing less than 0.37 GBq (10 millicuries) of radium-226.
- 1C238 Chlorine trifluoride (ClF_3).
- 1C239 High explosives, other than those specified in the Munitions List, or substances or mixtures containing more than 2% by weight thereof, with a crystal density greater than 1.8 g/cm^3 and having a detonation velocity greater than 8,000 m/s.
- 1C240 Nickel powder and porous nickel metal, other than those specified in 0C005, as follows:
- a. Nickel powder having both of the following characteristics:
 1. A nickel purity content of 99.0% or greater by weight; and
 2. A mean particle size of less than 10 micrometres measured by American Society for Testing and Materials (ASTM) B330 standard;
 - b. Porous nickel metal produced from materials specified in 1C240.a.
- Note:* 1C240 does not control the following:
- a. Filamentary nickel powders;
 - b. Single porous nickel sheets with an area of $1,000 \text{ cm}^2$ per sheet or less.
- Technical Note:*
1C240.b. refers to porous metal formed by compacting and sintering the materials in 1C240.a. to form a metal material with fine pores interconnected throughout the structure.
- N.B.: SEE 0C005 FOR NICKEL POWDERS SPECIALLY PREPARED FOR THE MANUFACTURE OF GASEOUS DIFFUSION BARRIERS**
- 1C241 Rhenium, and alloys containing 90% by weight or more rhenium; and alloys of rhenium and tungsten containing 90% by weight or more of any combination of rhenium and tungsten, having both of the following characteristics:
- a. In forms with a hollow cylindrical symmetry (including cylinder segments) with an inside diameter between 100 and 300 mm; and
 - b. A mass greater than 20kg.
-

1C350	Chemicals, which may be used as precursors for toxic chemical agents, as follows, and “chemical mixtures” containing one or more thereof: N.B.: SEE ALSO MUNITIONS LIST AND 1C450. <ol style="list-style-type: none">1. Thiodiglycol (111-48-8);2. Phosphorus oxychloride (10025-87-3);3. Dimethyl methylphosphonate (756-79-6);4. SEE MUNITIONS LIST FOR Methyl phosphonyl difluoride (676-99-3);5. Methyl phosphonyl dichloride (676-97-1);6. Dimethyl phosphite (DMP) (868-85-9);7. Phosphorus trichloride (7719-12-2);8. Trimethyl phosphite (TMP) (121-45-9);9. Thionyl chloride (7719-09-7);10. 3-Hydroxy-1-methylpiperidine (3554-74-3);11. N,N-Diisopropyl-(beta)-aminoethyl chloride (96-79-7);12. N,N-Diisopropyl-(beta)-aminoethane thiol (5842-07-9);13. 3-Quinuclidinol (1619-34-7);14. Potassium fluoride (7789-23-3);15. 2-Chloroethanol (107-07-3);16. Dimethylamine (124-40-3);17. Diethyl ethylphosphonate (78-38-6);18. Diethyl-N,N-dimethylphosphoramidate (2404-03-7);19. Diethyl phosphite (762-04-9);20. Dimethylamine hydrochloride (506-59-2);21. Ethyl phosphinyl dichloride (1498-40-4);22. Ethyl phosphonyl dichloride (1066-50-8);23. SEE MUNITIONS LIST FOR Ethyl phosphonyl difluoride (753-98-0);24. Hydrogen fluoride (7664-39-3);25. Methyl benzilate (76-89-1);26. Methyl phosphinyl dichloride (676-83-5);27. N,N-Diisopropyl-(beta)-amino ethanol (96-80-0);28. Pinacolyl alcohol (464-07-3);29. SEE MUNITIONS LIST FOR O-Ethyl-2-diisopropylaminoethyl methyl phosphonite (QL) (57856-11-8);30. Triethyl phosphite (122-52-1);
-------	---

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
31. Arsenic trichloride (7784-34-1);
 32. Benzilic acid (76-93-7);
 33. Diethyl methylphosphonite (15715-41-0);
 34. Dimethyl ethylphosphonate (6163-75-3);
 35. Ethyl phosphinyl difluoride (430-78-4);
 36. Methyl phosphinyl difluoride (753-59-3);
 37. 3-Quinuclidone (3731-38-2);
 38. Phosphorus pentachloride (10026-13-8);
 39. Pinacolone (75-97-8);
 40. Potassium cyanide (151-50-8);
 41. Potassium bifluoride (7789-29-9);
 42. Ammonium hydrogen fluoride or ammonium bifluoride (1341-49-7);
 43. Sodium fluoride (7681-49-4);
 44. Sodium bifluoride (1333-83-1);
 45. Sodium cyanide (143-33-9);
 46. Triethanolamine (102-71-6);
 47. Phosphorus pentasulphide (1314-80-3);
 48. Di-isopropylamine (108-18-9);
 49. Diethylaminoethanol (100-37-8);
 50. Sodium sulphide (1313-82-2);
 51. Sulphur monochloride (10025-67-9);
 52. Sulphur dichloride (10545-99-0);
 53. Triethanolamine hydrochloride (637-39-8);
 54. N,N-Diisopropyl-(Beta)-aminoethyl chloride hydrochloride (4261-68-1);
 55. Methylphosphonic acid (993-13-5);
 56. Diethyl methylphosphonate (683-08-9);
 57. N,N-Dimethylaminophosphoryl dichloride (677-43-0);
 58. Triisopropyl phosphite (116-17-6);
 59. Ethyldiethanolamine (139-87-7);
 60. O,O-Diethyl phosphorothioate (2465-65-8);
 61. O,O-Diethyl phosphorodithioate (298-06-6);
 62. Sodium hexafluorosilicate (16893-85-9);
 63. Methylphosphonothioic dichloride (676-98-2);
 64. Thiophosphoryl chloride (3982-91-0);
-

65. Oxalyl chloride (79-37-8).

Note 1: For exports to “States not Party to the Chemical Weapons Convention”, IC350 does not control “chemical mixtures” containing one or more of the chemicals specified in entries IC350.1, .3, .5, .11, .12, .13, .17, .18, .21, .22, .26, .27, .28, .31, .32, .33, .34, .35, .36, .54, .55, .56, .57 and .63 in which no individually specified chemical constitutes more than 10% by the weight of the mixture.

Note 2: For exports to “States Party to the Chemical Weapons Convention”, IC350 does not control “chemical mixtures” containing one or more of the chemicals specified in entries IC350.1, .3, .5, .11, .12, .13, .17, .18, .21, .22, .26, .27, .28, .31, .32, .33, .34, .35, .36, .54, .55, .56, .57 and .63 in which no individually specified chemical constitutes more than 30% by the weight of the mixture.

Note 3: IC350 does not control “chemical mixtures” containing one or more of the chemicals specified in entries IC350 .2, .6, .7, .8, .9, .10, .14, .15, .16, .19, .20, .24, .25, .30, .37, .38, .39, .40, .41, .42, .43, .44, .45, .46, .47, .48, .49, .50, .51, .52, .53, .58, .59, .60, .61, .62, .64 and .65 in which no individually specified chemical constitutes more than 30% by the weight of the mixture.

Note 4: IC350 does not control products identified as consumer goods packaged for retail sale for personal use or packaged for individual use.

1C351 Human pathogens, zoonoses and “toxins”, as follows:

- a. Viruses, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
 1. Andes virus;
 2. Chapare virus;
 3. Chikungunya virus;
 4. Choclo virus;
 5. Congo-Crimean haemorrhagic fever virus;
 6. Dengue fever virus;
 7. Dobrava-Belgrade virus;
 8. Eastern equine encephalitis virus;
 9. Ebola virus;
 10. Guanarito virus;
 11. Hantaan virus;
 12. Hendra virus (Equine morbillivirus);
 13. Japanese encephalitis virus;
 14. Junin virus;
 15. Kyasanur Forest virus;

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
16. Laguna Negra virus;
 17. Lassa fever virus;
 18. Louping ill virus;
 19. Lujo virus;
 20. Lymphocytic choriomeningitis virus;
 21. Machupo virus;
 22. Marburg virus;
 23. Monkey pox virus;
 24. Murray Valley encephalitis virus;
 25. Nipah virus;
 26. Omsk haemorrhagic fever virus;
 27. Oropouche virus;
 28. Powassan virus;
 29. Rift Valley fever virus;
 30. Rocio virus;
 31. Sabia virus;
 32. Seoul virus;
 33. Sin nombre virus;
 34. St Louis encephalitis virus;
 35. Tick-borne encephalitis virus (Russian Spring-Summer encephalitis virus);
 36. Variola virus;
 37. Venezuelan equine encephalitis virus;
 38. Western equine encephalitis virus;
 39. Yellow fever virus;
- b. Not used;
- c. Bacteria, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
1. Bacillus anthracis;
 2. Brucella abortus;
 3. Brucella melitensis;
 4. Brucella suis;
 5. Chlamydophila psittaci (formerly known as Chlamydia psittaci);
 6. Clostridium botulinum;
 7. Clostridium argentinense (formerly known as Clostridium botulinum Type G), botulinum neurotoxin producing strains;
 8. Clostridium baratii, botulinum neurotoxin producing strains;
 9. Clostridium butyricum, botulinum neurotoxin producing strains;
 10. Francisella tularensis;
-

-
11. Burkholderia mallei (Pseudomonas mallei);
 12. Burkholderia pseudomallei (Pseudomonas pseudomallei);
 13. Salmonella typhi;
 14. Shigella dysenteriae;
 15. Vibrio cholerae;
 16. Yersinia pestis;
 17. Clostridium perfringens, epsilon toxin producing types;
 18. Shiga toxin producing Escherichia coli (STEC) of serogroups O26, O45, O103, O104, O111, O121, O145, O157, and other shiga toxin producing serogroups;
Note: Shiga toxin producing Escherichia coli (STEC) is also known as enterohaemorrhagic E. coli (EHEC) or verocytotoxin producing E. coli (VTEC).
 19. Coxiella burnetii;
 20. Rickettsia prowazekii;
- d. “Toxins”, as follows, and “sub-unit of toxins” thereof:
1. Botulinum toxins;
 2. Clostridium perfringens alpha, beta 1, beta 2, epsilon and iota toxins;
 3. Conotoxin;
 4. Ricin;
 5. Saxitoxin;
 6. Shiga toxin;
 7. Staphylococcus aureus enterotoxins, hemolysin alpha toxin, and toxic shock syndrome toxin (formerly known as Staphylococcus enterotoxin F);
 8. Tetrodotoxin;
 9. Verotoxin and shiga-like ribosome inactivating proteins;
 10. Microcystin (Cyanginosin);
 11. Aflatoxins;
 12. Abrin;
 13. Cholera toxin;
 14. Diacetoxyscirpenol toxin;
 15. T-2 toxin;
 16. HT-2 toxin;
 17. Modeccin;
 18. Volkensin;
 19. Viscum album Lectin 1 (Viscumin);
-

Note 1: IC351 does not control immunotoxins.

Note 2: IC351.d. does not control botulinum toxins or conotoxins in product form meeting all of the following criteria:

- a. Are pharmaceutical formulations designed for human administration in the treatment of medical conditions;*
- b. Are pre-packaged for distribution as medical products;*
- c. Are authorised by a state authority to be marketed as medical products.*

- e. Fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:

1. *Coccidioides immitis*;
2. *Coccidioides posadasii*.

Note: IC351 does not control “vaccines” or “immunotoxins”.

1C352 Animal pathogens, as follows:

- a. Viruses, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
1. African swine fever virus;
 2. Avian influenza virus, which are:
 - a. Uncharacterised; or
 - b. Defined in Annex I(2) EC Directive 2005/94/EC (O.J. L.10 14.1.2006 p.16) as having high pathogenicity, as follows:
 1. Type A viruses with an IVPI (intravenous pathogenicity index) in 6 week old chickens of greater than 1.2; or
 2. Type A viruses of the subtypes H5 or H7 with genome sequences codified for multiple basic amino acids at the cleavage site of the haemagglutinin molecule similar to that observed for other HPAI viruses, indicating that the haemagglutinin molecule can be cleaved by a host ubiquitous protease;
 3. Bluetongue virus;
 4. Foot and mouth disease virus;
 5. Goat pox virus;
 6. Herpes virus (Aujeszky’s disease);
 7. Swine fever virus (Hog cholera virus);
 8. Rabies virus and all other members of the Lyssavirus genus;
 9. Newcastle disease virus;

-
10. Peste des petits ruminants virus;
 11. Porcine enterovirus type 9 (swine vesicular disease virus);
 12. Rinderpest virus;
 13. Sheep pox virus;
 14. Teschen disease virus;
 15. Vesicular stomatitis virus;
 16. Lumpy skin disease virus;
 17. African horse sickness virus;
- b. Mycoplasmas, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
1. Mycoplasma mycoides subspecies mycoides SC (small colony);
 2. Mycoplasma capricolum subspecies capripneumoniae (strain F38);

Note: 1C352 does not control “vaccines”.

1C353 Genetic elements and genetically modified organisms, as follows:

- a. Genetically modified organisms or genetic elements that contain nucleic acid sequences associated with pathogenicity of organisms specified in 1C351.a., 1C351.c, 1C351.e., 1C352 or 1C354;
- b. Genetically modified organisms or genetic elements that contain nucleic acid sequences coding for any of the “toxins” specified in 1C351.d. or “sub-units of toxins” thereof.

Technical Notes:

1. Genetic elements include, inter alia, chromosomes, genomes, plasmids, transposons and vectors whether genetically modified or unmodified.
2. Nucleic acid sequences associated with the pathogenicity of any of the micro-organisms specified in 1C351.a., 1C351.c., 1C351.e., 1C352 or 1C354 means any sequence specific to the specified micro-organism that:
 - a. In itself or through its transcribed or translated products represents a significant hazard to human, animal or plant health; or
 - b. Is known to enhance the ability of a specified micro-organism, or any other organism into which it may be inserted or otherwise integrated, to cause serious harm to humans, animals or plant health.

Note: 1C353 does not apply to nucleic acid sequences associated with the pathogenicity of enterohaemorrhagic *Escherichia coli*, serotype O157 and other verotoxin producing strains, other than those coding for the verotoxin, or for its sub-units.

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
- 1C354 Plant pathogens, as follows:
- a. Viruses, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
 - 1. Potato Andean latent tymovirus;
 - 2. Potato spindle tuber viroid;
 - b. Bacteria, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material which has been deliberately inoculated or contaminated with such cultures, as follows:
 - 1. *Xanthomonas albilineans*;
 - 2. *Xanthomonas campestris* pv. *citri* including strains referred to as *Xanthomonas campestris* pv. *citri* types A,B,C,D,E or otherwise classified as *Xanthomonas citri*, *Xanthomonas campestris* pv. *aurantifolia* or *Xanthomonas campestris* pv. *citrumelo*;
 - 3. *Xanthomonas oryzae* pv. *Oryzae* (*Pseudomonas campestris* pv. *Oryzae*);
 - 4. *Clavibacter michiganensis* subsp. *Sepedonicus* (*Corynebacterium michiganensis* subsp. *Sepedonicum* or *Corynebacterium Sepedonicum*);
 - 5. *Ralstonia solanacearum* Races 2 and 3 (*Pseudomonas solanacearum* Races 2 and 3 or *Burkholderia solanacearum* Races 2 and 3);
 - c. Fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material which has been deliberately inoculated or contaminated with such cultures, as follows:
 - 1. *Colletotrichum coffeanum* var. *virulans* (*Colletotrichum kahawae*);
 - 2. *Cochliobolus miyabeanus* (*Helminthosporium oryzae*);
 - 3. *Microcyclus ulei* (syn. *Dothidella ulei*);
 - 4. *Puccinia graminis* ssp. *graminis* var. *graminis* / *Puccinia graminis* ssp. *graminis* var. *stakmanii* (*Puccinia graminis* [syn. *Puccinia graminis* f. sp. *tritici*]);
 - 5. *Puccinia striiformis* (syn. *Puccinia glumarum*);
 - 6. *Magnaporthe grisea* (*pyricularia grisea*/*pyricularia oryzae*).
- 1C450 Toxic chemicals and toxic chemical precursors, as follows, and “chemical mixtures” containing one or more thereof:
- N.B.: SEE ALSO ENTRY 1C350, 1C351.d. AND MUNITIONS LIST.**
- a. Toxic chemicals, as follows:
 - 1. Amiton: O,O-Diethyl S-[2-(diethylamino)ethyl] phosphorothiolate (78-53-5) and corresponding alkylated or protonated salts;
 - 2. PFIB: 1,1,3,3,3-Pentafluoro-2-(trifluoromethyl)-1-propene (382-21-8);
-

-
3. SEE MUNITIONS LIST FOR BZ: 3-Quinuclidinyl benzilate (6581-06-2);
 4. Phosgene: Carbonyl dichloride (75-44-5);
 5. Cyanogen chloride (506-77-4);
 6. Hydrogen cyanide (74-90-8);
 7. Chloropicrin: Trichloronitromethane (76-06-2);

Note 1: For exports to “States not Party to the Chemical Weapons Convention”, IC450 does not control “chemical mixtures” containing one or more of the chemicals specified in entries IC450.a.1. and .a.2. in which no individually specified chemical constitutes more than 1% by the weight of the mixture.

Note 2: For exports to “States Party to the Chemical Weapons Convention”, IC450 does not control “chemical mixtures” containing one or more of the chemicals specified in entries IC450.a.1. and .a.2. in which no individually specified chemical constitutes more than 30% by the weight of the mixture.

Note 3: IC450 does not control “chemical mixtures” containing one or more of the chemicals specified in entries IC450.a.4., .a.5., .a.6. and .a.7. in which no individually specified chemical constitutes more than 30% by the weight of the mixture.

Note 4: IC450 does not control products identified as consumer goods packaged for retail sale for personal use or packaged for individual use.

b. Toxic chemical precursors, as follows:

1. Chemicals, other than those specified in the Munitions List or in IC350, containing a phosphorus atom to which is bonded one methyl, ethyl or propyl (normal or iso) group but not further carbon atoms;

Note: IC450.b.1 does not control Fonofos: O-Ethyl S-phenyl ethylphosphonothiolothionate (944-22-9).

2. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] phosphoramidic dihalides, other than N,N-Dimethylaminophosphoryl dichloride;

N.B.: See IC350.57. for N,N-Dimethylaminophosphoryl dichloride.

3. Dialkyl [methyl, ethyl or propyl (normal or iso)] N,N-dialkyl [methyl, ethyl or propyl (normal or iso)]-phosphoramidates, other than Diethyl-N,N-dimethylphosphoramidate which is specified in IC350;
 4. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethyl-2-chlorides and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethyl chloride or N,N-Diisopropyl-(beta)-aminoethyl chloride hydrochloride which are specified in IC350;
-

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

-
5. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-ols and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethanol (96-80-0) and N,N-Diethylaminoethanol (100-37-8) which are specified in 1C350;

Note: 1C450.b.5. does not control the following:

- a. N,N-Dimethylaminoethanol (108-01-0) and corresponding protonated salts;
- b. Protonated salts of N,N-Diethylaminoethanol (100-37-8).

6. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-thiols and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethane thiol which is specified in 1C350;

7. See 1C350 for ethyldiethanolamine (139-87-7);

8. Methyldiethanolamine (105-59-9).

Note 1: For exports to “States not Party to the Chemical Weapons Convention”, 1C450 does not control “chemical mixtures” containing one or more of the chemicals specified in entries 1C450.b.1., .b.2., .b.3., .b.4., .b.5. and .b.6. in which no individually specified chemical constitutes more than 10% by the weight of the mixture.

Note 2: For exports to “States Party to the Chemical Weapons Convention”, 1C450 does not control “chemical mixtures” containing one or more of the chemicals specified in entries 1C450.b.1., .b.2., .b.3., .b.4., .b.5. and .b.6. in which no individually specified chemical constitutes more than 30% by the weight of the mixture.

Note 3: 1C450 does not control “chemical mixtures” containing one or more of the chemicals specified in entry 1C450.b.8. in which no individually specified chemical constitutes more than 30% by the weight of the mixture.

Note 4: 1C450 does not control products identified as consumer goods packaged for retail sale for personal use or packaged for individual use.

1D Software

1D001 “Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in 1B001 to 1B003.

1D002 “Software” for the “development” of organic “matrix”, metal “matrix” or carbon “matrix” laminates or “composites”.

-
- | | |
|-------|--|
| 1D003 | “Software” specially designed or modified to enable equipment to perform the functions of equipment specified in 1A004.c. or 1A004.d. |
| 1D101 | “Software” specially designed or modified for the operation or maintenance of goods specified in 1B101, 1B102, 1B115, 1B117, 1B118 or 1B119. |
| 1D103 | “Software” specially designed for analysis of reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures. |
| 1D201 | “Software” specially designed for the “use” of goods specified in 1B201. |

1E Technology

- | | |
|-------|---|
| 1E001 | “Technology” according to the General Technology Note for the “development” or “production” of equipment or materials specified in 1A001.b., 1A001.c., 1A002 to 1A005, 1A006.b., 1A007, 1B or 1C. |
| 1E002 | Other “technology” as follows: <ul style="list-style-type: none"> a. “Technology” for the “development” or “production” of polybenzothiazoles or polybenzoxazoles; b. “Technology” for the “development” or “production” of fluoroelastomer compounds containing at least one vinyl ether monomer; c. “Technology” for the design or “production” of the following base materials or non-“composite” ceramic materials: <ul style="list-style-type: none"> 1. Base materials having all of the following: <ul style="list-style-type: none"> a. Any of the following compositions: <ul style="list-style-type: none"> 1. Single or complex oxides of zirconium and complex oxides of silicon or aluminium; 2. Single nitrides of boron (cubic crystalline forms); 3. Single or complex carbides of silicon or boron; or 4. Single or complex nitrides of silicon; b. Any of the following total metallic impurities (excluding intentional additions): <ul style="list-style-type: none"> 1. Less than 1,000 ppm for single oxides or carbides; or 2. Less than 5,000 ppm for complex compounds or single nitrides; and c. Being any of the following: <ul style="list-style-type: none"> 1. Zirconia with an average particle size equal to or less than 1 µm and no more than 10% of the particles larger than 5 µm; |
-

Part 2 Dual-use list

Category 1 Materials, chemicals, microorganisms and toxins

	<ul style="list-style-type: none">2. Other base materials with an average particle size equal to or less than 5 µm and no more than 10% of the particles larger than 10 µm; or3. Having all of the following:<ul style="list-style-type: none">a. Platelets with a length to thickness ratio exceeding 5;b. Whiskers with a length to diameter ratio exceeding 10 for diameters less than 2 µm; andc. Continuous or chopped fibres less than 10 µm in diameter;
	<ul style="list-style-type: none">2. Non-“composite” ceramic materials composed of the materials specified in 1E002.c.1; <p><i>Note: 1E002.c.2. does not control “technology” for the design or production of abrasives.</i></p> <ul style="list-style-type: none">d. “Technology” for the “production” of aromatic polyamide fibres;e. “Technology” for the installation, maintenance or repair of materials specified in 1C001;f. “Technology” for the repair of “composite” structures, laminates or materials specified in 1A002, 1C007.c. or 1C007.d.; <p><i>Note: 1E002.f. does not control “technology” for the repair of “civil aircraft” structures using carbon “fibrous or filamentary materials” and epoxy resins, contained in aircraft manufacturers’ manuals.</i></p> <ul style="list-style-type: none">g. ‘Libraries (parametric technical databases)’ specially designed or modified to enable equipment to perform the functions of equipment specified in 1A004.c. or 1A004.d. <p><i>Technical Note:</i> <i>For the purpose of 1E002.g., ‘library (parametric technical database)’ means a collection of technical information, reference to which may enhance the performance of relevant equipment or systems.</i></p>
1E101	“Technology” according to the General Technology Note for the “use” of goods specified in 1A102, 1B001, 1B101, 1B102, 1B115 to 1B119, 1C001, 1C101, 1C107, 1C111 to 1C118, 1D101 or 1D103.
1E102	“Technology” according to the General Technology Note for the “development” of “software” specified in 1D001, 1D101 or 1D103.
1E103	“Technology” for the regulation of temperature, pressure or atmosphere in autoclaves or hydroclaves, when used for the “production” of “composites” or partially processed “composites”.

-
- | | |
|-------|---|
| 1E104 | <p>“Technology” relating to the “production” of pyrolytically derived materials formed on a mould, mandrel or other substrate from precursor gases which decompose in the 1,573 K (1,300°C) to 3,173 K (2,900°C) temperature range at pressures of 130 Pa to 20 kPa.</p> <p><i>Note: 1E104 includes “technology” for the composition of precursor gases, flow-rates and process control schedules and parameters.</i></p> |
| 1E201 | <p>“Technology” according to the General Technology Note for the “use” of goods specified in 1A002, 1A007, 1A202, 1A225 to 1A227, 1B201, 1B225 to 1B233, 1C002.b.3. or .b.4., 1C010.b., 1C202, 1C210, 1C216, 1C225 to 1C241 or 1D201.</p> |
| 1E202 | <p>“Technology” according to the General Technology Note for the “development” or “production” of goods specified in 1A007, 1A202 or 1A225 to 1A227.</p> |
| 1E203 | <p>“Technology” according to the General Technology Note for the “development” of “software” specified in 1D201.</p> |

Category 2—Materials processing

2A Systems, Equipment and Components

N.B.: For quiet running bearings, see the Munitions List.

2A001 Anti-friction bearings and bearing systems, as follows, and components therefor:

N.B.: SEE ALSO 2A101.

Note: 2A001 does not control balls with tolerances specified by the manufacturer in accordance with ISO 3290 as grade 5 or worse.

- a. Ball bearings and solid roller bearings, having all tolerances specified by the manufacturer in accordance with ISO 492 Tolerance Class 4 (or national equivalents), or better, and having both rings and rolling elements (ISO 5593), made from monel or beryllium;

Note: 2A001.a. does not control tapered roller bearings.

- b. Not used;
- c. Active magnetic bearing systems using any of the following:
 - 1. Materials with flux densities of 2.0 T or greater and yield strengths greater than 414 MPa;
 - 2. All-electromagnetic 3D homopolar bias designs for actuators; or
 - 3. High temperature (450 K (177°C) and above) position sensors.

2A101 Radial ball bearings, other than those specified in 2A001, having all tolerances specified in accordance with ISO 492 Tolerance Class 2 (or ANSI/ABMA Std 20 Tolerance Class ABEC-9 or other national equivalents), or better and having all the following characteristics:

- a. An inner ring bore diameter between 12 mm and 50 mm;
- b. An outer ring bore diameter between 25 mm and 100 mm; and
- c. A width between 10 mm and 20 mm.

2A225 Crucibles made of materials resistant to liquid actinide metals, as follows:

- a. Crucibles having both of the following characteristics:
 - 1. A volume of between 150 cm³ (150 ml) and 8,000 cm³ (8 litres); and
 - 2. Made of or coated with any of the following materials, or combination of the following materials, having an overall impurity level of 2% or less by weight:
 - a. Calcium fluoride (CaF₂);
 - b. Calcium zirconate (metazirconate) (CaZrO₃);
 - c. Cerium sulphide (Ce₂S₃);

- d. Erbium oxide (erbia) (Er_2O_3);
 - e. Hafnium oxide (hafnia) (HfO_2);
 - f. Magnesium oxide (MgO);
 - g. Nitrided niobium-titanium-tungsten alloy (approximately 50% Nb, 30% Ti, 20% W);
 - h. Yttrium oxide (yttria) (Y_2O_3); or
 - i. Zirconium oxide (zirconia) (ZrO_2);
- b. Crucibles having both of the following characteristics:
1. A volume of between 50 cm^3 and $2,000 \text{ cm}^3$; and
 2. Made of or lined with tantalum, having a purity of 99.9% or greater by weight;
- c. Crucibles having all of the following characteristics:
1. A volume of between 50 cm^3 and $2,000 \text{ cm}^3$;
 2. Made of or lined with tantalum, having a purity of 98% or greater by weight; and
 3. Coated with tantalum carbide, nitride, boride, or any combination thereof.

2A226 Valves having all of the following characteristics:

- a. A 'nominal size' of 5 mm or greater;
- b. Having a bellows seal; and
- c. Wholly made of or lined with aluminium, aluminium alloy, nickel, or nickel alloy containing more than 60% nickel by weight.

Technical Note:

For valves with different inlet and outlet diameters, the 'nominal size' in 2A226 refers to the smallest diameter.

2B **Test, Inspection and Production Equipment**

Technical Notes:

1. *Secondary parallel contouring axes, (e.g., the w-axis on horizontal boring mills or a secondary rotary axis the centre line of which is parallel to the primary rotary axis) are not counted in the total number of contouring axes. Rotary axes need not rotate over 360° . A rotary axis can be driven by a linear device (e.g., a screw or a rack-and-pinion).*
2. *For the purposes of 2B, the number of axes which can be co-ordinated simultaneously for "contouring control" is the number of axes along or around which, during processing of the workpiece, simultaneous and interrelated motions are performed between the workpiece and a tool. This does not include any additional axes along or around which other relative movement within the machine are performed such as:*
 - a. *Wheel-dressing systems in grinding machines;*
 - b. *Parallel rotary axes designed for mounting of separate workpieces;*

-
- c. *Co-linear rotary axes designed for manipulating the same workpiece by holding it in a chuck from different ends.*
 - 3. *Axis nomenclature shall be in accordance with International Standard ISO 841, 'Numerical Control Machines — Axis and Motion Nomenclature'.*
 - 4. *For the purposes of 2B001 to 2B009 a “tilting spindle” is counted as a rotary axis.*
 - 5. *'Stated positioning accuracy' derived from measurements made according to ISO 230/2 (2006) or national equivalents may be used for each machine tool model as an alternative to individual machine tests. 'Stated positioning accuracy' means the accuracy value provided to the competent authorities of the Member State in which the exporter is established as representative of the accuracy of a specific machine model.*
Determination of 'stated positioning accuracy':
 - a. *Select five machines of a model to be evaluated;*
 - b. *Measure the linear axis accuracies according to ISO 230/2 (2006);*
 - c. *Determine the A-values for each axis of each machine. The method of calculating the A-value is described in the ISO standard;*
 - d. *Determine the mean value of the A-value of each axis. This mean value \hat{A} becomes the stated value of each axis for the model ($\hat{A}_x \hat{A}_y \dots$);*
 - e. *Since the Category 2 list refers to each linear axis there will be as many stated values as there are linear axes;*
 - f. *If any axis of a machine model not specified by 2B001.a. to 2B001.c. has a stated accuracy \hat{A} equal to or less than the specified positioning accuracy of each machine tool model plus 2 μm , the builder should be required to reaffirm the accuracy level once every eighteen months.*
 - 6. *For the purposes of 2B, measurement uncertainty for the positioning accuracy of machine tools, as defined in the International Standard ISO 230/2 (2006) or national equivalents, shall not be considered.*

2B001 Machine tools and any combination thereof, for removing (or cutting) metals, ceramics or “composites”, which, according to the manufacturer’s technical specification, can be equipped with electronic devices for “numerical control”, as follows:

N.B.: SEE ALSO 2B201.

Note 1: 2B001 does not control special purpose machine tools limited to the manufacture of gears. For such machines see 2B003.

Note 2: 2B001 does not control special purpose machine tools limited to the manufacture of any of the following:

- a. *Crankshafts or camshafts;*
 - b. *Tools or cutters;*
 - c. *Extruder worms; or*
 - d. *Engraved or faceted jewellery parts.*
 - e. *Dental prostheses.*
-

Note 3: A machine tool having at least two of the three turning, milling or grinding capabilities (e.g., a turning machine with milling capability), must be evaluated against each applicable entry 2B001.a., b. or c.

N.B.: For optical finishing machines, see 2B002.

- a. Machine tools for turning having all of the following:
1. Positioning accuracy with “all compensations available” equal to or less (better) than 3 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; and
 2. Two or more axes which can be coordinated simultaneously for “contouring control”;

Note: 2B001.a. does not control turning machines specially designed for producing contact lenses, having all of the following:

- a. Machine controller limited to using ophthalmic based software for part programming data input; and*
- b. No vacuum chucking.*

- b. Machine tools for milling having any of the following:
1. Having all of the following:
 - a. Positioning accuracy with “all compensations available” equal to or less (better) than 3 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; and
 - b. Three linear axes plus one rotary axis which can be coordinated simultaneously for “contouring control”;
 2. Five or more axes which can be coordinated simultaneously for “contouring control” having any of the following:

Note: ‘Parallel mechanism machine tools’ are specified by 2B001.b.2.d.

- a. Positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis with a travel length less than 1 m;
- b. Positioning accuracy with “all compensations available” equal to or less (better) than 4.5 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis with a travel length equal to or greater than 1 m and less than 2 m;
- c. Positioning accuracy with “all compensations available” equal to or less (better) than $4.5 + 7x(L-2)$ µm (L is the travel length in meters) according to ISO 230/2 (2006) or national equivalents along one or more linear axis with a travel length equal to or greater than 2 m; or
- d. Being a ‘parallel mechanism machine tool’;

Technical Note:

A 'parallel mechanism machine tool' is a machine tool having multiple rods which are linked with a platform and actuators; each of the actuators operates the respective rod simultaneously and independently.

3. A positioning accuracy for jig boring machines, with “all compensations available”, equal to or less (better) than 3 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; or
 4. Fly cutting machines having all of the following:
 - a. Spindle “run-out” and “camming” less (better) than 0.0004 mm TIR; and
 - b. Angular deviation of slide movement (yaw, pitch and roll) less (better) than 2 seconds of arc, TIR over 300 mm of travel;
 - c. Machine tools for grinding having any of the following:
 1. Having all of the following:
 - a. Positioning accuracy with “all compensations available” equal to or less (better) than 3 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; and
 - b. Three or more axes which can be coordinated simultaneously for “contouring control”; or
 2. Five or more axes which can be coordinated simultaneously for “contouring control”;
- Note: 2B001.c. does not control grinding machine as follows:*
- a. *Cylindrical external, internal, and external-internal grinding machines, having all of the following:*
 1. *Limited to cylindrical grinding; and*
 2. *Limited to a maximum workpiece capacity of 150 mm outside diameter or length.*
 - b. *Machines designed specifically as jig grinders that do not have a z-axis or a w-axis, with a positioning accuracy with “all compensations available” less (better) than 3 µm according to ISO 230/2 (2006) or national equivalents.*
 - c. *Surface grinders.*
- d. Electrical discharge machines (EDM) of the non-wire type which have two or more rotary axes which can be coordinated simultaneously for “contouring control”;
 - e. Machine tools for removing metals, ceramics or “composites”, having all of the following:
 1. Removing material by means of any of the following:
 - a. Water or other liquid jets, including those employing abrasive additives;
 - b. Electron beam; or
-

-
- c. “Laser” beam; and
 - 2. Having two or more rotary axes and all of the following:
 - a. Can be coordinated simultaneously for “contouring control”; and
 - b. A positioning accuracy of less (better) than 0.003°;
 - f. Deep-hole-drilling machines and turning machines modified for deep-hole-drilling, having a maximum depth-of-bore capability exceeding 5 m and specially designed components therefor.

2B002 Numerically controlled optical finishing machine tools equipped for selective material removal to produce non-spherical optical surfaces having all of the following characteristics:

- a. Finishing the form to less (better) than 1.0 µm;
- b. Finishing to a roughness less (better) than 100 nm rms;
- c. Four or more axes which can be coordinated simultaneously for “contouring control”; and
- d. Using any of the following processes:
 - 1. Magnetorheological finishing (‘MRF’);
 - 2. Electrorheological finishing (‘ERF’);
 - 3. ‘Energetic particle beam finishing’;
 - 4. ‘Inflatable membrane tool finishing’; or
 - 5. ‘Fluid jet finishing’.

Technical Note:

For the purposes of 2B002:

- 1. ‘MRF’ is a material removal process using an abrasive magnetic fluid whose viscosity is controlled by a magnetic field.
- 2. ‘ERF’ is a removal process using an abrasive fluid whose viscosity is controlled by an electric field.
- 3. ‘Energetic particle beam finishing’ uses Reactive Atom Plasmas (RAP) or ion-beams to selectively remove material.
- 4. ‘Inflatable membrane tool finishing’ is a process that uses a pressurised membrane that deforms to contact the workpiece over a small area.
- 5. ‘Fluid jet finishing’ makes use of a fluid stream for material removal.

2B003 “Numerically controlled” or manual machine tools, and specially designed components, controls and accessories therefor, specially designed for the shaving, finishing, grinding or honing of hardened (Rc = 40 or more) spur, helical and double-helical gears with a pitch diameter exceeding 1,250 mm and a face width of 15% of pitch diameter or larger finished to a quality of AGMA 14 or better (equivalent to ISO 1328 class 3).

2B004	<p>Hot “isostatic presses” having all of the following, and specially designed components and accessories therefor:</p> <p>N.B.: SEE ALSO 2B104 and 2B204.</p> <ol style="list-style-type: none"> a. A controlled thermal environment within the closed cavity and a chamber cavity with an inside diameter of 406 mm or more; and b. Having any of the following: <ol style="list-style-type: none"> 1. A maximum working pressure exceeding 207 MPa; 2. A controlled thermal environment exceeding 1,773 K (1,500°C); or 3. A facility for hydrocarbon impregnation and removal of resultant gaseous degradation products. <p><i>Technical Note:</i></p> <p><i>The inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.</i></p> <p><i>N.B.: For specially designed dies, moulds and tooling see 1B003, 9B009 and the Munitions List.</i></p>
2B005	<p>Equipment specially designed for the deposition, processing and in-process control of inorganic overlays, coatings and surface modifications, as follows, for non-electronic substrates, by processes shown in the Table and associated Notes following 2E003.f., and specially designed automated handling, positioning, manipulation and control components therefor:</p> <ol style="list-style-type: none"> a. Chemical vapour deposition (CVD) production equipment having all of the following: <p>N.B.: SEE ALSO 2B105.</p> <ol style="list-style-type: none"> 1. A process modified for one of the following: <ol style="list-style-type: none"> a. Pulsating CVD; b. Controlled nucleation thermal deposition (CNTD); or c. Plasma enhanced or plasma assisted CVD; and 2. Having any of the following: <ol style="list-style-type: none"> a. Incorporating high vacuum (equal to or less than 0.01 Pa) rotating seals; or b. Incorporating <i>in situ</i> coating thickness control; b. Ion implantation production equipment having beam currents of 5 mA or more; c. Electron beam physical vapour deposition (EB-PVD) production equipment incorporating power systems rated for over 80 kW and having any of the following: <ol style="list-style-type: none"> 1. A liquid pool level “laser” control system which regulates precisely the ingots feed rate; or

-
- 2. A computer controlled rate monitor operating on the principle of photo-luminescence of the ionised atoms in the evaporant stream to control the deposition rate of a coating containing two or more elements;
 - d. Plasma spraying production equipment having any of the following:
 - 1. Operating at reduced pressure controlled atmosphere (equal to or less than 10 kPa measured above and within 300 mm of the gun nozzle exit) in a vacuum chamber capable of evacuation down to 0.01 Pa prior to the spraying process; or
 - 2. Incorporating *in situ* coating thickness control;
 - e. Sputter deposition production equipment capable of current densities of 0.1 mA/mm² or higher at a deposition rate of 15 µm/h or more;
 - f. Cathodic arc deposition production equipment incorporating a grid of electromagnets for steering control of the arc spot on the cathode;
 - g. Ion plating production equipment allowing for the *in situ* measurement of any of the following:
 - 1. Coating thickness on the substrate and rate control; or
 - 2. Optical characteristics.

Note: 2B005.a., 2B005.b., 2B005.e., 2B005.f. and 2B005.g. do not control chemical vapour deposition, cathodic arc, sputter deposition, ion plating or ion implantation equipment, specially designed for cutting or machining tools.

2B006 Dimensional inspection or measuring systems, equipment and “electronic assemblies”, as follows:

N.B.: SEE ALSO 2B206.

- a. Computer controlled or “numerically controlled” Coordinate Measuring Machines (CMM), having a three dimensional (volumetric) maximum permissible error of length measurement ($E_{0,MPE}$) at any point within the operating range of the machine (i.e. within the length of axes) equal to or less (better) than $(1.7 + L/1,000)$ µm (where L is the measured length in mm), according to ISO 10360–2 (2009);

Technical Note:

The $E_{0,MPE}$ of the most accurate configuration of the CMM specified by the manufacturer (e.g. best of the following: probe, stylus length, motion parameters, environment) and with “all compensations available” shall be compared to the $1.7+L/1,000$ µm threshold.

- b. Linear and angular displacement measuring instruments, as follows:
 - 1. ‘Linear displacement’ measuring instruments having any of the following:

Note: Displacement measuring “laser” interferometers are only specified by 2B006.b.1.c.

Technical Note:

For the purpose of 2B006.b.1. 'linear displacement' means the change of distance between the measuring probe and the measured object.

- a. Non-contact type measuring systems with a “resolution” equal to or less (better) than 0.2 µm within a measuring range up to 0.2 mm;
- b. Linear Variable Differential Transformer (LVDT) systems having all of the following:
 - 1. Having any of the following:
 - a. “Linearity” equal to or less (better) than 0.1% measured from 0 to the ‘full operating range’, for LVDTs with a ‘full operating range’ up to and including ± 5 mm; or
 - b. “Linearity” equal to or less (better) than 0.1% measured from 0 to 5 mm for LVDTs with a ‘full operating range’ greater than ± 5 mm; and
 - 2. Drift equal to or less (better) than 0.1% per day at a standard ambient test room temperature ±1 K;

Technical Note:

For the purposes of 2B006.b.1.b., ‘full operating range’ is half of the total possible linear displacement of the LVDT. For example, LVDTs with a ‘full operating range’ up to and including ± 5 mm can measure a total possible linear displacement of 10 mm.

- c. Measuring systems having all of the following:
 - 1. Containing a “laser”; and
 - 2. Maintaining, for at least 12 hours, at a temperature of 20±1°C, all of the following:
 - a. A “resolution” over their full scale of 0.1 µm or less (better); and
 - b. Capable of achieving a “measurement uncertainty” equal to or less (better) than $(0.2 + L/2,000)$ µm (L is the measured length in mm) at any point within a measuring range, when compensated for the refractive index of air; or
- d. “Electronic assemblies” specially designed to provide feedback capability in systems specified in 2B006.b.1.c.;

Note: 2B006.b.1. does not control measuring interferometer systems, with an automatic control system that is designed to use no feedback techniques, containing a “laser” to measure slide movement errors of machine-tools, dimensional inspection machines or similar equipment.

-
2. Angular displacement measuring instruments having an angular position “accuracy” equal to or less (better) than 0.00025°;
Note: 2B006.b.2. does not control optical instruments, such as autocollimators, using collimated light (e.g., laser light) to detect angular displacement of a mirror.
- c. Equipment for measuring surface roughness (including surface defects), by measuring optical scatter with a sensitivity of 0.5 nm or less (better).
Note: 2B006. includes machine tools, other than those specified by 2B001., that can be used as measuring machines if they meet or exceed the criteria specified for the measuring machine function.
- 2B007 “Robots” having any of the following characteristics and specially designed controllers and “end-effectors” therefor:
N.B.: SEE ALSO 2B207.
- a. Capable in real time of full three-dimensional image processing or full three-dimensional ‘scene analysis’ to generate or modify “programs” or to generate or modify numerical program data;
Technical Note:
The ‘scene analysis’ limitation does not include approximation of the third dimension by viewing at a given angle, or limited grey scale interpretation for the perception of depth or texture for the approved tasks (2 1/2 D).
- b. Specially designed to comply with national safety standards applicable to potentially explosive munitions environments;
Note: 2B007.b. does not control “robots” specially designed for paint-spraying booths.
- c. Specially designed or rated as radiation-hardened to withstand a total radiation dose greater than 5×10^3 Gy (silicon) without operational degradation; or
Technical Note:
The term Gy(silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionising radiation.
- d. Specially designed to operate at altitudes exceeding 30,000 m.
- 2B008 Assemblies or units, specially designed for machine tools, or dimensional inspection or measuring systems and equipment, as follows:
- a. Linear position feedback units (e.g., inductive type devices, graduated scales, infrared systems or “laser” systems) having an overall “accuracy” less (better) than $(800 + (600 \times L \times 10^{-3}))$ nm (L equals the effective length in mm);
N.B.: For “laser” systems see also Note to 2B006.b.1.c. and d.
-

-
- b. Rotary position feedback units (e.g., inductive type devices, graduated scales, infrared systems or “laser” systems) having an “accuracy” less (better) than 0.00025°;

N.B.: For “laser” systems see also Note to 2B006.b.2.

Note: 2B008.a. and 2B008.b. apply to units, which are designed to determine the positioning information for feedback control, such as inductive type devices, graduated scales, infrared systems or “laser” systems.

- c. “Compound rotary tables” and “tilting spindles”, capable of upgrading, according to the manufacturer’s specifications, machine tools to or above the levels specified in 2B.

2B009 Spin-forming machines and flow-forming machines, which, according to the manufacturer’s technical specification, can be equipped with “numerical control” units or a computer control and having all of the following:

N.B.: SEE ALSO 2B109 AND 2B209.

- a. Two or more controlled axes of which at least two can be coordinated simultaneously for “contouring control”; and
- b. A roller force more than 60 kN.

Technical Note:

For the purpose of 2B009, machines combining the function of spin-forming and flow-forming are regarded as flow-forming machines.

2B104 “Isostatic presses”, other than those specified in 2B004, having all of the following:

N.B.: SEE ALSO 2B204.

- a. Maximum working pressure of 69 MPa or greater;
- b. Designed to achieve and maintain a controlled thermal environment of 873 K (600°C) or greater; and
- c. Possessing a chamber cavity with an inside diameter of 254 mm or greater.

2B105 Chemical vapour deposition (CVD) furnaces, other than those specified in 2B005.a., designed or modified for the densification of carbon-carbon composites.

2B109 Flow-forming machines, other than those specified in 2B009, and specially designed components as follows:

N.B.: SEE ALSO 2B209.

- a. Flow-forming machines having all of the following:
 - 1. According to the manufacturer’s technical specification, can be equipped with “numerical control” units or a computer control, even when not equipped with such units; and

2. With more than two axes which can be coordinated simultaneously for “contouring control”;
- b. Specially designed components for flow-forming machines specified in 2B009 or 2B109.a.

Note: 2B109 does not control machines that are not usable in the production of propulsion components and equipment (e.g. motor cases) for systems specified in 9A005, 9A007.a. or 9A105.a.

Technical Note:

Machines combining the function of spin-forming and flow-forming are for the purpose of 2B109 regarded as flow-forming machines.

2B116 Vibration test systems, equipment and components therefor, as follows:

- a. Vibration test systems employing feedback or closed loop techniques and incorporating a digital controller, capable of vibrating a system at an acceleration equal to or greater than 10 g rms between 20 Hz and 2 kHz while imparting forces equal to or greater than 50 kN, measured ‘bare table’;
- b. Digital controllers, combined with specially designed vibration test software, with a ‘real-time control bandwidth’ greater than 5 kHz designed for use with vibration test systems specified in 2B116.a.;

Technical Note:

In 2B116.b., ‘real-time control bandwidth’ means the maximum rate at which a controller can execute complete cycles of sampling, processing data and transmitting control signals.

- c. Vibration thrusters (shaker units), with or without associated amplifiers, capable of imparting a force equal to or greater than 50 kN, measured ‘bare table’, and usable in vibration test systems specified in 2B116.a.;
- d. Test piece support structures and electronic units designed to combine multiple shaker units in a system capable of providing an effective combined force equal to or greater than 50 kN, measured ‘bare table’, and usable in vibration systems specified in 2B116.a.

Technical Note:

In 2B116, ‘bare table’ means a flat table, or surface, with no fixture or fittings.

2B117 Equipment and process controls, other than those specified in 2B004, 2B005.a., 2B104 or 2B105, designed or modified for densification and pyrolysis of structural composite rocket nozzles and reentry vehicle nose tips.

2B119 Balancing machines and related equipment, as follows:

N.B.: SEE ALSO 2B219.

	<p>a. Balancing machines having all the following characteristics:</p> <ol style="list-style-type: none">1. Not capable of balancing rotors/assemblies having a mass greater than 3 kg;2. Capable of balancing rotors/assemblies at speeds greater than 12,500 rpm;3. Capable of correcting unbalance in two planes or more; and4. Capable of balancing to a residual specific unbalance of 0.2 g mm per kg of rotor mass; <p><i>Note: 2B119.a. does not control balancing machines designed or modified for dental or other medical equipment.</i></p> <p>b. Indicator heads designed or modified for use with machines specified in 2B119.a.</p> <p><i>Technical Note:</i> <i>Indicator heads are sometimes known as balancing instrumentation.</i></p>
2B120	<p>Motion simulators or rate tables having all of the following characteristics:</p> <p>a. Two axes or more;</p> <p>b. Designed or modified to incorporate slip rings or integrated non-contact devices capable of transferring electrical power, signal information, or both; and</p> <p>c. Having any of the following characteristics:</p> <ol style="list-style-type: none">1. For any single axis having all of the following:<ol style="list-style-type: none">a. Capable of rates of 400 degrees/s or more, or 30 degrees/s or less; andb. A rate resolution equal to or less than 6 degrees/s and an accuracy equal to or less than 0.6 degrees/s;2. Having a worst-case rate stability equal to or better (less) than plus or minus 0.05 % averaged over 10 degrees or more; or3. A positioning “accuracy” equal to or less (better) than 5 arc second. <p><i>Note 1: 2B120 does not control rotary tables designed or modified for machine tools or for medical equipment. For controls on machine tool rotary tables see 2B008.</i></p> <p><i>Note 2: Motion simulators or rate tables specified in 2B120 remain controlled whether or not slip rings or integrated non-contact devices are fitted at time of export.</i></p>
2B121	<p>Positioning tables (equipment capable of precise rotary positioning in any axes), other than those specified in 2B120, having all the following characteristics:</p> <p>a. Two axes or more; and</p> <p>b. A positioning “accuracy” equal to or less (better) than 5 arc second.</p>

Note: 2B121 does not control rotary tables designed or modified for machine tools or for medical equipment. For controls on machine tool rotary tables see 2B008.

2B122 Centrifuges capable of imparting accelerations above 100 g and designed or modified to incorporate slip rings or integrated non-contact devices capable of transferring electrical power, signal information, or both.

Note: Centrifuges specified in 2B122 remain controlled whether or not slip rings or integrated non-contact devices are fitted at time of export.

2B201 Machine tools and any combination thereof, other than those specified in 2B001, as follows, for removing or cutting metals, ceramics or “composites”, which, according to the manufacturer’s technical specification, can be equipped with electronic devices for simultaneous “contouring control” in two or more axes:

- a. Machine tools for milling, having any of the following characteristics:
1. Positioning accuracies with “all compensations available” equal to or less (better) than 6 µm according to ISO 230/2 (1988) or national equivalents along any linear axis; or
 2. Two or more contouring rotary axes;

Note: 2B201.a. does not control milling machines having the following characteristics:

- a. X-axis travel greater than 2 m; and*
- b. Overall positioning accuracy on the x-axis more (worse) than 30 µm.*

- b. Machine tools for grinding, having any of the following characteristics:
1. Positioning accuracies with “all compensations available” equal to or less (better) than 4 µm according to ISO 230/2 (1988) or national equivalents along any linear axis; or
 2. Two or more contouring rotary axes.

Note: 2B201.b. does not control the following grinding machines:

- a. Cylindrical external, internal, and external-internal grinding machines having all of the following characteristics:*
 - 1. Limited to a maximum workpiece capacity of 150 mm outside diameter or length; and*
 - 2. Axes limited to x, z and c;*
- b. Jig grinders that do not have a z-axis or a w-axis with an overall positioning accuracy less (better) than 4 µm according to ISO 230/2 (1988) or national equivalents.*

Note 1: 2B201 does not control special purpose machine tools limited to the manufacture of any of the following parts:

- a. Gears;*
 - b. Crankshafts or camshafts;*
 - c. Tools or cutters;*
-

d. Extruder worms.

Note 2: A machine tool having at least two of the three turning, milling or grinding capabilities (e.g., a turning machine with milling capability), must be evaluated against each applicable entry 2B001.a. or 2B201.a. or b.

2B204 “Isostatic presses”, other than those specified in 2B004 or 2B104, and related equipment, as follows:

- a. “Isostatic presses” having both of the following characteristics:
 - 1. Capable of achieving a maximum working pressure of 69 MPa or greater; and
 - 2. A chamber cavity with an inside diameter in excess of 152 mm;
- b. Dies, moulds and controls, specially designed for “isostatic presses” specified in 2B204.a.

Technical Note:

In 2B204 the inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.

2B206 Dimensional inspection machines, instruments or systems, other than those specified in 2B006, as follows:

- a. Computer controlled or “numerically controlled” Coordinate Measuring Machines (CMM) having either of the following characteristics:
 - 1. Having only two axes and having a maximum permissible error of length measurement along any axis (one dimensional), identified as any combination of $E_{0x\text{ MPE}}$, $E_{0y\text{ MPE}}$ or $E_{0z\text{ MPE}}$, equal to or less (better) than $(1.25 + L/1000) \mu\text{m}$ (where L is the measured length in mm) at any point within the operating range of the machine (i.e., within the length of the axis), according to ISO 10360-2(2009); or
 - 2. Three or more axes and having a three dimensional (volumetric) maximum permissible error of length measurement ($E_{0\text{ MPE}}$) equal to or less (better) than $(1.7 + L/800) \mu\text{m}$ (where L is the measured length in mm) at any point within the operating range of the machine (i.e. within the length of the axis), according to ISO 10360-2(2009);

Technical Note:

The $E_{0\text{ MPE}}$ of the most accurate configuration of the CMM specified according to ISO 10360-2(2009) by the manufacturer (e.g., best of the following: probe, stylus length, motion parameters, environment) and with all compensations available shall be compared to the $1.7 + L/800 \mu\text{m}$ threshold.

- b. Linear displacement measuring instruments, as follows:
-

-
1. Non-contact type measuring systems with a “resolution” equal to or better (less) than 0.2 µm within a measuring range up to 0.2 mm;
 2. Linear variable differential transformer (LVDT) systems having both of the following characteristics:
 - a. Having any of the following:
 1. “Linearity” equal to or less (better) than 0.1% measured from 0 to the full operating range, for LVDTs with an operating range up to 5 mm; or
 2. “Linearity” equal to or less (better) than 0.1% measured from 0 to 5 mm, for LVDTs with an operating range greater than 5 mm; and
 - b. Drift equal to or better (less) than 0.1% per day at a standard ambient test room temperature ± 1 K;
 3. Measuring systems having both of the following characteristics:
 - a. Contain a laser; and
 - b. Maintain for at least 12 hours, over a temperature range of ± 1 K around a standard temperature and a standard pressure:
 1. A “resolution” over their full scale of 0.1 µm or better; and
 2. With a “measurement uncertainty” equal to or better (less) than $(0.2 + L/2000)$ µm (L is the measured length in millimeters);

Note: Item 2B206.b.3. does not control measuring interferometer systems, without closed or open loop feedback, containing a laser to measure slide movement errors of machine tools, dimensional inspection machines, or similar equipment.

Technical Note:

In Item 2B206.b. ‘linear displacement’ means the change of distance between the measuring probe and the measured object.

- c. Angular displacement measuring instruments having an “angular position deviation” equal to or better (less) than 0.00025°;

Note: Item 2B206.c. does not control optical instruments, such as autocollimators, using collimated light (e.g., laser light) to detect angular displacement of a mirror.

- d. Systems for simultaneous linear-angular inspection of hemishells, having both of the following characteristics:
 1. “Measurement uncertainty” along any linear axis equal to or less (better) than 3.5 µm per 5 mm; and
 2. “Angular position deviation” equal to or less than 0.02°.

Note 1: Machine tools that can be used as measuring machines are controlled if they meet or exceed the criteria specified for the machine tool function or the measuring machine function.

Note 2: A machine specified in 2B206 is controlled if it exceeds the control threshold anywhere within its operating range.

Technical Note:

All parameters of measurement values in 2B206 represent plus/minus i.e. not total band.

2B207 “Robots”, “end-effectors” and control units, other than those specified in 2B007, as follows:

- a. “Robots” or “end-effectors” specially designed to comply with national safety standards applicable to handling high explosives (for example, meeting electrical code ratings for high explosives);
- b. Control units specially designed for any of the “robots” or “end-effectors” specified in 2B207.a.

2B209 Flow forming machines, spin forming machines capable of flow forming functions, other than those specified in 2B009 or 2B109, and mandrels, as follows:

- a. Machines having both of the following characteristics:
 1. Three or more rollers (active or guiding); and
 2. Which, according to the manufacturer’s technical specification, can be equipped with “numerical control” units or a computer control;
- b. Rotor-forming mandrels designed to form cylindrical rotors of inside diameter between 75 mm and 400 mm.

Note: 2B209.a. includes machines which have only a single roller designed to deform metal plus two auxiliary rollers which support the mandrel, but do not participate directly in the deformation process.

2B219 Centrifugal multiplane balancing machines, fixed or portable, horizontal or vertical, as follows:

- a. Centrifugal balancing machines designed for balancing flexible rotors having a length of 600 mm or more and having all of the following characteristics:
 1. Swing or journal diameter greater than 75 mm;
 2. Mass capability of from 0.9 to 23 kg; and
 3. Capable of balancing speed of revolution greater than 5,000 r.p.m.;
- b. Centrifugal balancing machines designed for balancing hollow cylindrical rotor components and having all of the following characteristics:
 1. Journal diameter greater than 75 mm;
 2. Mass capability of from 0.9 to 23 kg;

-
3. Capable of balancing to a residual imbalance equal to or less than 0.01 kg x mm/kg per plane; and
4. Belt drive type.
- 2B225 Remote manipulators that can be used to provide remote actions in radiochemical separation operations or hot cells, having either of the following characteristics:
- A capability of penetrating 0.6 m or more of hot cell wall (through-the-wall operation); or
 - A capability of bridging over the top of a hot cell wall with a thickness of 0.6 m or more (over-the-wall operation).
- Technical Note:*
Remote manipulators provide translation of human operator actions to a remote operating arm and terminal fixture. They may be of 'master/slave' type or operated by joystick or keypad.
- 2B226 Controlled atmosphere (vacuum or inert gas) induction furnaces, and power supplies therefor, as follows:
- N.B.: SEE ALSO 3B.**
- Furnaces having all of the following characteristics:
 - Capable of operation above 1,123 K (850°C);
 - Induction coils 600 mm or less in diameter; and
 - Designed for power inputs of 5 kW or more;
 - Power supplies, with a specified power output of 5 kW or more, specially designed for furnaces specified in 2B226.a.
- Note:* 2B226.a. does not control furnaces designed for the processing of semiconductor wafers.
- 2B227 Vacuum or other controlled atmosphere metallurgical melting and casting furnaces and related equipment as follows:
- Arc remelt and casting furnaces having both of the following characteristics:
 - Consumable electrode capacities between 1,000 cm³ and 20,000 cm³; and
 - Capable of operating with melting temperatures above 1,973 K (1,700°C);
 - Electron beam melting furnaces and plasma atomisation and melting furnaces, having both of the following characteristics:
 - A power of 50 kW or greater; and
 - Capable of operating with melting temperatures above 1,473 K (1,200°C);
-

-
- c. Computer control and monitoring systems specially configured for any of the furnaces specified in 2B227.a. or b.
- 2B228 Rotor fabrication or assembly equipment, rotor straightening equipment, bellows-forming mandrels and dies, as follows:
- a. Rotor assembly equipment for assembly of gas centrifuge rotor tube sections, baffles, and end caps;
- Note: 2B228.a. includes precision mandrels, clamps, and shrink fit machines.*
- b. Rotor straightening equipment for alignment of gas centrifuge rotor tube sections to a common axis;
- Technical Note:*
In 2B228.b. such equipment normally consists of precision measuring probes linked to a computer that subsequently controls the action of, for example, pneumatic rams used for aligning the rotor tube sections.
- c. Bellows-forming mandrels and dies for producing single-convolution bellows.
- Technical Note:*
In 2B228.c. the bellows have all of the following characteristics:
- 1. Inside diameter between 75 mm and 400 mm;*
 - 2. Length equal to or greater than 12.7 mm;*
 - 3. Single convolution depth greater than 2 mm; and*
 - 4. Made of high-strength aluminium alloys, maraging steel or high strength "fibrous or filamentary materials".*
- 2B230 All types of "pressure transducers" capable of measuring absolute pressures and having all of the following characteristics:
- a. Pressure sensing elements made of or protected by aluminium, aluminium alloy, aluminium oxide (alumina or sapphire), nickel, nickel alloy with more than 60% nickel by weight or fully fluorinated hydrocarbon polymers;
- b. Seals, if any, essential for sealing the pressure sensing element, and in direct contact with the process medium, made of or protected by aluminium, aluminium alloy, aluminium oxide (alumina or sapphire), nickel, nickel alloy with more than 60% nickel by weight, or fully fluorinated hydrocarbon polymers; and
- c. Having either of the following characteristics:
1. A full scale of less than 13 kPa and an 'accuracy' of better than $\pm 1\%$ of full-scale; or
 2. A full scale of 13 kPa or greater and an 'accuracy' of better than ± 130 Pa when measuring at 13 kPa.
-

Technical Note:

For the purposes of 2B230, 'accuracy' includes non-linearity, hysteresis and repeatability at ambient temperature.

2B231 Vacuum pumps having all of the following characteristics:

- a. Input throat size equal to or greater than 380 mm;
- b. Pumping speed equal to or greater than 15 m³/s; and
- c. Capable of producing an ultimate vacuum better than 13 mPa.

Technical Notes:

1. *The pumping speed is determined at the measurement point with nitrogen gas or air.*
2. *The ultimate vacuum is determined at the input of the pump with the input of the pump blocked off.*

2B232 High-velocity gun systems (propellant, gas, coil, electromagnetic, and electrothermal types, and other advanced systems) capable of accelerating projectiles to 1.5 km/s or greater.

Note: This item does not control guns specially designed for high velocity weapon systems.

2B233 Bellows-sealed scroll-type compressors and bellows-sealed scroll-type vacuum pumps having all of the following characteristics:

- a. Capable of an inlet volume flow rate of 50 m³/h or greater;
- b. Capable of a pressure ratio of 2:1 or greater; and
- c. Having all surfaces that come in contact with the process gas made from any of the following materials:
 1. Aluminium or aluminium alloy;
 2. Aluminium oxide;
 3. Stainless steel;
 4. Nickel or nickel alloy;
 5. Phosphor bronze; or
 6. Fluoropolymers.

Technical Notes:

1. *In a scroll compressor or vacuum pump, crescent-shaped pockets of gas are trapped between one or more pairs of intermeshed spiral vanes, or scrolls, one of which moves while the other remains stationary. The moving scroll orbits the stationary scroll; it does not rotate. As the moving scroll orbits the stationary scroll, the gas pockets diminish in size (i.e., they are compressed) as they move toward the outlet port of the machine.*

-
2. *In a bellows-sealed scroll compressor or vacuum pump, the process gas is totally isolated from the lubricated parts of the pump and from the external atmosphere by a metal bellows. One end of the bellows is attached to the moving scroll and the other end is attached to the stationary housing of the pump.*
 3. *Fluoropolymers include, but are not limited to, the following materials:*
 - a. *Polytetrafluoroethylene (PTFE),*
 - b. *Fluorinated Ethylene Propylene (FEP),*
 - c. *Perfluoroalkoxy (PFA),*
 - d. *Polychlorotrifluoroethylene (PCTFE); and*
 - e. *Vinylidene fluoride-hexafluoropropylene copolymer.*

2B350 Chemical manufacturing facilities, equipment and components, as follows:

- a. Reaction vessels or reactors, with or without agitators, with total internal (geometric) volume greater than 0.1 m³ (100 litres) and less than 20 m³ (20,000 litres), where all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:
 1. Alloys with more than 25% nickel and 20% chromium by weight;
 2. Fluoropolymers;
 3. Glass (including vitrified or enamelled coating or glass lining);
 4. Nickel or alloys with more than 40% nickel by weight;
 5. Tantalum or tantalum alloys;
 6. Titanium or titanium alloys;
 7. Zirconium or zirconium alloys; or
 8. Niobium (columbium) or niobium alloys;
- b. Agitators designed for use in reaction vessels or reactors specified in 2B350.a.; and impellers, blades or shafts designed for such agitators: where all surfaces of the agitator that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:
 1. Alloys with more than 25% nickel and 20% chromium by weight;
 2. Fluoropolymers;
 3. Glass (including vitrified or enamelled coatings or glass lining);
 4. Nickel or alloys with more than 40% nickel by weight;
 5. Tantalum or tantalum alloys;
 6. Titanium or titanium alloys;
 7. Zirconium or zirconium alloys; or
 8. Niobium (columbium) or niobium alloys;

-
- c. Storage tanks, containers or receivers with a total internal (geometric) volume greater than 0.1 m³ (100 litres) where all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:
1. Alloys with more than 25% nickel and 20% chromium by weight;
 2. Fluoropolymers;
 3. Glass (including vitrified or enamelled coatings or glass lining);
 4. Nickel or alloys with more than 40% nickel by weight;
 5. Tantalum or tantalum alloys;
 6. Titanium or titanium alloys;
 7. Zirconium or zirconium alloys; or
 8. Niobium (columbium) or niobium alloys;
- d. Heat exchangers or condensers with a heat transfer surface area greater than 0.15 m², and less than 20 m²; and tubes, plates, coils or blocks (cores) designed for such heat exchangers or condensers, where all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:
1. Alloys with more than 25% nickel and 20% chromium by weight;
 2. Fluoropolymers;
 3. Glass (including vitrified or enamelled coatings or glass lining);
 4. Graphite or 'carbon graphite';
 5. Nickel or alloys with more than 40% nickel by weight;
 6. Tantalum or tantalum alloys;
 7. Titanium or titanium alloys;
 8. Zirconium or zirconium alloys;
 9. Silicon carbide;
 10. Titanium carbide; or
 11. Niobium (columbium) or niobium alloys;
- e. Distillation or absorption columns of internal diameter greater than 0.1 m; and liquid distributors, vapour distributors or liquid collectors designed for such distillation or absorption columns, where all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:
1. Alloys with more than 25% nickel and 20% chromium by weight;
 2. Fluoropolymers;
 3. Glass (including vitrified or enamelled coatings or glass lining);
 4. Graphite or 'carbon graphite';
 5. Nickel or alloys with more than 40% nickel by weight;
 6. Tantalum or tantalum alloys;
 7. Titanium or titanium alloys;
 8. Zirconium or zirconium alloys; or
 9. Niobium (columbium) or niobium alloys;
-

-
- f. Remotely operated filling equipment in which all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:
 - 1. Alloys with more than 25% nickel and 20% chromium by weight; or
 - 2. Nickel or alloys with more than 40% nickel by weight;
 - g. Valves with nominal sizes greater than 10 mm and casings (valve bodies) or preformed casing liners designed for such valves, in which all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:
 - 1. Alloys with more than 25% nickel and 20% chromium by weight;
 - 2. Fluoropolymers;
 - 3. Glass (including vitrified or enamelled coatings or glass lining);
 - 4. Nickel or alloys with more than 40% nickel by weight;
 - 5. Tantalum or tantalum alloys;
 - 6. Titanium or titanium alloys;
 - 7. Zirconium or zirconium alloys; or
 - 8. Niobium (columbium) or niobium alloys;
 - 9. Ceramic materials as follows:
 - a. Silicon carbide with purity of 80% or more by weight;
 - b. Aluminium oxide (alumina) with purity of 99.9% or more by weight;
 - c. Zirconium oxide (zirconia);
 - h. Multi-walled piping incorporating a leak detection port, in which all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:
 - 1. Alloys with more than 25% nickel and 20% chromium by weight;
 - 2. Fluoropolymers;
 - 3. Glass (including vitrified or enamelled coatings or glass lining);
 - 4. Graphite or 'carbon graphite';
 - 5. Nickel or alloys with more than 40% nickel by weight;
 - 6. Tantalum or tantalum alloys;
 - 7. Titanium or titanium alloys;
 - 8. Zirconium or zirconium alloys; or
 - 9. Niobium (columbium) or niobium alloys;
-

- i. Multiple-seal and seal-less pumps, with manufacturer's specified maximum flow-rate greater than 0.6 m³/hour, or vacuum pumps with manufacturer's specified maximum flow-rate greater than 5 m³/hour (under standard temperature (273 K (0°C)) and pressure (101.3 kPa) conditions); and casings (pump bodies), preformed casing liners, impellers, rotors or jet pump nozzles designed for such pumps, in which all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:
 1. Alloys with more than 25% nickel and 20% chromium by weight;
 2. Ceramics;
 3. Ferrosilicon;
 4. Fluoropolymers;
 5. Glass (including vitrified or enamelled coatings or glass lining);
 6. Graphite or 'carbon graphite';
 7. Nickel or alloys with more than 40% nickel by weight;
 8. Tantalum or tantalum alloys;
 9. Titanium or titanium alloys;
 10. Zirconium or zirconium alloys; or
 11. Niobium (columbium) or niobium alloys;
- j. Incinerators designed to destroy chemicals specified in 1C350, having specially designed waste supply systems, special handling facilities and an average combustion chamber temperature greater than 1,273 K (1,000°C), in which all surfaces in the waste supply system that come into direct contact with the waste products are made from or lined with any of the following materials:
 1. 'Alloys' with more than 25% nickel and 20% chromium by weight;
 2. Ceramics; or
 3. Nickel or 'alloys' with more than 40% nickel by weight.

Technical Note:

1. 'Carbon graphite' is a composition consisting of amorphous carbon and graphite, in which the graphite content is eight percent or more by weight.
2. For the listed materials in the above entries, the term 'alloy' when not accompanied by a specific elemental concentration is understood as identifying those alloys where the identified metal is present in a higher percentage by weight than any other element.

- 2B351 Toxic gas monitoring systems and their dedicated detecting components, other than those specified in 1A004, as follows, and detectors, sensor devices, and replaceable sensor cartridges therefor:
- a. Designed for continuous operation and usable for the detection of chemical warfare agents or chemicals specified in 1C350, at concentrations of less than 0.3 mg/m³; or
 - b. Designed for the detection of cholinesterase-inhibiting activity.

-
- 2B352 Equipment capable of use in handling biological materials, as follows:
- a. Complete biological containment facilities at P3, P4 containment level;
Technical Note:
P3 or P4 (BL3, BL4, L3, L4) containment levels are as specified in the WHO Laboratory Biosafety manual (3rd edition Geneva 2004).
 - b. Fermenters and components thereof, as follows:
 1. Fermenters capable of cultivation of pathogenic “microorganisms” or of live cells for the production of pathogenic viruses or toxins, without the propagation of aerosols, having a total capacity of 20 litres or more;
 2. Components designed for fermenters specified by 2B352.b.1., as follows:
 - a. Cultivation chambers designed to be sterilized or disinfected in situ;
 - b. Cultivation chamber holding devices; or
 - c. Process control units capable of simultaneously monitoring and controlling two or more fermentation system parameters (e.g. temperature, pH, nutrients, agitation, dissolved oxygen, air flow, foam control).*Technical Note:*
Fermenters include bioreactors (including single-use (disposable) bioreactors), chemostats and continuous-flow systems.
 - c. Centrifugal separators, capable of continuous separation without the propagation of aerosols, having all the following characteristics:
 1. Flow rate exceeding 100 litres per hour;
 2. Components of polished stainless steel or titanium;
 3. One or more sealing joints within the steam containment area; and
 4. Capable of in-situ steam sterilisation in a closed state;*Technical Note:*
Centrifugal separators include decanters.
 - d. Cross (tangential) flow filtration equipment and components as follows:
 1. Cross (tangential) flow filtration equipment capable of separation of pathogenic micro-organisms, viruses, toxins or cell cultures, without the propagation of aerosols, having all of the following characteristics:
 - a. A total filtration area equal to or greater than 1 m²; and
 - b. Having any of the following characteristics:
 1. Capable of being sterilised or disinfected in-situ; or
 2. Using disposable or single-use filtration components;
-

Technical Note:

In 2B352.d.1.b. sterilised denotes the elimination of all viable microbes from the equipment through the use of either physical (e.g. steam) or chemical agents. Disinfected denotes the destruction of potential microbial infectivity in the equipment through the use of chemical agents with a germicidal effect. Disinfection and sterilisation are distinct from sanitisation, the latter referring to cleaning procedures designed to lower the microbial content of equipment without necessarily achieving elimination of all microbial infectivity or viability.

2. Cross (tangential) flow filtration components (e.g. modules, elements, cassettes, cartridges, units or plates) with filtration area equal to or greater than 0.2 m² for each component and designed for use in cross (tangential) flow filtration equipment specified in 2B352.d.;

Note: 2B352.d. does not control reverse osmosis equipment, as specified by the manufacturer.

- e. Steam sterilisable freeze drying equipment with a condenser capacity exceeding 10 kg of ice in 24 hours and less than 1,000 kg of ice in 24 hours;
- f. Protective and containment equipment, as follows:
 1. Protective full or half suits, or hoods dependent upon a tethered external air supply and operating under positive pressure;
Note: 2B352.f.1. does not control suits designed to be worn with self-contained breathing apparatus.
 2. Class III biological safety cabinets or isolators with similar performance standards;
Note: In 2B352.f.2., isolators include flexible isolators, dry boxes, anaerobic chambers, glove boxes and laminar flow hoods (closed with vertical flow).
- g. Chambers designed for aerosol challenge testing with “microorganisms”, viruses or “toxins” and having a capacity of 1 m³ or greater.
- h. Spray drying equipment capable of drying toxins or pathogenic microorganisms having all of the following characteristics:
 1. A water evaporation capacity of ≥ 0.4 kg/h and ≤ 400 kg/h;
 2. The ability to generate a typical mean product particle size of ≤ 10 micrometers with existing fittings or by minimal modification of the spray-dryer with atomization nozzles enabling generation of the required particle size; and
 3. Capable of being sterilized or disinfected in situ.

2C Materials

None.

2D Software

- 2D001 “Software”, other than that specified in 2D002, as follows:
- a. “Software” specially designed or modified for the “development” or “production” of equipment specified in 2A or 2B.
 - b. “Software” specially designed or modified for the “use” of equipment specified by 2A001.c, 2B001, or 2B003 to 2B009.
- Note:* 2D001. does not apply to part programming “software” that generates “numerical control” codes for machining various parts.
- 2D002 “Software” for electronic devices, even when residing in an electronic device or system, enabling such devices or systems to function as a “numerical control” unit, capable of co-ordinating simultaneously more than four axes for “contouring control”.
- Note 1:* 2D002 does not control “software” specially designed or modified for the operation of items not specified in Category 2.
- Note 2:* 2D002 does not control “software” for items specified in 2B002. See 2D001 and 2D003 for “software” for items specified in 2B002.
- Note 3:* 2D002. does not apply to “software” that is exported with, and the minimum necessary for the operation of, items not specified by Category 2.
- 2D003. “Software”, designed or modified for the operation of equipment specified by 2B002., that converts optical design, workpiece measurements and material removal functions into “numerical control” commands to achieve the desired workpiece form.
- 2D101 “Software” specially designed or modified for the “use” of equipment specified in 2B104, 2B105, 2B109, 2B116, 2B117 or 2B119 to 2B122.
- N.B.: SEE ALSO 9D004.**
- 2D201 “Software” specially designed for the “use” of equipment specified in 2B204, 2B206, 2B207, 2B209, 2B219 or 2B227.
- 2D202 “Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in 2B201.
-

Note: Item 2D202 does not control part programming “software” that generates “numerical control” command codes but does not allow direct use of equipment for machining various parts.

2D351 “Software”, other than that specified in 1D003, specially designed for “use” of equipment specified in 2B351.

2E Technology

2E001 “Technology” according to the General Technology Note for the “development” of equipment or “software” specified in 2A, 2B or 2D.

Note: 2E001. includes “technology” for the integration of probe systems into coordinate measurement machines specified by 2B006.a.

2E002 “Technology” according to the General Technology Note for the “production” of equipment specified in 2A or 2B.

2E003 Other “technology”, as follows:

- a. “Technology” for the “development” of interactive graphics as an integrated part in “numerical control” units for preparation or modification of part programs;
- b. “Technology” for metal-working manufacturing processes, as follows:
 1. “Technology” for the design of tools, dies or fixtures specially designed for any of the following processes:
 - a. “Superplastic forming”;
 - b. “Diffusion bonding”; or
 - c. “Direct-acting hydraulic pressing”;
 2. Technical data consisting of process methods or parameters as listed below used to control:
 - a. “Superplastic forming” of aluminium alloys, titanium alloys or “superalloys”:
 1. Surface preparation;
 2. Strain rate;
 3. Temperature;
 4. Pressure;
 - b. “Diffusion bonding” of “superalloys” or titanium alloys:
 1. Surface preparation;
 2. Temperature;
 3. Pressure;
 - c. “Direct-acting hydraulic pressing” of aluminium alloys or titanium alloys:
 1. Pressure;

-
- 2. Cycle time;
 - d. “Hot isostatic densification” of titanium alloys, aluminium alloys or “superalloys”:
 - 1. Temperature;
 - 2. Pressure;
 - 3. Cycle time;
 - c. “Technology” for the “development” or “production” of hydraulic stretch-forming machines and dies therefor, for the manufacture of airframe structures;
 - d. “Technology” for the “development” of generators of machine tool instructions (e.g., part programs) from design data residing inside “numerical control” units;
 - e. “Technology” for the “development” of integration “software” for incorporation of expert systems for advanced decision support of shop floor operations into “numerical control” units;
 - f. “Technology” for the application of inorganic overlay coatings or inorganic surface modification coatings (specified in column 3 of the following table) to non-electronic substrates (specified in column 2 of the following table), by processes specified in column 1 of the following table and defined in the Technical Note.

Note: The table and Technical Note appear after 2E301.

N.B.: This table should be read to specify the technology of a particular Coating Process only when the Resultant Coating in column 3 is in a paragraph directly across from the relevant Substrate under column 2. For example, Chemical Vapour Deposition (CVD) coating process technical data are included for the application of silicides to carbon-carbon, ceramic and metal “matrix” “composites” substrates, but are not included for the application of silicides to ‘cemented tungsten carbide’ (16), ‘silicon carbide’ (18) substrates. In the second case, the resultant coating is not listed in the paragraph under column 3 directly across from the paragraph under column 2 listing ‘cemented tungsten carbide’ (16), ‘silicon carbide’ (18).

- 2E101 “Technology” according to the General Technology Note for the “use” of equipment or “software” specified in 2B004, 2B009, 2B104, 2B109, 2B116, 2B119 to 2B122 or 2D101.
 - 2E201 “Technology” according to the General Technology Note for the “use” of equipment or “software” specified in 2A225, 2A226, 2B001, 2B006, 2B007.b., 2B007.c., 2B008, 2B009, 2B201, 2B204, 2B206, 2B207, 2B209, 2B225 to 2B233, 2D201 or 2D202.
-

2E301 “Technology” according to the General Technology Note for the “use” of goods specified in 2B350 to 2B352.

TABLE — DEPOSITION TECHNIQUES

Column 1 Coating Process	Column 2 Substrate	Column 3 Resultant Coating
A. Chemical Vapour Deposition (CVD)	“Superalloys”	Aluminides for internal passages
	Ceramics (19) and Low-expansion glasses (14)	Silicides Carbides Dielectric layers (15) Diamond Diamond-like carbon (17)
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Silicides Carbides Refractory metals Mixtures thereof (4) Dielectric layers (15) Aluminides Alloyed aluminides (2) Boron nitride
	Cemented tungsten carbide (16), Silicon carbide (18)	Carbides Tungsten Mixtures thereof (4) Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15) Diamond Diamond-like carbon (17)
	Sensor window materials (9)	Dielectric layers (15) Diamond Diamond-like carbon (17)
B. Thermal-Evaporation Physical Vapour Deposition (TE-PVD)		
B.1. Physical Vapour Deposition (PVD): Electron-Beam (EB-PVD)	“Superalloys”	Alloyed silicides Alloyed aluminides (2) MCrAlX (5) Modified zirconia (12) Silicides Aluminides Mixtures thereof (4)
	Ceramics (19) and Low-expansion glasses (14)	Dielectric layers (15)

Part 2 Dual-use list
Category 2 Materials processing

Column 1 Coating Process	Column 2 Substrate	Column 3 Resultant Coating
	Corrosion resistant steel (7)	MCrAlX (5) Modified zirconia (12) Mixtures thereof (4)
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Silicides Carbides Refractory metals Mixtures thereof (4) Dielectric layers (15) Boron nitride
	Cemented tungsten carbide (16), Silicon carbide (18)	Carbides Tungsten Mixtures thereof (4) Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15) Borides Beryllium
	Sensor window materials (9)	Dielectric layers (15)
	Titanium alloys (13)	Borides Nitrides
B.2. Ion assisted resistive heating Physical Vapour Deposition (PVD) (Ion Plating)	Ceramics (19) and Low-expansion glasses (14)	Dielectric layers (15) Diamond-like carbon (17)
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Dielectric layers (15)
	Cemented tungsten carbide (16), Silicon carbide (18)	Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15)
	Sensor window materials (9)	Dielectric layers (15) Diamond-like carbon (17)
B.3. Physical Vapour Deposition (PVD): “Laser” Vaporisation	Ceramics (19) and Low-expansion glasses (14)	Silicides Dielectric layers (15) Diamond-like carbon (17)
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Dielectric layers (15)

Column 1 Coating Process	Column 2 Substrate	Column 3 Resultant Coating
	Cemented tungsten carbide (16), Silicon carbide (18)	Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15)
	Sensor window materials (9)	Dielectric layers (15) Diamond-like carbon (17)
B.4. Physical Vapour Deposition (PVD): Cathodic Arc Discharge	“Superalloys”	Alloyed silicides Alloyed aluminides (2) MCrAlX (5)
	Polymers (11) and Organic “matrix” “composites”	Borides Carbides Nitrides Diamond-like carbon (17)
C. Pack cementation (see A above for out-of-pack cementation) (10)	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Silicides Carbides Mixtures thereof (4)
	Titanium alloys (13)	Silicides Aluminides Alloyed aluminides (2)
	Refractory metals and alloys (8)	Silicides Oxides
D. Plasma spraying	“Superalloys”	MCrAlX (5) Modified zirconia (12) Mixtures thereof (4) Abradable Nickel-Graphite Abradable materials containing Ni-Cr-Al Abradable Al-Si-Polyester Alloyed aluminides (2)
	Aluminium alloys (6)	MCrAlX (5) Modified zirconia (12) Silicides Mixtures thereof (4)
	Refractory metals and alloys (8)	Aluminides Silicides Carbides

Part 2 Dual-use list
Category 2 Materials processing

Column 1 Coating Process	Column 2 Substrate	Column 3 Resultant Coating
	Corrosion resistant steel (7)	MCrAlX (5) Modified zirconia (12) Mixtures thereof (4)
	Titanium alloys (13)	Carbides Aluminides Silicides Alloyed aluminides (2) Abradable Nickel-Graphite Abradable materials containing Ni-Cr-Al Abradable Al-Si-Polyester
E. Slurry Deposition	Refractory metals and alloys (8)	Fused silicides Fused aluminides except for resistance heating elements
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Silicides Carbides Mixtures thereof (4)
F. Sputter Deposition	“Superalloys”	Alloyed silicides Alloyed aluminides (2) Noble metal modified aluminides (3) MCrAlX (5) Modified zirconia (12) Platinum Mixtures thereof (4)
	Ceramics (19) and Low-expansion glasses (14)	Silicides Platinum Mixtures thereof (4) Dielectric layers (15) Diamond-like carbon (17)
	Titanium alloys (13)	Borides Nitrides Oxides Silicides Aluminides Alloyed aluminides (2) Carbides
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Silicides Carbides Refractory metals Mixtures thereof (4) Dielectric layers (15) Boron nitride

Column 1 Coating Process	Column 2 Substrate	Column 3 Resultant Coating
	Cemented tungsten carbide (16), Silicon carbide (18)	Carbides Tungsten Mixtures thereof (4) Dielectric layers (15) Boron nitride
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Borides Dielectric layers (15) Beryllium
	Sensor window materials (9)	Dielectric layers (15) Diamond-like carbon (17)
	Refractory metals and alloys (8)	Aluminides Silicides Oxides Carbides
G. Ion Implantation	High temperature bearing steels	Additions of Chromium Tantalum or Niobium (Columbium)
	Titanium alloys (13)	Borides Nitrides
	Beryllium and Beryllium alloys	Borides
	Cemented tungsten carbide (16)	Carbides Nitrides

TABLE — DEPOSITION TECHNIQUES: NOTES

1. The term ‘coating process’ includes coating repair and refurbishing as well as original coating.
2. The term ‘alloyed aluminide coating’ includes single or multiple-step coatings in which an element or elements are deposited prior to or during application of the aluminide coating, even if these elements are deposited by another coating process. It does not, however, include the multiple use of single-step pack cementation processes to achieve alloyed aluminides.
3. The term ‘noble metal modified aluminide’ coating includes multiple-step coatings in which the noble metal or noble metals are laid down by some other coating process prior to application of the aluminide coating.
4. The term ‘mixtures thereof’ includes infiltrated material, graded compositions, co-deposits and multilayer deposits and are obtained by one or more of the coating processes specified in the Table.

-
5. 'MCrAlX' refers to a coating alloy where M equals cobalt, iron, nickel or combinations thereof and X equals hafnium, yttrium, silicon, tantalum in any amount or other intentional additions over 0.01% by weight in various proportions and combinations, except:
 - a. CoCrAlY coatings which contain less than 22% by weight of chromium, less than 7% by weight of aluminium and less than 2% by weight of yttrium;
 - b. CoCrAlY coatings which contain 22 to 24% by weight of chromium, 10 to 12% by weight of aluminium and 0.5 to 0.7% by weight of yttrium; or
 - c. NiCrAlY coatings which contain 21 to 23% by weight of chromium, 10 to 12% by weight of aluminium and 0.9 to 1.1% by weight of yttrium.
 6. The term 'aluminium alloys' refers to alloys having an ultimate tensile strength of 190 MPa or more measured at 293 K (20°C).
 7. The term 'corrosion resistant steel' refers to AISI (American Iron and Steel Institute) 300 series or equivalent national standard steels.
 8. 'Refractory metals and alloys' include the following metals and their alloys: niobium (columbium), molybdenum, tungsten and tantalum.
 9. 'Sensor window materials', as follows: alumina, silicon, germanium, zinc sulphide, zinc selenide, gallium arsenide, diamond, gallium phosphide, sapphire and the following metal halides: sensor window materials of more than 40 mm diameter for zirconium fluoride and hafnium fluoride.
 10. "Technology" for single-step pack cementation of solid airfoils is not controlled by Category 2.
 11. 'Polymers', as follows: polyimide, polyester, polysulphide, polycarbonates and polyurethanes.
 12. 'Modified zirconia' refers to additions of other metal oxides (e.g., calcia, magnesia, yttria, hafnia, rare earth oxides) to zirconia in order to stabilise certain crystallographic phases and phase compositions. Thermal barrier coatings made of zirconia, modified with calcia or magnesia by mixing or fusion, are not controlled.
 13. 'Titanium alloys' refers only to aerospace alloys having an ultimate tensile strength of 900 MPa or more measured at 293 K (20°C).
 14. 'Low-expansion glasses' refers to glasses which have a coefficient of thermal expansion of $1 \times 10^{-7} \text{ K}^{-1}$ or less measured at 293 K (20°C).
 15. 'Dielectric layers' are coatings constructed of multi-layers of insulator materials in which the interference properties of a design composed of materials of various refractive indices are used to reflect, transmit or absorb various wavelength bands. Dielectric layers refers to more than four dielectric layers or dielectric/metal "composite" layers.
 16. 'Cemented tungsten carbide' does not include cutting and forming tool materials consisting of tungsten carbide/(cobalt, nickel), titanium carbide/(cobalt, nickel), chromium carbide/nickel-chromium and chromium carbide/nickel.
-

-
17. “Technology” specially designed to deposit diamond-like carbon on any of the following is not controlled:

magnetic disk drives and heads, equipment for the manufacture of disposables, valves for faucets, acoustic diaphragms for speakers, engine parts for automobiles, cutting tools, punching-pressing dies, office automation equipment, microphones or medical devices or moulds, for casting or moulding of plastics, manufactured from alloys containing less than 5% beryllium.
 18. ‘Silicon carbide’ does not include cutting and forming tool materials.
 19. Ceramic substrates, as used in this entry, does not include ceramic materials containing 5% by weight, or greater, clay or cement content, either as separate constituents or in combination.

TABLE — DEPOSITION TECHNIQUES: TECHNICAL NOTE

Processes specified in Column 1 of the Table are defined as follows:

- a. Chemical Vapour Deposition (CVD) is an overlay coating or surface modification coating process wherein a metal, alloy, “composite”, dielectric or ceramic is deposited upon a heated substrate. Gaseous reactants are decomposed or combined in the vicinity of a substrate resulting in the deposition of the desired elemental, alloy or compound material on the substrate. Energy for this decomposition or chemical reaction process may be provided by the heat of the substrate, a glow discharge plasma, or “laser” irradiation.

N.B. 1: CVD includes the following processes: directed gas flow out-of-pack deposition, pulsating CVD, controlled nucleation thermal deposition (CNTD), plasma enhanced or plasma assisted CVD processes.

N.B. 2: Pack denotes a substrate immersed in a powder mixture.

N.B. 3: The gaseous reactants used in the out-of-pack process are produced using the same basic reactions and parameters as the pack cementation process, except that the substrate to be coated is not in contact with the powder mixture.
- b. Thermal Evaporation-Physical Vapour Deposition (TE-PVD) is an overlay coating process conducted in a vacuum with a pressure less than 0.1 Pa wherein a source of thermal energy is used to vaporise the coating material. This process results in the condensation, or deposition, of the evaporated species onto appropriately positioned substrates.

The addition of gases to the vacuum chamber during the coating process to synthesise compound coatings is an ordinary modification of the process.

The use of ion or electron beams, or plasma, to activate or assist the coating’s deposition is also a common modification in this technique. The use of monitors to provide in-process measurement of optical characteristics and thickness of coatings can be a feature of these processes.

Specific TE-PVD processes are as follows:
 1. Electron Beam PVD uses an electron beam to heat and evaporate the material which forms the coating;

-
2. Ion Assisted Resistive Heating PVD employs electrically resistive heating sources in combination with impinging ion beam(s) to produce a controlled and uniform flux of evaporated coating species;
 3. “Laser” Vaporisation uses either pulsed or continuous wave “laser” beams to vaporise the material which forms the coating;
 4. Cathodic Arc Deposition employs a consumable cathode of the material which forms the coating and has an arc discharge established on the surface by a momentary contact of a ground trigger. Controlled motion of arcing erodes the cathode surface creating a highly ionised plasma. The anode can be either a cone attached to the periphery of the cathode, through an insulator, or the chamber. Substrate biasing is used for non line-of-sight deposition;
- N.B.: This definition does not include random cathodic arc deposition with non-biased substrates.*
5. Ion Plating is a special modification of a general TE-PVD process in which a plasma or an ion source is used to ionise the species to be deposited, and a negative bias is applied to the substrate in order to facilitate the extraction of the species from the plasma. The introduction of reactive species, evaporation of solids within the process chamber, and the use of monitors to provide in-process measurement of optical characteristics and thicknesses of coatings are ordinary modifications of the process.
- c. Pack Cementation is a surface modification coating or overlay coating process wherein a substrate is immersed in a powder mixture (a pack), that consists of:
 1. The metallic powders that are to be deposited (usually aluminium, chromium, silicon or combinations thereof);
 2. An activator (normally a halide salt); and
 3. An inert powder, most frequently alumina.

The substrate and powder mixture is contained within a retort which is heated to between 1,030 K (757°C) and 1,375 K (1,102°C) for sufficient time to deposit the coating.
 - d. Plasma Spraying is an overlay coating process wherein a gun (spray torch) which produces and controls a plasma accepts powder or wire coating materials, melts them and propels them towards a substrate, whereon an integrally bonded coating is formed. Plasma spraying constitutes either low pressure plasma spraying or high velocity plasma spraying.
- N.B. 1: Low pressure means less than ambient atmospheric pressure.*
- N.B. 2: High velocity refers to nozzle-exit gas velocity exceeding 750 m/s calculated at 293 K (20°C) at 0.1 MPa.*
- e. Slurry Deposition is a surface modification coating or overlay coating process wherein a metallic or ceramic powder with an organic binder is suspended in a liquid and is applied to a substrate by either spraying, dipping or painting, subsequent air or oven drying, and heat treatment to obtain the desired coating.
-

-
- f. Sputter Deposition is an overlay coating process based on a momentum transfer phenomenon, wherein positive ions are accelerated by an electric field towards the surface of a target (coating material). The kinetic energy of the impacting ions is sufficient to cause target surface atoms to be released and deposited on an appropriately positioned substrate.

N.B. 1: The Table refers only to triode, magnetron or reactive sputter deposition which is used to increase adhesion of the coating and rate of deposition and to radio frequency (RF) augmented sputter deposition used to permit vaporisation of non-metallic coating materials.

N.B. 2: Low-energy ion beams (less than 5 keV) can be used to activate the deposition.

- g. Ion Implantation is a surface modification coating process in which the element to be alloyed is ionised, accelerated through a potential gradient and implanted into the surface region of the substrate. This includes processes in which ion implantation is performed simultaneously with electron beam physical vapour deposition or sputter deposition.

Category 3—Electronics

3A Systems, Equipment and Components

Note 1: The control status of equipment and components described in 3A001 or 3A002, other than those described in 3A001.a.3. to 3A001.a.10., 3A001.a.12. or 3A001.a.13, which are specially designed for or which have the same functional characteristics as other equipment is determined by the control status of the other equipment.

Note 2: The control status of integrated circuits described in 3A001.a.3. to 3A001.a.9, 3A001.a.12 or 3A001.a.13. which are unalterably programmed or designed for a specific function for another equipment is determined by the control status of the other equipment.

N.B.: When the manufacturer or applicant cannot determine the control status of the other equipment, the control status of the integrated circuits is determined in 3A001.a.3. to 3A001.a.9., 3A001.a.12 or 3A001.a.13.

3A001 Electronic components and specially designed components therefor, as follows:

a. General purpose integrated circuits, as follows:

Note 1: The control status of wafers (finished or unfinished), in which the function has been determined, is to be evaluated against the parameters of 3A001.a.

Note 2: Integrated circuits include the following types:

- a. "Monolithic integrated circuits";*
- b. "Hybrid integrated circuits";*
- c. "Multichip integrated circuits";*
- d. "Film type integrated circuits", including silicon-on-sapphire integrated circuits;*
- e. "Optical integrated circuits".*
- f. "Three dimensional integrated circuits".*

1. Integrated circuits designed or rated as radiation hardened to withstand any of the following:

- a. A total dose of 5×10^3 Gy (silicon) or higher;
- b. A dose rate upset of 5×10^6 Gy (silicon)/s or higher; or
- c. A fluence (integrated flux) of neutrons (1 MeV equivalent) of 5×10^{13} n/cm² or higher on silicon, or its equivalent for other materials;

Note: 3A001.a.1.c. does not apply to Metal Insulator Semiconductors (MIS).

-
2. “Microprocessor microcircuits”, “microcomputer microcircuits”, microcontroller microcircuits, storage integrated circuits manufactured from a compound semiconductor, analogue-to-digital converters, digital-to-analogue converters, electro-optical or “optical integrated circuits” designed for “signal processing”, field programmable logic devices, custom integrated circuits for which either the function is unknown or the control status of the equipment in which the integrated circuit will be used is unknown, Fast Fourier Transform (FFT) processors, electrical erasable programmable read-only memories (EEPROMs), flash memories or static random-access memories (SRAMs), having any of the following:
- a. Rated for operation at an ambient temperature above 398 K (125°C);
 - b. Rated for operation at an ambient temperature below 218 K (-55°C); or
 - c. Rated for operation over the entire ambient temperature range from 218 K (-55°C) to 398 K (125°C);

Note: 3A001.a.2. does not apply to integrated circuits for civil automobiles or railway train applications.

3. “Microprocessor microcircuits”, “microcomputer microcircuits” and microcontroller microcircuits, manufactured from a compound semiconductor and operating at a clock frequency exceeding 40 MHz;

Note: 3A001.a.3. includes digital signal processors, digital array processors and digital coprocessors.

4. Not used;
5. Analogue-to-digital and digital-to-analogue converter integrated circuits, as follows:
- a. ADCs having any of the following:

N.B. SEE ALSO 3A101

1. A resolution of 8 bit or more, but less than 10 bit, with an output rate greater than 1 billion words per second;
2. A resolution of 10 bit or more, but less than 12 bit, with an output rate greater than 300 million words per second;
3. A resolution of 12 bit with an output rate greater than 200 million words per second;
4. A resolution of more than 12 bit, but equal to or less than 14 bit, with an output rate greater than 125 million words per second; or
5. A resolution of more than 14 bit with an output rate greater than 20 million words per second;

Technical Notes:

-
1. *A resolution of n bit corresponds to a quantisation of 2^n levels.*
 2. *The number of bits in the output word is equal to the resolution of the ADC.*
 3. *The output rate is the maximum output rate of the converter, regardless of the architecture or oversampling.*
 4. *For 'multiple channel ADCs', the outputs are not aggregated and the output rate is the maximum output rate of any single channel.*
 5. *For 'interleaved ADCs' or for 'multiple channel ADCs' that are specified to have an interleaved mode of operation, the outputs are aggregated and the output rate is the maximum combined total output rate of all of the outputs.*
 6. *Vendors may also refer to the output rate as sampling rate, conversion rate or throughput rate. It is often specified in megahertz (MHz) or mega samples per second (MSPS).*
 7. *For the purpose of measuring output rate, one output word per second is equivalent to one Hertz or one sample per second.*
 8. *'Multiple channel ADCs' are defined as devices which integrate more than one ADC, designed so that each ADC has a separate analogue input.*
 9. *'Interleaved ADCs' are defined as devices which have multiple ADC units that sample the same analogue input at different times such that when the outputs are aggregated, the analogue input has been effectively sampled and converted at a higher sampling rate.*
- b. Digital-to-Analogue Converters (DAC) having any of the following:
1. A resolution of 10 bit or more with an 'adjusted update rate' of 3,500 MSPS or greater; or
 2. A resolution of 12 bit or more with an 'adjusted update rate' of equal to or greater than 1,250 MSPS and having any of the following:
 - a. A settling time less than 9 ns to 0.024% of full scale from a full scale step; or
 - b. A 'Spurious Free Dynamic Range' (SFDR) greater than 68 dBc (carrier) when synthesising a full scale analogue signal of 100 MHz or the highest full scale analogue signal frequency specified below 100 MHz.
-

Technical Notes:

1. *'Spurious Free Dynamic Range' (SFDR) is defined as the ratio of the RMS value of the carrier frequency (maximum signal component) at the input of the DAC to the RMS value of the next largest noise or harmonic distortion component at its output.*
 2. *SFDR is determined directly from the specification table or from the characterisation plots of SFDR versus frequency.*
 3. *A signal is defined to be full scale when its amplitude is greater than -3 dBfs (full scale).*
 4. *'Adjusted update rate' for DACs:*
 - a. *For conventional (non-interpolating) DACs, the 'adjusted update rate' is the rate at which the digital signal is converted to an analogue signal and the output analogue values are changed by the DAC. For DACs where the interpolation mode may be bypassed (interpolation factor of one), the DAC should be considered as a conventional (non-interpolating) DAC;*
 - b. *For interpolating DACs (oversampling DACs), the 'adjusted update rate' is defined as the DAC update rate divided by the smallest interpolating factor. For interpolating DACs, the 'adjusted update rate' may be referred to by different terms including:*
 - *input data rate*
 - *input word rate*
 - *input sample rate*
 - *maximum total input bus rate*
 - *maximum DAC clock rate for DAC clock input.*
6. Electro-optical and "optical integrated circuits", designed for "signal processing" and having all of the following:
- a. One or more than one internal "laser" diode;
 - b. One or more than one internal light detecting element; and
 - c. Optical waveguides;
7. 'Field programmable logic devices' having any of the following:
- a. A maximum number of single-ended digital input/outputs greater than 500; or
 - b. An 'aggregate one-way peak serial transceiver data rate' of 200 Gb/s or greater;
- Note:* 3A001.a.7. includes:
- a. *Simple Programmable Logic Devices (SPLDs)*
 - b. *Complex Programmable Logic Devices (CPLDs)*
 - c. *Field Programmable Gate Arrays (FPGAs)*
-

- d. Field Programmable Logic Arrays (FPLAs)
- e. Field Programmable Interconnects (FPICs)

Technical Notes:

1. 'Field programmable logic devices' are also known as field programmable gate or field programmable logic arrays.
2. Maximum number of digital input/outputs in 3A001.a.7.a. is also referred to as the maximum user input/outputs or maximum available input/outputs, whether the integrated circuit is packaged or bare die.
3. 'Aggregate one-way peak serial transceiver data rate' is the product of the peak serial one-way transceiver data rate times the number of transceivers on the FPGA.
8. Not used;
9. Neural network integrated circuits;
10. Custom integrated circuits for which the function is unknown, or the control status of the equipment in which the integrated circuits will be used is unknown to the manufacturer, having any of the following:
 - a. More than 1,500 terminals;
 - b. A typical "basic gate propagation delay time" of less than 0.02 ns; or
 - c. An operating frequency exceeding 3 GHz;
11. Digital integrated circuits, other than those described in 3A001.a.3. to 3A001.a.10. and 3A001.a.12., based upon any compound semiconductor and having any of the following:
 - a. An equivalent gate count of more than 3,000 (2 input gates); or
 - b. A toggle frequency exceeding 1.2 GHz;
12. Fast Fourier Transform (FFT) processors having a rated execution time for an N-point complex FFT of less than $(N \log_2 N) / 20,480$ ms, where N is the number of points;

Technical Note:

When N is equal to 1,024 points, the formula in 3A001.a.12. gives an execution time of 500 μ s.

13. Direct Digital Synthesizer (DDS) integrated circuits having any of the following:
 - a. A Digital-to-Analogue Converter (DAC) clock frequency of 3.5 GHz or more and a DAC resolution of 10 bit or more, but less than 12 bit; or
 - b. A DAC clock frequency of 1.25 GHz or more and a DAC resolution of 12 bit or more;

Technical Note:

The DAC clock frequency may be specified as the master clock frequency or the input clock frequency.

-
- b. Microwave or millimetre wave components, as follows:

Technical Note:

For purposes of 3A001.b., the parameter peak saturated power output may also be referred to on product data sheets as output power, saturated power output, maximum power output, peak power output, or peak envelope power output.

1. Electronic vacuum tubes and cathodes, as follows:

Note 1: 3A001.b.1. does not control tubes designed or rated for operation in any frequency band and having all of the following:

- a. Does not exceed 31.8 GHz; and*
- b. Is “allocated by the ITU” for radio-communications services, but not for radio-determination.*

Note 2: 3A001.b.1. does not control non-“space-qualified” tubes having all of the following:

- a. An average output power equal to or less than 50 W; and*
 - b. Designed or rated for operation in any frequency band and having all of the following:*
 - 1. Exceeds 31.8 GHz but does not exceed 43.5 GHz; and*
 - 2. Is “allocated by the ITU” for radio-communications services, but not for radio-determination.*
- a. Travelling wave tubes, pulsed or continuous wave, as follows:
1. Tubes operating at frequencies exceeding 31.8 GHz;
 2. Tubes having a cathode heater element with a turn on time to rated RF power of less than 3 seconds;
 3. Coupled cavity tubes, or derivatives thereof, with a “fractional bandwidth” of more than 7% or a peak power exceeding 2.5 kW;
 4. Helix tubes, or derivatives thereof, having any of the following:
 - a. An “instantaneous bandwidth” of more than one octave, and average power (expressed in kW) times frequency (expressed in GHz) of more than 0.5;
 - b. An “instantaneous bandwidth” of one octave or less, and average power (expressed in kW) times frequency (expressed in GHz) of more than 1; or
 - c. Being “space-qualified”;
- b. Crossed-field amplifier tubes with a gain of more than 17 dB;

-
- c. Impregnated cathodes designed for electronic tubes producing a continuous emission current density at rated operating conditions exceeding 5 A/cm²;
 - 2. Microwave “Monolithic Integrated Circuits” (MMIC) power amplifiers that are any of the following:
 - a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following:
 - 1. A peak saturated power output greater than 75 W (48.75 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;
 - 2. A peak saturated power output greater than 55 W (47.4 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;
 - 3. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; or
 - 4. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz;
 - b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 16 GHz with a “fractional bandwidth” greater than 10%, and having any of the following:
 - 1. A peak saturated power output greater than 10 W (40 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; or
 - 2. A peak saturated power output greater than 5 W (37 dBm) at any frequency exceeding 8.5 GHz up to and including 16 GHz;
 - c. Rated for operation with a peak saturated power output greater than 3 W (34.77 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz, and with a “fractional bandwidth” of greater than 10%;
 - d. Rated for operation with a peak saturated power output greater than 0.1n W (-70 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;
 - e. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;
 - f. Rated for operation with a peak saturated power output greater than 31.62 mW (15 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;
-

-
- g. Rated for operation with a peak saturated power output greater than 10 mW (10 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; or
 - h. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz;

Note 1: Not used.

Note 2: The control status of the MMIC whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by 3A001.b.2.a. to 3A001.b.2.h., is determined by the lowest peak saturated power output threshold.

Note 3: Notes 1 and 2 in 3A mean that 3A001.b.2. does not control MMICs if they are specially designed for other applications, e.g. telecommunications, radar, automobiles.

- 3. Discrete microwave transistors that are any of the following:
 - a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz and having any of the following:
 - 1. A peak saturated power output greater than 400 W (56 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;
 - 2. A peak saturated power output greater than 205 W (53.12 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;
 - 3. A peak saturated power output greater than 115 W (50.61 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; or
 - 4. A peak saturated power output greater than 60 W (47.78 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz;
 - b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 31.8 GHz and having any of the following:
 - 1. A peak saturated power output greater than 50 W (47 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz;
 - 2. A peak saturated power output greater than 15 W (41.76 dBm) at any frequency exceeding 8.5 GHz up to and including 12 GHz;
 - 3. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 12 GHz up to and including 16 GHz; or
 - 4. A peak saturated power output greater than 7 W (38.45 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz;

-
- c. Rated for operation with a peak saturated power output greater than 0.5 W (27 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;
 - d. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz; or
 - e. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 43.5 GHz;

Note 1: The status of a transistor whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by 3A001.b.3.a. through 3A001.b.3.e., is determined by the lowest peak saturated power output threshold.

Note 2: 3A001.b.3. includes bare dice, dice mounted on carriers, or dice mounted in packages. Some discrete transistors may also be referred to as power amplifiers, but the status of these discrete transistors is determined by 3A001.b.3.

- 4. Microwave solid state amplifiers and microwave assemblies/modules containing microwave solid state amplifiers, that are any of the following:
 - a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following:
 - 1. A peak saturated power output greater than 500 W (57 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;
 - 2. A peak saturated power output greater than 270 W (54.3 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;
 - 3. A peak saturated power output greater than 200 W (53 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; or
 - 4. A peak saturated power output greater than 90 W (49.54 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz;
 - b. Rated for operation at frequencies greater than 6.8 GHz up to and including 31.8 GHz with a “fractional bandwidth” greater than 10%, and having any of the following:
 - 1. A peak saturated power output greater than 70 W (48.54 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz;
 - 2. A peak saturated power output greater than 50 W (47 dBm) at any frequency exceeding 8.5 GHz up to and including 12 GHz;
-

3. A peak saturated power output greater than 30 W (44.77 dBm) at any frequency exceeding 12 GHz up to and including 16 GHz; or
4. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz;
- c. Rated for operation with a peak saturated power output greater than 0.5 W (27 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;
- d. Rated for operation with a peak saturated power output greater than 2 W (33 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;
- e. Rated for operation at frequencies exceeding 43.5 GHz and having any of the following:
 1. A peak saturated power output greater than 0.2 W (23 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;
 2. A peak saturated power output greater than 20 mW (13 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; or
 3. A peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz; or
- f. Rated for operation at frequencies above 2.7 GHz and having all of the following:
 1. A peak saturated power output (in watts), P_{sat} , greater than 400 divided by the maximum operating frequency (in GHz) squared [$P_{\text{sat}} > 400 \text{ W} \cdot \text{GHz}^2 / f_{\text{GHz}}^2$];
 2. A “fractional bandwidth” of 5% or greater; and
 3. Any two sides perpendicular to one another with either length d (in cm) equal to or less than 15 divided by the lowest operating frequency in GHz [$d \leq 15 \text{ cm} \cdot \text{GHz} / f_{\text{GHz}}$];

Technical Note:

2.7 GHz should be used as the lowest operating frequency (f_{GHz}) in the formula in 3A001.b.4.f.3., for amplifiers that have a rated operation range extending downward to 2.7 GHz and below [$d \leq 15 \text{ cm} \cdot \text{GHz} / 2.7 \text{ GHz}$].

N.B.: MMIC power amplifiers should be evaluated against the criteria in 3A001.b.2.

Note 1: Not used.

Note 2: The status of an item whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by 3A001.b.4.a. through 3A001.b.4.e., is determined by the lowest peak saturated power output threshold.

Note 3: 3A001.b.4. includes transmit/receive modules and transmit modules.

5. Electronically or magnetically tunable band-pass or band-stop filters, having more than 5 tunable resonators capable of tuning across a 1.5:1 frequency band (f_{\max}/f_{\min}) in less than 10 μ s and having any of the following:
 - a. A band-pass bandwidth of more than 0.5% of centre frequency; or
 - b. A band-stop bandwidth of less than 0.5% of centre frequency;
6. Not used;
7. Converters and harmonic mixers, designed to extend the frequency range of equipment described in 3A002.c., 3A002.d., 3A002.e. or 3A002.f. beyond the limits stated therein;
8. Microwave power amplifiers containing tubes specified in 3A001.b.1. and having all of the following:
 - a. Operating frequencies above 3 GHz;
 - b. An average output power density to mass ratio exceeding 80 W/kg; and
 - c. A volume of less than 400 cm³;

Note: 3A001.b.8. does not control equipment designed or rated for operation in any frequency band which is "allocated by the ITU" for radio-communications services, but not for radio-determination.

9. Microwave power modules (MPM) consisting of, at least, a travelling wave tube, a microwave "monolithic integrated circuit" and an integrated electronic power conditioner and having all of the following:
 - a. A 'turn-on time' from off to fully operational in less than 10 seconds;
 - b. A volume less than the maximum rated power in Watts multiplied by 10 cm³/W; and
 - c. An "instantaneous bandwidth" greater than 1 octave ($f_{\max} > 2f_{\min}$) and having any of the following:
 1. For frequencies equal to or less than 18 GHz, an RF output power greater than 100 W; or
 2. A frequency greater than 18 GHz;

Technical Notes:

1. *To calculate the volume in 3A001.b.9.b., the following example is provided: for a maximum rated power of 20 W, the volume would be: 20 W x 10 cm³/W = 200 cm³.*

-
2. *The 'turn-on time' in 3A001.b.9.a. refers to the time from fully-off to fully operational, i.e., it includes the warm-up time of the MPM.*
10. Oscillators or oscillator assemblies, designed to operate with all of the following:
- a. A single sideband (SSB) phase noise, in dBc/Hz, better than $-(126+20\log_{10}F-20\log_{10}f)$ anywhere within the range $10\text{ Hz} < F < 10\text{ kHz}$; and
 - b. A single sideband (SSB) phase noise, in dBc/Hz, better than $-(114+20\log_{10}F-20\log_{10}f)$ anywhere within the range $10\text{ kHz} \leq F < 500\text{ kHz}$;

Technical Note:

In 3A001.b.10., F is the offset from the operating frequency in Hz and f is the operating frequency in MHz.

11. "Frequency synthesiser" "electronic assemblies" having a "frequency switching time" as specified by any of the following:
- a. Less than 156 ps;
 - b. Less than 100 μs for any frequency change exceeding 1.6 GHz within the synthesised frequency range exceeding 4.8 GHz but not exceeding 10.6 GHz;
 - c. Less than 250 μs for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 10.6 GHz but not exceeding 31.8 GHz;
 - d. Less than 500 μs for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 31.8 GHz but not exceeding 43.5 GHz; or
 - e. Less than 1 ms for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 43.5 GHz but not exceeding 56 GHz.
 - f. Less than 1 ms for any frequency change exceeding 2.2 GHz within the synthesized frequency range exceeding 56 GHz but not exceeding 75 GHz; or
 - g. Less than 1 ms within the synthesized frequency range exceeding 75 GHz;

N.B.: For general purpose "signal analysers", signal generators, network analysers and microwave test receivers, see 3A002.c., 3A002.d., 3A002.e. and 3A002.f., respectively.

- c. Acoustic wave devices as follows and specially designed components therefor:
 - 1. Surface acoustic wave and surface skimming (shallow bulk) acoustic wave devices, having any of the following:
 - a. A carrier frequency exceeding 6 GHz;

-
- b. A carrier frequency exceeding 1 GHz, but not exceeding 6 GHz and having any of the following:
 - 1. A 'frequency side-lobe rejection' exceeding 65 dB;
 - 2. A product of the maximum delay time and the bandwidth (time in μs and bandwidth in MHz) of more than 100;
 - 3. A bandwidth greater than 250 MHz; or
 - 4. A dispersive delay of more than 10 μs ; or
 - c. A carrier frequency of 1 GHz or less and having any of the following:
 - 1. A product of the maximum delay time and the bandwidth (time in μs and bandwidth in MHz) of more than 100;
 - 2. A dispersive delay of more than 10 μs ; or
 - 3. A 'frequency side-lobe rejection' exceeding 65 dB and a bandwidth greater than 100 MHz;

Technical Note:

'Frequency side-lobe rejection' is the maximum rejection value specified in data sheet.

- 2. Bulk (volume) acoustic wave devices which permit the direct processing of signals at frequencies exceeding 6 GHz;
- 3. Acoustic-optic "signal processing" devices employing interaction between acoustic waves (bulk wave or surface wave) and light waves which permit the direct processing of signals or images, including spectral analysis, correlation or convolution;

Note: 3A001.c. does not control acoustic wave devices that are limited to a single band pass, low pass, high pass or notch filtering, or resonating function.

- d. Electronic devices and circuits containing components, manufactured from "superconductive" materials, specially designed for operation at temperatures below the "critical temperature" of at least one of the "superconductive" constituents and having any of the following:
 - 1. Current switching for digital circuits using "superconductive" gates with a product of delay time per gate (in seconds) and power dissipation per gate (in watts) of less than 10^{-14} J; or
 - 2. Frequency selection at all frequencies using resonant circuits with Q-values exceeding 10,000;
- e. High energy devices as follows:
 - 1. 'Cells' as follows:
 - a. 'Primary cells' having an 'energy density' exceeding 550 Wh/kg at 20°C;
 - b. 'Secondary cells' having an 'energy density' exceeding 250 Wh/kg ;

Technical Notes:

1. For the purpose of 3A001.e.1., 'energy density' (Wh/kg) is calculated from the nominal voltage multiplied by the nominal capacity in ampere-hours (Ah) divided by the mass in kilograms. If the nominal capacity is not stated, energy density is calculated from the nominal voltage squared then multiplied by the discharge duration in hours divided by the discharge load in ohms and the mass in kilograms.
2. For the purpose of 3A001.e.1., a 'cell' is defined as an electrochemical device, which has positive and negative electrodes, an electrolyte, and is a source of electrical energy. It is the basic building block of a battery.
3. For the purpose of 3A001.e.1.a., a 'primary cell' is a 'cell' that is not designed to be charged by any other source.
4. For the purpose of 3A001.e.1.b., a 'secondary cell' is a 'cell' that is designed to be charged by an external electrical source.

Note: 3A001.e.1. does not control batteries, including single-cell batteries.

2. High energy storage capacitors as follows:

N.B.: SEE ALSO 3A201.a.and Munitions List

- a. Capacitors with a repetition rate of less than 10 Hz (single shot capacitors) and having all of the following:
 1. A voltage rating equal to or more than 5 kV;
 2. An energy density equal to or more than 250 J/kg; and
 3. A total energy equal to or more than 25 kJ;
- b. Capacitors with a repetition rate of 10 Hz or more (repetition rated capacitors) and having all of the following:
 1. A voltage rating equal to or more than 5 kV;
 2. An energy density equal to or more than 50 J/kg;
 3. A total energy equal to or more than 100 J; and
 4. A charge/discharge cycle life equal to or more than 10,000;
3. "Superconductive" electromagnets and solenoids, specially designed to be fully charged or discharged in less than one second and having all of the following:

N.B.: SEE ALSO 3A201.b.

Note: 3A001.e.3. does not control "superconductive" electromagnets or solenoids specially designed for Magnetic Resonance Imaging (MRI) medical equipment.

- a. Energy delivered during the discharge exceeding 10 kJ in the first second;
- b. Inner diameter of the current carrying windings of more than 250 mm; and

-
- c. Rated for a magnetic induction of more than 8 T or “overall current density” in the winding of more than 300 A/mm²;
 - 4. Solar cells, cell-interconnect-coverglass (CIC) assemblies, solar panels, and solar arrays, which are “space-qualified”, having a minimum average efficiency exceeding 20% at an operating temperature of 301 K (28°C) under simulated ‘AM0’ illumination with an irradiance of 1,367 watts per square metre (W/m²);

Technical Note:

‘AM0’, or ‘Air Mass Zero’, refers to the spectral irradiance of sun light in the earth’s outer atmosphere when the distance between the earth and sun is one astronomical unit (AU).

- f. Rotary input type absolute position encoders having an accuracy equal to or less (better) than ± 1.0 second of arc;
- g. Solid-state pulsed power switching thyristor devices and ‘thyristor modules’, using either electrically, optically, or electron radiation controlled switch methods and having any of the following:
 - 1. A maximum turn-on current rate of rise (di/dt) greater than 30,000 A/μs and off-state voltage greater than 1,100 V; or
 - 2. A maximum turn-on current rate of rise (di/dt) greater than 2,000 A/μs and having all of the following:
 - a. An off-state peak voltage equal to or greater than 3,000 V; and
 - b. A peak (surge) current equal to or greater than 3,000 A.

Note 1: 3A001.g. includes:

- a. *Silicon Controlled Rectifiers (SCRs)*
- b. *Electrical Triggering Thyristors (ETTs)*
- c. *Light Triggering Thyristors (LTTs)*
- d. *Integrated Gate Commutated Thyristors (IGCTs)*
- e. *Gate Turn-off Thyristors (GTOs)*
- f. *MOS Controlled Thyristors (MCTs)*
- g. *Solidtrons*

Note 2: 3A001.g. does not control thyristor devices and ‘thyristor modules’ incorporated into equipment designed for civil railway or “civil aircraft” applications.

Technical Note:

For the purposes of 3A001.g., a ‘thyristor module’ contains one or more thyristor devices.

- h. Solid-state power semiconductor switches, diodes, or ‘modules’, having all of the following:
 - 1. Rated for a maximum operating junction temperature greater than 488 K (215°C);
 - 2. Repetitive peak off-state voltage (blocking voltage) exceeding 300 V; and
-

3. Continuous current greater than 1 A.

Note 1: Repetitive peak off-state voltage in 3A001.h. includes drain to source voltage, collector to emitter voltage, repetitive peak reverse voltage and peak repetitive off-state blocking voltage.

Note 2: 3A001.h. includes:

- a. Junction Field Effect Transistors (JFETs)
- b. Vertical Junction Field Effect Transistors (VJFETs)
- c. Metal Oxide Semiconductor Field effect Transistors (MOSFETs)
- d. Double Diffused Metal Oxide Semiconductor Field Effect Transistor (DMOSFET)
- e. Insulated Gate Bipolar Transistor (IGBT)
- f. High Electron Mobility Transistors (HEMTs)
- g. Bipolar Junction Transistors (BJTs)
- h. Thyristors and Silicon Controlled Rectifiers (SCRs)
- i. Gate Turn-Off Thyristors (GTOs)
- j. Emitter Turn-Off Thyristors (ETOs)
- k. PiN Diodes
- l. Schottky Diodes

Note 3: 3A001.h. does not control switches, diodes, or 'modules', incorporated into equipment designed for civil automobile, civil railway or "civil aircraft" applications.

Technical Note:

For the purposes of 3A001.h., 'modules' contain one or more solid-state power semiconductor switches or diodes.

3A002 General purpose electronic equipment, as follows:

a. Recording equipment and oscilloscopes, as follows:

1. Not used;
2. Not used;
3. Not used;
4. Not used;
5. Waveform digitisers and transient recorders, having all of the following:
 - a. Digitising rate equal to or more than 200 million samples per second and a resolution of 10 bit or more; and
 - b. A 'continuous throughput' of 2 Gbit/s or more;

Technical Notes:

1. *For those instruments with a parallel bus architecture, the 'continuous throughput' rate is the highest word rate multiplied by the number of bits in a word.*

-
2. *‘Continuous throughput’ is the fastest data rate the instrument can output to mass storage without the loss of any information whilst sustaining the sampling rate and analogue-to-digital conversion.*
 6. Digital instrumentation data recorder systems using magnetic disk storage technique and having all of the following, and specially designed digital recorders therefor:
 - a. Digitized instrumentation data rate equal to or more than 100 million samples per second at a resolution of 8 bit or more; and
 - b. A ‘continuous throughput’ of 1 Gbit/s or more;

Technical Note:

Digital instrumentation data recorder systems can be configured either with a digitizer integrated within or outside the digital recorder.

7. Real-time oscilloscopes having a vertical root-mean-square (rms) noise voltage of less than 2% of full-scale at the vertical scale setting that provides the lowest noise value for any input 3dB bandwidth of 60 GHz or greater per channel;

Note: 3A002.a.7. does not apply to equivalent-time sampling oscilloscopes.

- b. Not used;
- c. Radio-frequency “signal analysers” as follows:
 1. “Signal analysers” having a 3 dB resolution bandwidth (RBW) exceeding 10 MHz anywhere within the frequency range exceeding 31.8 GHz but not exceeding 37.5 GHz;
 2. “Signal analysers” having Displayed Average Noise Level (DANL) less (better) than -150 dBm/Hz anywhere within the frequency range exceeding 43.5 GHz but not exceeding 75 GHz;
 3. “Signal analysers” having a frequency exceeding 75 GHz;
 4. “Signal analysers” having all of the following:
 - a. “Real-time bandwidth” exceeding 85 MHz; and
 - b. 100% probability of discovery with less than a 3 dB reduction from full amplitude due to gaps or windowing effects of signals having a duration of 15 µs or less;

Technical Notes:

1. *Probability of discovery in 3A002.c.4.b. is also referred to as probability of intercept or probability of capture.*
 2. *For the purposes of 3A002.c.4.b., the duration for 100% probability of discovery is equivalent to the minimum signal duration necessary for the specified level measurement uncertainty.*
-

Note: 3A002.c.4. does not apply to those “signal analysers” using only constant percentage bandwidth filters (also known as octave or fractional octave filters).

5. “Signal analysers” having a “frequency mask trigger” function with 100% probability of trigger (capture) for signals having a duration of 15 µs or less;
- d. Frequency synthesised signal generators producing output frequencies, the accuracy and short term and long term stability of which are controlled, derived from or disciplined by the internal master reference oscillator and having any of the following:
 1. Specified to generate pulse modulated signals having all of the following, anywhere within the synthesized frequency range exceeding 31.8 GHz but not exceeding 75 GHz:
 - a. ‘Pulse duration’ of less than 100 ns; and
 - b. On/off ratio equal to or exceeding 65 dB;
 2. An output power exceeding 100 mW (20 dBm) anywhere within the synthesised frequency exceeding 43.5 GHz but not exceeding 75 GHz;
 3. A “frequency switching time” as specified by any of the following:
 - a. Not used;
 - b. Less than 100 µs for any frequency change exceeding 1.6 GHz within the synthesised frequency range exceeding 4.8 GHz but not exceeding 10.6 GHz;
 - c. Less than 250 µs for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 10.6 GHz but not exceeding 31.8 GHz;
 - d. Less than 500 µs for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 31.8 GHz but not exceeding 43.5 GHz;
 - e. Less than 1 ms within the synthesised frequency range exceeding 43.5 GHz but not exceeding 56 GHz; or
 - f. Less than 1 ms for any frequency change exceeding 2.2 GHz within the synthesized frequency range exceeding 56 GHz but not exceeding 75 GHz;
 4. Single sideband (SSB) phase noise, in dBc/Hz, specified as being all of the following:
 - a. Less (better) than $-(126+20 \log_{10}F-20 \log_{10}f)$ anywhere within the range of $10 \text{ Hz} < F < 10 \text{ kHz}$ anywhere within the synthesized frequency range exceeding 3.2 GHz but not exceeding 75 GHz; and
 - b. Less (better) than $-(114+20 \log_{10}F-20 \log_{10}f)$ anywhere within the range of $10 \text{ kHz} \leq F < 500 \text{ kHz}$ anywhere within the synthesized frequency range exceeding 3.2 GHz but not exceeding 75 GHz; or

Technical Note:

In 3A002.d.4., F is the offset from the operating frequency in Hz and f is the operating frequency in MHz.

5. A maximum synthesised frequency exceeding 75 GHz;

Note 1: For the purpose of 3A002.d., frequency synthesised signal generators include arbitrary waveform and function generators.

Note 2: 3A002.d. does not control equipment in which the output frequency is either produced by the addition or subtraction of two or more crystal oscillator frequencies, or by an addition or subtraction followed by a multiplication of the result.

Technical Notes:

- 1. The maximum synthesized frequency of an arbitrary waveform or function generator is calculated by dividing the sample rate, in samples/second, by a factor of 2.5.*
- 2. For the purposes of 3A002.d.1., 'pulse duration' is defined as the time interval from the point on the leading edge that is 50% of the pulse amplitude to the point on the trailing edge that is 50 % of the pulse amplitude.*

- e. Network analysers having any of the following:

1. An output power exceeding 31.62 mW (15 dBm) anywhere within the operating frequency range exceeding 43.5 GHz but not exceeding 75 GHz;
2. An output power exceeding 1 mW (0 dBm) anywhere within the operating frequency range exceeding 75 GHz but not exceeding 110 GHz;
3. 'Nonlinear vector measurement functionality' at frequencies exceeding 50 GHz but not exceeding 110 GHz; or

Technical Note:

'Nonlinear vector measurement functionality' is an instrument's ability to analyse the test results of devices driven into the large-signal domain or the non-linear distortion range.

4. A maximum operating frequency exceeding 110 GHz;

- f. Microwave test receivers having all of the following:

1. A maximum operating frequency exceeding 110 GHz; and
2. Being capable of measuring amplitude and phase simultaneously;

- g. Atomic frequency standards being any of the following:

1. "Space-qualified";
2. Non-rubidium and having a long-term stability less (better) than 1×10^{-11} /month; or
3. Non-"space-qualified" and having all of the following:
 - a. Being a rubidium standard;
 - b. Long-term stability less (better) than 1×10^{-11} /month; and
 - c. Total power consumption of less than 1 W.

-
- 3A003 Spray cooling thermal management systems employing closed loop fluid handling and reconditioning equipment in a sealed enclosure where a dielectric fluid is sprayed onto electronic components using specially designed spray nozzles that are designed to maintain electronic components within their operating temperature range, and specially designed components therefor.
- 3A101 Electronic equipment, devices and components, other than those specified in 3A001, as follows:
- a. Analogue-to-digital converters, usable in “missiles”, designed to meet military specifications for ruggedised equipment;
 - b. Accelerators capable of delivering electromagnetic radiation produced by bremsstrahlung from accelerated electrons of 2 MeV or greater, and systems containing those accelerators.
- Note: 3A101.b. above does not specify equipment specially designed for medical purposes.*
- 3A102 ‘Thermal batteries’ designed or modified for ‘missiles’.
- Technical Notes:*
1. *In 3A102 ‘thermal batteries’ are single use batteries that contain a solid non-conducting inorganic salt as the electrolyte. These batteries incorporate a pyrolytic material that, when ignited, melts the electrolyte and activates the battery.*
 2. *In 3A102 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.*
- 3A201 Electronic components, other than those specified in 3A001, as follows:
- a. Capacitors having either of the following sets of characteristics:
 1. a. Voltage rating greater than 1.4 kV;
 - b. Energy storage greater than 10 J;
 - c. Capacitance greater than 0.5 µF; and
 - d. Series inductance less than 50 nH; or
 2. a. Voltage rating greater than 750 V;
 - b. Capacitance greater than 0.25 µF; and
 - c. Series inductance less than 10 nH;
 - b. Superconducting solenoidal electromagnets having all of the following characteristics:
 1. Capable of creating magnetic fields greater than 2 T;
 2. A ratio of length to inner diameter greater than 2;
 3. Inner diameter greater than 300 mm; and
 4. Magnetic field uniform to better than 1% over the central 50% of the inner volume;
-

Note: 3A201.b. does not control magnets specially designed for and exported 'as parts of' medical nuclear magnetic resonance (NMR) imaging systems. The phrase 'as part of' does not necessarily mean physical part in the same shipment; separate shipments from different sources are allowed, provided the related export documents clearly specify that the shipments are dispatched 'as part of' the imaging systems.

- c. Flash X-ray generators or pulsed electron accelerators having either of the following sets of characteristics:
1. a. An accelerator peak electron energy of 500 keV or greater but less than 25 MeV; and
 - b. With a 'figure of merit' (K) of 0.25 or greater; or
 2. a. An accelerator peak electron energy of 25 MeV or greater; and
 - b. A 'peak power' greater than 50 MW.

Note: 3A201.c. does not control accelerators that are component parts of devices designed for purposes other than electron beam or X-ray radiation (electron microscopy, for example) nor those designed for medical purposes:

Technical Notes:

1. The 'figure of merit' K is defined as:

$$K = 1.7 \times 10^3 V^{2.65} Q$$

where:

V is the peak electron energy in million electron volts.

If the accelerator beam pulse duration is less than or equal to 1 µs, then Q is the total accelerated charge in Coulombs. If the accelerator beam pulse duration is greater than 1 µs, then Q is the maximum accelerated charge in 1 µs.

Q equals the integral of i with respect to t, over the lesser of 1 µs or the time duration of the beam pulse ($Q = \int i dt$), where i is beam current in amperes and t is time in seconds.

2. 'Peak power' = (peak potential in volts) x (peak beam current in amperes).
 3. In machines based on microwave accelerating cavities, the time duration of the beam pulse is the lesser of 1 µs or the duration of the bunched beam packet resulting from one microwave modulator pulse.
 4. In machines based on microwave accelerating cavities, the peak beam current is the average current in the time duration of a bunched beam packet.
-

-
- 3A225 Frequency changers or generators, usable as a variable frequency or fixed frequency motor drive, other than those specified in 0B001.b.13., having all of the following characteristics:
- Multiphase output providing a power of 40 VA or greater;
 - Operating at a frequency of 600 Hz or more; and
 - Frequency control better (less) than 0.2%.
- Note 1: Item 3A225 only controls frequency changers intended for specific industrial machinery and/or consumer goods (machine tools, vehicles, etc.) if the frequency changers can meet the characteristics above when removed, and subject to General Note 3.*
- Note 2: For the purpose of export control, the Government will determine whether or not a particular frequency changer meets the characteristics above, taking into account hardware and software constraints.*
- Technical Note:*
- Frequency changers in 3A225 are also known as converters or inverters.
 - The characteristics specified in item 3.A.1. may be met by certain equipment marketed such as: Generators, Electronic Test Equipment, AC Power Supplies, Variable Speed Motor Drives, Variable Speed Drives (VSDs), Variable Frequency Drives (VFDs), Adjustable Frequency Drives (AFDs), or Adjustable Speed Drives (ASDs).
- N.B.: "Software" specially designed to enhance or release the performance of frequency changers or generators to meet the characteristics above is controlled in 3D202.*
- N.B.: SEE 0B001 FOR FREQUENCY CHANGERS AND GENERATORS SPECIALLY DESIGNED OR PREPARED FOR THE GAS CENTRIFUGE PROCESS.***
- 3A226 High-power direct current power supplies, other than those specified in 0B001.j.6., having both of the following characteristics:
- Capable of continuously producing, over a time period of 8 hours, 100 V or greater with current output of 500 A or greater; and
 - Current or voltage stability better than 0.1% over a time period of 8 hours.
- 3A227 High-voltage direct current power supplies, other than those specified in 0B001.j.5., having both of the following characteristics:
- Capable of continuously producing, over a time period of 8 hours, 20 kV or greater with current output of 1 A or greater; and
 - Current or voltage stability better than 0.1% over a time period of 8 hours.
-

-
- 3A228 Switching devices, as follows:
- a. Cold-cathode tubes, whether gas filled or not, operating similarly to a spark gap, having all of the following characteristics:
 - 1. Containing three or more electrodes;
 - 2. Anode peak voltage rating of 2.5 kV or more;
 - 3. Anode peak current rating of 100 A or more; and
 - 4. Anode delay time of 10 µs or less;

Note: 3A228 includes gas krytron tubes and vacuum spraytron tubes.
 - b. Triggered spark-gaps having both of the following characteristics:
 - 1. An anode delay time of 15 µs or less; and
 - 2. Rated for a peak current of 500 A or more;
 - c. Modules or assemblies with a fast switching function, other than those specified in 3A001.g. or 3A001.h., having all of the following characteristics:
 - 1. Anode peak voltage rating greater than 2 kV;
 - 2. Anode peak current rating of 500 A or more; and
 - 3. Turn-on time of 1 µs or less.
- 3A229 High-current pulse generators as follows:
- N.B.: SEE ALSO MUNITIONS LIST.**
- N.B.: See 1A007.a. for explosive detonator firing sets.*
- a. Not used;
 - b. Modular electrical pulse generators (pulsers) having all of the following characteristics:
 - 1. Designed for portable, mobile, or ruggedised-use;
 - 2. Not used;
 - 3. Capable of delivering their energy in less than 15 µs into loads of less than 40 ohms;
 - 4. Having an output greater than 100 A;
 - 5. Not used;
 - 6. No dimension greater than 300 mm;
 - 7. Weight less than 30 kg; and
 - 8. Specified for use over an extended temperature range 223 K (-50°C) to 373 K (100°C) or specified as suitable for aerospace applications.
 - c. Micro-firing units having all of the following characteristics:
 - 1. No dimension greater than 35 mm;
 - 2. Voltage rating of equal to or greater than 1 kV; and
 - 3. Capacitance of equal to or greater than 100 nF.

Note: 3A229.b. includes xenon flash-lamp drivers.
-

-
- 3A230 High-speed pulse generators and pulse heads therefor, having both of the following characteristics:
- a. Output voltage greater than 6 V into a resistive load of less than 55 ohms; and
 - b. 'Pulse transition time' less than 500 ps.
- Technical Notes:*
1. In 3A230.b. "pulse transition time" is defined as the time interval between 10% and 90% voltage amplitude.
 2. Pulse heads are impulse forming networks designed to accept a voltage step function and shape it into a variety of pulse forms that can include rectangular, triangular, step, impulse, exponential, or monocycle types. Pulse heads can be an integral part of the pulse generator, they can be a plug-in module to the device or they can be an externally connected device.
- 3A231 Neutron generator systems, including tubes, having both of the following characteristics:
- a. Designed for operation without an external vacuum system; and
 - b. Having any of the following:
 1. Utilising electrostatic acceleration to induce a tritium-deuterium nuclear reaction; or
 2. Utilising electrostatic acceleration to induce a deuterium-deuterium nuclear reaction and capable of an output of 3×10^9 neutrons/s or greater.
- 3A232 Multipoint initiation systems, other than those specified in 1A007, as follows:
- N.B.: SEE ALSO MUNITIONS LIST.**
- N.B.: See 1A007.b. for detonators.*
- a. Not used;
 - b. Arrangements using single or multiple detonators designed to nearly simultaneously initiate an explosive surface over greater than 5,000 mm² from a single firing signal with an initiation timing spread over the surface of less than 2.5 µs.
- Note: 3A232 does not control detonators using only primary explosives, such as lead azide.*
- 3A233 Mass spectrometers, other than those specified in 0B002.g., capable of measuring ions of 230 atomic mass units or greater and having a resolution of better than 2 parts in 230, as follows, and ion sources therefor:
- a. Inductively coupled plasma mass spectrometers (ICP/MS);
 - b. Glow discharge mass spectrometers (GDMS);
-

-
- c. Thermal ionisation mass spectrometers (TIMS);
 - d. Electron bombardment mass spectrometers having both of the following features:
 - 1. A molecular beam inlet system that injects a collimated beam of analyte molecules into a region of the ion source where the molecules are ionized by an electron beam; and
 - 2. One or more cold traps that can be cooled to a temperature of 193 K (-80°C) or less in order to trap analyte molecules that are not ionized by the electron beam;
 - e. Not used.
 - f. Mass spectrometers equipped with a microfluorination ion source designed for actinides or actinide fluorides.

Technical Notes:

- 1. *Item 3A233.d. describes mass spectrometers that are typically used for isotopic analysis of UF₆ gas samples.*
- 2. *Electron bombardment mass spectrometers in Item 3A233.d. are also known as electron impact mass spectrometers or electron ionization mass spectrometers.*
- 3. *In item 3A233.d.2., a 'cold trap' is a device that traps gas molecules by condensing or freezing them on cold surfaces. For the purposes of this entry, a closed-loop gaseous helium cryogenic vacuum pump is not a cold trap.*

- 3A234 High explosive containment vessels, chambers, containers and other similar containment devices designed for the testing of high explosives or explosive devices and having both of the following characteristics:
 - a. Designed to fully contain an explosion equivalent to 2 kg of TNT or greater; and
 - b. Having design elements or features enabling real time or delayed transfer of diagnostic or measurement information.
- 3A235 Striplines to provide low inductance path to detonators with the following characteristics:
 - a. Voltage rating greater than 2 kV; and
 - b. Inductance of less than 20 nH.

3B Test, Inspection and Production Equipment

- 3B001 Equipment for the manufacturing of semiconductor devices or materials, as follows and specially designed components and accessories therefor:
- a. Equipment designed for epitaxial growth as follows:
 1. Equipment capable of producing a layer of any material other than silicon with a thickness uniform to less than $\pm 2.5\%$ across a distance of 75 mm or more;
Note: 3B001.a.1. includes Atomic Layer Epitaxy (ALE) equipment.
 2. Metal Organic Chemical Vapour Deposition (MOCVD) reactors designed for compound semiconductor epitaxial growth of material having two or more of the following elements: aluminium, gallium, indium, arsenic, phosphorus, antimony, or nitrogen;
 3. Molecular beam epitaxial growth equipment using gas or solid sources;
 - b. Equipment designed for ion implantation and having any of the following:
 1. Not used;
 2. Being designed and optimized to operate at a beam energy of 20 keV or more and a beam current of 10 mA or more for hydrogen, deuterium or helium implant;
 3. Direct write capability;
 4. A beam energy of 65 keV or more and a beam current of 45 mA or more for high energy oxygen implant into a heated semiconductor material “substrate”; or
 5. Being designed and optimized to operate at a beam energy of 20 keV or more and a beam current of 10 mA or more for silicon implant into a semiconductor material “substrate” heated to 600°C or greater;
 - c. Anisotropic plasma dry etching equipment having all of the following:
 1. Designed or optimised to produce critical dimensions of 65 nm or less; and
 2. Within-wafer non-uniformity equal to or less than 10% 3σ measured with an edge exclusion of 2 mm or less;
 - d. Not used;
 - e. Automatic loading multi-chamber central wafer handling systems having all of the following:
 1. Interfaces for wafer input and output, to which more than two functionally different ‘semiconductor process tools’ specified in 3B001.a., 3B001.b., 3B001.c. or 3B001.d. are designed to be connected; and
 2. Designed to form an integrated system in a vacuum environment for ‘sequential multiple wafer processing’;
-

Note: 3B001.e. does not control automatic robotic wafer handling systems specially designed for parallel wafer processing.

Technical Notes:

1. *For the purpose of 3B001.e., 'semiconductor process tools' refers to modular tools that provide physical processes for semiconductor production that are functionally different, such as deposition, etch, implant or thermal processing.*
2. *For the purpose of 3B001.e., 'sequential multiple wafer processing' means the capability to process each wafer in different 'semiconductor process tools', such as by transferring each wafer from one tool to a second tool and on to a third tool with the automatic loading multi-chamber central wafer handling systems.*

f. **Lithography equipment as follows:**

1. Align and expose step and repeat (direct step on wafer) or step and scan (scanner) equipment for wafer processing using photo-optical or X-ray methods and having any of the following:
 - a. A light source wavelength shorter than 245 nm; or
 - b. Capable of producing a pattern with a 'Minimum Resolvable Feature size' (MRF) of 95 nm or less;

Technical Note:

The 'minimum resolvable feature size' (MRF) is calculated by the following formula:

$$\text{MRF} = \frac{(\text{an exposure light source wavelength in nm}) \times (\text{K factor})}{\text{numerical aperture}}$$

where the K factor = 0.35

2. Imprint lithography equipment capable of producing features of 95 nm or less;

Note: 3B001.f.2. includes:

- a. *Micro contact printing tools*
 - b. *Hot embossing tools*
 - c. *Nano-imprint lithography tools*
 - d. *Step and flash imprint lithography (S-FIL) tools.*
3. Equipment specially designed for mask making or semiconductor device processing using direct writing methods, having all of the following:
 - a. Using deflected focused electron beam, ion beam or "laser" beam; and
 - b. Having any of the following:
 1. A spot size smaller than 0.2 µm;
 2. Being capable of producing a pattern with a feature size of less than 1 µm; or
 3. An overlay accuracy of better than ± 0.20 µm (3 sigma);

	<ul style="list-style-type: none">g. Masks and reticles, designed for integrated circuits specified in 3A001;h. Multi-layer masks with a phase shift layer not specified by 3B001.g. and having any of the following:<ul style="list-style-type: none">1. Made on a mask “substrate blank” from glass specified as having less than 7 nm/cm birefringence; or2. Designed to be used by lithography equipment having a light source wavelength less than 245 nm;<p><i>Note: 3B001.h. does not apply to multi-layer masks with a phase shift layer designed for the fabrication of memory devices not controlled by 3A001.</i></p>i. Imprint lithography templates designed for integrated circuits specified in 3A001.
3B002	<p>Test equipment specially designed for testing finished or unfinished semiconductor devices as follows and specially designed components and accessories therefor:</p> <ul style="list-style-type: none">a. For testing S-parameters of transistor devices at frequencies exceeding 31.8 GHz;b. Not used;c. For testing microwave integrated circuits specified in 3A001.b.2.
3C	Materials
3C001	<p>Hetero-epitaxial materials consisting of a “substrate” having stacked epitaxially grown multiple layers of any of the following:</p> <ul style="list-style-type: none">a. Silicon (Si);b. Germanium (Ge);c. Silicon carbide (SiC); ord. “III/V compounds” of gallium or indium. <p><i>Note: 3C001.d. does not apply to a “substrate” having one or more P-type epitaxial layers of GaN, InGaN, AlGaN, InAlN, InAlGaP, GaP, InGaP, AlInP or InGaAlP, independent of the sequence of the elements, except if the P-type epitaxial layer is between N-type layers.</i></p>
3C002	<p>Resist materials as follows and “substrates” coated with the following resists:</p> <ul style="list-style-type: none">a. Resists designed for semiconductor lithography as follows:<ul style="list-style-type: none">1. Positive resists adjusted (optimised) for use at wavelengths less than 245 nm but equal to or greater than 15 nm;2. Resists adjusted (optimised) for use at wavelengths less than 15 nm but greater than 1 nm;

	<ul style="list-style-type: none"> b. All resists designed for use with electron beams or ion beams, with a sensitivity of 0.01 $\mu\text{coulomb}/\text{mm}^2$ or better; c. Not used; d. All resists optimised for surface imaging technologies; e. All resists designed or optimised for use with imprint lithography equipment specified in 3B001.f.2. that use either a thermal or photo-curable process.
3C003	<p>Organo-inorganic compounds as follows:</p> <ul style="list-style-type: none"> a. Organo-metallic compounds of aluminium, gallium or indium, having a purity (metal basis) better than 99.999%; b. Organo-arsenic, organo-antimony and organo-phosphorus compounds, having a purity (inorganic element basis) better than 99.999%. <p><i>Note: 3C003 only controls compounds whose metallic, partly metallic or non-metallic element is directly linked to carbon in the organic part of the molecule.</i></p>
3C004	<p>Hydrides of phosphorus, arsenic or antimony, having a purity better than 99.999%, even diluted in inert gases or hydrogen.</p> <p><i>Note: 3C004 does not control hydrides containing 20% molar or more of inert gases or hydrogen.</i></p>
3C005	<p>Silicon carbide (SiC), gallium nitride (GaN), aluminium nitride (AlN) or aluminium gallium nitride (AlGaIn) semiconductor “substrates”, or ingots, boules, or other preforms of those materials, having resistivities greater than 10,000 ohm-cm at 20°C.</p>
3C006	<p>“Substrates” specified in 3C005 with at least one epitaxial layer of silicon carbide, gallium nitride, aluminium nitride or aluminium gallium nitride.</p>
3D	Software
3D001	<p>“Software” specially designed for the “development” or “production” of equipment specified in 3A001.b. to 3A002.g. or 3B.</p>
3D002	<p>“Software” specially designed for the “use” of equipment specified in 3B001.a. to f. or 3B002.</p>
3D003	<p>‘Physics-based’ simulation “software” specially designed for the “development” of lithographic, etching or deposition processes for translating masking patterns into specific topographical patterns in conductors, dielectrics or semiconductor materials.</p>

Technical Note:

‘Physics-based’ in 3D003 means using computations to determine a sequence of physical cause and effect events based on physical properties (e.g., temperature, pressure, diffusion constants and semiconductor materials properties).

Note: Libraries, design attributes or associated data for the design of semiconductor devices or integrated circuits are considered as “technology”.

3D004 “Software” specially designed for the “development” of the equipment specified in 3A003.

3D101 “Software” specially designed or modified for the “use” of equipment specified in 3A101.b.

3D201 “Software” specially designed or modified for the “use” of equipment specified in 3A225.

3D202 “Software” or encryption keys/codes specially designed to enhance or release the performance characteristics of equipment not controlled in 3A225 so that it meets or exceeds the characteristics specified in 3A225.

3D203 “Software” specially designed to enhance or release the performance characteristics of equipment controlled in 3A225.

3E Technology

3E001 “Technology” according to the General Technology Note for the “development” or “production” of equipment, materials or “software” specified in 3A, 3B, 3C or 3D201 to 3D203;

Note 1: 3E001 does not control “technology” for the “production” of equipment or components controlled by 3A003.

Note 2: 3E001 does not control “technology” for the “development” or “production” of integrated circuits specified in 3A001.a.3. to 3A001.a.12., having all of the following:

- a. Using “technology” at or above 0.130 µm; and*
- b. Incorporating multi-layer structures with three or fewer metal layers.*

3E002	<p>“Technology” according to the General Technology Note, other than that specified in 3E001, for the “development” or “production” of a “microprocessor microcircuit”, “microcomputer microcircuit” or microcontroller microcircuit core, having an arithmetic logic unit with an access width of 32 bits or more and any of the following features or characteristics:</p> <ul style="list-style-type: none"> a. A ‘vector processor unit’ designed to perform more than two calculations on floating-point vectors (one-dimensional arrays of 32-bit or larger numbers) simultaneously; <p><i>Technical Note:</i> A ‘vector processor unit’ is a processor element with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 32-bit or larger numbers) simultaneously, having at least one vector arithmetic logic unit.</p> <ul style="list-style-type: none"> b. Designed to perform more than four 64-bit or larger floating-point operation results per cycle; or c. Designed to perform more than four 16-bit fixed-point multiply-accumulate results per cycle (e.g., digital manipulation of analogue information that has been previously converted into digital form, also known as digital “signal processing”). <p><i>Note:</i> 3E002.c. does not control “technology” for multimedia extensions.</p> <p><i>Note 1:</i> 3E002 does not control “technology” for the “development” or “production” of micro-processor cores, having all of the following:</p> <ul style="list-style-type: none"> a. Using “technology” at or above 0.130 µm; and b. Incorporating multi-layer structures with five or fewer metal layers. <p><i>Note 2:</i> 3E002 includes “technology” for digital signal processors and digital array processors.</p>
3E003	<p>Other “technology” for the “development” or “production” of the following:</p> <ul style="list-style-type: none"> a. Vacuum microelectronic devices; b. Hetero-structure semiconductor devices such as high electron mobility transistors (HEMT), hetero-bipolar transistors (HBT), quantum well and super lattice devices; <p><i>Note:</i> 3E003.b. does not control “technology” for high electron mobility transistors (HEMT) operating at frequencies lower than 31.8 GHz and hetero-junction bipolar transistors (HBT) operating at frequencies lower than 31.8 GHz.</p> <ul style="list-style-type: none"> c. “Superconductive” electronic devices; d. Substrates of films of diamond for electronic components; e. Substrates of silicon-on-insulator (SOI) for integrated circuits in which the insulator is silicon dioxide; f. Substrates of silicon carbide for electronic components;

-
- g. Electronic vacuum tubes operating at frequencies of 31.8 GHz or higher.
- 3E101 “Technology” according to the General Technology Note for the “use” of equipment or “software” specified in 3A001.a.1. or 2., 3A101, 3A102 or 3D101.
- 3E102 “Technology” according to the General Technology Note for the “development” of “software” specified in 3D101.
- 3E201 “Technology” according to the General Technology Note for the “use” of equipment or “software” specified in 3A001.e.2., 3A001.e.3., 3A001.g., 3A201, 3A225 to 3A235 or 3D201 to 3D203.

Category 4—Computers

Note 1: Computers, related equipment and “software” performing telecommunications or “local area network” functions must also be evaluated against the performance characteristics of Category 5, Part 1 (Telecommunications).

Note 2: Control units which directly interconnect the buses or channels of central processing units, “main storage” or disk controllers are not regarded as telecommunications equipment described in Category 5, Part 1 (Telecommunications).

N.B.: For the control status of “software” specially designed for packet switching, see 5D001.

Note 3: Computers, related equipment and “software” performing cryptographic, cryptanalytic, certifiable multi-level security or certifiable user isolation functions, or which limit electromagnetic compatibility (EMC), must also be evaluated against the performance characteristics in Category 5, Part 2 (“Information Security”).

4A Systems, Equipment and Components

4A001 Electronic computers and related equipment, having any of the following and “electronic assemblies” and specially designed components therefor:

N.B.: SEE ALSO 4A101.

a. Specially designed to have any of the following:

1. Rated for operation at an ambient temperature below 228 K (-45°C) or above 358 K (85°C); or

Note: 4A001.a.1. does not control computers specially designed for civil automobile, railway train or “civil aircraft” applications.

2. Radiation hardened to exceed any of the following specifications:

- a. Total Dose 5×10^3 Gy (Si);
- b. Dose Rate Upset 5×10^6 Gy (Si)/s; or
- c. Single Event Upset 1×10^{-8} Error/bit/day;

Note: 4A001.a.2. does not control computers specially designed for “civil aircraft” applications.

b. Not used.

4A002 Not used.

4A003 “Digital computers”, “electronic assemblies”, and related equipment therefor, as follows and specially designed components therefor:

Note 1: 4A003 includes the following:

- a. ‘Vector processors’;*
- b. Array processors;*
- c. Digital signal processors;*
- d. Logic processors;*
- e. Equipment designed for “image enhancement”;*
- f. Equipment designed for “signal processing”.*

Note 2: The control status of the “digital computers” and related equipment described in 4A003 is determined by the control status of other equipment or systems provided:

- a. The “digital computers” or related equipment are essential for the operation of the other equipment or systems;*
- b. The “digital computers” or related equipment are not a “principal element” of the other equipment or systems; and*

N.B. 1: The control status of “signal processing” or “image enhancement” equipment specially designed for other equipment with functions limited to those required for the other equipment is determined by the control status of the other equipment even if it exceeds the “principal element” criterion.

N.B. 2: For the control status of “digital computers” or related equipment for telecommunications equipment, see Category 5, Part 1 (Telecommunications).

- c. The “technology” for the “digital computers” and related equipment is determined by 4E.*

- a. Not used.
- b. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 8.0 Weighted TeraFLOPS (WT);
- c. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit specified in 4A003.b.;

Note 1: 4A003.c. controls only “electronic assemblies” and programmable interconnections not exceeding the limit specified in 4A003.b. when shipped as unintegrated “electronic assemblies”. It does not control “electronic assemblies” inherently limited by nature of their design for use as related equipment specified in 4A003.e.

Note 2: 4A003.c. does not control “electronic assemblies” specially designed for a product or family of products whose maximum configuration does not exceed the limit specified in 4A003.b.

- d. Not used;

	<ul style="list-style-type: none">e. Equipment performing analogue-to-digital conversions exceeding the limits specified in 3A001.a.5.;f. Not used;g. Equipment specially designed to provide external interconnection of “digital computers” or associated equipment which allows communications at data rates exceeding 2.0 Gbyte/s. <p><i>Note: 4A003.g. does not control internal interconnection equipment (e.g. backplanes, buses), passive interconnection equipment, “network access controllers” or “communications channel controllers”.</i></p>
4A004	Computers as follows and specially designed related equipment, “electronic assemblies” and components therefor: <ul style="list-style-type: none">a. “Systolic array computers”;b. “Neural computers”;c. “Optical computers”.
4A005	Systems, equipment, and components therefor, specially designed or modified for the generation, operation or delivery of, or communication with, “intrusion software”.
4A101	Analogue computers, “digital computers” or digital differential analysers, other than those specified in 4A001.a.1., which are ruggedised and designed or modified for use in space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.
4A102	“Hybrid computers” specially designed for modelling, simulation or design integration of space launch vehicles specified in 9A004 or sounding rockets specified in 9A104. <p><i>Note: This control only applies when the equipment is supplied with “software” specified in 7D103 or 9D103.</i></p>
4B	Test, Inspection and Production Equipment None.
4C	Materials None.

4D Software

Note: The status of “software” for equipment described in other Categories is dealt with in the appropriate Category.

4D001 “Software” as follows:

- a. “Software” specially designed or modified for the “development”, or “production” of equipment or “software” specified in 4A or 4D;
- b. “Software”, other than that specified in 4D001.a., specially designed or modified for the “development” or “production” of equipment as follows:
 1. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 0.6 Weighted TeraFLOPS (WT);
 2. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit in 4D001.b.1.;

4D002 “Software” specially designed or modified to support “technology” specified in 4E.

4D003 Not used.

N.B.: See Category 5–Part 2 for “software” performing or incorporating “information security” functions.

4D004 “Software” specially designed or modified for the generation, operation or delivery of, or communication with, “intrusion software”.

4E Technology

- 4E001
 - a. “Technology” according to the General Technology Note, for the “development”, “production” or “use” of equipment or “software” specified in 4A or 4D.
 - b. “Technology”, other than that specified in 4E001.a., specially designed or modified for the “development” or “production” of equipment as follows:
 1. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 0.6 Weighted TeraFLOPS (WT);
 2. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit in 4E001.b.1.
 - c. “Technology” for the “development” of “intrusion software”.

TECHNICAL NOTE ON “ADJUSTED PEAK PERFORMANCE” (“APP”)

“APP” is an adjusted peak rate at which “digital computers” perform 64-bit or larger floating point additions and multiplications.

“APP” is expressed in Weighted TeraFLOPS (WT), in units of 10^{12} adjusted floating point operations per second

Abbreviations used in this Technical Note

- n number of processors in the “digital computer”
i processor number (i,...n)
 t_i processor cycle time ($t_i = 1/F_i$)
 F_i processor frequency
 R_i peak floating point calculating rate
 W_i architecture adjustment factor

Outline of “APP” calculation method

1. For each processor i, determine the peak number of 64-bit or larger floating point operations, FPO_i , performed per cycle for each processor in the “digital computer”.

Note: In determining FPO , include only 64-bit or larger floating point additions and/or multiplications. All floating point operations must be expressed in operations per processor cycle; operations requiring multiple cycles may be expressed in fractional results per cycle. For processors not capable of performing calculations on floating point operands of 64-bit or more, the effective calculating rate R is zero.

2. Calculate the floating point rate R for each processor:

$$R_i = \frac{FPO_i}{t_i}$$

3. Calculate “APP”:

$$APP = W_1 \times R_1 + W_2 \times R_2 + \dots + W_n \times R_n$$

4. For ‘vector processors’, $W_i = 0.9$. For non-‘vector processors’, $W_i = 0.3$.

Note 1: For processors that perform compound operations in a cycle, such as addition and multiplication, each operation is counted.

Note 2: For a pipelined processor the effective calculating rate R is the faster of the pipelined rate, once the pipeline is full, or the non-pipelined rate.

Note 3: The calculating rate R of each contributing processor is to be calculated at its maximum value theoretically possible before the “APP” of the combination is derived. Simultaneous operations are assumed to exist when the computer manufacturer claims concurrent, parallel, or simultaneous operation or execution in a manual or brochure for the computer.

Note 4: Do not include processors that are limited to input/output and peripheral functions (e.g., disk drive, communication and video display) when calculating “APP”.

Note 5: “APP” values are not to be calculated for processor combinations (inter)connected by “Local Area Networks”, Wide Area Networks, I/O shared connections/devices, I/O controllers and any communication interconnection implemented by “software”.

Note 6: “APP” values must be calculated for:

- a. Processor combinations containing processors specially designed to enhance performance by aggregation, operating simultaneously and sharing memory; or*
- b. Multiple memory/processor combinations operating simultaneously utilising specially designed hardware.*

Note 7: A ‘vector processor’ is defined as a processor with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 64-bit or larger numbers) simultaneously, having at least 2 vector functional units and at least 8 vector registers of at least 64 elements each.

Category 5—Telecommunications and “information security”

Part 1—TELECOMMUNICATIONS

Note 1: The control status of components, “lasers”, test and “production” equipment and “software” therefor which are specially designed for telecommunications equipment or systems is determined in Category 5, Part 1.

N.B.1: For “lasers” specially designed for telecommunications equipment or systems, see 6A005.

N.B.2: See also Category 5, Part 2 for equipment, components, and “software” performing or incorporating “information security” functions.

Note 2: “Digital computers”, related equipment or “software”, when essential for the operation and support of telecommunications equipment described in this Category, are regarded as specially designed components, provided they are the standard models customarily supplied by the manufacturer. This includes operation, administration, maintenance, engineering or billing computer systems.

5A1 Systems, Equipment and Components

5A001 Telecommunications systems, equipment, components and accessories as follows:

- a. Any type of telecommunications equipment having any of the following characteristics, functions or features:
 1. Specially designed to withstand transitory electronic effects or electromagnetic pulse effects, both arising from a nuclear explosion;
 2. Specially hardened to withstand gamma, neutron or ion radiation; or
 3. Specially designed to operate outside the temperature range from 218 K (-55°C) to 397 K (124°C);

Note: 5A001.a.3. applies only to electronic equipment.

Note: 5A001.a.2. and 5A001.a.3. do not control equipment designed or modified for use on board satellites.

- b. Telecommunication systems and equipment, and specially designed components and accessories therefor, having any of the following characteristics, functions or features:
 1. Being underwater untethered communications systems having any of the following:
 - a. An acoustic carrier frequency outside the range from 20 kHz to 60 kHz;
 - b. Using an electromagnetic carrier frequency below 30 kHz;

-
- c. Using electronic beam steering techniques; or
 - d. Using “lasers” or light-emitting diodes (LEDs), with an output wavelength greater than 400 nm and less than 700 nm, in a “local area network”;
2. Being radio equipment operating in the 1.5 MHz to 87.5 MHz band and having all of the following:
- a. Automatically predicting and selecting frequencies and “total digital transfer rates” per channel to optimise the transmission; and
 - b. Incorporating a linear power amplifier configuration having a capability to support multiple signals simultaneously at an output power of 1 kW or more in the frequency range of 1.5 MHz or more but less than 30 MHz, or 250 W or more in the frequency range of 30 MHz or more but not exceeding 87.5 MHz, over an “instantaneous bandwidth” of one octave or more and with an output harmonic and distortion content of better than -80 dB;
3. Being radio equipment employing “spread spectrum” techniques, including “frequency hopping” techniques, other than those specified in 5A001.b.4. and having any of the following:
- a. User programmable spreading codes; or
 - b. A total transmitted bandwidth which is 100 or more times the bandwidth of any one information channel and in excess of 50 kHz;
- Note: 5A001.b.3.b. does not control radio equipment specially designed for use with civil cellular radio-communications systems.*
- Note: 5A001.b.3 does not control equipment designed to operate at an output power of 1 W or less.*
4. Being radio equipment employing ultra-wideband modulation techniques, having user programmable channelising codes, scrambling codes or network identification codes and having any of the following:
- a. A bandwidth exceeding 500 MHz; or
 - b. A “fractional bandwidth” of 20% or more;
5. Being digitally controlled radio receivers having all of the following:
- a. More than 1,000 channels;
 - b. A ‘channel switching time’ of less than 1 ms;
 - c. Automatic searching or scanning of a part of the electromagnetic spectrum; and
 - d. Identification of the received signals or the type of transmitter; or
-

Note: 5A001.b.5. does not control radio equipment specially designed for use with civil cellular radio-communications systems.

Technical Note:

‘Channel switching time’: the time (i.e., delay) to change from one receiving frequency to another, to arrive at or within $\pm 0.05\%$ of the final specified receiving frequency. Items having a specified frequency range of less than $\pm 0.05\%$ around their centre frequency are defined to be incapable of channel frequency switching.

6. Employing functions of digital “signal processing” to provide ‘voice coding’ output at rates of less than 2,400 bit/s;

Technical Notes:

1. For variable rate ‘voice coding’, 5A001.b.6. applies to the ‘voice coding’ output of continuous speech.
2. For the purposes of 5A001.b.6., ‘voice coding’ is defined as the technique to take samples of human voice and then convert these samples into a digital signal, taking into account specific characteristics of human speech.

- c. Optical fibres of more than 500 m in length and specified by the manufacturer as being capable of withstanding a ‘proof test’ tensile stress of 2×10^9 N/m² or more;

N.B.: For underwater umbilical cables, see 8A002.a.3.

Technical Note:

‘Proof Test’: on-line or off-line production screen testing that dynamically applies a prescribed tensile stress over a 0.5 to 3 m length of fibre at a running rate of 2 to 5 m/s while passing between capstans approximately 50 mm in diameter. The ambient temperature is a nominal 293 K (20°C) and relative humidity 40%. Equivalent national standards may be used for executing the proof test.

- d. “Electronically steerable phased array antennae” operating above 31.8 GHz;

Note: 5A001.d. does not control “electronically steerable phased array antennae” for landing systems with instruments meeting ICAO standards covering Microwave Landing Systems (MLS).

- e. Radio direction finding equipment operating at frequencies above 30 MHz and having all of the following, and specially designed components therefor:

1. “Instantaneous bandwidth” of 10 MHz or more; and
2. Capable of finding a Line Of Bearing (LOB) to non-cooperating radio transmitters with a signal duration of less than 1 ms;

- f. Mobile telecommunications interception or jamming equipment, and monitoring equipment therefor, as follows, and specially designed components therefor:

1. Interception equipment designed for the extraction of voice or data, transmitted over the air interface;
2. Interception equipment not specified in 5A001.f.1., designed for the extraction of client device or subscriber identifiers (e.g., IMSI, TIMSI or IMEI), signalling, or other metadata transmitted over the air interface;
3. Jamming equipment specially designed or modified to intentionally and selectively interfere with, deny, inhibit, degrade or seduce mobile telecommunication services and performing any of the following:
 - a. Simulate the functions of Radio Access Network (RAN) equipment;
 - b. Detect and exploit specific characteristics of the mobile telecommunications protocol employed (e.g., GSM); or
 - c. Exploit specific characteristics of the mobile telecommunications protocol employed (e.g., GSM);
4. RF monitoring equipment designed or modified to identify the operation of items specified in 5A001.f.1., 5A001.f.2. or 5A001.f.3.;

Note: 5A001.f.1. and 5A001.f.2. do not apply to any of the following:

- a. Equipment specially designed for the interception of analogue Private Mobile Radio (PMR), IEEE 802.11 WLAN;*
- b. Equipment designed for mobile telecommunications network operators; or*
- c. Equipment designed for the “development” or “production” of mobile telecommunications equipment or systems.*

N.B.1: See also the Munitions List.

N.B.2: For radio receivers see 5A001.b.5.

- g. Passive Coherent Location (PCL) systems or equipment, specially designed for detecting and tracking moving objects by measuring reflections of ambient radio frequency emissions, supplied by non-radar transmitters;

Technical Note:

Non-radar transmitters may include commercial radio, television or cellular telecommunications base stations.

Note: 5A001.g. does not control any of the following:

- a. Radio-astronomical equipment; or*
- b. Systems or equipment, that require any radio transmission from the target.*

-
- h. Counter Improvised Explosive Device (IED) equipment and related equipment, as follows:
 - 1. Radio Frequency (RF) transmitting equipment, not specified by 5A001.f., designed or modified for prematurely activating or preventing the initiation of Improvised Explosive Devices;
 - 2. Equipment using techniques designed to enable radio communications in the same frequency channels on which co-located equipment specified by 5A001.h.1. is transmitting.

N.B.: See also the Munitions List.
 - i. Not used

N.B.: See 5A001.f. for items previously specified by 5A001.i.
 - j. IP network communications surveillance systems or equipment, and specially designed components therefor, having all of the following:
 - 1. Performing all of the following on a carrier class IP network (e.g., national grade IP backbone):
 - a. Analysis at the application layer (e.g., Layer 7 of Open Systems Interconnection (OSI) model (ISO/IEC 7498-1));
 - b. Extraction of selected metadata and application content (e.g., voice, video, messages, attachments); and
 - c. Indexing of extracted data; and
 - 2. Being specially designed to carry out all of the following:
 - a. Execution of searches on the basis of ‘hard selectors’; and
 - b. Mapping of the relational network of an individual or of a group of people.

Technical Note:

‘Hard selectors’: data or set of data, related to an individual (e.g., family name, given name, e-mail, street address, phone number or group affiliations).

Note: 5A001.j. does not apply to systems or equipment, specially designed for any of the following:

 - a. Marketing purpose;
 - b. Network Quality of Service (QoS); or
 - c. Quality of Experience (QoE)

5A101 Telemetry and telecontrol equipment, including ground equipment, designed or modified for ‘missiles’.

Technical Note:

In 5A101 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.

Note: 5A101 does not control:

- a. Equipment designed or modified for manned aircraft or satellites;

- b. *Ground based equipment designed or modified for terrestrial or marine applications;*
- c. *Equipment designed for commercial, civil or ‘Safety of Life’ (e.g. data integrity, flight safety) GNSS services.*

5B1 Test, Inspection and Production Equipment

5B001 Telecommunications test, inspection and production equipment, components and accessories, as follows:

- a. Equipment and specially designed components or accessories therefor, specially designed for the “development”, “production” or “use” of equipment, functions or features, specified in 5A001;

Note: 5B001.a. does not control optical fibre characterisation equipment.

- b. Equipment and specially designed components or accessories therefor, specially designed for the “development” of any of the following telecommunication transmission or switching equipment:

- 1. Not used
- 2. Equipment employing a “laser” and having any of the following:
 - a. A transmission wavelength exceeding 1750 nm;
 - b. Performing “optical amplification” using praseodymium-doped fluoride fibre amplifiers (PDFFA);
 - c. Employing coherent optical transmission or coherent optical detection techniques (also called optical heterodyne or homodyne techniques); or

Note: 5B001.b.2.c. applies to equipment specially designed for the “development” of systems using an optical local oscillator in the receiving side to synchronize with a carrier “laser”.

Technical Note:

For the purpose of 5.B.1.b.2.c., these techniques include optical heterodyne, homodyne or intradyne techniques.

- d. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz;

Note: 5B001.b.2.d. does not control equipment specially designed for the “development” of commercial TV systems.

- 3. Not used
- 4. Radio equipment employing Quadrature-Amplitude-Modulation (QAM) techniques above level 256.
- 5. Not used

5C1	Materials
	None
5D1	Software
5D001	<p>“Software” as follows:</p> <ol style="list-style-type: none"> a. “Software” specially designed or modified for the “development”, “production” or “use” of equipment, functions or features, specified in 5A001; b. “Software” specially designed or modified to support “technology” specified in 5E001; c. Specific “software” specially designed or modified to provide characteristics, functions or features of equipment, specified in 5A001 or 5B001; d. “Software” specially designed or modified for the “development” of any of the following telecommunication transmission or switching equipment: <ol style="list-style-type: none"> 1. Not used 2. Equipment employing a “laser” and having any of the following: <ol style="list-style-type: none"> a. A transmission wavelength exceeding 1,750 nm; or b. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; <p><i>Note: 5D001.d.2.b. does not control “software” specially designed or modified for the “development” of commercial TV systems.</i></p> 3. Not used 4. Radio equipment employing Quadrature-Amplitude-Modulation (QAM) techniques above level 256.
5D101	“Software” specially designed or modified for the “use” of equipment specified in 5A101.
5E1	Technology
5E001	<p>“Technology” as follows:</p> <ol style="list-style-type: none"> a. “Technology” according to the General Technology Note for the “development”, “production” or “use” (excluding operation) of equipment, functions or features specified in 5A001 or “software” specified in 5D001.a.;

-
- b. Specific “technology” as follows:
1. “Required” “technology” for the “development” or “production” of telecommunications equipment specially designed to be used on board satellites;
 2. “Technology” for the “development” or “use” of “laser” communication techniques with the capability of automatically acquiring and tracking signals and maintaining communications through exoatmosphere or sub-surface (water) media;
 3. “Technology” for the “development” of digital cellular radio base station receiving equipment whose reception capabilities that allow multi-band, multi-channel, multi-mode, multi-coding algorithm or multi-protocol operation can be modified by changes in “software”;
 4. “Technology” for the “development” of “spread spectrum” techniques, including “frequency hopping” techniques;
- Note: 5E001.b.4. does not apply to “technology” for the “development” of any of the following:*
- a. Civil cellular radio-communications systems; or
 - b. Fixed or mobile satellite earth stations for commercial civil telecommunications.
- c. “Technology” according to the General Technology Note for the “development” or “production” of any of the following:
1. Equipment employing digital techniques designed to operate at a “total digital transfer rate” exceeding 120 Gbit/s;
- Technical Note:*
For telecommunication switching equipment, the “total digital transfer rate” is the unidirectional speed of a single interface, measured at the highest speed port or line.
2. Equipment employing a “laser” and having any of the following:
 - a. A transmission wavelength exceeding 1,750 nm;
 - b. Performing “optical amplification” using Praseodymium-Doped Fluoride Fibre Amplifiers (PDFFA);
 - c. Employing coherent optical transmission or coherent optical detection techniques (also called optical heterodyne or homodyne techniques);
- Note: 5E001.c.2.c. applies to “technology” for the “development” or “production” of systems using an optical local oscillator in the receiving side to synchronize with a carrier “laser”.*
- Technical Note:*
For the purpose of 5E001.c.2.c., these techniques include optical heterodyne, homodyne or intradyne techniques.
- d. Employing wavelength division multiplexing techniques of optical carriers at less than 100 GHz spacing; or
-

-
- e. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz;
Note: 5E001.c.2.e. does not control “technology” for the “development” or “production” of commercial TV systems.
N.B.: For “technology” for the “development” or “production” of non-telecommunications equipment employing a laser, see 6E.
 - 3. Equipment employing “optical switching” and having a switching time less than 1 ms;
 - 4. Radio equipment having any of the following:
 - a. Quadrature-Amplitude-Modulation (QAM) techniques above level 256;
 - b. Operating at input or output frequencies exceeding 31.8 GHz; or
Note: 5E001.c.4.b. does not control “technology” for the “development” or “production” of equipment designed or modified for operation in any frequency band which is “allocated by the ITU” for radio-communications services, but not for radio-determination.
 - c. Operating in the 1.5 MHz to 87.5 MHz band and incorporating adaptive techniques providing more than 15 dB suppression of an interfering signal; or
 - 5. Not used
 - 6. Mobile equipment having all of the following:
 - a. Operating at an optical wavelength greater than or equal to 200 nm and less than or equal to 400 nm; and
 - b. Operating as a “local area network”;
 - d. “Technology” according to the General Technology Note for the “development” or “production” of Microwave Monolithic Integrated Circuit (MMIC) power amplifiers specially designed for telecommunications and that are any of the following:
Technical Note:
For purposes of 5E001.d., the parameter peak saturated power output may also be referred to on product data sheets as output power, saturated power output, maximum power output, peak power output, or peak envelope power output.
 - 1. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following:
 - a. A peak saturated power output greater than 75 W (48.75 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;
-

-
- b. A peak saturated power output greater than 55 W (47.4 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;
 - c. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; or
 - d. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz;
- 2. Rated for operation at frequencies exceeding 6.8 GHz up to and including 16 GHz with a “fractional bandwidth” greater than 10%, and having any of the following:
 - a. A peak saturated power output greater than 10 W (40 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; or
 - b. A peak saturated power output greater than 5 W (37 dBm) at any frequency exceeding 8.5 GHz up to and including 16 GHz;
 - 3. Rated for operation with a peak saturated power output greater than 3 W (34.77 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz, and with a “fractional bandwidth” of greater than 10%;
 - 4. Rated for operation with a peak saturated power output greater than 0.1n W (-70 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;
 - 5. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;
 - 6. Rated for operation with a peak saturated power output greater than 31.62 mW (15 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;
 - 7. Rated for operation with a peak saturated power output greater than 10 mW (10 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; or
 - 8. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz;
-

Part 2 Dual-use list

Category 5 Telecommunications and “information security”

-
- e. “Technology” according to the General Technology Note for the “development” or “production” of electronic devices and circuits, specially designed for telecommunications and containing components manufactured from “superconductive” materials, specially designed for operation at temperatures below the “critical temperature” of at least one of the “superconductive” constituents and having any of the following:
1. Current switching for digital circuits using “superconductive” gates with a product of delay time per gate (in seconds) and power dissipation per gate (in watts) of less than 10^{-14} J; or
 2. Frequency selection at all frequencies using resonant circuits with Q-values exceeding 10,000.
- 5E101 “Technology” according to the General Technology Note for the “development”, “production” or “use” of equipment specified in 5A101.

Part 2 — “INFORMATION SECURITY”

Note 1: The control status of “information security” equipment, “software”, systems, application specific “electronic assemblies”, modules, integrated circuits, components or functions is determined in Category 5, Part 2 even if they are components or “electronic assemblies” of other equipment.

Note 2: Category 5 — Part 2 does not control products when accompanying their user for the user’s personal use.

Note 3: Cryptography Note

5A002. and 5D002. do not apply to items as follows:

- a. *Items meeting all of the following:*
 1. *Generally available to the public by being sold, without restriction, from stock at retail selling points by means of any of the following:*
 - a. *Over-the-counter transactions;*
 - b. *Mail order transactions;*
 - c. *Electronic transactions; or*
 - d. *Telephone call transactions;*
 2. *The cryptographic functionality cannot easily be changed by the user;*
 3. *Designed for installation by the user without further substantial support by the supplier; and*
 4. *Not used*
 5. *When necessary, details of the items are accessible and will be provided, upon request, to the appropriate authority in the exporter’s country in order to ascertain compliance with conditions described in paragraphs 1. to 3. above;*

-
- b. *Hardware components or ‘executable software’, of existing items described in paragraph a. of this Note, that have been designed for these existing items, and meeting all of the following:*
1. *“Information security” is not the primary function or set of functions of the component or ‘executable software’;*
 2. *The component or ‘executable software’ does not change any cryptographic functionality of the existing items, or add new cryptographic functionality to the existing items;*
 3. *The feature set of the component or ‘executable software’ is fixed and is not designed or modified to customer specification; and*
 4. *When necessary as determined by the appropriate authority in the exporter’s country, details of the component or ‘executable software’, and details of relevant end-items are accessible and will be provided to the authority upon request, in order to ascertain compliance with conditions described above.*

Technical Note:

For the purpose of the Cryptography Note, ‘executable software’ means “software” in executable form, from an existing hardware component excluded from 5A002. by the Cryptography Note.

Note: ‘Executable software’ does not include complete binary images of the “software” running on an end-item.

Note to the Cryptography Note:

1. *To meet paragraph a. of Note 3, all of the following must apply:*
 - a. *The item is of potential interest to a wide range of individuals and businesses; and*
 - b. *The price and information about the main functionality of the item are available before purchase without the need to consult the vendor or supplier.*
2. *In determining eligibility of paragraph a. of Note 3, national authorities may take into account relevant factors such as quantity, price, required technical skill, existing sales channels, typical customers, typical use or any exclusionary practices of the supplier.*

Note 4: Category 5, Part 2 does not control items incorporating or using “cryptography” and meeting all of the following:

- a. *The primary function or set of functions is not any of the following:*
 1. *“Information security”;*
 2. *A computer, including operating systems, parts and components therefor;*
-

-
3. *Sending, receiving or storing information (except in support of entertainment, mass commercial broadcasts, digital rights management or medical records management); or*
 4. *Networking (includes operation, administration, management and provisioning);*
 - b. *The cryptographic functionality is limited to supporting their primary function or set of functions; and*
 - c. *When necessary, details of the items are accessible and will be provided, on request, to the appropriate authority in the exporter’s country in order to ascertain compliance with conditions described in paragraphs a. and b. above.*

5A2 Systems, Equipment and Components

5A002 “Information security” systems, equipment and components therefor, as follows:

- a. Systems, equipment, application specific “electronic assemblies”, modules and integrated circuits for “information security”, as follows and components therefor specially designed for “information security”:

N.B.: For Global Navigation Satellite Systems (GNSS) receiving equipment containing or employing decryption see 7A005., and for related decryption “software” and “technology” see 7D005. and 7E001.

1. Designed or modified to use “cryptography” employing digital techniques performing any cryptographic function other than authentication, digital signature or the execution of copy-protected “software”, and having any of the following:

Technical Notes:

1. *Functions for authentication, digital signature and the execution of copy-protected “software” include their associated key management function.*
2. *Authentication includes all aspects of access control where there is no encryption of files or text except as directly related to the protection of passwords, Personal Identification Numbers (PINs) or similar data to prevent unauthorised access.*
- a. A “symmetric algorithm” employing a key length in excess of 56 bits; or

Technical Note:

In Category 5 — Part 2, parity bits are not included in the key length.

-
- b. An “asymmetric algorithm” where the security of the algorithm is based on any of the following:
1. Factorisation of integers in excess of 512 bits (e.g., RSA);
 2. Computation of discrete logarithms in a multiplicative group of a finite field of size greater than 512 bits (e.g., Diffie-Hellman over $\mathbb{Z}/p\mathbb{Z}$); or
 3. Discrete logarithms in a group other than mentioned in 5A002.a.1.b.2. in excess of 112 bits (e.g., Diffie-Hellman over an elliptic curve);
2. Designed or modified to perform cryptanalytic functions;
 3. Not used;
 4. Specially designed or modified to reduce the compromising emanations of information-bearing signals beyond what is necessary for health, safety or electromagnetic interference standards;
 5. Designed or modified to use cryptographic techniques to generate the spreading code for “spread spectrum” systems, other than those specified in 5A002.a.6., including the hopping code for “frequency hopping” systems;
 6. Designed or modified to use cryptographic techniques to generate channelising codes, scrambling codes or network identification codes, for systems using ultra-wideband modulation techniques and having any of the following:
 - a. A bandwidth exceeding 500 MHz; or
 - b. A “fractional bandwidth” of 20% or more;
 7. Non-cryptographic information and communications technology (ICT) security systems and devices evaluated to an assurance level exceeding class EAL-6 (evaluation assurance level) of the Common Criteria (CC) or equivalent;
 8. Communications cable systems designed or modified using mechanical, electrical or electronic means to detect surreptitious intrusion;
Note: 5A002.a.8. applies only to physical layer security.
 9. Designed or modified to use or perform “quantum cryptography”.
Technical Note:
“Quantum cryptography” is also known as Quantum Key Distribution (QKD).
- b. Systems, equipment, application specific “electronic assemblies”, modules and integrated circuits, designed or modified to enable an item to achieve or exceed the controlled performance levels for functionality specified by 5A002.a. that would not otherwise be enabled.
- Note: 5A002 does not apply to any of the following:*
- a. Smart cards and smart card ‘readers/writers’ as follows:
-

-
1. *A smart card or an electronically readable personal document (e.g. token coin, e-passport) that meets any of the following:*
 - a. *The cryptographic capability is restricted for use in equipment or systems excluded from 5A002 by Note 4 in Category 5, Part 2 or entries b. to i. of this Note, and cannot be reprogrammed for any other use; or*
 - b. *Having all of the following:*
 1. *It is specially designed and limited to allow protection of ‘personal data’ stored within;*
 2. *Has been, or can only be, personalized for public or commercial transactions or individual identification; and*
 3. *Where the cryptographic capability is not user-accessible;*

Technical Note:

‘Personal data’ includes any data specific to a particular person or entity, such as the amount of money stored and data necessary for authentication.

2. *‘Readers/writers’ specially designed or modified, and limited, for items specified by a.1. of this Note.*

Technical Note:

‘Readers/writers’ include equipment that communicates with smart cards or electronically readable documents through a network.

- b. *Not used;*
N.B. See Note 4 in Category 5-Part 2 for items previously specified in 5.A.2. Note b.
- c. *Not used;*
N.B. See Note 4 in Category 5-Part 2 for items previously specified in 5.A.2. Note c.
- d. *Cryptographic equipment specially designed and limited for banking use or ‘money transactions’;*

Technical Note:

‘Money transactions’ in 5A002 Note d. includes the collection and settlement of fares or credit functions.

- e. *Portable or mobile radiotelephones for civil use (e.g. for use with commercial civil cellular radio communication systems) that are not capable of transmitting encrypted data directly to another radiotelephone or equipment (other than Radio Access Network (RAN) equipment), nor of passing encrypted data through RAN equipment (e.g. Radio Network Controller (RNC) or Base Station Controller (BSC));*
-

-
- f. *Cordless telephone equipment not capable of end-to-end encryption where the maximum effective range of unboosted cordless operation (i.e. a single, unrelayed hop between terminal and home base station) is less than 400 m according to the manufacturer’s specifications;*
 - g. *Portable or mobile radiotelephones and similar client wireless devices for civil use, that implement only published or commercial cryptographic standards (except for anti-piracy functions, which may be non-published) and also meet the provisions of paragraphs b. to d. of the Cryptography Note (Note 3 in Category 5, Part 2), that have been customised for a specific civil industry application with features that do not affect the cryptographic functionality of these original non-customised devices;*
 - h. *Not used;*
N.B. See Note 4 in Category 5-Part 2 for items previously specified in 5.A.2. Note h.
 - i. *Wireless “personal area network” equipment that implement only published or commercial cryptographic standards and where the cryptographic capability is limited to a nominal operating range not exceeding 30 m according to the manufacturer’s specifications, or not exceeding 100 metres according to the manufacturer’s specifications for equipment that cannot interconnect with more than seven devices; or*
 - j. *Equipment, having no functionality specified by 5A002.a.2., 5A002.a.4., 5A002.a.7., or 5A002.a.8., where all cryptographic capability specified by 5A002.a. meets any of the following:*
 - 1. *It cannot be used; or*
 - 2. *It can only be made useable by means of “cryptographic activation”.**N.B. See 5A002.a. for equipment that has undergone “cryptographic activation”.*
 - k. *Mobile telecommunications Radio Access Network (RAN) equipment designed for civil use, which also meet the provisions 2. to 5. of part a. of the Cryptography Note (Note 3 in Category 5, Part 2), having an RF output power limited to 0.1 W (20 dBm) or less, and supporting 16 or fewer concurrent users.*

5B2 Test, Inspection and Production Equipment

- 5B002 “Information security” test, inspection and “production” equipment, as follows:
- a. Equipment specially designed for the “development” or “production” of equipment specified in 5A002 or 5B002.b.;
 - b. Measuring equipment specially designed to evaluate and validate the “information security” functions of the equipment specified in 5A002 or “software” specified in 5D002.a. or 5D002.c.
-

5C2 Materials

None.

5D2 Software

5D002 “Software” as follows:

- a. “Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in 5A002 or “software” specified in 5D002.c.;
- b. “Software” specially designed or modified to support “technology” specified in 5E002;
- c. Specific “software”, as follows:
 1. “Software” having the characteristics, or performing or simulating the functions of the equipment, specified in 5A002;
 2. “Software” to certify “software” specified in 5D002.c.1.;
- d. “Software” designed or modified to enable an item to achieve or exceed the controlled performance levels for functionality specified by 5A002.a. that would not otherwise be enabled.

5E2 Technology

5E002 “Technology” as follows:

- a. “Technology” according to the General Technology Note for the “development”, “production” or “use” of equipment specified in 5A002, 5B002 or “software” specified in 5D002.a. or 5D002.c.;
- b. “Technology” to enable an item to achieve or exceed the controlled performance levels for functionality specified by 5A002.a. that would not otherwise be enabled.

Note: 5E002. includes “information security” technical data resulting from procedures carried out to evaluate or determine the implementation of functions, features or techniques specified in Category 5-Part 2.

Category 6—Sensors and lasers

6A Systems, Equipment and Components

6A001 Acoustic systems, equipment and components, as follows:

- a. Marine acoustic systems, equipment and specially designed components therefor, as follows:
 1. Active (transmitting or transmitting-and-receiving) systems, equipment and specially designed components therefor, as follows:

Note: 6A001.a.1. does not control equipment as follows:

- a. Depth sounders operating vertically below the apparatus, not including a scanning function exceeding $\pm 20^\circ$, and limited to measuring the depth of water, the distance of submerged or buried objects or fish finding;
- b. Acoustic beacons, as follows:
 1. Acoustic emergency beacons;
 2. Pingers specially designed for relocating or returning to an underwater position.

- a. Acoustic seabed survey equipment as follows:

1. Surface vessel survey equipment designed for seabed topographic mapping and having all of the following:
 - a. Designed to take measurements at an angle exceeding 20° from the vertical;
 - b. Designed to measure seabed topography at seabed depths exceeding 600 m;
 - c. 'Sounding resolution' less than 2; and
 - d. 'Enhancement' of the depth accuracy through compensation for all the following:
 1. Motion of the acoustic sensor;
 2. In-water propagation from sensor to the seabed and back; and
 3. Sound speed at the sensor;

Technical Notes:

1. 'Sounding resolution' is the swath width (degrees) divided by the maximum number of soundings per swath.
2. 'Enhancement' includes the ability to compensate by external means.

2. Underwater survey equipment designed for seabed topographic mapping and having any of the following:

Technical Note:

The acoustic sensor pressure rating determines the depth rating of the equipment specified by 6A001.a.1.a.2.

- a. Having all of the following:
 - 1. Designed or modified to operate at depths exceeding 300 m; and
 - 2. 'Sounding rate' greater than 3,800; or

Technical Note:
'Sounding rate' is the product of the maximum speed (m/s) at which the sensor can operate and the maximum number of soundings per swath.
- b. Survey equipment, not specified by 6A001.a.1.a.2.a., having all of the following:
 - 1. Designed or modified to operate at depths exceeding 100 m;
 - 2. Designed to take measurements at an angle exceeding 20° from the vertical;
 - 3. Having any of the following:
 - a. Operating frequency below 350 kHz; or
 - b. Designed to measure seabed topography at a range exceeding 200 m from the acoustic sensor; and
 - 4. 'Enhancement' of the depth accuracy through compensation of all of the following:
 - a. Motion of the acoustic sensor;
 - b. In-water propagation from sensor to the seabed and back; and
 - c. Sound speed at the sensor.

- 3. Side Scan Sonar (SSS) or Synthetic Aperture Sonar (SAS), designed for seabed imaging and having all of the following:
 - a. Designed or modified to operate at depths exceeding 500 m;
 - b. An 'area coverage rate' of greater than 570 m²/s while operating with an 'along track resolution' of less than 15 cm; and
 - c. An 'across track resolution' of less than 15 cm.

Technical Notes:

- 1. 'Area coverage rate' (m²/s) is twice the product of the sonar range (m) and the maximum speed (m/s) at which the sensor can operate at that range.

-
2. *'Along track resolution' (cm), for SSS only, is the product of azimuth (horizontal) beamwidth (degrees) and maximum sonar range (m) and 0.873.*
 3. *'Across track resolution' (cm) is 75 divided by the signal bandwidth (kHz).*
- b. Systems or transmitting and receiving arrays, designed for object detection or location, having any of the following:
1. A transmitting frequency below 10 kHz;
 2. Sound pressure level exceeding 224 dB (reference 1 μ Pa at 1 m) for equipment with an operating frequency in the band from 10 kHz to 24 kHz inclusive;
 3. Sound pressure level exceeding 235 dB (reference 1 μ Pa at 1 m) for equipment with an operating frequency in the band between 24 kHz and 30 kHz;
 4. Forming beams of less than 1° on any axis and having an operating frequency of less than 100 kHz;
 5. Designed to operate with an unambiguous display range exceeding 5,120 m; or
 6. Designed to withstand pressure during normal operation at depths exceeding 1,000 m and having transducers with any of the following:
 - a. Dynamic compensation for pressure; or
 - b. Incorporating other than lead zirconate titanate as the transduction element;
- c. Acoustic projectors, including transducers, incorporating piezoelectric, magnetostrictive, electrostrictive, electrodynamic or hydraulic elements operating individually or in a designed combination and having any of the following:
-

Note 1: The control status of acoustic projectors, including transducers, specially designed for other equipment is determined by the control status of the other equipment.

Note 2: 6A001.a.1.c. does not apply to electronic sources which direct the sound vertically only, or mechanical (e.g. air gun or vapour-shock gun) or chemical (e.g. explosive) sources.

Note 3: Piezoelectric elements specified in 6.A.1.a.1.c. include those made from lead-magnesium-niobate/lead-titanate ($Pb(Mg_{1/3}Nb_{2/3})O_3$ - $PbTiO_3$, or PMN-PT) single crystals grown from solid solution or lead-indium-niobate/lead-magnesium niobate/lead-titanate ($Pb(In_{1/2}Nb_{1/2})O_3$ - $Pb(Mg_{1/3}Nb_{2/3})O_3$ - $PbTiO_3$, or PIN-PMN-PT) single crystals grown from solid solution.

1. An instantaneous radiated 'acoustic power density' exceeding $0.01 \text{ mW/mm}^2/\text{Hz}$ for devices operating at frequencies below 10 kHz;
2. A continuously radiated 'acoustic power density' exceeding $0.001 \text{ mW/mm}^2/\text{Hz}$ for devices operating at frequencies below 10 kHz; or

Technical Note:

'Acoustic power density' is obtained by dividing the output acoustic power by the product of the area of the radiating surface and the frequency of operation.

3. Side-lobe suppression exceeding 22 dB;
- d. Acoustic systems and equipment, designed to determine the position of surface vessels or underwater vehicles and having all the following, and specially designed components therefor:
1. Detection range exceeding 1,000 m; and
 2. Positioning accuracy of less than 10 m rms (root mean square) when measured at a range of 1,000 m;

Note: 6A001.a.1.d. includes:

- a. *Equipment using coherent "signal processing" between two or more beacons and the hydrophone unit carried by the surface vessel or underwater vehicle;*
- b. *Equipment capable of automatically correcting speed-of-sound propagation errors for calculation of a point.*

-
- e. Active individual sonars, specially designed or modified to detect, locate and automatically classify swimmers or divers, having all of the following, and specially designed transmitting and receiving acoustic arrays therefor:
1. Detection range exceeding 530 m;
 2. Positioning accuracy of less than 15 m rms (root mean square) when measured at a range of 530 m; and
 3. Transmitted pulse signal bandwidth exceeding 3 kHz;

N.B.: For diver detection systems specially designed or modified for military use, see the Military Goods Controls.

Note: For 6A001.a.1.e., where multiple detection ranges are specified for various environments, the greatest detection range is used.

2. Passive systems, equipment and specially designed components therefor, as follows:

- a. Hydrophones having any of the following:

Note: The control status of hydrophones specially designed for other equipment is determined by the control status of the other equipment.

Technical Note:

Hydrophones consist of one or more sensing elements producing a single acoustic output channel. Those that contain multiple elements can be referred to as a hydrophone group.

1. Incorporating continuous flexible sensing elements;
2. Incorporating flexible assemblies of discrete sensing elements with either a diameter or length less than 20 mm and with a separation between elements of less than 20 mm;
3. Having any of the following sensing elements:
 - a. Optical fibres;
 - b. 'Piezoelectric polymer films' other than polyvinylidene-fluoride (PVDF) and its co-polymers {P(VDF-TrFE) and P(VDF-TFE)}; or
 - c. 'Flexible piezoelectric composites';
 - d. Lead-magnesium-niobate/lead-titanate (i.e., $\text{Pb}(\text{Mg}_{1/3}\text{Nb}_{2/3})\text{O}_3$ - PbTiO_3 or PMN-PT) piezoelectric single crystals grown from solid solution; or

-
- e. Lead-indium-niobate/lead-magnesium niobate/lead-titanate (i.e., $\text{Pb}(\text{In}_{1/2}\text{Nb}_{1/2})\text{O}_3$ - $\text{Pb}(\text{Mg}_{1/3}\text{Nb}_{2/3})\text{O}_3$ - PbTiO_3 , or PIN-PMN-PT) piezoelectric single crystals grown from solid solution;
 - 4. A 'hydrophone sensitivity' better than -180 dB at any depth with no acceleration compensation;
 - 5. Designed to operate at depths exceeding 35 m with acceleration compensation; or
 - 6. Designed for operation at depths exceeding 1,000 m;
- Technical Notes:*
- 1. 'Piezoelectric polymer film' sensing elements consist of polarised polymer film that is stretched over and attached to a supporting frame or spool (mandrel).
 - 2. 'Flexible piezoelectric composite' sensing elements consist of piezoelectric ceramic particles or fibres combined with an electrically insulating, acoustically transparent rubber, polymer or epoxy compound, where the compound is an integral part of the sensing elements.
 - 3. 'Hydrophone sensitivity' is defined as twenty times the logarithm to the base 10 of the ratio of rms output voltage to a 1 V rms reference, when the hydrophone sensor, without a pre-amplifier, is placed in a plane wave acoustic field with an rms pressure of 1 μPa . For example, a hydrophone of -160 dB (reference 1 V per μPa) would yield an output voltage of 10^{-8} V in such a field, while one of -180 dB sensitivity would yield only 10^{-9} V output. Thus, -160 dB is better than -180 dB.
- b. Towed acoustic hydrophone arrays having any of the following:
- Technical Note*
- Hydrophone arrays consist of a number of hydrophones providing multiple acoustic output channels.*
- 1. Hydrophone group spacing of less than 12.5 m or 'able to be modified' to have hydrophone group spacing of less than 12.5 m;
-

-
2. Designed or 'able to be modified' to operate at depths exceeding 35 m;
Technical Note:
'Able to be modified' in 6A001.a.2.b.1. and 6A001.a.2.b.2. means having provisions to allow a change of the wiring or interconnections to alter hydrophone group spacing or operating depth limits. These provisions are: spare wiring exceeding 10% of the number of wires, hydrophone group spacing adjustment blocks or internal depth limiting devices that are adjustable or that control more than one hydrophone group.
 3. Heading sensors specified in 6A001.a.2.d.;
 4. Longitudinally reinforced array hoses;
 5. An assembled array of less than 40 mm in diameter; or
 6. Not used;
 7. Hydrophone characteristics specified in 6A001.a.2.a.;
 8. Accelerometer-based hydro-acoustic sensors specified by 6A001.a.2.g.;
- c. Processing equipment, specially designed for towed acoustic hydrophone arrays, having "user accessible programmability" and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;
- d. Heading sensors having all of the following:
1. An accuracy of better than $\pm 0.5^\circ$; and
 2. Designed to operate at depths exceeding 35 m or having an adjustable or removable depth sensing device in order to operate at depths exceeding 35 m;
- e. Bottom or bay cable systems, having any of the following:
1. Incorporating hydrophones specified in 6A001.a.2.a.; or
 2. Incorporating multiplexed hydrophone group signal modules having all of the following characteristics:
 - a. Designed to operate at depths exceeding 35 m or having an adjustable or removable depth sensing device in order to operate at depths exceeding 35 m; and
 - b. Capable of being operationally interchanged with towed acoustic hydrophone array modules;
 3. Incorporating accelerometer-based hydro-acoustic sensors specified by 6A001.a.2.g.;
-

-
- f. Processing equipment, specially designed for bottom or bay cable systems, having “user accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;

Note: 6A001.a.2. also controls receiving equipment, whether or not related in normal application to separate active equipment, and specially designed components therefor.

- g. Accelerometer-based hydro-acoustic sensors having all of the following:
1. Composed of three accelerometers arranged along three distinct axes;
 2. Having an overall ‘acceleration sensitivity’ better than 48 dB (reference 1,000 mV rms per 1g);
 3. Designed to operate at depths greater than 35 meters; and
 4. Operating frequency below 20 kHz.

Note: 6A001.a.2.g. does not apply to particle velocity sensors or geophones.

Note: 6A001.a.2. also applies to receiving equipment, whether or not related in normal application to separate active equipment, and specially designed components therefor.

Technical Notes:

1. Accelerometer-based hydro-acoustic sensors are also known as vector sensors.
2. ‘Acceleration sensitivity’ is defined as twenty times the logarithm to the base 10 of the ratio of rms output voltage to a 1 V rms reference, when the hydro-acoustic sensor, without a preamplifier, is placed in a plane wave acoustic field with an rms acceleration of 1 g (i.e., 9.81 m/s²).

- b. Correlation-velocity and doppler-velocity sonar log equipment, designed to measure the horizontal speed of the equipment carrier relative to the sea bed, as follows:
1. Correlation-velocity sonar log equipment having any of the following characteristics:
 - a. Designed to operate at distances between the carrier and the sea bed exceeding 500 m; or
 - b. Having speed accuracy better than 1% of speed;
 2. Doppler-velocity sonar log equipment having speed accuracy better than 1% of speed.

Note 1: 6A001.b. does not control depth sounders limited to any of the following:

- a. Measuring the depth of water;

- b. Measuring the distance of submerged or buried objects; or*
- c. Fish finding.*

Note 2: 6A001.b. does not control equipment specially designed for installation on surface vessels.

- c. Not used.*

6A002 Optical sensors or equipment and components therefor, as follows:

N.B.: SEE ALSO 6A102.

- a. Optical detectors as follows:

- 1. “Space-qualified” solid-state detectors as follows:

Note: For the purpose of 6A002.a.1., solid-state detectors include “focal plane arrays”.

- a. “Space-qualified” solid-state detectors having all of the following:
 - 1. A peak response in the wavelength range exceeding 10 nm but not exceeding 300 nm; and
 - 2. A response of less than 0.1% relative to the peak response at a wavelength exceeding 400 nm;
 - b. “Space-qualified” solid-state detectors having all of the following:
 - 1. A peak response in the wavelength range exceeding 900 nm but not exceeding 1,200 nm; and
 - 2. A response “time constant” of 95 ns or less;
 - c. “Space-qualified” solid-state detectors having a peak response in the wavelength range exceeding 1,200 nm but not exceeding 30,000 nm;
 - d. “Space-qualified” “focal plane arrays” having more than 2,048 elements per array and having a peak response in the wavelength range exceeding 300 nm but not exceeding 900 nm.

- 2. Image intensifier tubes and specially designed components therefor, as follows:

Note: 6A002.a.2. does not control non-imaging photomultiplier tubes having an electron sensing device in the vacuum space limited solely to any of the following:

- a. A single metal anode; or*
 - b. Metal anodes with a centre to centre spacing greater than 500 µm.*

Technical Note:

‘Charge multiplication’ is a form of electronic image amplification and is defined as the generation of charge carriers as a result of an impact ionisation gain process. ‘Charge multiplication’ sensors may take the form of an image intensifier tube, solid state detector or “focal plane array”.

- a. Image intensifier tubes having all of the following:
 - 1. A peak response in the wavelength range exceeding 400 nm but not exceeding 1,050 nm;
 - 2. Electron image amplification using any of the following:
 - a. A microchannel plate with a hole pitch (centre-to-centre spacing) of 12 µm or less; or
 - b. An electron sensing device with a non-binned pixel pitch of 500 µm or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate; and
 - 3. Any of the following photocathodes:
 - a. Multialkali photocathodes (e.g., S-20 and S-25) having a luminous sensitivity exceeding 350 µA/lm;
 - b. GaAs or GaInAs photocathodes; or
 - c. Other “III/V compound” semiconductor photocathodes having a maximum “radiant sensitivity” exceeding 10 mA/W;
- b. Image intensifier tubes having all of the following:
 - 1. A peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,800 nm;
 - 2. Electron image amplification using any of the following:
 - a. A microchannel plate with a hole pitch (centre-to-centre spacing) of 12 µm or less; or
 - b. An electron sensing device with a non-binned pixel pitch of 500 µm or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate; and
 - 3. “III/V compound” semiconductor (e.g., GaAs or GaInAs) photocathodes and transferred electron photocathodes, having a maximum “radiant sensitivity” exceeding 15 mA/W;
- c. Specially designed components as follows:
 - 1. Microchannel plates having a hole pitch (centre-to-centre spacing) of 12 µm or less;

-
2. An electron sensing device with a non-binned pixel pitch of 500 µm or less, specially designed or modified to achieve 'charge multiplication' other than by a microchannel plate;
 3. "III/V compound" semiconductor (e.g., GaAs or GaInAs) photocathodes and transferred electron photocathodes;

Note: 6A002.a.2.c.3. does not control compound semiconductor photocathodes designed to achieve a maximum "radiant sensitivity" of any of the following:

- a. 10 mA/W or less at the peak response in the wavelength range exceeding 400 nm but not exceeding 1,050 nm; or
- b. 15 mA/W or less at the peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,800 nm.

3. Non-"space-qualified" "focal plane arrays" as follows:

N.B.: 'Microbolometer' non-"space-qualified" "focal plane arrays" are only specified in 6A002.a.3.f.

Technical Note:

Linear or two-dimensional multi-element detector arrays are referred to as "focal plane arrays";

Note 1: 6A002.a.3. includes photoconductive arrays and photovoltaic arrays.

Note 2: 6A002.a.3. does not apply to:

- a. Multi-element (not to exceed 16 elements) encapsulated photoconductive cells using either lead sulphide or lead selenide;
- b. Pyroelectric detectors using any of the following:
 1. Triglycine sulphate and variants;
 2. Lead-lanthanum-zirconium titanate and variants;
 3. Lithium tantalate;
 4. Polyvinylidene fluoride and variants; or
 5. Strontium barium niobate and variants.
- c. "Focal plane arrays" specially designed or modified to achieve 'charge multiplication' and limited by design to have a maximum "radiant sensitivity" of 10 mA/W or less for wavelengths exceeding 760 nm, having all of the following:
 1. Incorporating a response limiting mechanism designed not to be removed or modified; and

-
2. Any of the following:
 - a. The response limiting mechanism is integral to or combined with the detector element; or
 - b. The “focal plane array” is only operable with the response limiting mechanism in place.

Technical Note:

A response limiting mechanism integral to the detector element is designed not to be removed or modified without rendering the detector inoperable.

Technical Note:

‘Charge multiplication’ is a form of electronic image amplification and is defined as the generation of charge carriers as a result of an impact ionisation gain process. ‘Charge multiplication’ sensors may take the form of an image intensifier tube, solid state detector or “focal plane array”.

- a. Non-“space-qualified” “focal plane arrays” having all of the following:
 1. Individual elements with a peak response within the wavelength range exceeding 900 nm but not exceeding 1,050 nm; and
 2. Any of the following:
 - a. A response “time constant” of less than 0.5 ns; or
 - b. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W;
- b. Non-“space-qualified” “focal plane arrays” having all of the following:
 1. Individual elements with a peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,200 nm; and
 2. Any of the following:
 - a. A response “time constant” of 95 ns or less; or
 - b. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W;
- c. Non-“space-qualified” non-linear (2-dimensional) “focal plane arrays” having individual elements with a peak response in the wavelength range exceeding 1,200 nm but not exceeding 30,000 nm;

N.B.: Silicon and other material based ‘microbolometer’ non-“space-qualified” “focal plane arrays” are only specified in 6A002.a.3.f.

-
- d. Non-“space-qualified” linear (1-dimensional) “focal plane arrays” having all of the following:
1. Individual elements with a peak response in the wavelength range exceeding 1,200 nm but not exceeding 3,000 nm; and
 2. Any of the following:
 - a. A ratio of ‘scan direction’ dimension of the detector element to the ‘cross-scan direction’ dimension of the detector element of less than 3.8; or
 - b. Signal processing in the detector elements;;

Note: 6A002.a.3.d. does not control “focal plane arrays” (not to exceed 32 elements) having detector elements limited solely to germanium material.

Technical Note:

For the purposes of 6A002.a.3.d., ‘cross-scan direction’ is defined as the axis parallel to the linear array of detector elements and the ‘scan direction’ is defined as the axis perpendicular to the linear array of detector elements.

- e. Non-“space-qualified” linear (1-dimensional) “focal plane arrays” having individual elements with a peak response in the wavelength range exceeding 3,000 nm but not exceeding 30,000 nm;
- f. Non-“space-qualified” non-linear (2-dimensional) infrared “focal plane arrays” based on ‘microbolometer’ material having individual elements with an unfiltered response in the wavelength range equal to or exceeding 8,000 nm but not exceeding 14,000 nm;

Technical Note:

For the purposes of 6A002.a.3.f., ‘microbolometer’ is defined as a thermal imaging detector that, as a result of a temperature change in the detector caused by the absorption of infrared radiation, is used to generate any usable signal.

- g. Non-“space-qualified” “focal plane arrays” having all of the following:
1. Individual detector elements with a peak response in the wavelength range exceeding 400 nm but not exceeding 900 nm;
 2. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W for wavelengths exceeding 760 nm; and
 3. Greater than 32 elements;

- b. “Monospectral imaging sensors” and “multispectral imaging sensors”, designed for remote sensing applications and having any of the following:
-

1. An Instantaneous-Field-Of-View (IFOV) of less than 200 μ rad (microradians); or
2. Specified for operation in the wavelength range exceeding 400 nm but not exceeding 30,000 nm and having all the following:
 - a. Providing output imaging data in digital format; and
 - b. Having any of the following characteristics:
 1. “Space-qualified”; or
 2. Designed for airborne operation, using other than silicon detectors, and having an IFOV of less than 2.5 mrad (milliradians);

Note: 6A002.b.1. does not control “monospectral imaging sensors” with a peak response in the wavelength range exceeding 300 nm but not exceeding 900 nm and only incorporating any of the following non-“space-qualified” detectors or non-“space-qualified” “focal plane arrays”:

- a. Charge Coupled Devices (CCD) not designed or modified to achieve ‘charge multiplication’; or
- b. Complementary Metal Oxide Semiconductor (CMOS) devices not designed or modified to achieve ‘charge multiplication’.

- c. ‘Direct view’ imaging equipment incorporating any of the following:
 1. Image intensifier tubes specified in 6A002.a.2.a. or 6A002.a.2.b.;
 2. “Focal plane arrays” specified in 6A002.a.3.; or
 3. Solid state detectors specified in 6A002.a.1.;

Technical Note:

‘Direct view’ refers to imaging equipment that presents a visual image to a human observer without converting the image into an electronic signal for television display, and that cannot record or store the image photographically, electronically or by any other means.

Note: 6A002.c. does not control equipment as follows, when incorporating other than GaAs or GaInAs photocathodes:

- a. Industrial or civilian intrusion alarm, traffic or industrial movement control or counting systems;
- b. Medical equipment;
- c. Industrial equipment used for inspection, sorting or analysis of the properties of materials;
- d. Flame detectors for industrial furnaces;
- e. Equipment specially designed for laboratory use.

- d. Special support components for optical sensors, as follows:
 1. “Space-qualified” cryocoolers;
 2. Non-“space-qualified” cryocoolers having a cooling source temperature below 218 K (-55°C), as follows:

	<ol style="list-style-type: none"> a. Closed cycle type with a specified Mean-Time-To-Failure (MTTF) or Mean-Time-Between-Failures (MTBF), exceeding 2,500 hours; b. Joule-Thomson (JT) self-regulating minicoolers having bore (outside) diameters of less than 8 mm;
	<ol style="list-style-type: none"> 3. Optical sensing fibres specially fabricated either compositionally or structurally, or modified by coating, to be acoustically, thermally, inertially, electromagnetically or nuclear radiation sensitive; <p><i>Note: 6A002.d.3. does not control encapsulated optical sensing fibres specially designed for bore hole sensing applications.</i></p>
	e. Not used.
6A003	Cameras, systems or equipment, and components therefor, as follows:
	<p>N.B.: FOR TELEVISION AND FILM-BASED PHOTOGRAPHIC STILL CAMERAS SPECIALLY DESIGNED OR MODIFIED FOR UNDERWATER USE, SEE 8A002.D.1. AND 8A002.E.</p>
	<ol style="list-style-type: none"> a. Instrumentation cameras and specially designed components therefor, as follows: <p><i>Note: Instrumentation cameras, specified in 6A003.a.3. to 6A003.a.5., with modular structures should be evaluated by their maximum capability, using plug-ins available according to the camera manufacturer's specifications.</i></p> <ol style="list-style-type: none"> 1. High-speed cinema recording cameras using any film format from 8 mm to 16 mm inclusive, in which the film is continuously advanced throughout the recording period, and that are capable of recording at framing rates exceeding 13,150 frames/s; <p><i>Note: 6A003.a.1. does not control cinema recording cameras designed for civil purposes.</i></p> <ol style="list-style-type: none"> 2. Mechanical high speed cameras, in which the film does not move, capable of recording at rates exceeding 1,000,000 frames/s for the full framing height of 35 mm film, or at proportionately higher rates for lesser frame heights, or at proportionately lower rates for greater frame heights; 3. Mechanical or electronic streak cameras, having writing speeds exceeding 10mm/μs; 4. Electronic framing cameras having a speed exceeding 1,000,000 frames/s; 5. Electronic cameras having all of the following: <ol style="list-style-type: none"> a. An electronic shutter speed (gating capability) of less than 1 μs per full frame; and b. A read out time allowing a framing rate of more than 125 full frames per second;

-
6. Plug-ins having all of the following characteristics:
- a. Specially designed for instrumentation cameras which have modular structures and which are specified in 6A003.a.; and
 - b. Enabling these cameras to meet the characteristics specified in 6A003.a.3., 6A003.a.4., or 6A003.a.5., according to the manufacturer's specifications;

- b. Imaging cameras as follows:

Note: 6A003.b. does not control television or video cameras, specially designed for television broadcasting.

1. Video cameras incorporating solid state sensors, having a peak response in the wavelength range exceeding 10 nm, but not exceeding 30,000 nm and having all of the following:
 - a. Having any of the following:
 1. More than 4×10^6 "active pixels" per solid state array for monochrome (black and white) cameras;
 2. More than 4×10^6 "active pixels" per solid state array for colour cameras incorporating three solid state arrays; or
 3. More than 12×10^6 "active pixels" for solid state array colour cameras incorporating one solid state array; and
 - b. Having any of the following:
 1. Optical mirrors specified in 6A004.a.;
 2. Optical control equipment specified in 6A004.d.; or
 3. The capability for annotating internally generated 'camera tracking data';

Technical Note:

1. *For the purpose of this entry, digital video cameras should be evaluated by the maximum number of "active pixels" used for capturing moving images.*
 2. *For the purpose of this entry, 'camera tracking data' is the information necessary to define camera line of sight orientation with respect to the earth. This includes: 1) the horizontal angle the camera line of sight makes with respect to the earth's magnetic field direction and; 2) the vertical angle between the camera line of sight and the earth's horizon.*
2. Scanning cameras and scanning camera systems, having all of the following:
 - a. A peak response in the wavelength range exceeding 10 nm, but not exceeding 30,000 nm;
 - b. Linear detector arrays with more than 8,192 elements per array; and
 - c. Mechanical scanning in one direction;

Note: 6A003.b.2. does not control scanning cameras, and scanning camera systems, specially designed for any of the following:

- a. Industrial or civilian photocopiers;
- b. Image scanners specially designed for civil, stationary, close proximity scanning applications (e.g. reproduction of images or print contained in documents, artwork or photographs); or
- c. Medical equipment.

3. Imaging cameras incorporating image intensifier tubes specified in 6A002.a.2.a. or 6A002.a.2.b.;
4. 'Imaging cameras' incorporating "focal plane arrays" having any of the following:
 - a. Incorporating "focal plane arrays" specified in 6A002.a.3.a. to 6A002.a.3.e.;
 - b. Incorporating "focal plane arrays" specified in 6A002.a.3.f.; or
 - c. Incorporating "focal plane arrays" specified in 6A002.a.3.g.;

Note 1: Imaging cameras specified in 6A003.b.4. include "focal plane arrays" combined with sufficient "signal processing" electronics, beyond the read out integrated circuit, to enable as a minimum the output of an analogue or digital signal once power is supplied.

Note 2: 6A003.b.4.a. does not control imaging cameras incorporating linear "focal plane arrays" with 12 elements or fewer, not employing time-delay-and-integration within the element and designed for any of the following:

- a. Industrial or civilian intrusion alarm, traffic or industrial movement control or counting systems;
- b. Industrial equipment used for inspection or monitoring of heat flows in buildings, equipment or industrial processes;
- c. Industrial equipment used for inspection, sorting or analysis of the properties of materials;
- d. Equipment specially designed for laboratory use; or
- e. Medical equipment.

Note 3: 6A003.b.4.b. does not control imaging cameras having any of the following:

- a. A maximum frame rate equal to or less than 9 Hz;
- b. Having all of the following:
 1. Having a minimum horizontal or vertical 'Instantaneous-Field-of-View (IFOV)' of at least 10 mrad/pixel (milliradians/pixel);
 2. Incorporating a fixed focal-length lens that is not designed to be removed;

-
3. Not incorporating a 'direct view' display; and
 4. Having any of the following:
 - a. No facility to obtain a viewable image of the detected field-of-view; or
 - b. The camera is designed for a single kind of application and designed not to be user modified; or
 - c. The camera is specially designed for installation into a civilian passenger land vehicle of less than 3 tonnes (gross vehicle weight) and having all of the following:
 1. Is only operable when installed in any of the following:
 - a. The civilian passenger land vehicle for which it was intended; or
 - b. A specially designed, authorised maintenance test facility; and
 2. Incorporates an active mechanism that forces the camera not to function when it is removed from the vehicle for which it was intended.

Technical Notes:

1. 'Instantaneous Field of View (IFOV)' specified in 6A003.b.4. Note 3.b. is the lesser figure of the 'Horizontal IFOV' or the 'Vertical IFOV'.
'Horizontal IFOV' = horizontal Field of View (FOV) / number of horizontal detector elements
'Vertical IFOV' = vertical Field of View (FOV) / number of vertical detector elements.
2. 'Direct view' in 6A003.b.4. Note 3.b. refers to an imaging camera operating in the infrared spectrum that presents a visual image to a human observer using a near-to-eye micro display incorporating any light-security mechanism.

Note: When necessary, details of the item will be provided, upon request, to the appropriate authority in the exporter's country in order to ascertain compliance with the conditions described in Note 3.b.4. and Note 3.c. above.

Note 4: 6A003.b.4.c. does not control imaging cameras having any of the following:

-
- a. *Having all of the following:*
 - 1. *Where the camera is specially designed for installation as an integrated component into indoor and wall-plug-operated systems or equipment, limited by design for a single kind of application, as follows:*
 - a. *Industrial process monitoring, quality control, or analysis of the properties of materials;*
 - b. *Laboratory equipment specially designed for scientific research;*
 - c. *Medical equipment;*
 - d. *Financial fraud detection equipment; and*
 - 2. *Is only operable when installed in any of the following:*
 - a. *The system(s) or equipment for which it was intended; or*
 - b. *A specially designed, authorised maintenance facility; and*
 - 3. *Incorporates an active mechanism that forces the camera not to function when it is removed from the system(s) or equipment for which it was intended;*
 - b. *Where the camera is specially designed for installation into a civilian passenger land vehicle of less than three tonnes (gross vehicle weight), or passenger and vehicle ferries having a length overall (LOA) 65 m or greater, and having all of the following:*
 - 1. *Is only operable when installed in any of the following:*
 - a. *The civilian passenger land vehicle or passenger and vehicle ferry for which it was intended; or*
 - b. *A specially designed, authorised maintenance test facility; and*
 - 2. *Incorporates an active mechanism that forces the camera not to function when it is removed from the vehicle for which it was intended;*
 - c. *Limited by design to have a maximum “radiant sensitivity” of 10 mW/W or less for wavelengths exceeding 760 nm, having all of the following:*
 - 1. *Incorporating a response limiting mechanism designed not to be removed or modified;*
 - 2. *Incorporates an active mechanism that forces the camera not to function when the response limiting mechanism is removed; and*
-

3. *Not specially designed or modified for underwater use; or*
- d. *Having all of the following:*
 1. *Not incorporating a 'direct view' or electronic image display;*
 2. *Has no facility to output a viewable image of the detected field of view;*
 3. *The "focal plane array" is only operable when installed in the camera for which it was intended; and*
 4. *The "focal plane array" incorporates an active mechanism that forces it to be permanently inoperable when removed from the camera for which it was intended.*

Note: When necessary, details of the item will be provided, upon request, to the appropriate authority in the exporter's country in order to ascertain compliance with the conditions described in Note 4 above.

5. Imaging cameras incorporating solid-state detectors specified in 6A002.a.1.

6A004 Optical equipment and components, as follows:

a. Optical mirrors (reflectors) as follows:

N.B.: For optical mirrors specially designed for lithography equipment, see 3B001.

1. "Deformable mirrors" having either continuous or multi-element surfaces, and specially designed components therefor, capable of dynamically repositioning portions of the surface of the mirror at rates exceeding 100 Hz;
2. Lightweight monolithic mirrors having an average "equivalent density" of less than 30 kg/m^2 and a total mass exceeding 10 kg;
3. Lightweight "composite" or foam mirror structures having an average "equivalent density" of less than 30 kg/m^2 and a total mass exceeding 2 kg;
4. Beam steering mirrors more than 100 mm in diameter or length of major axis, which maintain a flatness of $\lambda/2$ or better (λ is equal to 633 nm) having a control bandwidth exceeding 100 Hz;

b. Optical components made from zinc selenide (ZnSe) or zinc sulphide (ZnS) with transmission in the wavelength range exceeding 3,000 nm but not exceeding 25,000 nm and having any of the following:

1. Exceeding 100 cm^3 in volume; or
2. Exceeding 80 mm in diameter or length of major axis and 20 mm in thickness (depth);

-
- c. “Space-qualified” components for optical systems, as follows:
1. Components lightweighted to less than 20% “equivalent density” compared with a solid blank of the same aperture and thickness;
 2. Raw substrates, processed substrates having surface coatings (single-layer or multi-layer, metallic or dielectric, conducting, semiconducting or insulating) or having protective films;
 3. Segments or assemblies of mirrors designed to be assembled in space into an optical system with a collecting aperture equivalent to or larger than a single optic 1 m in diameter;
 4. Components manufactured from “composite” materials having a coefficient of linear thermal expansion equal to or less than 5×10^{-6} in any coordinate direction;
- d. Optical control equipment as follows:
1. Equipment specially designed to maintain the surface figure or orientation of the “space-qualified” components specified in 6A004.c.1. or 6A004.c.3.;
 2. Equipment having steering, tracking, stabilisation or resonator alignment bandwidths equal to or more than 100 Hz and an accuracy of 10 μ rad (microradians) or less;
 3. Gimbals having all of the following:
 - a. A maximum slew exceeding 5°;
 - b. A bandwidth of 100 Hz or more;
 - c. Angular pointing errors of 200 μ rad (microradians) or less; and
 - d. Having any of the following:
 1. Exceeding 0.15 m but not exceeding 1 m in diameter or major axis length and capable of angular accelerations exceeding 2 rad (radians)/s²; or
 2. Exceeding 1 m in diameter or major axis length and capable of angular accelerations exceeding 0.5 rad (radians)/s²;
 4. Specially designed to maintain the alignment of phased array or phased segment mirror systems consisting of mirrors with a segment diameter or major axis length of 1 m or more;
- e. ‘Aspheric optical elements’ having all of the following:
1. Largest dimension of the optical-aperture greater than 400 mm;
 2. Surface roughness less than 1 nm (rms) for sampling lengths equal to or greater than 1 mm; and
 3. Coefficient of linear thermal expansion’s absolute magnitude less than 3×10^{-6} /K at 25°C.

Technical Notes:

1. *An ‘aspheric optical element’ is any element used in an optical system whose imaging surface or surfaces are designed to depart from the shape of an ideal sphere.*
-

2. *Manufacturers are not required to measure the surface roughness listed in 6A004.e.2. unless the optical element was designed or manufactured with the intent to meet, or exceed, the control parameter.*

Note: 6A004.e. does not apply to 'aspheric optical elements' having any of the following:

- a.* Largest optical-aperture dimension less than 1 m and focal length to aperture ratio equal to or greater than 4.5:1;
- b.* Largest optical-aperture dimension equal to or greater than 1 m and focal length to aperture ratio equal to or greater than 7:1;
- c.* Designed as Fresnel, flyeye, stripe, prism or diffractive optical elements;
- d.* Fabricated from borosilicate glass having a coefficient of linear thermal expansion greater than 2.5×10^{-6} /K at 25°C; or
- e.* An x-ray optical element having inner mirror capabilities (e.g., tube-type mirrors).

N.B.: For 'aspheric optical elements' specially designed for lithography equipment, see 3B001.

6A005 "Lasers", other than those specified in 0B001.g.5. or 0B001.h.6., components and optical equipment, as follows:

N.B.: SEE ALSO 6A205.

Note 1: Pulsed "lasers" include those that run in a continuous wave (CW) mode with pulses superimposed.

Note 2: Excimer, semiconductor, chemical, CO, CO₂, and 'non-repetitive pulsed' Nd:glass "lasers" are only specified in 6A005.d.

Technical Note:

'Non-repetitive pulsed' refers to "lasers" that produce either a single output pulse or that have a time interval between pulses exceeding one minute.

Note 3: 6A005 includes fibre "lasers".

Note 4: The control status of "lasers" incorporating frequency conversion (i.e., wavelength change) by means other than one "laser" pumping another "laser" is determined by applying the control parameters for both the output of the source "laser" and the frequency-converted optical output.

Note 5: 6A005 does not control "lasers" as follows:

- a.* Ruby with output energy below 20 J;
- b.* Nitrogen;
- c.* Krypton.

-
- a. Non-“tunable” continuous wave “(CW) lasers” having any of the following:
1. Output wavelength less than 150 nm and output power exceeding 1 W;
 2. Output wavelength of 150 nm or more but not exceeding 510 nm and output power exceeding 30 W;
Note: 6A005.a.2. does not control Argon “lasers” having an output power equal to or less than 50 W.
 3. Output wavelength exceeding 510 nm but not exceeding 540 nm and any of the following:
 - a. Single transverse mode output and output power exceeding 50 W; or
 - b. Multiple transverse mode output and output power exceeding 150 W;
 4. Output wavelength exceeding 540 nm but not exceeding 800 nm and output power exceeding 30 W;
 5. Output wavelength exceeding 800 nm but not exceeding 975 nm and any of the following:
 - a. Single transverse mode output and output power exceeding 50 W; or
 - b. Multiple transverse mode output and output power exceeding 80 W;
 6. Output wavelength exceeding 975 nm but not exceeding 1,150 nm and any of the following:
 - a. Single transverse mode output and output power exceeding 200 W; or
 - b. Multiple transverse mode output and any of the following:
 1. ‘Wall-plug efficiency’ exceeding 18% and output power exceeding 500 W; or
 2. Output power exceeding 2 kW;
Note 1: 6A005.a.6.b. does not control multiple transverse mode, industrial “lasers” with output power exceeding 2 kW and not exceeding 6 kW with a total mass greater than 1,200 kg. For the purpose of this note, total mass includes all components required to operate the “laser”, e.g., “laser”, power supply, heat exchanger, but excludes external optics for beam conditioning and/or delivery.

Note 2: 6A005.a.6.b. does not apply to multiple transverse mode, industrial “lasers” having any of the following:
 - a. Output power exceeding 500 W but not exceeding 1 kW and having all of the following:
-

-
1. Beam Parameter Product (BPP) exceeding $0.7 \text{ mm} \cdot \text{mrad}$; and
 2. 'Brightness' not exceeding $1024 \text{ W}/(\text{mm} \cdot \text{mrad})^2$;
- b. Output power exceeding 1 kW but not exceeding 1.6 kW and having a BPP exceeding $1.25 \text{ mm} \cdot \text{mrad}$;
 - c. Output power exceeding 1.6 kW but not exceeding 2.5 kW and having a BPP exceeding $1.7 \text{ mm} \cdot \text{mrad}$;
 - d. Output power exceeding 2.5 kW but not exceeding 3.3 kW and having a BPP exceeding $2.5 \text{ mm} \cdot \text{mrad}$;
 - e. Output power exceeding 3.3 kW but not exceeding 4 kW and having a BPP exceeding $3.5 \text{ mm} \cdot \text{mrad}$;
 - f. Output power exceeding 4 kW but not exceeding 5 kW and having a BPP exceeding $5 \text{ mm} \cdot \text{mrad}$;
 - g. Output power exceeding 5 kW but not exceeding 6 kW and having a BPP exceeding $7.2 \text{ mm} \cdot \text{mrad}$;
 - h. Output power exceeding 6 kW but not exceeding 8 kW and having a BPP exceeding $12 \text{ mm} \cdot \text{mrad}$; or
 - i. Output power exceeding 8 kW but not exceeding 10 kW and having a BPP exceeding $24 \text{ mm} \cdot \text{mrad}$;

Technical Note:

For the purpose of 6A005.a.6.b., Note 2.a., 'brightness' is defined as the output power of the "laser" divided by the squared Beam Parameter Product (BPP), i.e., $(\text{output power})/\text{BPP}^2$.

Technical Note:

In 6A005 'Wall-plug efficiency' is defined as the ratio of "laser" output power (or "average output power") to total electrical input power required to operate the "laser", including the power supply/conditioning and thermal conditioning/heat exchanger.

7. Output wavelength exceeding 1,150 nm but not exceeding 1,555 nm and of the following:
 - a. Single transverse mode and output power exceeding 50 W; or
 - b. Multiple transverse mode and output power exceeding 80 W; or
-

-
- 8. Output wavelength exceeding 1,555 nm and output power exceeding 1 W;
 - b. Non-“tunable” “pulsed lasers” having any of the following:
 - 1. Output wavelength less than 150 nm and any of the following:
 - a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; or
 - b. “Average output power” exceeding 1 W;
 - 2. Output wavelength of 150 nm or more but not exceeding 510 nm and any of the following:
 - a. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 30 W; or
 - b. “Average output power” exceeding 30 W;

Note: 6A005.b.2.b. does not control Argon “lasers” having an “average output power” equal to or less than 50 W.

 - 3. Output wavelength exceeding 510 nm but not exceeding 540 nm and any of the following:
 - a. Single transverse mode output and any of the following:
 - 1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 50 W; or
 - 2. “Average output power” exceeding 50 W; or
 - b. Multiple transverse mode output and any of the following:
 - 1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 150 W; or
 - 2. “Average output power” exceeding 150 W;
 - 4. Output wavelength exceeding 540 nm but not exceeding 800 nm and any of the following:
 - a. “Pulse duration” less than 1 ps and any of the following:
 - 1. Output energy exceeding 0.005 J per pulse and “peak power” exceeding 5 GW; or
 - 2. “Average output power” exceeding 20 W; or
 - b. “Pulse duration” equal to or exceeding 1 ps and any of the following:
 - 1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 30 W; or
 - 2. “Average output power” exceeding 30 W;
 - 5. Output wavelength exceeding 800 nm but not exceeding 975 nm and any of the following:
 - a. “Pulse duration” less than 1 ps and any of the following:
 - 1. Output energy exceeding 0.005 J per pulse and “peak power” exceeding 5 GW; or
 - 2. Single transverse mode output and “average output power” exceeding 20 W;
-

-
- b. “Pulse duration” equal to or exceeding 1 ps and not exceeding 1 µs and any of the following:
 - 1. Output energy exceeding 0.5 J per pulse and “peak power” exceeding 50 W;
 - 2. Single transverse mode output and “average output power” exceeding 20 W; or
 - 3. Multiple transverse mode output and “average output power” exceeding 50 W; or
 - c. “Pulse duration” exceeding 1 µs and any of the following:
 - 1. Output energy exceeding 2 J per pulse and “peak power” exceeding 50 W;
 - 2. Single transverse mode output and “average output power” exceeding 50 W; or
 - 3. Multiple transverse mode output and “average output power” exceeding 80 W;
6. Output wavelength exceeding 975 nm but not exceeding 1,150 nm and any of the following:
- a. “Pulse duration” of less than 1 ps and any of the following:
 - 1. Output “peak power” exceeding 2 GW per pulse;
 - 2. “Average output power” exceeding 10 W; or
 - 3. Output energy exceeding 0.002 J per pulse;
 - b. “Pulse duration” equal to or exceeding 1 ps and less than 1 ns, and any of the following:
 - 1. Output “peak power” exceeding 5 GW per pulse;
 - 2. “Average output power” exceeding 10 W; or
 - 3. Output energy exceeding 0.1 J per pulse;
 - c. “Pulse duration” equal to or exceeding 1 ns but not exceeding 1 µs, and any of the following:
 - 1. Single transverse mode output and any of the following:
 - a. “Peak power” exceeding 100 MW;
 - b. “Average output power” exceeding 20 W limited by design to a maximum pulse repetition frequency less than or equal to 1 kHz;
 - c. ‘Wall-plug efficiency’ exceeding 12%, “average output power” exceeding 100 W and capable of operating at a pulse repetition frequency greater than 1 kHz;
 - d. “Average output power” exceeding 150 W and capable of operating at a pulse repetition frequency greater than 1 kHz; or
 - e. Output energy exceeding 2 J per pulse; or
-

-
2. Multiple transverse mode output and any of the following:
 - a. “Peak power” exceeding 400 MW;
 - b. ‘Wall-plug efficiency’ exceeding 18% and “average output power” exceeding 500 W;
 - c. “Average output power” exceeding 2 kW; or
 - d. Output energy exceeding 4 J per pulse; or
 - d. “Pulse duration” exceeding 1 μ s and any of the following:
 1. Single transverse mode output and any of the following:
 - a. “Peak power” exceeding 500 kW;
 - b. ‘Wall-plug efficiency’ exceeding 12% and “average output power” exceeding 100 W; or
 - c. “Average output power” exceeding 150 W; or
 2. Multiple transverse mode output and any of the following:
 - a. “Peak power” exceeding 1 MW;
 - b. ‘Wall-plug efficiency’ exceeding 18% and “average output power” exceeding 500 W; or
 - c. “Average output power” exceeding 2 kW;
7. Output wavelength exceeding 1,150 nm but not exceeding 1,555 nm, and any of the following:
 - a. “Pulse duration” not exceeding 1 μ s and any of the following:
 1. Output energy exceeding 0.5 J per pulse and “peak power” exceeding 50 W;
 2. Single transverse mode output and “average output power” exceeding 20 W; or
 3. Multiple transverse mode output and “average output power” exceeding 50 W; or
 - b. “Pulse duration” exceeding 1 μ s and any of the following:
 1. Output energy exceeding 2 J per pulse and “peak power” exceeding 50 W;
 2. Single transverse mode output and “average output power” exceeding 50 W; or
 3. Multiple transverse mode output and “average output power” exceeding 80 W; or
8. Output wavelength exceeding 1,555 nm and any of the following:
 - a. Output energy exceeding 100 mJ per pulse and “peak power” exceeding 1 W; or
 - b. “Average output power” exceeding 1 W;
-

-
- c. “Tunable” “lasers” having any of the following:
- Note:* 6A005.c. includes titanium–sapphire (Ti: Al₂O₃), thulium-YAG (Tm: YAG), thulium-YSGG (Tm: YSGG), alexandrite (Cr: BeAl₂O₄), colour centre “lasers”, dye “lasers”, and liquid “lasers”.
1. Output wavelength less than 600 nm and any of the following:
 - a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; or
 - b. Average or CW output power exceeding 1 W;

Note: 6A005.c.1. does not control dye lasers or other liquid lasers, having a multimode output and a wavelength of 150 nm or more but not exceeding 600 nm and all of the following:

 1. Output energy less than 1.5 J per pulse or a “peak power” less than 20 W; and
 2. Average or CW output power less than 20 W.
 2. Output wavelength of 600 nm or more but not exceeding 1,400 nm, and any of the following:
 - a. Output energy exceeding 1 J per pulse and “peak power” exceeding 20 W; or
 - b. Average or CW output power exceeding 20 W; or
 3. Output wavelength exceeding 1,400 nm and any of the following:
 - a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; or
 - b. Average or CW output power exceeding 1 W;
- d. Other “lasers”, not specified in 6A005.a., 6A005.b. or 6A005.c. as follows:
1. Semiconductor “lasers” as follows:

Note 1: 6A005.d.1. includes semiconductor “lasers” having optical output connectors (e.g. fibre optic pigtails).

Note 2: The control status of semiconductor “lasers” specially designed for other equipment is determined by the control status of the other equipment.

 - a. Individual single-transverse mode semiconductor “lasers” having any of the following:
 1. Wavelength equal to or less than 1,510 nm and average or CW output power exceeding 1.5 W; or
 2. Wavelength greater than 1,510 nm and average or CW output power exceeding 500 mW;
 - b. Individual, multiple-transverse mode semiconductor “lasers” having any of the following:
 1. Wavelength of less than 1,400 nm and average or CW output power exceeding 15 W;
-

-
- 2. Wavelength equal to or greater than 1,400 nm and less than 1,900 nm and average or CW output power exceeding 2.5 W; or
 - 3. Wavelength equal to or greater than 1,900 nm and average or CW output power exceeding 1 W;
 - c. Individual semiconductor “laser” ‘bars’, having any of the following:
 - 1. Wavelength of less than 1,400 nm and average or CW output power exceeding 100 W;
 - 2. Wavelength equal to or greater than 1,400 nm and less than 1,900 nm and average or CW output power exceeding 25 W; or
 - 3. Wavelength equal to or greater than 1,900 nm and average or CW output power exceeding 10 W;
 - d. Semiconductor “laser” ‘stacked arrays’ (two-dimensional arrays) having any of the following:
 - 1. Wavelength less than 1,400 nm and having any of the following:
 - a. Average or CW total output power less than 3 kW and having average or CW output ‘power density’ greater than 500 W/cm²;
 - b. Average or CW total output power equal to or exceeding 3 kW but less than or equal to 5 kW, and having average or CW output ‘power density’ greater than 350 W/cm²;
 - c. Average or CW total output power exceeding 5 kW;
 - d. Peak pulsed ‘power density’ exceeding 2,500 W/cm²; or
 - e. Spatially coherent average or CW total output power, greater than 150 W;
 - 2. Wavelength greater than or equal to 1,400 nm but less than 1,900 nm, and having any of the following:
 - a. Average or CW total output power less than 250 W and average or CW output ‘power density’ greater than 150 W/cm²;
 - b. Average or CW total output power equal to or exceeding 250 W but less than or equal to 500 W, and having average or CW output ‘power density’ greater than 50 W/cm²;
 - c. Average or CW total output power exceeding 500 W;
 - d. Peak pulsed ‘power density’ exceeding 500 W/cm²; or
-

-
- e. Spatially coherent average or CW total output power exceeding 15 W;
 - 3. Wavelength greater than or equal to 1,900 nm and having any of the following:
 - a. Average or CW output 'power density' greater than 50 W/cm²;
 - b. Average or CW output power greater than 10 W; or
 - c. Spatially coherent average or CW total output power exceeding 1.5 W; or
 - 4. At least one "laser" 'bar' specified in 6A005.d.1.c.;

Technical Note:

For the purposes of 6A005.d.1.d., 'power density' means the total "laser" output power divided by the emitter surface area of the 'stacked array'.

- e. Semiconductor "laser" 'stacked arrays', other than those specified in 6A005.d.1.d., having all of the following:
 - 1. Specially designed or modified to be combined with other 'stacked arrays' to form a larger 'stacked array'; and
 - 2. Integrated connections, common for both electronics and cooling;

Note 1: 'Stacked arrays', formed by combining semiconductor "laser" 'stacked arrays' specified by 6A005.d.1.e., that are not designed to be further combined or modified are specified by 6A005.d.1.d.

Note 2: 'Stacked arrays', formed by combining semiconductor "laser" 'stacked arrays' specified by 6A005.d.1.e., that are designed to be further combined or modified are specified by 6A005.d.1.e.

Note 3: 6A005.d.1.e. does not apply to modular assemblies of single 'bars' designed to be fabricated into end-to-end stacked linear arrays.

Technical Notes:

- 1. Semiconductor "lasers" are commonly called "laser" diodes.
 - 2. A 'bar' (also called a semiconductor "laser" 'bar', a "laser" diode 'bar' or diode 'bar') consists of multiple semiconductor "lasers" in a one-dimensional array.
 - 3. A 'stacked array' consists of multiple 'bars' forming a two-dimensional array of semiconductor "lasers".
 - 2. Carbon monoxide (CO) "lasers" having any of the following:
 - a. Output energy exceeding 2 J per pulse and "peak power" exceeding 5 kW; or
 - b. Average or CW output power exceeding 5 kW;
-

-
3. Carbon dioxide (CO₂) “lasers” having any of the following:
 - a. CW output power exceeding 15 kW;
 - b. Pulsed output with a “pulse duration” exceeding 10 µs and any of the following:
 1. “Average output power” exceeding 10 kW; or
 2. “Peak power” exceeding 100 kW; or
 - c. Pulsed output with a “pulse duration” equal to or less than 10 µs and any of the following:
 1. Pulse energy exceeding 5 J per pulse; or
 2. “Average output power” exceeding 2.5 kW;
 4. Excimer “lasers” having any of the following:
 - a. Output wavelength not exceeding 150 nm and any of the following:
 1. Output energy exceeding 50 mJ per pulse; or
 2. “Average output power” exceeding 1 W;
 - b. Output wavelength exceeding 150 nm but not exceeding 190 nm and any of the following:
 1. Output energy exceeding 1.5 J per pulse; or
 2. “Average output power” exceeding 120 W;
 - c. Output wavelength exceeding 190 nm but not exceeding 360 nm and any of the following:
 1. Output energy exceeding 10 J per pulse; or
 2. “Average output power” exceeding 500 W; or
 - d. Output wavelength exceeding 360 nm and any of the following:
 1. Output energy exceeding 1.5 J per pulse; or
 2. “Average output power” exceeding 30 W;

N.B.: For excimer “lasers” specially designed for lithography equipment, see 3B001.
 5. “Chemical lasers” as follows:
 - a. Hydrogen Fluoride (HF) “lasers”;
 - b. Deuterium Fluoride (DF) “lasers”;
 - c. “Transfer lasers” as follows:
 1. Oxygen Iodine (O₂I) “lasers”;
 2. Deuterium Fluoride-Carbon dioxide (DF-CO₂) “lasers”;
 6. ‘Non-repetitive pulsed’ Nd: glass “lasers” having any of the following:
 - a. “Pulse duration” not exceeding 1 µs and output energy exceeding 50 J per pulse; or
 - b. “Pulse duration” exceeding 1 µs and output energy exceeding 100 J per pulse;
 - e. Components as follows:
 1. Mirrors cooled either by ‘active cooling’ or by heat pipe cooling;
Technical Note:
‘Active cooling’ is a cooling technique for optical components using flowing fluids within the subsurface (nominally less than 1 mm below the optical surface) of the optical component to remove heat from the optic.
-

	<ol style="list-style-type: none"> 2. Optical mirrors or transmissive or partially transmissive optical or electro-optical components, specially designed for use with specified “lasers”;
	<p>f. Optical equipment as follows:</p> <p><i>N.B.: For shared aperture optical elements, capable of operating in “Super-High Power Laser” (“SHPL”) applications, see the Military Goods Lists.</i></p> <ol style="list-style-type: none"> 1. Dynamic wavefront (phase) measuring equipment capable of mapping at least 50 positions on a beam wavefront and any of the following: <ol style="list-style-type: none"> a. Frame rates equal to or more than 100 Hz and phase discrimination of at least 5% of the beam’s wavelength; or b. Frame rates equal to or more than 1,000 Hz and phase discrimination of at least 20% of the beam’s wavelength; 2. “Laser” diagnostic equipment capable of measuring “SHPL” system angular beam steering errors of equal to or less than 10 µrad; 3. Optical equipment and components, specially designed for a phased-array “SHPL” system for coherent beam combination to an accuracy of $\lambda/10$ at the designed wavelength, or 0.1 µm, whichever is the smaller; 4. Projection telescopes specially designed for use with “SHPL” systems.
	<p>g. ‘Laser acoustic detection equipment’ having all of the following:</p> <ol style="list-style-type: none"> 1. CW laser output power equal to or exceeding 20 mW; 2. Laser frequency stability equal to or better (less) than 10 MHz; 3. Laser wavelengths equal to or exceeding 1,000 nm but not exceeding 2,000 nm; 4. Optical system resolution better (less) than 1 nm; and 5. Optical Signal to Noise ratio equal to or exceeding 10^3. <p><i>Technical Note:</i></p> <p><i>‘Laser acoustic detection equipment’ is sometimes referred to as a Laser Microphone or Particle Flow Detection Microphone.</i></p>
6A006	<p>“Magnetometers”, “magnetic gradiometers”, “intrinsic magnetic gradiometers”, underwater electric field sensors, “compensation systems”, and specially designed components therefor, as follows:</p> <p><i>Note: 6A006 does not control instruments specially designed for fishery applications or biomagnetic measurements for medical diagnostics.</i></p>

-
- a. “Magnetometers” and subsystems as follows:
 - 1. “Magnetometers” using “superconductive” (SQUID) “technology” and having any of the following:
 - a. SQUID systems designed for stationary operation, without specially designed subsystems designed to reduce in-motion noise, and having a ‘sensitivity’ equal to or lower (better) than 50 fT (rms) per square root Hz at a frequency of 1 Hz; or
 - b. SQUID systems having an in-motion-magnetometer ‘sensitivity’ lower (better) than 20 pT (rms) per square root Hz at a frequency of 1 Hz and specially designed to reduce in-motion noise;
 - 2. “Magnetometers” using optically pumped or nuclear precession (proton/Overhauser) “technology” having a ‘sensitivity’ lower (better) than 20 pT (rms) per square root Hz at a frequency of 1 Hz;
 - 3. “Magnetometers” using fluxgate “technology” having a ‘sensitivity’ equal to or lower (better) than 10 pT (rms) per square root Hz at a frequency of 1 Hz;
 - 4. Induction coil “magnetometers” having a ‘sensitivity’ lower (better) than any of the following:
 - a. 0.05 nT (rms) per square root Hz at frequencies of less than 1 Hz;
 - b. 1×10^{-3} nT (rms) per square root Hz at frequencies of 1 Hz or more but not exceeding 10 Hz; or
 - c. 1×10^{-4} nT (rms) per square root Hz at frequencies exceeding 10 Hz;
 - 5. Fibre optic “magnetometers” having a ‘sensitivity’ lower (better) than 1 nT (rms) per square root Hz;
 - b. Underwater electric field sensors having a ‘sensitivity’ lower (better) than 8 nanovolt per metre per square root Hz when measured at 1 Hz;
 - c. “Magnetic gradiometers” as follows:
 - 1. “Magnetic gradiometers” using multiple “magnetometers” specified in 6A006.a.;
 - 2. Fibre optic “intrinsic magnetic gradiometers” having a magnetic gradient field ‘sensitivity’ lower (better) than 0.3 nT/m rms per square root Hz;
 - 3. “Intrinsic magnetic gradiometers”, using “technology” other than fibre-optic “technology”, having a magnetic gradient field ‘sensitivity’ lower (better) than 0.015 nT/m rms per square root Hz;
 - d. “Compensation systems” for magnetic or underwater electric field sensors resulting in a performance equal to or better than the specified parameters of 6A006.a., 6A006.b. or 6A006.c.
 - e. Underwater electromagnetic receivers incorporating magnetic field sensors specified by 6A006.a. or underwater electric field sensors specified by 6A006.b.
-

Technical Note:

For the purposes of 6A006., 'sensitivity' (noise level) is the root mean square of the device-limited noise floor which is the lowest signal that can be measured.

6A007 Gravity meters (gravimeters) and gravity gradiometers, as follows:

N.B.: SEE ALSO 6A107.

- a. Gravity meters designed or modified for ground use and having a static accuracy of less (better) than 10 µGal;

Note: 6A007.a. does not control ground gravity meters of the quartz element (Worden) type.

- b. Gravity meters designed for mobile platforms and having all of the following:

1. A static accuracy of less (better) than 0.7 mGal; and
2. An in-service (operational) accuracy of less (better) than 0.7 mGal having a 'time-to-steady-state registration' of less than 2 minutes under any combination of attendant corrective compensations and motional influences;

Technical Note:

For the purposes of 6A007.b., 'time-to-steady-state registration' (also referred to as the gravimeter's response time) is the time over which the disturbing effects of platform induced accelerations (high frequency noise) are reduced.

- c. Gravity gradiometers.

6A008 Radar systems, equipment and assemblies, having any of the following, and specially designed components therefor:

N.B.: SEE ALSO 6A108.

Note: 6A008 does not control:

- a. Secondary surveillance radar (SSR);
- b. Civil Automotive Radar;
- c. Displays or monitors used for air traffic control (ATC);
- d. Meteorological (weather) radar;
- e. Precision approach radar (PAR) equipment conforming to ICAO standards and employing electronically steerable linear (1-dimensional) arrays or mechanically positioned passive antennae.

- a. Operating at frequencies from 40 GHz to 230 GHz and having any of the following:

1. An average output power exceeding 100 mW; or
2. Locating accuracy of 1 m or less (better) in range and 0.2 degree or less (better) in azimuth;

-
- b. A tunable bandwidth exceeding $\pm 6.25\%$ of the ‘centre operating frequency’;
Technical Note:
The ‘centre operating frequency’ equals one half of the sum of the highest plus the lowest specified operating frequencies.
 - c. Capable of operating simultaneously on more than two carrier frequencies;
 - d. Capable of operating in synthetic aperture (SAR), inverse synthetic aperture (ISAR) radar mode, or sidelooking airborne (SLAR) radar mode;
 - e. Incorporating “electronically steerable phased array antennae”;
 - f. Capable of heightfinding non-cooperative targets;
 - g. Specially designed for airborne (balloon or airframe mounted) operation and having Doppler “signal processing” for the detection of moving targets;
 - h. Employing processing of radar signals and using any of the following:
 - 1. “Radar spread spectrum” techniques; or
 - 2. “Radar frequency agility” techniques;
 - i. Providing ground-based operation with a maximum “instrumented range” exceeding 185 km;
Note: 6A008.i. does not control:
 - a. Fishing ground surveillance radar;
 - b. Ground radar equipment specially designed for enroute air traffic control and having all the following:
 - 1. A maximum “instrumented range” of 500 km or less;
 - 2. Configured so that radar target data can be transmitted only one way from the radar site to one or more civil ATC centres;
 - 3. Contains no provisions for remote control of the radar scan rate from the enroute ATC centre; and
 - 4. Permanently installed;
 - c. Weather balloon tracking radars.
 - j. Being “laser” radar or Light Detection and Ranging (LIDAR) equipment and having any of the following:
 - 1. “Space-qualified”;
 - 2. Employing coherent heterodyne or homodyne detection techniques and having an angular resolution of less (better) than 20 μrad (microradians); or
 - 3. Designed for carrying out airborne bathymetric littoral surveys to International Hydrographic Organisation (IHO) Order 1a Standard (5th Edition February 2008) for Hydrographic Surveys or better, and using one or more lasers with a wavelength exceeding 400 nm but not exceeding 600 nm;
-

-
- Note 1: LIDAR equipment specially designed for surveying is only specified in 6A008.j.3.*
- Note 2: 6A008.j. does not control LIDAR equipment specially designed for meteorological observation.*
- Note 3: Parameters in the IHO Order 1a Standard 5th Edition February 2008 are summarised as follows:*
- a. Horizontal Accuracy (95% Confidence Level) = 5 m + 5% of depth*
 - b. Depth Accuracy for Reduced Depths (95% confidence level) = $\pm\sqrt{(a^2 + (b*d)^2)}$, where:*
 - a = 0.5 m = constant depth error, i.e. the sum of all constant depth errors*
 - b = 0.013 = factor of depth dependent error*
 - b*d = depth dependent error, i.e. the sum of all depth dependent errors*
 - d = depth*
 - c. Feature Detection = Cubic features > 2 m in depths up to 40 m; 10% of depth beyond 40 m*

- k. Having “signal processing” sub-systems using “pulse compression” and having any of the following:
 - 1. A “pulse compression” ratio exceeding 150; or
 - 2. A compressed pulse width of less than 200 ns; or

Note: 6A008.k.2. does not apply to two dimensional ‘marine radar’ or ‘vessel traffic service’ radar, having all of the following:

 - a. “Pulse compression” ratio not exceeding 150;*
 - b. Compressed pulse width of greater than 30 ns;*
 - c. Single and rotating mechanically scanned antenna;*
 - d. Peak output power not exceeding 250 W; and*
 - e. Not capable of “frequency hopping”.*

- l. Having data processing sub-systems and having any of the following:
 - 1. “Automatic target tracking” providing, at any antenna rotation, the predicted target position beyond the time of the next antenna beam passage; or

Note: 6A008.l.1. does not control conflict alert capability in ATC systems, or ‘marine radar’.

- 2. Not used;
- 3. Not used;
- 4. Configured to provide superposition and correlation, or fusion, of target data within six seconds from two or more “geographically dispersed” radar sensors to improve the aggregate performance beyond that of any single sensor specified by 6A008.f. or 6A008.i.

N.B.: See also Munitions List controls.

Note: 6A008.l. does not apply to systems, equipment and assemblies used for 'vessel traffic services'.

Technical Notes:

- 1. For the purposes of 6A008., 'marine radar' is a radar that is used to navigate safely at sea, inland waterways or near-shore environments.*
- 2. For the purposes of 6A008., 'vessel traffic service' is a vessel traffic monitoring and control service similar to air traffic control for aircraft.*

6A102 Radiation hardened 'detectors', other than those specified in 6A002, specially designed or modified for protecting against nuclear effects (e.g. electromagnetic pulse (EMP), X-rays, combined blast and thermal effects) and usable for "missiles", designed or rated to withstand radiation levels which meet or exceed a total irradiation dose of 5×10^5 rads (silicon).

Technical Note:

In 6A102, a 'detector' is defined as a mechanical, electrical, optical or chemical device that automatically identifies and records, or registers a stimulus such as an environmental change in pressure or temperature, an electrical or electromagnetic signal or radiation from a radioactive material. This includes devices that sense by one time operation or failure.

6A107 Gravity meters (gravimeters) or gravity gradiometers, usable in "missiles", and components for gravity meters and gravity gradiometers, as follows:

- a. Gravity meters, other than those specified in 6A007.b, designed or modified for airborne or marine use, and having all of the following:
 1. A static or operational accuracy equal to or less (better) than 0.7 milligal (mgal); and
 2. A time to state registration of two minutes or less;
- b. Specially designed components for gravity meters specified in 6A007.b. or 6A107.a..

6A108 Radar systems and tracking systems, other than those specified in entry 6A008, as follows:

- a. Radar and laser radar systems designed or modified for use in space launch vehicles specified in 9A004 or sounding rockets specified in 9A104;

Note: 6A108.a. includes the following:

- a. Terrain contour mapping equipment;*
- b. Imaging sensor equipment;*
- c. Scene mapping and correlation (both digital and analogue) equipment;*
- d. Doppler navigation radar equipment.*

-
- b. Precision tracking systems, usable for ‘missiles’, as follows:
1. Tracking systems which use a code translator in conjunction with either surface or airborne references or navigation satellite systems to provide real-time measurements of in-flight position and velocity;
 2. Range instrumentation radars including associated optical/infrared trackers with all of the following capabilities:
 - a. Angular resolution better than 1.5 milliradians;
 - b. Range of 30 km or greater with a range resolution better than 10 m rms;
 - c. Velocity resolution better than 3 m/s.

Technical Note:

In 6A108.b. ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.

6A202 Photomultiplier tubes having both of the following characteristics:

- a. Photocathode area of greater than 20 cm²; and
- b. Anode pulse rise time of less than 1 ns.

6A203 High-speed cameras and imaging devices and components therefor, other than those specified in 6A003, as follows:

N.B.: “Software” specially designed to enhance or release the performance of cameras or imaging devices to meet the characteristics below is controlled in 6D201 and 6D202.

- a. Streak cameras, and specially designed components therefor, as follows:
 1. Streak cameras with writing speeds greater than 0.5 mm/μs;
 2. Electronic streak cameras capable of 50 ns or less time resolution;
 3. Streak tubes for cameras specified in 6A203.a.2.;
 4. Plug-ins specially designed for use with streak cameras which have modular structures and that enable the performance specifications in 6A203.a.1 or 6A203.a.2.;
 5. Synchronizing electronics units, rotor assemblies consisting of turbines, mirrors and bearings specially designed for cameras specified in 6A203.a.1.
 - b. Framing cameras and specially designed components therefor as follows:
 1. Framing cameras with recording rates greater than 225,000 frames per second;
 2. Framing cameras capable of 50 ns or less frame exposure time;
 3. Framing tubes and solid-state imaging devices having a fast image gating (shutter) time of 50ns or less specially designed for cameras specified in 6A203.b.1. or 6A203.b.2.;
-

-
4. Plug-ins specially designed for use with framing cameras which have modular structures and that enable the performance specifications in 6A203.b.1. or 6A203.b.2.;
 5. Synchronizing electronics units, rotor assemblies consisting of turbines, mirrors and bearings specially designed for cameras specified in 6A203.b.1. or 6A203.b.2.
- c. Solid state or electron tube cameras and specially designed components therefor as follows:
1. Solid-state cameras or electron tube cameras with a fast image gating (shutter) time of 50 ns or less;
 2. Solid-state imaging devices and image intensifiers tubes having a fast image gating (shutter) time of 50 ns or less specially designed for cameras specified in 6A203.c.1.;
 3. Electro-optical shuttering devices (Kerr or Pockels cells) with a fast image gating (shutter) time of 50 ns or less;
 4. Plug-ins specially designed for use with cameras which have modular structures and that enable the performance specifications in 6A203.c.1.

Technical Note:

High speed single frame cameras can be used alone to produce a single image of a dynamic event, or several such cameras can be combined in a sequentially-triggered system to produce multiple images of an event.

- 6A204 Radiation-hardened TV cameras, or lenses thereof, specially designed or rated as radiation hardened to withstand a total radiation dose greater than 5×10^4 'Gy (silicon)' without operational degradation.

Technical Note:

In 6A204, the term 'Gy (silicon)' refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionizing radiation.

- 6A205 "Lasers", "laser" amplifiers and oscillators, other than those specified in 0B001.g.5., 0B001.h.6. and 6A005; as follows:

N.B.: For copper vapour lasers, see 6A005.b.

- a. Argon ion "lasers" having both of the following characteristics:
 1. Operating at wavelengths between 400 nm and 515 nm; and
 2. An average output power greater than 40 W;
- b. Tunable pulsed single-mode dye laser oscillators having all of the following characteristics:
 1. Operating at wavelengths between 300 nm and 800 nm;
 2. An average output power greater than 1 W;
 3. A repetition rate greater than 1 kHz; and
 4. Pulse width less than 100 ns;

-
- c. Tunable pulsed dye laser amplifiers and oscillators, having all of the following characteristics:
 - 1. Operating at wavelengths between 300 nm and 800 nm;
 - 2. An average output power greater than 30 W;
 - 3. A repetition rate greater than 1 kHz; and
 - 4. Pulse width less than 100 ns;

Note: 6A205.c. does not control single mode oscillators.
 - d. Pulsed carbon dioxide “lasers” having all of the following characteristics:
 - 1. Operating at wavelengths between 9,000 nm and 11,000 nm;
 - 2. A repetition rate greater than 250 Hz;
 - 3. An average output power greater than 500 W; and
 - 4. Pulse width of less than 200 ns;
 - e. Para-hydrogen Raman shifters designed to operate at 16 micrometre output wavelength and at a repetition rate greater than 250 Hz;
 - f. Neodymium-doped (other than glass) “lasers” with an output wavelength between 1000 and 1100 nm having either of the following:
 - 1. Pulse-excited and Q-switched with a pulse duration equal to or more than 1 ns, and having either of the following:
 - a. A single-transverse mode output with an average output power greater than 40 W; or
 - b. A multiple-transverse mode output having an average power greater than 50 W; or
 - 2. Incorporating frequency doubling to give an output wavelength between 500 and 550 nm with an average output power of more than 40 W.
 - g. Pulsed carbon monoxide lasers, other than those specified in 6A005.d.2., having all of the following characteristics:
 - 1. Operating at wavelengths between 5000 and 6000 nm;
 - 2. A repetition rate greater than 250 Hz;
 - 3. An average output power greater than 200 W; and
 - 4. Pulse width of less than 200 ns.

N.B.: SEE ALSO 6A005.d.2.

6A225 Velocity interferometers for measuring velocities exceeding 1 km/s during time intervals of less than 10 microseconds.

Note: 6A225 includes velocity interferometers such as VISARs (Velocity Interferometer Systems for Any Reflector), DLIs (Doppler Laser Interferometers) and PDV (Photonic Doppler Velocimeters) also known as Het-V (Heterodyne Velocimeters).

6A226	Pressure sensors, as follows: <ul style="list-style-type: none">a. Shock pressure gauges capable of measuring pressures greater than 10 GPa, including gauges made with manganin, ytterbium, and polyvinylidene bifluoride (PVBF, PVF2);b. Quartz pressure transducers for pressures greater than 10 GPa.
6B	Test, Inspection and Production Equipment
6B004	Optical equipment as follows: <ul style="list-style-type: none">a. Equipment for measuring absolute reflectance to an accuracy of $\pm 0.1\%$ of the reflectance value;b. Equipment other than optical surface scattering measurement equipment, having an unobscured aperture of more than 10 cm, specially designed for the non-contact optical measurement of a non-planar optical surface figure (profile) to an “accuracy” of 2 nm or less (better) against the required profile. <p><i>Note: 6B004 does not control microscopes.</i></p>
6B007	Equipment to produce, align and calibrate land-based gravity meters with a static accuracy of better than 0.1 mGal.
6B008	Pulse radar cross-section measurement systems having transmit pulse widths of 100 ns or less, and specially designed components therefor. N.B.: SEE ALSO 6B108.
6B108	Systems, other than those specified in 6B008, specially designed for radar cross section measurement usable for ‘missiles’ and their subsystems. <p><i>Technical Note:</i> <i>In 6B108 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
6C	Materials
6C002	Optical sensor materials as follows: <ul style="list-style-type: none">a. Elemental tellurium (Te) of purity levels of 99.9995% or more;b. Single crystals (including epitaxial wafers) of any of the following:<ul style="list-style-type: none">1. Cadmium zinc telluride (CdZnTe), with zinc content of less than 6% by ‘mole fraction’;2. Cadmium telluride (CdTe) of any purity level; or3. Mercury cadmium telluride (HgCdTe) of any purity level.

Technical Note:

'Mole fraction' is defined as the ratio of moles of ZnTe to the sum of moles of CdTe and ZnTe present in the crystal.

- 6C004 Optical materials as follows:
- a. Zinc selenide (ZnSe) and zinc sulphide (ZnS) “substrate blanks”, produced by the chemical vapour deposition process and having any of the following:
 1. A volume greater than 100 cm^3 ; or
 2. A diameter greater than 80 mm and a thickness of 20 mm or more;
 - b. Electro-optic materials and non-linear optical materials, as follows:
 1. Potassium titanyl arsenate (KTA) (CAS 59400-80-5);
 2. Silver gallium selenide (AgGaSe_2 , also known as AGSE) (CAS 12002-67-4); or
 3. Thallium arsenic selenide (Tl_3AsSe_3 , also known as TAS) (CAS 16142-89-5);
 4. Zinc germanium phosphide (ZnGeP_2 , also known as ZGP, zinc germanium biphosphide or zinc germanium diphosphide); or
 5. Gallium selenide (GaSe) (CAS 12024-11-2);
 - c. Non-linear optical materials, other than those specified by 6C004.b., having any of the following:
 1. Having all of the following:
 - a. Dynamic (also known as non-stationary) third order non-linear susceptibility ($\chi^{(3)}$, chi 3) of $10^{-6} \text{ m}^2/\text{V}^2$ or more; and
 - b. Response time of less than 1 ms; or\
 2. Second order non-linear susceptibility ($\chi^{(2)}$, chi 2) of $3.3 \times 10^{-11} \text{ m/V}$ or more;
 - d. “Substrate blanks” of silicon carbide or beryllium beryllium (Be/Be) deposited materials, exceeding 300 mm in diameter or major axis length;
 - e. Glass, including fused silica, phosphate glass, fluorophosphate glass, zirconium fluoride (ZrF_4) and hafnium fluoride (HfF_4) and having all of the following:
 1. A hydroxyl ion (OH^-) concentration of less than 5 ppm;
 2. Integrated metallic purity levels of less than 1 ppm; and
 3. High homogeneity (index of refraction variance) less than 5×10^{-6} ;
 - f. Synthetically produced diamond material with an absorption of less than 10^{-5} cm^{-1} for wavelengths exceeding 200 nm but not exceeding 14,000 nm.
-

-
- 6C005 Synthetic crystalline “laser” host material in unfinished form as follows:
- a. Titanium doped sapphire;
 - b. Not used.
- 6D Software**
- 6D001 “Software” specially designed for the “development” or “production” of equipment specified in 6A004, 6A005, 6A008 or 6B008.
- 6D002 “Software” specially designed for the “use” of equipment specified in 6A002.b., 6A008 or 6B008.
- 6D003 Other “software” as follows:
- a. “Software” as follows:
 1. “Software” specially designed for acoustic beam forming for the “real time processing” of acoustic data for passive reception using towed hydrophone arrays;
 2. “Source code” for the “real time processing” of acoustic data for passive reception using towed hydrophone arrays;
 3. “Software” specially designed for acoustic beam forming for “real time processing” of acoustic data for passive reception using bottom or bay cable systems;
 4. “Source code” for “real time processing” of acoustic data for passive reception using bottom or bay cable systems;
 5. “Software” or “source code”, specially designed for all of the following:
 - a. “Real time processing” of acoustic data from sonar systems specified by 6A001.a.1.e.; and
 - b. Automatically detecting, classifying and determining the location of divers or swimmers;

N.B.: For diver detection “software” or “source code”, specially designed or modified for military use, see the Munitions List controls.
 - b. Not used;
 - c. “Software” designed or modified for cameras incorporating “focal plane arrays” specified in 6A002.a.3.f. and designed or modified to remove a frame rate restriction and allow the camera to exceed the frame rate specified in 6A003.b.4. Note 3.a.
 - d. Not used;
 - e. Not used;
 - f. “Software” as follows:
-

	<ol style="list-style-type: none"> 1. “Software” specially designed for magnetic and electric field “compensation systems” for magnetic sensors designed to operate on mobile platforms; 2. “Software” specially designed for magnetic and electric field anomaly detection on mobile platforms; 3. “Software” specially designed for “real time processing” of electromagnetic data using underwater electromagnetic receivers specified by 6A006.e.; 4. “Source code” for “real time processing” of electromagnetic data using underwater electromagnetic receivers specified by 6A006.e.;
	g. “Software” specially designed to correct motional influences of gravity meters or gravity gradiometers;
	h. “Software” as follows: <ol style="list-style-type: none"> 1. Air Traffic Control (ATC) “software” application “programmes” designed to be hosted on general purpose computers located at Air Traffic Control centres and capable of accepting radar target data from more than four primary radars; 2. “Software” for the design or “production” of radomes and having all of the following: <ol style="list-style-type: none"> a. Specially designed to protect the “electronically steerable phased array antennae” specified in 6A008.e.; and b. Resulting in an antenna pattern having an ‘average side lobe level’ more than 40 dB below the peak of the main beam level. <p><i>Technical Note:</i> ‘Average side lobe level’ in 6D003.h.2.b. is measured over the entire array excluding the angular extent of the main beam and the first two side lobes on either side of the main beam.</p>
6D102	“Software” specially designed or modified for the “use” of goods specified in 6A108.
6D103	<p>“Software” which processes post-flight, recorded data, enabling determination of vehicle position throughout its flight path, specially designed or modified for ‘missiles’.</p> <p><i>Technical Note:</i> In 6D103 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</p>
6D201	“Software” or encryption keys/codes specially designed to enhance or release the performance characteristics of equipment not controlled in 6A203 so that it meets or exceeds the characteristics specified in 6A203.

6D202 “Software” or encryption keys/codes specially designed to enhance or release the performance characteristics of equipment controlled in 6A203.

6E Technology

6E001 “Technology” according to the General Technology Note for the “development” of equipment, materials or “software” specified in 6A, 6B, 6C or 6D.

6E002 “Technology” according to the General Technology Note for the “production” of equipment, materials or software specified in 6A, 6B, 6C, 6D201 or 6D202.

6E003 Other “technology” as follows:

a. “Technology” as follows:

1. Optical surface coating and treatment “technology”, “required” to achieve an ‘optical thickness’ uniformity of 99.5% or better for optical coatings 500 mm or more in diameter or major axis length and with a total loss (absorption and scatter) of less than 5×10^{-3} ;

N.B.: See also 2E003.f.

Technical Note:

‘Optical thickness’ is the mathematical product of the index of refraction and the physical thickness of the coating.

2. Optical fabrication “technology” using single point diamond turning techniques to produce surface finish accuracies of better than 10 nm rms on non-planar surfaces exceeding 0.5 m²;

b. “Technology” “required” for the “development”, “production” or “use” of specially designed diagnostic instruments or targets in test facilities for “SHPL” testing or testing or evaluation of materials irradiated by “SHPL” beams.

6E101 “Technology” according to the General Technology Note for the “use” of equipment or “software” specified in 6A002, 6A007.b. and c., 6A008, 6A102, 6A107, 6A108, 6B108, 6D102 or 6D103.

Note: 6E101 only specifies “technology” for equipment specified in 6A008 when it is designed for airborne applications and is usable in “missiles”.

6E201 “Technology” according to the General Technology Note for the “use” of equipment or “software” specified in 6A003, 6A005.a.2., 6A005.b.2., 6A005.b.3., 6A005.b.4., 6A005.b.6., 6A005.c.2., 6A005.d.3.c., 6A005.d.4.c., 6A202, 6A203, 6A205, 6A225, 6A226, 6D201 or 6D202.

Category 7—Navigation and avionics

7A Systems, Equipment and Components

N.B.: For automatic pilots for underwater vehicles, see Category 8. For radar, see Category 6.

7A001 Accelerometers as follows and specially designed components therefor:

N.B.: SEE ALSO 7A101.

N.B.: For angular or rotational accelerometers, see 7A001.b.

- a. Linear accelerometers having any of the following:
 - 1. Specified to function at linear acceleration levels less than or equal to 15 g and having any of the following:
 - a. A “bias” “stability” of less (better) than 130 micro g with respect to a fixed calibration value over a period of one year; or
 - b. A “scale factor” “stability” of less (better) than 130 ppm with respect to a fixed calibration value over a period of one year;
 - 2. Specified to function at linear acceleration levels exceeding 15 g and having all of the following:
 - a. A “bias” “repeatability” of less (better) than 1,250 micro g over a period of one year; and
 - b. A “scale factor” “repeatability” of less (better) than 1,250 ppm over a period of one year; or
 - 3. Designed for use in inertial navigation or guidance systems and specified to function at linear acceleration levels exceeding 100 g;
- Note:* 7A001.a.1. and 7A001.a.2. do not control accelerometers limited to measurement of only vibration or shock.
- b. Angular or rotational accelerometers, specified to function at linear acceleration levels exceeding 100 g.

7A002 Gyros or angular rate sensors, having any of the following and specially designed components therefor:

N.B.: SEE ALSO 7A102.

N.B.: For angular or rotational accelerometers, see 7A001.b.

- a. Specified to function at linear acceleration levels less than or equal to 100 g and having any of the following:
 - 1. A rate range of less than 500 degrees per second and having any of the following:

-
- a. A “bias” “stability” of less (better) than 0.5 degree per hour, when measured in a 1 g environment over a period of one month, and with respect to a fixed calibration value; or
 - b. An “angle random walk” of less (better) than or equal to 0.0035 degree per square root hour; or

Note: 7A002.a.1.b. does not control “spinning mass gyros”.
 - 2. A rate range greater than or equal to 500 degrees per second and having any of the following:
 - a. A “bias” “stability” of less (better) than 4 degrees per hour, when measured in a 1 g environment over a period of three minutes, and with respect to a fixed calibration value; or
 - b. An “angle random walk” of less (better) than or equal to 0.1 degree per square root hour; or

Note: 7A002.a.2.b. does not control “spinning mass gyros”.
 - b. Specified to function at linear acceleration levels exceeding 100 g.

7A003 ‘Inertial measurement equipment or systems’, having any of the following:

N.B.: SEE ALSO 7A103.

Note 1: ‘Inertial measurement equipment or systems’ incorporate accelerometers or gyroscopes to measure changes in velocity and orientation in order to determine or maintain heading or position without requiring an external reference once aligned. ‘Inertial measurement equipment or systems’ include:

- a. Attitude and Heading Reference Systems (AHRSS);*
- b. Gyrocompasses;*
- c. Inertial Measurement Units (IMUs);*
- d. Inertial Navigation Systems (INSs);*
- e. Inertial Reference Systems (IRSs);*
- f. Inertial Reference Units (IRUs).*

Note 2: 7A003. does not apply to ‘inertial measurement equipment or systems’ which are certified for use on “civil aircraft” by civil authorities of a Wassenaar Arrangement Participating State.

Technical Notes:

- 1. ‘Positional aiding references’ independently provide position, and include:
 - a. Global Navigation Satellite Systems (GNSS);*
 - b. “Data-Based Referenced Navigation” (“DBRN”).*
- 2. ‘Circular Error Probable’ (‘CEP’) - *In a circular normal distribution, the radius of the circle containing 50% of the individual measurements being made, or the radius of the circle within which there is a 50% probability of being located.*

-
- a. Designed for “aircraft”, land vehicles or vessels, providing position without the use of ‘positional aiding references’, and having any of the following accuracies subsequent to normal alignment:
1. 0.8 nautical miles per hour (nm/hr) ‘Circular Error Probable’ (‘CEP’) rate or less (better);
 2. 0.5% distanced travelled ‘CEP’ or less (better); or
 3. Total drift of 1 nautical mile ‘CEP’ or less (better) in a 24 hr period;

Technical Note:

The performance parameters in 7A003.a.1., 7A003.a.2. and 7A003.a.3. typically apply to ‘inertial measurement equipment or systems’ designed for “aircraft”, vehicles and vessels, respectively. These parameters result from the utilisation of specialised non-positional aiding references (e.g., altimeter, odometer, velocity log). As a consequence, the specified performance values cannot be readily converted between these parameters. Equipment designed for multiple platforms are evaluated against each applicable entry 7A003.a.1., 7A003.a.2., or 7A003.a.3.

- b. Designed for “aircraft”, land vehicles or vessels, with an embedded ‘positional aiding reference’ and providing position after loss of all ‘positional aiding references’ for a period of up to 4 minutes, having an accuracy of less (better) than 10 meters ‘CEP’;

Technical Note:

7A003.b. refers to systems in which ‘inertial measurement equipment or systems’ and other independent ‘positional aiding references’ are built into a single unit (i.e., embedded) in order to achieve improved performance;

- c. Designed for “aircraft”, land vehicles or vessels, providing heading or True North determination and having any of the following:
1. A maximum operating angular rate less (lower) than 500 deg/s and a heading accuracy without the use of ‘positional aiding references’ equal to or less (better) than 0.07 deg sec(Lat) (equivalent to 6 arc minutes rms at 45 degrees latitude); or
 2. A maximum operating angular rate equal to or greater (higher) than 500 deg/s and a heading accuracy without the use of ‘positional aiding references’ equal to or less (better) than 0.2 deg sec(Lat) (equivalent to 17 arc minutes rms at 45 degrees latitude);
- d. Providing acceleration measurements or angular rate measurements, in more than one dimension, and having any of the following:
1. Performance specified by 7A001. or 7A002. along any axis, without the use of any aiding references; or
 2. Being “space-qualified” and providing angular rate measurements having an “angle random walk” along any axis of less (better) than or equal to 0.1 degree per square root hour.
-

Note: 7A003.d.2. does not apply to 'inertial measurement equipment or systems' that contain "spinning mass gyros" as the only type of gyro.

7A004 'Star trackers' and components therefor, as follows:

N.B.: SEE ALSO 7A104.

- a. 'Star trackers' with a specified azimuth accuracy of equal to or less (better) than 20 seconds of arc throughout the specified lifetime of the equipment;
- b. Components specially designed for equipment specified in 7.A.4.a. as follows:
 1. Optical heads or baffles;
 2. Data processing units.

Technical Note:

'Star trackers' are also referred to as stellar attitude sensors or gyro-astro compasses.

7A005 Global Navigation Satellite Systems (GNSS) receiving equipment having any of the following and specially designed components therefor:

N.B.: SEE ALSO 7A105.

N.B.: For equipment specially designed for military use, see Military Goods Controls.

- a. Employing a decryption algorithm specially designed or modified for government use to access the ranging code for position and time; or
- b. Employing 'adaptive antenna systems'.

Note: 7A005.b. does not control GNSS receiving equipment that only uses components designed to filter, switch, or combine signals from multiple omni-directional antennae that do not implement adaptive antenna techniques.

Technical Note:

For the purposes of 7A005.b., 'adaptive antenna systems' dynamically generate one or more spatial nulls in an antenna array pattern by signal processing in the time domain or frequency domain.

7A006 Airborne altimeters operating at frequencies other than 4.2 to 4.4 GHz inclusive and having any of the following:

N.B.: SEE ALSO 7A106.

- a. "Power management"; or
- b. Using phase shift key modulation.

-
- 7A008 Underwater sonar navigation systems using doppler velocity or correlation velocity logs integrated with a heading source and having a positioning accuracy of equal to or less (better) than 3% of distance travelled ‘Circular Error Probable’ (‘CEP’) and specially designed components therefor.
- Note:* 7A008 does not control systems specially designed for installation on surface vessels or systems requiring acoustic beacons or buoys to provide positioning data.
- N.B.:* See 6A001.a. for acoustic systems, and 6A001.b. for correlation-velocity and Doppler-velocity sonar log equipment. See 8A002 for other marine systems.
- 7A101 Linear accelerometers, other than those specified in 7A001, designed for use in inertial navigation systems or in guidance systems of all types, usable in ‘missiles’, having all the following characteristics, and specially designed components therefor:
- A “bias” “repeatability” of less (better) than 1250 micro g; and
 - A “scale factor” “repeatability” of less (better) than 1250 ppm;
- Note:* 7A101 does not specify accelerometers which are specially designed and developed as MWD (Measurement While Drilling) Sensors for use in downhole well service operations.
- Technical Notes:*
- In 7A101 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km;
 - In 7A101 the measurement of “bias” and “scale factor” refers to a one sigma standard deviation with respect to a fixed calibration over a period of one year;
- 7A102 All types of gyros, other than those specified in 7A002, usable in ‘missiles’, with a rated ‘drift rate’ ‘stability’ of less than 0.5° (1 sigma or rms) per hour in a 1 g environment and specially designed components therefor.
- Technical Notes:*
- In 7A102 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.
 - In 7A102 ‘stability’ is defined as a measure of the ability of a specific mechanism or performance coefficient to remain invariant when continuously exposed to a fixed operating condition (IEEE STD 528-2001 paragraph 2.247).
 - In 7A102 ‘drift rate’ is defined as the component of gyro output that is functionally independent of input rotation and is expressed as an angular rate. (IEEE STD 528-2001 paragraph 2.56).
-

-
- 7A103 Instrumentation, navigation equipment and systems, other than those specified in 7A003, as follows; and specially designed components therefor:
- a. Inertial or other equipment, using accelerometers or gyros as follows, and systems incorporating such equipment:
 - 1. Accelerometers specified in 7A001.a.3., 7A001.b. or 7A101 or gyros specified in 7A002 or 7A102; or
 - 2. Accelerometers specified in 7A001.a.1. or 7A001.a.2. and having all of the following:
 - a. Designed for use in inertial navigation systems or in guidance systems of all types and usable in ‘missiles’;
 - b. A “bias” “repeatability” of less (better) than 1250 micro g; and
 - c. A “scale factor” “repeatability” of less (better) than 1250 ppm;
- Note: 7A103.a. does not specify equipment containing accelerometers specified in 7A001 where such accelerometers are specially designed and developed as MWD (Measurement While Drilling) sensors for use in down-hole well services operations.*
- b. Integrated flight instrument systems which include gyrostabilisers or automatic pilots, designed or modified for use in ‘missiles’;
 - c. ‘Integrated navigation systems’, designed or modified for ‘missiles’ and capable of providing a navigational accuracy of 200 m Circle of Equal Probability (CEP) or less;
- Technical Note:*
An ‘integrated navigation system’ typically incorporates the following components:
- 1. *An inertial measurement device (e.g., an attitude and heading reference system, inertial reference unit, or inertial navigation system);*
 - 2. *One or more external sensors used to update the position and/or velocity, either periodically or continuously throughout the flight (e.g., satellite navigation receiver, radar altimeter, and/or Doppler radar); and*
 - 3. *Integration hardware and software;*
- d. Three axis magnetic heading sensors, designed or modified to be integrated with flight control and navigation systems, having all the following characteristics, and specially designed components therefor;
 - 1. Internal tilt compensation in pitch (± 90 degrees) and roll (± 180 degrees) axes;
 - 2. Capable of providing azimuthal accuracy better (less) than 0.5 degrees rms at latitude of ± 80 degrees, reference to local magnetic field.
-

Note: Flight control and navigation systems in 7A103.d. include gyrostabilisers, automatic pilots and inertial navigation systems.

Technical Note:

In 7A103 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.

- 7A104 Gyro-astro compasses and other devices, other than those specified in 7A004, which derive position or orientation by means of automatically tracking celestial bodies or satellites and specially designed components therefor.
- 7A105 Receiving equipment for Global Navigation Satellite Systems (GNSS; e.g. GPS, GLONASS, or Galileo), having any of the following characteristics, and specially designed components therefor:
- a. Designed or modified for use in space launch vehicles specified in 9A004, unmanned aerial vehicles specified in 9A012 or sounding rockets specified in 9A104; or
 - b. Designed or modified for airborne applications and having any of the following:
 1. Capable of providing navigation information at speeds in excess of 600 m/s;
 2. Employing decryption, designed or modified for military or governmental services, to gain access to GNSS secured signal/data; or
 3. Being specially designed to employ anti-jam features (e.g. null steering antenna or electronically steerable antenna) to function in an environment of active or passive countermeasures.

Note: 7A105.b.2. and 7A105.b.3. do not control equipment designed for commercial, civil or 'Safety of Life' (e.g., data integrity, flight safety) GNSS services.

- 7A106 Altimeters, other than those specified in 7A006, of radar or laser radar type, designed or modified for use in space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.
- 7A115 Passive sensors for determining bearing to specific electromagnetic source (direction finding equipment) or terrain characteristics, designed or modified for use in space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.

Note: 7A115 includes sensors for the following equipment:

- a. *Terrain contour mapping equipment;*
- b. *Imaging sensor equipment (both active and passive);*
- c. *Passive interferometer equipment.*

-
- 7A116 Flight control systems and servo valves, as follows; designed or modified for use in space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.
- a. Hydraulic, mechanical, electro-optical, or electro-mechanical flight control systems (including fly-by-wire types);
 - b. Attitude control equipment;
 - c. Flight control servo valves designed or modified for the systems specified in 7A116.a. or 7A116.b., and designed or modified to operate in a vibration environment greater than 10 g rms between 20 Hz and 2 kHz.
- 7A117 “Guidance sets”, usable in “missiles” capable of achieving system accuracy of 3.33% or less of the range (e.g., a “CEP” of 10 km or less at a range of 300 km).

7B Test, Inspection and Production Equipment

- 7B001 Test, calibration or alignment equipment, specially designed for equipment specified in 7A.

Note: 7B001 does not control test, calibration or alignment equipment for ‘Maintenance Level I’ or ‘Maintenance Level II’.

Technical Notes:

1. ‘Maintenance Level I’
The failure of an inertial navigation unit is detected on the aircraft by indications from the Control and Display Unit (CDU) or by the status message from the corresponding sub-system. By following the manufacturer’s manual, the cause of the failure may be localised at the level of the malfunctioning Line Replaceable Unit (LRU). The operator then removes the LRU and replaces it with a spare.
2. ‘Maintenance Level II’
The defective LRU is sent to the maintenance workshop (the manufacturer’s or that of the operator responsible for level II maintenance). At the maintenance workshop, the malfunctioning LRU is tested by various appropriate means to verify and localise the defective Shop Replaceable Assembly (SRA) module responsible for the failure. This SRA is removed and replaced by an operative spare. The defective SRA (or possibly the complete LRU) is then shipped to the manufacturer. ‘Maintenance Level II’ does not include the disassembly or repair of controlled accelerometers or gyro sensors.

Part 2 Dual-use list

Category 7 Navigation and avionics

7B002	Equipment specially designed to characterise mirrors for ring “laser” gyros, as follows: N.B.: SEE ALSO 7B102. a. Scatterometers having a measurement accuracy of 10 ppm or less (better); b. Profilometers having a measurement accuracy of 0.5 nm (5 angstrom) or less (better).
7B003	Equipment specially designed for the “production” of equipment specified in 7A. <i>Note: 7B003 includes:</i> a. Gyro tuning test stations; b. Gyro dynamic balance stations; c. Gyro run-in/motor test stations; d. Gyro evacuation and fill stations; e. Centrifuge fixtures for gyro bearings; f. Accelerometer axis align stations; g. Fibre optic gyro coil winding machines.
7B102	Reflectometers specially designed to characterise mirrors, for “laser” gyros, having a measurement accuracy of 50 ppm or less (better).
7B103	“Production facilities” and “production equipment” as follows: a. “Production facilities” specially designed for equipment specified in 7A117; b. “Production equipment”, and other test, calibration and alignment equipment, other than that specified in 7B001 to 7B003, designed or modified to be used with equipment specified in 7A. <i>Note: 7B103.b includes:</i> a. Inertial Measurement Unit (IMU) Module Testers; b. IMU Platform Testers; c. IMU Stable Element Handling Fixtures; d. IMU Platform Balance Fixtures; e. Accelerometer Test Stations.
7C	Materials None.
7D	Software
7D001	“Software” specially designed or modified for the “development” or “production” of equipment specified in 7A. or 7B.

7D002	<p>“Source code” for the operation or maintenance of any inertial navigation equipment, including inertial equipment not specified in 7A003 or 7A004, or Attitude and Heading Reference Systems (‘AHRs’).</p> <p><i>Note:</i> 7D002 does not control “source code” for the “use” of gimbaled ‘AHRs’.</p> <p><i>Technical Note:</i></p> <p>‘AHRs’ generally differ from Inertial Navigation Systems (INS) in that an ‘AHRs’ provides attitude and heading information and normally does not provide the acceleration, velocity and position information associated with an INS.</p>
7D003	<p>Other “software” as follows:</p> <ol style="list-style-type: none">“Software” specially designed or modified to improve the operational performance or reduce the navigational error of systems to the levels specified in 7A003, 7A004 or 7A008;“Source code” for hybrid integrated systems which improves the operational performance or reduces the navigational error of systems to the level specified in 7A003 or 7A008 by continuously combining heading data with any of the following:<ol style="list-style-type: none">Doppler radar or sonar velocity data;Global navigation satellite systems (i.e., GPS or GLONASS) reference data; orData from “Data-Based Referenced Navigation” (“DBRN”) systems;Not used;Not used; <p><i>N.B.:</i> For flight control “source code”, see 7D004.</p> <ol style="list-style-type: none">Computer-Aided-Design (CAD) “software” specially designed for the “development” of “active flight control systems”, helicopter multi-axis fly-by-wire or fly-by-light controllers or helicopter “circulation controlled anti-torque or circulation-controlled direction control systems”, whose “technology” is specified in 7E004.b., 7E004.c.1. or 7E004.c.2.
7D004	<p>“Source code” incorporating “development” “technology” specified by 7E004.a.1. to 6. or 7E004.b., for any of the following:</p> <ol style="list-style-type: none">Digital flight management systems for “total control of flight”;Integrated propulsion and flight control systems;Fly-by-wire or fly-by-light control systems;Fault-tolerant or self-reconfiguring “active flight control systems”;Not used;Air data systems based on surface static data; or

	<p>g. Three dimensional displays.</p> <p><i>Note:</i> 7D004. does not apply to “source code” associated with common computer elements and utilities (e.g., input signal acquisition, output signal transmission, computer program and data loading, built-in test, task scheduling mechanisms) not providing a specific flight control system function.</p>
7D005	“Software” specially designed to decrypt Global Navigation Satellite Systems (GNSS) ranging code designed for government use.
7D101	“Software” specially designed or modified for the “use” of equipment specified in 7A001 to 7A006, 7A101 to 7A106, 7A115, 7A116.a., 7A116.b., 7B001, 7B002, 7B003, 7B102 or 7B103.
7D102	<p>Integration “software” as follows:</p> <p>a. Integration “software” for the equipment specified in 7A103.b.;</p> <p>b. Integration “software” specially designed for the equipment specified in 7A003 or 7A103.a.</p> <p>c. Integration “software” designed or modified for the equipment specified in 7A103.c.</p> <p><i>Note:</i> A common form of integration “software” employs Kalman filtering.</p>
7D103	<p>“Software” specially designed for modelling or simulation of the “guidance sets” specified in 7A117 or for their design integration with the space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.</p> <p><i>Note:</i> “Software” specified in 7D103 remains controlled when combined with specially designed hardware specified in 4A102.</p>
7E	Technology
7E001	<p>“Technology” according to the General Technology Note for the “development” of equipment or “software”, specified in 7A, 7B or 7D001., 7D002., 7D003. or 7D005.</p> <p><i>Note:</i> 7E001. includes key management “technology” exclusively for equipment specified in 7A005.a.</p>
7E002	“Technology” according to the General Technology Note for the “production” of equipment specified in 7A or 7B.
7E003	“Technology” according to the General Technology Note for the repair, refurbishing or overhaul of equipment specified in 7A001 to 7A004.

Note: 7E003 does not control maintenance “technology” directly associated with calibration, removal or replacement of damaged or unserviceable LRUs and SRAs of a “civil aircraft” as described in ‘Maintenance Level I’ or ‘Maintenance Level II’.

N.B.: See Technical Notes to 7B001.

7E004 Other “technology” as follows:

- a. “Technology” for the “development” or “production” of any of the following:
 1. Not used;
 2. Air data systems based on surface static data only, i.e., which dispense with conventional air data probes;
 3. Three dimensional displays for “aircraft”;
 4. Not used;
 5. Electric actuators (i.e., electromechanical, electrohydrostatic and integrated actuator package) specially designed for “primary flight control”;
 6. “Flight control optical sensor array” specially designed for implementing “active flight control systems”; or
 7. “DBRN” systems designed to navigate underwater, using sonar or gravity databases, that provide a positioning accuracy equal to or less (better) than 0.4 nautical miles;
- b. “Development” “technology”, as follows, for “active flight control systems” (including fly-by-wire or fly-by-light):
 1. Photonic-based “technology” for sensing aircraft or flight control component state, transferring flight control data, or commanding actuator movement, “required” for fly-by-light “active flight control systems”;
 2. Not used;
 3. Real-time algorithms to analyze component sensor information to predict and preemptively mitigate impending degradation and failures of components within an “active flight control system”;
Note: 7E004.b.3. does not include algorithms for the purpose of off-line maintenance.
 4. Real-time algorithms to identify component failures and reconfigure force and moment controls to mitigate “active flight control system” degradations and failures;
Note: 7E004.b.4. does not include algorithms for the elimination of fault effects through comparison of redundant data sources, or off-line pre-planned responses to anticipated failures.
 5. Integration of digital flight control, navigation and propulsion control data, into a digital flight management system for “total control of flight”;

	<p><i>Note:</i> 7E004.b.5. does not control:</p> <ol style="list-style-type: none"> a. “Development” “technology” for integration of digital flight control, navigation and propulsion control data, into a digital flight management system for “flight path optimisation”; b. “Development” “technology” for “aircraft” flight instrument systems integrated solely for VOR, DME, ILS or MLS navigation or approaches.
	<p>6. Not used;</p> <p><i>Note:</i> 7E004.b. does not apply to technology associated with common computer elements and utilities (e.g., input signal acquisition, output signal transmission, computer program and data loading, built-in test, task scheduling mechanisms) not providing a specific flight control system function.</p>
	<p>c. “Technology” for the “development” of helicopter systems, as follows:</p> <ol style="list-style-type: none"> 1. Multi-axis fly-by-wire or fly-by-light controllers, which combine the functions of at least two of the following into one controlling element: <ol style="list-style-type: none"> a. Collective controls; b. Cyclic controls; c. Yaw controls; 2. “Circulation-controlled anti-torque or circulation-controlled directional control systems”; 3. Rotor blades incorporating “variable geometry airfoils”, for use in systems using individual blade control.
7E101	<p>“Technology” according to the General Technology Note for the “use” of equipment or software specified in 7A001 to 7A006, 7A101 to 7A106, 7A115 to 7A117, 7B001, 7B002, 7B003, 7B102, 7B103, 7D101 to 7D103.</p>
7E102	<p>“Technology” for protection of avionics and electrical subsystems against electromagnetic pulse (EMP) and electromagnetic interference (EMI) hazards, from external sources, as follows:</p> <ol style="list-style-type: none"> a. Design “technology” for shielding systems; b. Design “technology” for the configuration of hardened electrical circuits and subsystems; c. Design “technology” for the determination of hardening criteria of 7E102.a. and 7E102.b.
7E104	<p>“Technology” for the integration of the flight control, guidance, and propulsion data into a flight management system for optimisation of rocket system trajectory.</p>

Category 8—Marine

8A Systems, Equipment and Components

8A001 Submersible vehicles and surface vessels, as follows:

Note: For the control status of equipment for submersible vehicles, see:

- a. Category 5, Part 2 “Information Security” for encrypted communication equipment;
- b. Category 6 for sensors;
- c. Categories 7 and 8 for navigation equipment;
- d. Category 8A for underwater equipment.

- a. Manned, tethered submersible vehicles designed to operate at depths exceeding 1,000 m;
- b. Manned, untethered submersible vehicles having any of the following:
 1. Designed to ‘operate autonomously’ and having a lifting capacity of all the following:
 - a. 10% or more of their weight in air; and
 - b. 15 kN or more;
 2. Designed to operate at depths exceeding 1,000 m; or
 3. Having all of the following:
 - a. Designed to continuously ‘operate autonomously’ for 10 hours or more; and
 - b. ‘Range’ of 25 nautical miles or more;

Technical Notes:

1. For the purposes of 8A001.b., ‘operate autonomously’ means fully submerged, without snorkel, all systems working and cruising at minimum speed at which the submersible can safely control its depth dynamically by using its depth planes only, with no need for a support vessel or support base on the surface, sea-bed or shore, and containing a propulsion system for submerged or surface use.
 2. For the purposes of 8A001.b., ‘range’ means half the maximum distance a submersible vehicle can ‘operate autonomously’.
- c. Unmanned, tethered submersible vehicles designed to operate at depths exceeding 1,000 m and having any of the following:
 1. Designed for self-propelled manoeuvre using propulsion motors or thrusters specified in 8A002.a.2.; or
 2. Fibre optic data link;
 - d. Unmanned, untethered submersible vehicles having any of the following:
 1. Designed for deciding a course relative to any geographical reference without real-time human assistance;
 2. Acoustic data or command link; or

-
3. Fibre optic data or command link exceeding 1,000 m;
 - e. Ocean salvage systems with a lifting capacity exceeding 5 MN for salvaging objects from depths exceeding 250 m and having any of the following:
 1. Dynamic positioning systems capable of position keeping within 20 m of a given point provided by the navigation system; or
 2. Seafloor navigation and navigation integration systems, for depths exceeding 1,000 m and with positioning accuracies to within 10 m of a predetermined point;
 - f. Surface-effect vehicles (fully skirted variety) having all of the following:
 1. Maximum design speed, fully loaded, exceeding 30 knots in a significant wave height of 1.25 m (Sea State 3) or more;
 2. Cushion pressure exceeding 3,830 Pa; and
 3. Light-ship-to-full-load displacement ratio of less than 0.70;
 - g. Surface-effect vehicles (rigid sidewalls) with a maximum design speed, fully loaded, exceeding 40 knots in a significant wave height of 3.25 m (Sea State 5) or more;
 - h. Hydrofoil vessels with active systems for automatically controlling foil systems, with a maximum design speed, fully loaded, of 40 knots or more in a significant wave height of 3.25 m (Sea State 5) or more;
 - i. ‘Small waterplane area vessels’ having any of the following:
 1. Full load displacement exceeding 500 tonnes with a maximum design speed, fully loaded, exceeding 35 knots in a significant wave height of 3.25 m (Sea State 5) or more; or
 2. Full load displacement exceeding 1,500 tonnes with a maximum design speed, fully loaded, exceeding 25 knots in a significant wave height of 4 m (Sea State 6) or more.

Technical Note:

A ‘small waterplane area vessel’ is defined by the following formula: waterplane area at an operational design draught less than $2 \times (\text{displaced volume at the operational design draught})^{2/3}$.

8A002 Marine systems, equipment and components, as follows:

Note: For underwater communications systems, see Category 5, Part 1 — Telecommunications.

- a. Systems, equipment and components, specially designed or modified for submersible vehicles and designed to operate at depths exceeding 1,000 m, as follows:
 1. Pressure housings or pressure hulls with a maximum inside chamber diameter exceeding 1.5 m;
 2. Direct current propulsion motors or thrusters;
-

-
3. Umbilical cables, and connectors therefor, using optical fibre and having synthetic strength members;
 4. Components manufactured from material specified in 8C001;

Technical Note:

The objective of 8A002.a.4. should not be defeated by the export of 'syntactic foam' specified in 8C001 when an intermediate stage of manufacture has been performed and it is not yet in the final component form.

- b. Systems specially designed or modified for the automated control of the motion of submersible vehicles specified in 8A001, using navigation data, having closed loop servo-controls and having any of the following:
 1. Enabling a vehicle to move within 10 m of a predetermined point in the water column;
 2. Maintaining the position of the vehicle within 10 m of a predetermined point in the water column; or
 3. Maintaining the position of the vehicle within 10 m while following a cable on or under the seabed;
- c. Fibre optic hull penetrators or connectors;
- d. Underwater vision systems as follows:
 1. Television systems and television cameras, as follows:
 - a. Television systems (comprising camera, monitoring and signal transmission equipment) having a 'limiting resolution' when measured in air of more than 800 lines and specially designed or modified for remote operation with a submersible vehicle;
 - b. Underwater television cameras having a 'limiting resolution' when measured in air of more than 1,100 lines;
 - c. Low light level television cameras specially designed or modified for underwater use and having all of the following:
 1. Image intensifier tubes specified in 6A002.a.2.a.; and
 2. More than 150,000 "active pixels" per solid state area array;

Technical Note:

'Limiting resolution' is a measure of horizontal resolution usually expressed in terms of the maximum number of lines per picture height discriminated on a test chart, using IEEE Standard 208/1960 or any equivalent standard.

2. Systems specially designed or modified for remote operation with an underwater vehicle, employing techniques to minimise the effects of back scatter and including range-gated illuminators or "laser" systems;
-

-
- e. Photographic still cameras specially designed or modified for underwater use below 150 m, with a film format of 35 mm or larger and having any of the following:
 - 1. Annotation of the film with data provided by a source external to the camera;
 - 2. Automatic back focal distance correction; or
 - 3. Automatic compensation control specially designed to permit an underwater camera housing to be usable at depths exceeding 1,000 m;
 - f. Not used;
 - g. Light systems specially designed or modified for underwater use, as follows:
 - 1. Stroboscopic light systems capable of a light output energy of more than 300 J per flash and a flash rate of more than 5 flashes per second;
 - 2. Argon arc light systems specially designed for use below 1,000 m;
 - h. “Robots” specially designed for underwater use, controlled by using a dedicated computer and having any of the following:
 - 1. Systems that control the “robot” using information from sensors which measure force or torque applied to an external object, distance to an external object, or tactile sense between the “robot” and an external object; or
 - 2. The ability to exert a force of 250 N or more or a torque of 250 Nm or more and using titanium based alloys or “composite” “fibrous or filamentary materials” in their structural members;
 - i. Remotely controlled articulated manipulators specially designed or modified for use with submersible vehicles and having any of the following:
 - 1. Systems which control the manipulator using information from sensors which measure any of the following:
 - a. Torque or force applied to an external object; or
 - b. Tactile sense between the manipulator and an external object;or
 - 2. Controlled by proportional master-slave techniques and having 5 degrees of ‘freedom of movement’ or more;

Technical Note:

Only functions having proportional control using positional feedback are counted when determining the number of degrees of ‘freedom of movement’.

-
- j. Air independent power systems specially designed for underwater use, as follows:
1. Brayton or Rankine cycle engine air independent power systems having any of the following:
 - a. Chemical scrubber or absorber systems, specially designed to remove carbon dioxide, carbon monoxide and particulates from recirculated engine exhaust;
 - b. Systems specially designed to use a monoatomic gas;
 - c. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; or
 - d. Systems having all of the following:
 1. Specially designed to pressurise the products of reaction or for fuel reformation;
 2. Specially designed to store the products of the reaction; and
 3. Specially designed to discharge the products of the reaction against a pressure of 100 kPa or more;
 2. Diesel cycle engine air independent systems having all of the following:
 - a. Chemical scrubber or absorber systems, specially designed to remove carbon dioxide, carbon monoxide and particulates from recirculated engine exhaust;
 - b. Systems specially designed to use a monoatomic gas;
 - c. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; and
 - d. Specially designed exhaust systems that do not exhaust continuously the products of combustion;
 3. Fuel cell air independent power systems with an output exceeding 2 kW and having any of the following:
 - a. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; or
 - b. Systems having all of the following:
 1. Specially designed to pressurise the products of reaction or for fuel reformation;
 2. Specially designed to store the products of the reaction; and
 3. Specially designed to discharge the products of the reaction against a pressure of 100 kPa or more;
-

-
- 4. Stirling cycle engine air independent power systems having all of the following:
 - a. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; and
 - b. Specially designed exhaust systems which discharge the products of combustion against a pressure of 100 kPa or more;
 - k. Skirts, seals and fingers, having any of the following:
 - 1. Designed for cushion pressures of 3,830 Pa or more, operating in a significant wave height of 1.25 m (Sea State 3) or more and specially designed for surface effect vehicles (fully skirted variety) specified in 8A001.f.; or
 - 2. Designed for cushion pressures of 6,224 Pa or more, operating in a significant wave height of 3.25 m (Sea State 5) or more and specially designed for surface effect vehicles (rigid sidewalls) specified in 8A001.g.;
 - l. Lift fans rated at more than 400 kW and specially designed for surface effect vehicles specified in 8A001.f. or 8A001.g.;
 - m. Fully submerged subcavitating or supercavitating hydrofoils, specially designed for vessels specified in 8A001.h.;
 - n. Active systems specially designed or modified to control automatically the sea-induced motion of vehicles or vessels, specified in 8A001.f., 8A001.g., 8A001.h. or 8A001.i.;
 - o. Propellers, power transmission systems, power generation systems and noise reduction systems, as follows:
 - 1. Water-screw propeller or power transmission systems, as follows, specially designed for surface effect vehicles (fully skirted or rigid sidewall variety), hydrofoils or ‘small waterplane area vessels’ specified in 8A001.f., 8A001.g., 8A001.h. or 8A001.i., as follows:
 - a. Supercavitating, super-ventilated, partially-submerged or surface piercing propellers, rated at more than 7.5 MW;
 - b. Contrarotating propeller systems rated at more than 15 MW;
 - c. Systems employing pre-swirl or post-swirl techniques, for smoothing the flow into a propeller;
 - d. Light-weight, high capacity (K factor exceeding 300) reduction gearing;
 - e. Power transmission shaft systems incorporating “composite” material components and capable of transmitting more than 1 MW;
 - 2. Water-screw propeller, power generation systems or transmission systems, designed for use on vessels, as follows:
 - a. Controllable-pitch propellers and hub assemblies, rated at more than 30 MW;
-

-
- b. Internally liquid-cooled electric propulsion engines with a power output exceeding 2.5 MW;
 - c. “Superconductive” propulsion engines or permanent magnet electric propulsion engines, with a power output exceeding 0.1 MW;
 - d. Power transmission shaft systems incorporating “composite” material components and capable of transmitting more than 2 MW;
 - e. Ventilated or base-ventilated propeller systems, rated at more than 2.5 MW;
3. Noise reduction systems designed for use on vessels of 1,000 tonnes displacement or more, as follows:
- a. Systems that attenuate underwater noise at frequencies below 500 Hz and consist of compound acoustic mounts for the acoustic isolation of diesel engines, diesel generator sets, gas turbines, gas turbine generator sets, propulsion motors or propulsion reduction gears, specially designed for sound or vibration isolation and having an intermediate mass exceeding 30 % of the equipment to be mounted;
 - b. ‘Active noise reduction or cancellation systems’ or magnetic bearings, specially designed for power transmission systems;

Technical Note:

‘Active noise reduction or cancellation systems’ incorporate electronic control systems capable of actively reducing equipment vibration by the generation of anti-noise or anti-vibration signals directly to the source.

- p. Pumpjet propulsion systems having all of the following:
 - 1. Power output exceeding 2.5 MW; and
 - 2. Using divergent nozzle and flow conditioning vane techniques to improve propulsive efficiency or reduce propulsion-generated underwater-radiated noise;
- q. Underwater swimming and diving equipment as follows:
 - 1. Closed circuit rebreathers;
 - 2. Semi-closed circuit rebreathers;

Note: 8A002.q. does not control individual rebreathers for personal use when accompanying their users.

N.B.: For equipment and devices specially designed for military use, see ML17.a. on the Munitions List.
- r. Diver deterrent acoustic systems specially designed or modified to disrupt divers and having a sound pressure level equal to or exceeding 190 dB (reference 1 µPa at 1 m) at frequencies of 200 Hz and below.

Note 1: 8A002.r. does not apply to diver deterrent systems based on underwater explosive devices, air guns or combustible sources.

Note 2: 8A002.r. includes diver deterrent acoustic systems that use spark gap sources, also known as plasma sound sources.

8B Test, Inspection and Production Equipment

8B001 Water tunnels having a background noise of less than 100 dB (reference 1 μ Pa, 1 Hz), in the frequency range from 0 to 500 Hz and designed for measuring acoustic fields generated by a hydro-flow around propulsion system models.

8C Materials

8C001 'Syntactic foam' designed for underwater use and having all of the following:

N.B.: See also 8A002.a.4.

- a. Designed for marine depths exceeding 1,000 m; and
- b. A density less than 561 kg/m³.

Technical Note:

'Syntactic foam' consists of hollow spheres of plastic or glass embedded in a resin matrix.

8D Software

8D001 "Software" specially designed or modified for the "development", "production" or "use" of equipment or materials, specified in 8A, 8B or 8C.

8D002 Specific "software" specially designed or modified for the "development", "production", repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction.

8E Technology

8E001 "Technology" according to the General Technology Note for the "development" or "production" of equipment or materials, specified in 8A, 8B or 8C.

8E002 Other "technology" as follows:

- a. "Technology" for the "development", "production", repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction;
- b. "Technology" for the overhaul or refurbishing of equipment specified in 8A001, 8A002.b., 8A002.j., 8A002.o. or 8A002.p.

Category 9—Aerospace and propulsion

9A Systems, Equipment and Components

N.B.: For propulsion systems designed or rated against neutron or transient ionising radiation, see the Munitions List.

9A001 Aero gas turbine engines having any of the following:

N.B.: SEE ALSO 9A101.

- a. Incorporating any of the “technologies” specified in 9E003.a., 9E003.h. or 9E003.i.;

Note 1: 9A001.a. does not control aero gas turbine engines which meet all of the following:

- a. Certified by the civil aviation authority in a Wassenaar Arrangement Participating State; and*
- b. Intended to power non-military manned aircraft for which any of the following has been issued by a Wassenaar Arrangement Participating State for the aircraft with this specific engine type:*
 - 1. A civil type certificate; or*
 - 2. An equivalent document recognized by the International Civil Aviation Organisation (ICAO).*

Note 2: 9A001.a. does not apply to aero gas turbine engines designed for Auxiliary Power Units (APUs) approved by the civil aviation authority in a Wassenaar Arrangement Participating State.

- b. Designed to power an aircraft to cruise at Mach 1 or higher, for more than thirty minutes.

9A002 ‘Marine gas turbine engines’ with an ISO standard continuous power rating of 24,245 kW or more and a specific fuel consumption not exceeding 0.219 kg/kWh in the power range from 35 to 100%, and specially designed assemblies and components therefor.

Note: The term ‘marine gas turbine engines’ includes those industrial, or aero-derivative, gas turbine engines adapted for a ship’s electric power generation or propulsion.

9A003 Specially designed assemblies and components, incorporating any of the “technologies” specified in 9E003.a., 9E003.h. or 9E003.i., for any of the following gas turbine engine propulsion systems:

- a. Specified in 9A001; or
- b. Whose design or production origins are either non-participating states or unknown to the manufacturer.

-
- 9A004 Space launch vehicles and “spacecraft”.
- N.B.: SEE ALSO 9A104.**
- Note: 9A004 does not control payloads.*
- N.B.: For the control status of products contained in “spacecraft” payloads, see the appropriate Categories.*
- 9A005 Liquid rocket propulsion systems containing any of the systems or components, specified in 9A006.
- N.B.: SEE ALSO 9A105 AND 9A119.**
- 9A006 Systems and components, specially designed for liquid rocket propulsion systems, as follows:
- N.B.: SEE ALSO 9A106, 9A108 AND 9A120.**
- a. Cryogenic refrigerators, flightweight dewars, cryogenic heat pipes or cryogenic systems, specially designed for use in space vehicles and capable of restricting cryogenic fluid losses to less than 30% per year;
 - b. Cryogenic containers or closed-cycle refrigeration systems, capable of providing temperatures of 100 K (-173°C) or less for “aircraft” capable of sustained flight at speeds exceeding Mach 3, launch vehicles or “spacecraft”;
 - c. Slush hydrogen storage or transfer systems;
 - d. High pressure (exceeding 17.5 MPa) turbo pumps, pump components or their associated gas generator or expander cycle turbine drive systems;
 - e. High-pressure (exceeding 10.6 MPa) thrust chambers and nozzles therefor;
 - f. Propellant storage systems using the principle of capillary containment or positive expulsion (i.e., with flexible bladders);
 - g. Liquid propellant injectors with individual orifices of 0.381 mm or smaller in diameter (an area of $1.14 \times 10^{-3} \text{ cm}^2$ or smaller for non-circular orifices) and specially designed for liquid rocket engines;
 - h. One-piece carbon-carbon thrust chambers or one-piece carbon-carbon exit cones, with densities exceeding 1.4 g/cm^3 and tensile strengths exceeding 48 MPa.
- 9A007 Solid rocket propulsion systems having any of the following:
- N.B.: SEE ALSO 9A107 AND 9A119.**
- a. Total impulse capacity exceeding 1.1 MNs;
 - b. Specific impulse of 2.4 kNs/kg or more, when the nozzle flow is expanded to ambient sea level conditions for an adjusted chamber pressure of 7 MPa;
-

-
- c. Stage mass fractions exceeding 88% and propellant solid loadings exceeding 86%;
 - d. Components specified in 9A008; or
 - e. Insulation and propellant bonding systems, using direct-bonded motor designs to provide a 'strong mechanical bond' or a barrier to chemical migration between the solid propellant and case insulation material.

Technical Note:

'Strong mechanical bond' means bond strength equal to or more than propellant strength.

9A008 Components specially designed for solid rocket propulsion systems, as follows:

N.B.: SEE ALSO 9A108.

- a. Insulation and propellant bonding systems, using liners to provide a 'strong mechanical bond' or a barrier to chemical migration between the solid propellant and case insulation material;

Technical Note:

'Strong mechanical bond' means bond strength equal to or more than propellant strength.

- b. Filament-wound "composite" motor cases exceeding 0.61 m in diameter or having 'structural efficiency ratios (PV/W)' exceeding 25 km;

Technical Note:

'Structural efficiency ratio (PV/W)' is the burst pressure (P) multiplied by the vessel volume (V) divided by the total pressure vessel weight (W).

- c. Nozzles with thrust levels exceeding 45 kN or nozzle throat erosion rates of less than 0.075 mm/s;
- d. Movable nozzle or secondary fluid injection thrust vector control systems, capable of any of the following:
 - 1. Omni-axial movement exceeding $\pm 5^\circ$;
 - 2. Angular vector rotations of $20^\circ/\text{s}$ or more; or
 - 3. Angular vector accelerations of $40^\circ/\text{s}^2$ or more.

9A009 Hybrid rocket propulsion systems having any of the following:

- a. Total impulse capacity exceeding 1.1 MNs; or
- b. Thrust levels exceeding 220 kN in vacuum exit conditions.

-
- 9A010 Specially designed components, systems and structures, for launch vehicles, launch vehicle propulsion systems or “spacecraft”, as follows:
- N.B.: SEE ALSO 1A002 AND 9A110.**
- a. Components and structures, each exceeding 10 kg and specially designed for launch vehicles manufactured using metal “matrix”, “composite”, organic “composite”, ceramic “matrix” or intermetallic reinforced materials, specified in 1C007 or 1C010;
- Note: The weight cut-off is not relevant for nose cones.*
- b. Components and structures, specially designed for launch vehicle propulsion systems specified in 9A005 to 9A009 manufactured using metal “matrix”, “composite”, organic “composite”, ceramic “matrix” or intermetallic reinforced materials, specified in 1C007 or 1C010;
 - c. Structural components and isolation systems, specially designed to control actively the dynamic response or distortion of “spacecraft” structures;
 - d. Pulsed liquid rocket engines with thrust-to-weight ratios equal to or more than 1 kN/kg and a response time (the time required to achieve 90% of total rated thrust from start-up) of less than 30 ms.
- 9A011 Ramjet, scramjet or combined cycle engines, and specially designed components therefor.
- N.B.: SEE ALSO 9A111 AND 9A118.**
- 9A012 “Unmanned aerial vehicles” (“UAVs”), unmanned “airships”, related systems, equipment and components, as follows:
- a. “UAVs” or unmanned “airships”, having any of the following:
 1. An autonomous flight control and navigation capability (e.g., an autopilot with an Inertial Navigation System); or
 2. Capability of controlled-flight out of the direct vision range involving a human operator (e.g., televisual remote control);
 - b. Related systems, equipment and components, as follows:
 1. Equipment specially designed for remotely controlling the “UAVs” or unmanned “airships”, specified in 9A012.a.;
 2. Systems for navigation, attitude, guidance or control, other than those specified in 7A and specially designed to provide autonomous flight control or navigation capability to “UAVs” or unmanned “airships”, specified in 9A012.a.;
 3. Equipment or components, specially designed to convert a manned “aircraft” to a “UAV” or unmanned “airship”, specified in 9A012.a.;
 4. Air breathing reciprocating or rotary internal combustion type engines, specially designed or modified to propel “UAVs” or unmanned “airships”, at altitudes above 50,000 feet (15,240 metres).
-

Note: 9A012 does not apply to model aircraft or model "airships".

- 9A101 Turbojet and turbofan engines (including turbocompound engines), other than those specified in 9A001, as follows:
- a. Engines having both of the following characteristics:
 1. 'Maximum thrust value' greater than 400 N (achieved un-installed) excluding civil certified engines with a 'maximum thrust value' greater than 8.89 kN (achieved un-installed), and
 2. Specific fuel consumption of 0.15 kg N⁻¹ hr⁻¹ or less (at maximum continuous power at sea level static using the ICAO standard atmosphere);
 - b. Engines designed or modified for use in "missiles", or in other "unmanned aerial vehicles" capable of a range exceeding 300 km.

Technical Note:

In 9A101, 'maximum thrust value' is the manufacturer's demonstrated maximum thrust for the engine type un-installed. The civil type certified thrust value will be equal to or less than the manufacturer's demonstrated maximum thrust for the engine type.

- 9A102 'Turboprop engine systems' specially designed for "unmanned aerial vehicles" capable of a range exceeding 300 km, and specially designed components therefor, having a 'maximum power' greater than 10 kW.

Note: 9A102 does not control civil certified engines.

Technical Notes:

1. For the purposes of 9A102 a 'turboprop engine system' incorporates all of the following:
 - a. Turboshift engine; and
 - b. Power transmission system to transfer the power to a propeller.
2. For the purposes of 9A102 the 'maximum power' is achieved uninstalled at sea level static conditions using the ICAO standard atmosphere.

- 9A104 Sounding rockets, capable of a range of at least 300 km.

N.B.: SEE ALSO 9A004.

- 9A105 Liquid propellant rocket engines integrated, or designed or modified to be integrated, into a liquid propellant propulsion system, as follows:

N.B.: SEE ALSO 9A119.

- a. Liquid propellant rocket engines usable in "missiles", other than those specified in 9A005, having a total impulse capacity equal to or greater than 1.1 MNs;

-
- b. Liquid propellant rocket engines, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in 9A005 or 9A105.a., having a total impulse capacity equal to or greater than 0.841 MNs.

9A106 Systems or components, other than those specified in 9A006 as follows, specially designed for liquid rocket propulsion systems:

- a. Ablative liners for thrust or combustion chambers, usable in “missiles”, space launch vehicles specified in 9A004 or sounding rockets specified in 9A104;
- b. Rocket nozzles, usable in “missiles”, space launch vehicles specified in 9A004 or sounding rockets specified in 9A104;
- c. Thrust vector control sub-systems, usable in “missiles”;

Technical Note:

Examples of methods of achieving thrust vector control specified in 9A106.c. are:

1. Flexible nozzle;
2. Fluid or secondary gas injection;
3. Movable engine or nozzle;
4. Deflection of exhaust gas stream (jet vanes or probes); or
5. Thrust tabs.

- d. Liquid, slurry and gel propellant (including oxidisers) control systems, and specially designed components therefor, usable in “missiles”, designed or modified to operate in vibration environments greater than 10 g rms between 20 Hz and 2 kHz.

Note: The only servo valves and pumps specified in 9A106.d., are the following:

- a. Servo valves designed for flow rates equal to or greater than 24 litres per minute, at an absolute pressure equal to or greater than 7 MPa, that have an actuator response time of less than 100 ms;
- b. Pumps, for liquid propellants, with shaft speeds equal to or greater than 8,000 r.p.m. or with discharge pressures equal to or greater than 7 MPa.

9A107 Solid propellant rocket motors, usable in complete rocket systems or “unmanned aerial vehicles”, capable of a range of 300 km, other than those specified in 9A007, having total impulse capacity equal to or greater than 0.841 MNs.

N.B.: SEE ALSO 9A119.

-
- 9A108 Components, other than those specified in 9A008, as follows, specially designed for solid rocket propulsion systems:
- a. Rocket motor cases and “insulation” components therefor, usable in “missiles”, space launch vehicles specified in 9A004 or sounding rockets specified in 9A104;
 - b. Rocket nozzles, usable in “missiles”, space launch vehicles specified in 9A004 or sounding rockets specified in 9A104;
 - c. Thrust vector control sub-systems, usable in “missiles”.
- Technical Note:*
Examples of methods of achieving thrust vector control specified in 9A108.c. are:
1. Flexible nozzle;
 2. Fluid or secondary gas injection;
 3. Movable engine or nozzle;
 4. Deflection of exhaust gas stream (jet vanes or probes); or
 5. Thrust tabs.
- 9A109 Hybrid rocket motors, other than those specified in 9A009, and specially designed components thereof, as follows:
- a. Hybrid rocket motors usable in complete rocket systems or “unmanned aerial vehicles” capable of a range exceeding 300 km, having a total impulse capacity equal to or greater than 0.841 MNs, but less than 1.1 MNs;
 - b. Specially designed components for hybrid rocket motors specified in 9A109.a.
- N.B.: SEE ALSO 9A009 and 9A119.**
- 9A110 Composite structures, laminates and manufactures thereof, other than those specified in 9A010, specially designed for use in ‘missiles’ or the subsystems specified in 9A005, 9A007, 9A105, 9A106.c., 9A107, 9A108.c., 9A116 or 9A119.
- N.B.: SEE ALSO 1A002.**
- Technical Note:*
In 9A110 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.
- 9A111 Pulse jet engines, usable in “missiles” or unmanned aerial vehicles specified in 9A012, and specially designed components therefor.
- N.B.: SEE ALSO 9A011 AND 9A118.**
-

-
- 9A115 Launch support equipment as follows:
- a. Apparatus and devices for handling, control, activation or launching, designed or modified for space launch vehicles specified in 9A004, unmanned aerial vehicles specified in 9A012 or sounding rockets specified in 9A104;
 - b. Vehicles for transport, handling, control, activation or launching, designed or modified for space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.
- 9A116 Reentry vehicles, usable in “missiles”, and equipment designed or modified therefor, as follows:
- a. Reentry vehicles;
 - b. Heat shields and components therefor, fabricated of ceramic or ablative materials;
 - c. Heat sinks and components therefor, fabricated of light-weight, high heat capacity materials;
 - d. Electronic equipment specially designed for reentry vehicles.
- 9A117 Staging mechanisms, separation mechanisms, and interstages, usable in “missiles”.
- N.B.: SEE ALSO 9A121.**
- 9A118 Devices to regulate combustion usable in engines, which are usable in “missiles” or unmanned aerial vehicles specified in 9A012, specified in 9A011 or 9A111.
- 9A119 Individual rocket stages, usable in complete rocket systems or “unmanned aerial vehicles”, capable of a range of 300 km, other than those specified in 9A005, 9A007, 9A009, 9A105, 9A107 and 9A109.
- 9A120 Liquid propellant tanks, other than those specified in 9A006, specially designed for propellants specified in 1C111 or ‘other liquid propellants’, used in rocket systems capable of delivering at least a 500 kg payload to a range of at least 300 km.
- Note: In 9A120 ‘other liquid propellants’ includes, but is not limited to, propellants specified in the Munitions List.*
- 9A121 Umbilical and interstage electrical connectors specially designed for “missiles”.
- Technical Note:*
- Interstage connectors in 9A121 also include electrical connectors installed between a “missile” and its payload.*
-

-
- 9A350 Spraying or fogging systems, specially designed or modified for fitting to aircraft, “lighter-than-air vehicles” or unmanned aerial vehicles, and specially designed components therefor, as follows:
- Complete spraying or fogging systems capable of delivering, from a liquid suspension, an initial droplet ‘VMD’ of less than 50 µm at a flow rate of greater than two litres per minute;
 - Spray booms or arrays of aerosol generating units capable of delivering, from a liquid suspension, an initial droplet ‘VMD’ of less than 50 µm at a flow rate of greater than two litres per minute;
 - Aerosol generating units specially designed for fitting to systems specified in 9A350.a. and b.

Note: Aerosol generating units are devices specially designed or modified for fitting to aircraft such as nozzles, rotary drum atomisers and similar devices.

Note: 9A350 does not control spraying or fogging systems and components that are demonstrated not to be capable of delivering biological agents in the form of infectious aerosols.

Technical Notes:

- Droplet size for spray equipment or nozzles specially designed for use on aircraft, “lighter-than-air vehicles” or unmanned aerial vehicles should be measured using either of the following:*
 - Doppler laser method;*
 - Forward laser diffraction method.*
- In 9A350 ‘VMD’ means Volume Median Diameter and for water-based systems this equates to Mass Median Diameter (MMD).*

9B Test, Inspection and Production Equipment

- 9B001 Equipment, tooling and fixtures, specially designed for manufacturing gas turbine blades, vanes or tip shroud castings, as follows:
- Directional solidification or single crystal casting equipment;
 - Ceramic cores or shells;
- 9B002 On-line (real time) control systems, instrumentation (including sensors) or automated data acquisition and processing equipment, having all of the following:
- Specially designed for the “development” of gas turbine engines, assemblies or components; and
 - Incorporating “technology” specified in 9E003.h. or 9E003.i.

9B003	Equipment specially designed for the “production” or test of gas turbine brush seals designed to operate at tip speeds exceeding 335 m/s and temperatures in excess of 773 K (500°C), and specially designed components or accessories therefor.
9B004	Tools, dies or fixtures, for the solid state joining of “superalloy”, titanium or intermetallic airfoil-to-disk combinations described in 9E003.a.3. or 9E003.a.6. for gas turbines.
9B005	<p>On-line (real time) control systems, instrumentation (including sensors) or automated data acquisition and processing equipment, specially designed for use with any of the following:</p> <p>N.B.: SEE ALSO 9B105.</p> <p>a. Wind tunnels designed for speeds of Mach 1.2 or more;</p> <p><i>Note: 9B005.a. does not control wind tunnels specially designed for educational purposes and having a ‘test section size’ (measured laterally) of less than 250 mm.</i></p> <p><i>Technical Note:</i> <i>‘Test section size’ means the diameter of the circle, or the side of the square, or the longest side of the rectangle, at the largest test section location.</i></p> <p>b. Devices for simulating flow-environments at speeds exceeding Mach 5, including hot-shot tunnels, plasma arc tunnels, shock tubes, shock tunnels, gas tunnels and light gas guns; or</p> <p>c. Wind tunnels or devices, other than two-dimensional sections, capable of simulating Reynolds number flows exceeding 25×10^6.</p>
9B006	<p>Acoustic vibration test equipment capable of producing sound pressure levels of 160 dB or more (referenced to 20 µPa) with a rated output of 4 kW or more at a test cell temperature exceeding 1,273 K (1,000°C), and specially designed quartz heaters therefor.</p> <p>N.B.: SEE ALSO 9B106.</p>
9B007	Equipment specially designed for inspecting the integrity of rocket motors and using Non-Destructive Test (NDT) techniques other than planar x-ray or basic physical or chemical analysis.
9B008	Transducers specially designed for the direct measurement of the wall skin friction of the test flow with a stagnation temperature exceeding 833 K (560°C).
9B009	Tooling specially designed for producing turbine engine powder metallurgy rotor components capable of operating at stress levels of 60% of Ultimate Tensile Strength (UTS) or more and metal temperatures of 873 K (600°C) or more.

-
- 9B010 Equipment specially designed for the production of “UAVs” and associated systems, equipment and components, specified in 9A012.
- 9B105 ‘Aerodynamic test facilities’ for speeds of Mach 0.9 or more, other than those specified in 9B005, usable for ‘missiles’ and their subsystems.
- N.B.: SEE ALSO 9B005.**
- Note: 9B105 does not control wind-tunnels for speeds of Mach 3 or less with dimension of the ‘test cross section size’ equal to or less than 250 mm.*
- Technical Notes:*
1. *In 9B105 ‘missile’ means complete rocket systems or “unmanned aerial vehicle” capable of a range exceeding 300 km.*
 2. *‘Aerodynamic test facilities’ includes wind tunnels and shock tunnels for the study of airflow over objects.*
 3. *‘Test cross section size’ means the diameter of the circle, or the side of the square, or the longest side of the rectangle, or the major axis of the ellipse at the largest ‘test cross section’ location. ‘Test cross section’ is the section perpendicular to the flow direction.*
- 9B106 Environmental chambers and anechoic chambers, as follows:
- a. Environmental chambers capable of simulating all the following flight conditions:
 1. Having any of the following:
 - a. Altitude equal to or greater than 15 km; or
 - b. Temperature range from below 223 K (-50°C) to above 398 K (+125°C);
 2. Incorporating, or ‘designed or modified’ to incorporate, a shaker unit or other vibration test equipment to produce vibration environments equal to or greater than 10 g rms, measured ‘bare table’, between 20 Hz and 2 kHz while imparting forces equal to or greater than 5 kN;
- Technical Notes:*
1. *9B106.a.2. describes systems that are capable of generating a vibration environment with a single wave (e.g., a sine wave) and systems capable of generating a broad band random vibration (i.e., power spectrum).*
 2. *In 9B106.a.2., ‘designed or modified’ means the environmental chamber provides appropriate interfaces (e.g., sealing devices) to incorporate a shaker unit or other vibration test equipment as specified in 2B116.*
 3. *In 9B106.a.2. ‘bare table’ means a flat table, or surface, with no fixture or fittings.*
-

	<p>b. Environmental chambers capable of simulating the following flight conditions:</p> <ol style="list-style-type: none"> 1. Acoustic environments at an overall sound pressure level of 140 dB or greater (referenced to 20 µPa) or with a total rated acoustic power output of 4 kW or greater; and 2. Altitude equal to or greater than 15 km; or 3. Temperature range from below 223 K (-50°C) to above 398 K (+125°C).
9B115	Specially designed “production equipment” for the systems, sub-systems and components specified in 9A005 to 9A009, 9A011, 9A101, 9A102, 9A105 to 9A109, 9A111, 9A116 to 9A120.
9B116	Specially designed “production facilities” for the space launch vehicles specified in 9A004, or systems, sub-systems, and components specified in 9A005 to 9A009, 9A011, 9A101, 9A102, 9A104 to 9A109, 9A111, 9A116 to 9A120, or complete rocket systems or “unmanned aerial vehicles” capable of a range exceeding 300 km.
9B117	<p>Test benches and test stands for solid or liquid propellant rockets or rocket motors, having either of the following characteristics:</p> <ol style="list-style-type: none"> a. The capacity to handle more than 68 kN of thrust; or b. Capable of simultaneously measuring the three axial thrust components.
9C	Materials
9C108	<p>“Insulation” material in bulk form and “interior lining”, other than those specified in 9A008, for rocket motor cases usable in “missiles” or specially designed for ‘missiles’.</p> <p><i>Technical Note:</i></p> <p><i>In 9C108 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
9C110	<p>Resin impregnated fibre prepregs and metal coated fibre preforms therefor, for composite structures, laminates and manufactures specified in 9A110, made either with organic matrix or metal matrix utilising fibrous or filamentary reinforcements having a “specific tensile strength” greater than 7.62×10^4 m and a “specific modulus” greater than 3.18×10^6 m.</p> <p>N.B.: SEE ALSO 1C010 AND 1C210.</p> <p><i>Note: The only resin impregnated fibre prepregs specified in entry 9C110 are those using resins with a glass transition temperature (T_g), after cure, exceeding 418 K (145°C) as determined by ASTM D4065 or equivalent.</i></p>

9D	Software
9D001	“Software” specially designed or modified for the “development” of equipment or “technology”, specified in 9A001 to 9A121, 9B or 9E003.
9D002	“Software” specially designed or modified for the “production” of equipment specified in 9A001 to 9A121 or 9B.
9D003	“Software” incorporating “technology” specified in 9E003.h. and used in “FADEC systems” for propulsion systems specified in 9A or equipment specified in 9B.
9D004	<p>Other “software” as follows:</p> <ol style="list-style-type: none"> a. 2D or 3D viscous “software”, validated with wind tunnel or flight test data required for detailed engine flow modelling; b. “Software” for testing aero gas turbine engines, assemblies or components, specially designed to collect, reduce and analyse data in real time and capable of feedback control, including the dynamic adjustment of test articles or test conditions, as the test is in progress; c. “Software” specially designed to control directional solidification or single crystal casting; d. Not used; e. “Software” specially designed or modified for the “use” of “UAVs” and associated systems, equipment and components, specified in 9A012; f. “Software” specially designed to design the internal cooling passages of aero gas turbine blades, vans and tip shrouds; g. “Software” having all of the following: <ol style="list-style-type: none"> 1. Specially designed to predict aero thermal, aeromechanical and combustion conditions in aero gas turbine engines; and 2. Theoretical modelling predictions of the aero thermal, aeromechanical and combustion conditions, which have been validated with actual aero gas turbine engine (experimental or production) performance data.
9D101	“Software” specially designed or modified for the “use” of goods specified in 9B105, 9B106, 9B116 or 9B117.
9D103	<p>“Software” specially designed for modelling, simulation or design integration of the space launch vehicles specified in 9A004 or sounding rockets specified in 9A104, or the subsystems specified in 9A005, 9A007, 9A105, 9A106.c., 9A107, 9A108.c., 9A116 or 9A119.</p> <p><i>Note: “Software” specified in 9D103 remains controlled when combined with specially designed hardware specified in 4A102.</i></p>

9D104	“Software” specially designed or modified for the “use” of goods specified in 9A001, 9A005, 9A006.d., 9A006.g., 9A007.a., 9A008.d., 9A009.a., 9A010.d., 9A011, 9A101, 9A102, 9A105, 9A106.c., 9A106.d., 9A107, 9A108.c., 9A109, 9A111, 9A115.a., 9A116.d., 9A117 or 9A118.
9D105	“Software” which coordinates the function of more than one subsystem, specially designed or modified for “use” in space launch vehicles specified in 9A004 or sounding rockets specified in 9A104.
9E	Technology
	<i>Note: “Development” or “production” “technology” specified in 9E001 to 9E003 for gas turbine engines remains controlled when used as “use” “technology” for repair, rebuild and overhaul. Excluded from control are: technical data, drawings or documentation for maintenance activities directly associated with calibration, removal or replacement of damaged or unserviceable line replaceable units, including replacement of whole engines or engine modules.</i>
9E001	“Technology” according to the General Technology Note for the “development” of equipment or “software”, specified in 9A001.b., 9A004 to 9A012, 9A350, 9B or 9D.
9E002	“Technology” according to the General Technology Note for the “production” of equipment specified in 9A001.b., 9A004 to 9A011, 9A350 or 9B. <i>N.B.: For “technology” for the repair of controlled structures, laminates or materials, see 1E002.f.</i>
9E003	Other “technology” as follows: <ul style="list-style-type: none"> a. “Technology” “required” for the “development” or “production” of any of the following gas turbine engine components or systems: <ul style="list-style-type: none"> 1. Gas turbine blades, vanes or tip shrouds, made from directionally solidified (DS) or single crystal (SC) alloys and having (in the 001 Miller Index Direction) a stress-rupture life exceeding 400 hours at 1,273 K (1,000°C) at a stress of 200 MPa, based on the average property values; 2. Combustors having any of the following: <ul style="list-style-type: none"> a. Thermally decoupled liners designed to operate at ‘combustor exit temperature’ exceeding 1,883 K (1,610°C); b. Non-metallic liners; c. Non-metallic shells; or d. Liners designed to operate at ‘combustor exit temperature’ exceeding 1,883 K (1,610°C) and having holes that meet the parameters specified by 9E003.c.;

Note: The “required” “technology” for holes in 9E003.a.2. is limited to the derivation of the geometry and location of the holes.

Technical Note:

‘Combustor exit temperature’ is the bulk average gas path total (stagnation) temperature between the combustor exit plane and the leading edge of the turbine inlet guide vane (i.e., measured at engine station T40 as defined in SAE ARP 755A) when the engine is running in a ‘steady state mode’ of operation at the certificated maximum continuous operating temperature.

N.B.: See 9E003.c. for “technology” “required” for manufacturing cooling holes.

3. Components manufactured from any of the following:
 - a. Organic “composite” materials designed to operate above 588 K (315°C);
 - b. Metal “matrix” “composite”, ceramic “matrix”, intermetallic or intermetallic reinforced materials, specified in 1C007; or
 - c. “Composite” material specified in 1C010 and manufactured with resins specified in 1C008;
4. Uncooled turbine blades, vanes, tip-shrouds or other components, designed to operate at gas path total (stagnation) temperatures of 1,323 K (1,050°C) or more at sea-level static take-off (ISA) in a ‘steady state mode’ of engine operation;
5. Cooled turbine blades, vanes, “tip-shrouds” other than those described in 9E003.a.1., designed to operate at a ‘gas path temperature’ of 1,693 K (1,420°C) or more;

Technical Notes:

1. ‘Gas path temperature’ is the bulk average gas path total (stagnation) temperature at the leading edge plane of the turbine component when the engine is running in a ‘steady state mode’ of operation at the certificated or specified maximum continuous operating temperature.
 2. The term ‘steady state mode’ defines engine operation conditions, where the engine parameters, such as thrust/power, rpm and others, have no appreciable fluctuations, when the ambient air temperature and pressure at the engine inlet are constant.
6. Airfoil-to-disk blade combinations using solid state joining;
 7. Gas turbine engine components using “diffusion bonding” “technology” specified in 2E003.b.;
 8. ‘Damage tolerant’ gas turbine engine rotor components using powder metallurgy materials specified in 1C002.b.; or

Technical Note:

‘Damage tolerant’ components are designed using methodology and substantiation to predict and limit crack growth.

-
9. Not used;
 10. Not used;
 11. Hollow fan blades;
 - b. “Technology” “required” for the “development” or “production” of any of the following:
 1. Wind tunnel aero-models equipped with non-intrusive sensors capable of transmitting data from the sensors to the data acquisition system; or
 2. “Composite” propeller blades or propfans, capable of absorbing more than 2,000 kW at flight speeds exceeding Mach 0.55;
 - c. “Technology” “required” for manufacturing cooling holes, in gas turbine engine components incorporating any of the “technologies” specified by 9E003.a.1., 9E003.a.2. or 9E003.a.5., and having any of the following:
 1. Having all of the following:
 - a. Minimum ‘cross-sectional area’ less than 0.45 mm²;
 - b. ‘Hole shape ratio’ greater than 4.52; and
 - c. ‘Incidence angle’ equal to or less than 25°; or
 2. Having all of the following:
 - a. Minimum ‘cross-sectional area’ less than 0.12 mm²;
 - b. ‘Hole shape ratio’ greater than 5.65; and
 - c. ‘Incidence angle’ more than 25°;

Note: 9E003.c. does not apply to “technology” for manufacturing constant radius cylindrical holes that are straight through and enter and exit on the external surfaces of the component.

Technical Notes:

1. *For the purposes of 9E003.c., the ‘cross-sectional area’ is the area of the hole in the plane perpendicular to the hole axis.*
 2. *For the purposes of 9E003.c., ‘hole shape ratio’ is the nominal length of the axis of the hole divided by the square root of its minimum ‘cross-sectional area’.*
 3. *For the purposes of 9E003.c., ‘incidence angle’ is the acute angle measured between the plane tangential to the aerofoil surface and the hole axis at the point where the hole axis enters the aerofoil surface.*
 4. *Techniques for manufacturing holes in 9E003.c. include “laser”, water jet, Electro-Chemical Machining (ECM) or Electrical Discharge Machining (EDM) methods.*
- d. “Technology” “required” for the “development” or “production” of helicopter power transfer systems or tilt rotor or tilt wing “aircraft” power transfer systems;

-
- e. “Technology” for the “development” or “production” of reciprocating diesel engine ground vehicle propulsion systems having all of the following:
1. ‘Box volume’ of 1.2 m³ or less;
 2. An overall power output of more than 750 kW based on 80/1269/EEC, ISO 2534 or national equivalents; and
 3. Power density of more than 700 kW/m³ of ‘box volume’;

Technical Note:

‘Box volume’ in 9E003.e. is the product of three perpendicular dimensions measured in the following way:

Length: The length of the crankshaft from front flange to flywheel face;

Width: The widest of any of the following:

- a. The outside dimension from valve cover to valve cover;*
- b. The dimensions of the outside edges of the cylinder heads; or*
- c. The diameter of the flywheel housing;*

Height: The largest of any of the following:

- a. The dimension of the crankshaft centre-line to the top plane of the valve cover (or cylinder head) plus twice the stroke; or*
- b. The diameter of the flywheel housing.*

- f. “Technology” “required” for the “production” of specially designed components for high output diesel engines, as follows:
1. “Technology” “required” for the “production” of engine systems having all of the following components employing ceramics materials specified in 1C007:
 - a. Cylinder liners;
 - b. Pistons;
 - c. Cylinder heads; and
 - d. One or more other components (including exhaust ports, turbochargers, valve guides, valve assemblies or insulated fuel injectors);
 2. “Technology” “required” for the “production” of turbocharger systems with single-stage compressors and having all of the following:
 - a. Operating at pressure ratios of 4:1 or higher;
 - b. Mass flow in the range from 30 to 130 kg per minute; and
 - c. Variable flow area capability within the compressor or turbine sections;

-
3. “Technology” “required” for the “production” of fuel injection systems with a specially designed multifuel (e.g., diesel or jet fuel) capability covering a viscosity range from diesel fuel (2.5 cSt at 310.8 K (37.8°C)) down to gasoline fuel (0.5 cSt at 310.8 K (37.8°C)) and having all of the following:
 - a. Injection amount in excess of 230 mm³ per injection per cylinder; and
 - b. Electronic control features specially designed for switching governor characteristics automatically depending on fuel property to provide the same torque characteristics by using the appropriate sensors;
 - g. “Technology” “required” for the “development” or “production” of ‘high output diesel engines’ for solid, gas phase or liquid film (or combinations thereof) cylinder wall lubrication and permitting operation to temperatures exceeding 723 K (450°C), measured on the cylinder wall at the top limit of travel of the top ring of the piston.

Technical Note:

‘High output diesel engines’ are diesel engines with a specified brake mean effective pressure of 1.8 MPa or more at a speed of 2,300 r.p.m., provided the rated speed is 2,300 r.p.m. or more.

- h. “Technology” for gas turbine engine “FADEC systems” as follows:
 1. “Development” “technology” for deriving the functional requirements for the components necessary for the “FADEC system” to regulate engine thrust or shaft power (e.g. feedback sensor time constants and accuracies, fuel valve slew rate);
 2. “Development” or “production” “technology” for control and diagnostic components unique to the “FADEC system” and used to regulate engine thrust or shaft power;
 3. “Development” “technology” for the control law algorithms, including “source code”, unique to the “FADEC system” and used to regulate engine thrust or shaft power.

Note: 9E003.h. does not control technical data related to engine-aircraft integration required by the civil aviation certification authorities to be published for general airline use (e.g. installation manuals, operating instructions, instructions for continued airworthiness) or interface functions (e.g. input/output processing, airframe thrust or shaft power demand).

- i. “Technology” for adjustable flow path systems designed to maintain engine stability for gas generator turbines, fan or power turbines, or propelling nozzles, as follows:
 1. “Development” “technology” for deriving the functional requirements for the components that maintain engine stability;
 2. “Development” or “production” “technology” for components unique to the adjustable flow path system and that maintain engine stability;
-

-
3. “Development” “technology” for the control law algorithms, including “source code”, unique to the adjustable flow path system and that maintain engine stability.

Note: 9E003.i. does not control “development” or “production” “technology” for any of the following:

- a. Inlet guide vanes;
- b. Variable pitch fans or prop-fans;
- c. Variable compressor vanes;
- d. Compressor bleed valves; or
- e. Adjustable flow path geometry for reverse thrust.

- 9E101 a. “Technology” according to the General Technology Note for the “development” of goods specified in 9A101, 9A102, 9A104 to 9A111 or 9A115 to 9A121.
- b. “Technology” according to the General Technology Note for the “production” of ‘UAV’s specified in 9A012 or goods specified in 9A101, 9A102, 9A104 to 9A111 or 9A115 to 9A121.

Technical Note:

In 9E101.b. ‘UAV’ means unmanned aerial vehicle systems capable of a range exceeding 300 km.

- 9E102 “Technology” according to the General Technology Note for the “use” of space launch vehicles specified in 9A004, goods specified in 9A005 to 9A011, ‘UAV’s specified in 9A012 or goods specified in 9A101, 9A102, 9A104 to 9A111, 9A115 to 9A121, 9B105, 9B106, 9B115 to 9B117, 9D101 or 9D103.

Technical Note:

In 9E102, ‘UAV’ means unmanned aerial vehicle systems capable of a range exceeding 300 km.

Part 2 Dual-use list

Sensitive list of dual-use goods and technologies

Sensitive list of dual-use goods and technologies

Note: This list contains a sub-set of the items controlled in Categories 1 to 9 of the Part 2 List of Dual-Use Goods and Technologies. The items in this List are considered to be sensitive, requiring additional care in their transfer. General Export Licences are generally not available for the export of the following sensitive goods.

N.B.: Where abbreviated entries are used, see the List of Dual-Use Goods and Technologies for full details. Text that differs from that in the List of Dual-Use Goods and Technologies is **shaded**.

Category 1	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
1A002	“Composite” structures or laminates...
1C001	Materials specially designed for use as absorbers of electromagnetic waves...
1C007.c. & 1C007.d.	Ceramic-ceramic “composite” materials...
1C010.c. & 1C010.d.	“Fibrous or filamentary materials”...
1C012	Materials as follows...
1C101	Materials or devices for reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures; other than those specified in 1C001, usable in ‘missiles’, “missile” subsystems or unmanned aerial vehicles specified in 9A012. <i>Note:</i> 1C101 does not control materials if such goods are formulated solely for civil applications. <i>Technical Note:</i> In 1C101 ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.
1C239	High explosives, other than those specified in the Munitions List, or substances or mixtures containing more than 2% by weight thereof, with a crystal [density greater than 1.8 g/cm ³ and having a detonation velocity greater than 8,000 m/s.
1D002	“Software” for the “development” of organic “matrix”, metal “matrix” or carbon “matrix” laminates or “composites” specified by this List .
1D103	“Software” specially designed for analysis of reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures.

Category 1	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
1E001	“Technology” according to the General Technology Note for the “development” or “production” of equipment and materials specified by 1A002 or 1C of this List.
1E002.e. & 1E002.f.	Other “technology”...
1E101	“Technology” according to the GTN for the “use” of goods specified in 1C101 or 1D103.
1E102	“Technology” according to the General Technology Note for the “development” of “software” specified in 1D001, 1D101 or 1D103.
1E201	“Technology” according to the GTN for the “development” of “software” specified in 1D103.

Category 2	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
2B001.a	Not used since 2002
2B001.b	Not used since 2002
2B001.d	Not used since 2002
2B001.f	Not used since 2002
2B003	Not used since 2002
2D001	<p>“Software”, other than that specified by 2D002, specially designed for the “development” or “production” of equipment as follows:</p> <ol style="list-style-type: none"> a. Machine tools for turning having all of the following: <ol style="list-style-type: none"> 1. Positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; and 2. Two or more axes which can be coordinated simultaneously for “contouring control”; b. Machine tools for milling having any of the following: <ol style="list-style-type: none"> 1. Having all of the following: <ol style="list-style-type: none"> a. Positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; and b. Three linear axes plus one rotary axis which can be coordinated simultaneously for “contouring control”;

Part 2 Dual-use list

Sensitive list of dual-use goods and technologies

Category 2	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
	<ol style="list-style-type: none"> 2. Specified by 2B001.b.2.a., 2B001.b.2.b. or 2B001.b.2.c., and having a positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; or 3. A positioning accuracy for jig boring machines, with “all compensations available”, equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; <p>c. Electrical discharge machines (EDM) as specified in 2B001.d</p> <p>d. Deep-hole-drilling machines as specified in 2B001.f</p> <p>e. “Numerically controlled” or manual machine tools as specified in 2B003</p>
2E001	<p>“Technology” according to the General Technology Note for the “development” of “software” specified by 2D of this List or for the “development” of equipment as follows:</p> <ol style="list-style-type: none"> a. Machine tools for turning having all of the following: <ol style="list-style-type: none"> 1. Positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; and 2. Two or more axes which can be coordinated simultaneously for “contouring control”; b. Machine tools for milling having any of the following: <ol style="list-style-type: none"> 1. Having all of the following: <ol style="list-style-type: none"> a. Positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; and b. Three linear axes plus one rotary axis which can be coordinated simultaneously for “contouring control”; 2. Specified by 2B001.b.2.a., 2B001.b.2.b. or 2B001.b.2.c., and having a positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; or 3. A positioning accuracy for jig boring machines, with “all compensations available”, equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; c. Electrical discharge machines (EDM) as specified in 2B001.d. d. Deep-hole-drilling machines as specified in 2B001.f. e. “Numerically controlled” or manual machine tools as specified in 2B003

Category 2	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
2E002	<p>“Technology” according to the General Technology Note for the “production” of equipment as follows:</p> <ul style="list-style-type: none"> a. Machine tools for turning having all of the following: <ul style="list-style-type: none"> 1. Positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; and 2. Two or more axes which can be coordinated simultaneously for “contouring control”; b. Machine tools for milling having any of the following: <ul style="list-style-type: none"> 1. Having all of the following: <ul style="list-style-type: none"> a. Positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; and b. Three linear axes plus one rotary axis which can be coordinated simultaneously for “contouring control”; 2. Specified by 2B001.b.2.a., 2B001.b.2.b. or 2B001.b.2.c., and having a positioning accuracy with “all compensations available” equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; or 3. A positioning accuracy for jig boring machines, with “all compensations available”, equal to or less (better) than 3.0 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; c. Electrical discharge machines (EDM) as specified in 2B001.d. d. Deep-hole-drilling machines as specified in 2B001.f. e. “Numerically controlled” or manual machine tools as specified in 2B003

Category 3	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
3A002.g.1	Atomic frequency standards... “Space-qualified”
3A229	High-current pulse generators, as follows... <i>N.B.: See also ML4, ML909</i>
3A232	Multipoint initiation systems, other than those specified in 1A007, as follows... <i>N.B.: See also ML4</i>
3B001.a.2	Not used
3D001.	“Software” specially designed for the “development” or “production” of equipment specified by 3A002.g. of this List.

Part 2 Dual-use list

Sensitive list of dual-use goods and technologies

Category 3	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
3E001	“Technology” according to the General Technology Note for the “development” or “production” of equipment specified by 3A of this List.
3E201	“Technology” according to the General Technology Note for the “use” of equipment specified in 3A229 or 3A232.

Category 4	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
4A001.a.2.	Electronic computers...radiation hardened...
4A003.b.	Not used since 2002
4A003.c.	Not used since 2001
4D001	“Software” specially designed for the “development” or “production” of equipment specified by 4A of this List or for the “development” or “production” of “digital computers” having an ‘Adjusted Peak Performance’ (‘APP’) exceeding 1.0 Weighted TeraFLOPS (WT).
4E001	“Technology” according to the General Technology Note for the “development” or “production” of any of the following equipment or “software”: <ul style="list-style-type: none"> a. Equipment specified by 4.A. of this List; b. “Digital computers” having an ‘Adjusted Peak Performance’ (‘APP’) exceeding 1.0 Weighted TeraFLOPS (WT); or c. “Software” specified by 4.D. of this List.

Category 5	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
Part 1	
5A001.b.3.	Being radio equipment...
5A001.b.5.	Being digitally controlled radio receivers...
5A001.h.	Counter Improvised Explosive Device (IED) equipment and related equipment...
5B001.a.	Equipment and specially designed components or accessories therefor, specially designed for the “development”, “production” or “use” of equipment, functions or features in 5A001 of this List.

Category 5 SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES	
5D001.a.	“Software” specially designed for the “development” or “production” of equipment, functions or features, specified by 5A001 of this List.
5D001.b.	“Software” specially designed or modified to support “technology” specified by 5E001 of this List.
5E001.a.	“Technology” according to the General Technology Note for the “development” or “production” of equipment, functions or features specified by 5A001 or “software” specified by 5D001.a. of this List.
Part 2	None

Category 6 SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES	
6A001.a.1.b.	Systems or transmitting and receiving arrays, designed for object detection or location, having any of the following: <ol style="list-style-type: none"> 1. A transmitting frequency below 5 kHz or a sound pressure level exceeding 224 dB (reference 1 µPa at 1 m) for equipment with an operating frequency in the band from 5 kHz to 10 kHz inclusive; 2. Sound pressure level exceeding 224 dB... 3. Sound pressure level exceeding 235 dB... 4. Forming beams of... 5. Designed to operate... 6. Designed to withstand
6A001.a.2.a.1.	Hydrophones...Incorporating...
6A001.a.2.a.2.	Hydrophones...Incorporating flexible assemblies...
6A001.a.2.a.3.	Hydrophones...Having any...
6A001.a.2.a.5.	Hydrophones...Designed to operate...
6A001.a.2.a.6.	Hydrophones...Designed for...
6A001.a.2.b.	Towed acoustic hydrophone arrays...
6A001.a.2.c.	Processing equipment, specially designed for real time application with towed acoustic hydrophone arrays, having “user accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;
6A001.a.2.d.	Heading sensors...

Part 2 Dual-use list

Sensitive list of dual-use goods and technologies

Category 6	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
6A001.a.2.e.	Bottom or bay cable systems, having any of the following: <ol style="list-style-type: none"> 1. Incorporating hydrophones... or 2. Incorporating multiplexed hydrophone group signal modules...
6A001.a.2.f.	Processing equipment, specially designed for real time application with bottom or bay cable systems, having “user accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes.
6A002.a.1.a., b. and c.	“Space-qualified” solid-state detectors...
6A002.a.1.d.	“Space-qualified” “focal plane arrays”....
6A002.a.2.a.	Image intensifier tubes ... <ol style="list-style-type: none"> 1. A peak response... 2. Electron image amplification... 3. Photocathodes, as follows: <ol style="list-style-type: none"> a. Multialkali photocathodes (e.g., S-20 and S-25) having a luminous sensitivity exceeding 700 $\mu\text{A}/\text{lm}$; b. GaAs or GaInAs photocathodes; c. Other “III/V compound” semiconductor photocathodes.
6A002.a.2.b.	Image intensifier tubes...
6A002.a.3.	Non-“space-qualified” “focal plane arrays”...;
	<i>Note 3</i> 6A002.a.3. does not apply to the following “focal plane arrays” in this List: <ol style="list-style-type: none"> a. Platinum Silicide (PtSi) “focal plane arrays” having less than 10,000 elements;
	b. Iridium Silicide (IrSi) “focal plane arrays”. <i>Note 4</i> 6A002.a.3. does not apply to the following “focal plane arrays” in this List: <ol style="list-style-type: none"> a. Indium Antimonide (InSb) or Lead Selenide (PbSe) “focal plane arrays” having less than 256 elements; b. Indium Arsenide (InAs) “focal plane arrays”; c. Lead Sulphide (PbS) “focal plane arrays”; d. Indium Gallium Arsenide (InGaAs) “focal plane arrays”.

Category 6	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
	<p><i>Note 5</i> 6A002.a.3. does not apply to Mercury Cadmium Telluride (HgCdTe) “focal plane arrays” as follows in this List:</p> <ol style="list-style-type: none"> a. ‘Scanning Arrays’ having any of the following: <ol style="list-style-type: none"> 1. 30 elements or less; or 2. Incorporating time delay-and-integration within the element and having 2 elements or less; b. ‘Staring Arrays’ having less than 256 elements. <p><i>Technical Notes:</i></p> <ol style="list-style-type: none"> 1. ‘Scanning Arrays’ are defined as “focal plane arrays” designed for use with a scanning optical system that images a scene in a sequential manner to produce an image; 2. ‘Staring Arrays’ are defined as “focal plane arrays” designed for use with a non-scanning optical system that images a scene. <p><i>Note 6</i> 6A002.a.3. does not apply to the following “focal plane arrays” in this List:</p> <ol style="list-style-type: none"> a. Gallium Arsenide (GaAs) or Gallium Aluminium Arsenide (GaAlAs) quantum well “focal plane arrays” having less than 256 elements; b. Microbolometer “focal plane arrays” having less than 8,000 elements. <p><i>Note 7</i> 6A002.a.3.g. does not apply to the linear (1-dimensional) “focal plane arrays” specially designed or modified to achieve ‘charge multiplication’ having 4,096 elements or less.</p> <p><i>Note 8</i> 6A002.a.3.g. does not apply to the non-linear (2-dimensional) “focal plane arrays” specially designed or modified to achieve ‘charge multiplication’ having a maximum linear dimension of 4,096 elements and a total of 250,000 elements or less.</p>
6A002.b.	“Monospectral imaging sensors” and “multispectral imaging sensors”...
6A002.c.	<p>‘Direct view’ imaging equipment incorporating any of the following:</p> <ol style="list-style-type: none"> 1. Image intensifier tubes having the characteristics listed in 6A002.a.2.a. or 6A002.a.2.b. of this List; 2. “Focal plane arrays” having the characteristics listed in 6A002.a.3. of this List; or 3. Solid-state detectors having the characteristics listed in 6A002.a.1.;
6A002.e.	<p>Not used since 2008</p> <p><i>N.B.: Entry moved to 6A002.a.1.d. in 2008.</i></p>

Part 2 Dual-use list

Sensitive list of dual-use goods and technologies

Category 6	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
6A003.b.3.	Imaging cameras incorporating image intensifier tubes having the characteristics listed in 6A002.a.2.a. or 6A002.a.2.b. of this List; <i>Note:</i> 6A003.b.3. does not apply to imaging cameras specially designed or modified for underwater use.
6A003.b.4.	Imaging cameras incorporating “focal plane arrays” having any of the following: a. Incorporating “focal plane arrays” specified by 6A002.a.3.a. to 6A002.a.3.e. of this List; b. Incorporating “focal plane arrays” specified by 6A002.a.3.f. of this List; or c. Incorporating “focal plane arrays” listed in 6A002.a.3.g. of this List.
6A003.b.4.	<i>Note 1</i> ... <i>Note 2</i> ... <i>Note 3</i> ... <i>Note 4</i> ...
6A003.b.5.	Imaging cameras incorporating solid-state detectors specified by 6A002.a.1.;
6A004.c.	“Space-qualified” components for optical systems...
6A004.d.	Optical control equipment...
6A006.a.	Not used since 2006
6A006.a.1.	“Magnetometers”... Using “superconductive” (SQUID) “technology”...
6A006.a.2.	“Magnetometers” ... Using optically pumped or nuclear precession (proton/Overhauser) “technology” having a ‘sensitivity’ lower (better) than 2pT rms per square root Hz;
6A006.c.1.	“Magnetic gradiometers” using multiple “magnetometers” specified by 6A006.a.1. or 6A006.a.2. of this List;
6A006.d.	“Compensation systems” for the following: 1. Magnetic sensors specified by 6A006.a.2 and using optically pumped or nuclear precession (proton/Overhauser) “technology” that will permit these sensors to realise a ‘sensitivity’ lower (better) than 2 pT rms per square root Hz. 2. Underwater electric field sensors specified by 6A006.b.

Category 6 SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES	
	3. Magnetic gradiometers specified by 6A006.c. that will permit these sensors to realise a ‘sensitivity’ lower (better) than 3 pT/m rms per square root Hz.
6A006.e.	Underwater electromagnetic receivers incorporating magnetometers specified by 6A006.a.1. or 6A006.a.2. of this List.
6A006.g.	Not used since 2006
6A006.h.	Not used since 2006
6A008.d.	Radar systems...Capable of...
6A008.h.	Radar systems...Employing processing...
6A008.k.	Radar systems...Having “signal processing”...
6A008.l.3.	Not used
6B008	Pulse radar cross-section...
6B108	Systems specially designed for radar cross section measurement usable for “missiles” and their subsystems.
6D001	“Software” specially designed for the “development” or “production” of equipment specified by 6A004, 6A008 or 6B008 of this List.
6D003.a.	“Software” for the “real time processing” of acoustic data;
6E001	“Technology” according to...
6E002	“Technology” according to the General Technology Note for the “production” of equipment specified by 6A or 6B of this List.

Category 7 SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES	
7A117	“Guidance sets”, usable in “missiles” capable of achieving system accuracy of 3.33 % or less of the range (e.g., a “CEP” of 10 km or less at a range of 300 km), except “guidance sets” designed for missiles with a range under 300 km or manned aircraft.

Part 2 Dual-use list

Sensitive list of dual-use goods and technologies

Category 7	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
7B103	Test, calibration or alignment equipment specially designed for equipment specified in 7A117 above. <i>Note: 7B001 does not control test, calibration or alignment equipment for Maintenance Level I or Maintenance Level II.</i>
7D002	“Source code” for the operation and maintenance...
7D003.a.	“Software” specially designed or modified to...
7D003.b.	“Source code” for...
7D003.c.	Not used
7D003.d.1. to 4. & 7.	Not used
7D004.a. to d. & g.	“Source code” incorporating “development” “technology” specified by...
7D101	“Software” specially designed for the “use” of equipment specified in 7B003 or 7B103 above.
7E001 & 7E002	“Technology” according to the General Technology Note...
7E101	“Technology” according to the General Technology Note for the “use” of equipment specified in 7A117, 7B003, 7B103 and 7D101 above.

Category 8	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
8A001.b.	Manned, untethered submersible vehicles...
8A001.c.	Unmanned, tethered submersible vehicles...
8A001.d.	Unmanned, untethered submersible vehicles...

Category 8	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
8A002.b.	Systems specially designed or modified for the automated control of the motion of submersible vehicles specified by 8A001 of this List using navigation data having closed loop servo-controls and having any of the following: <ol style="list-style-type: none"> 1. Enabling... 2. Maintaining... 3. Maintaining...
8A002.h.	“Robots” specially designed for underwater use...
8A002.j.	Air independent power systems...
8A002.o.3.	Noise reduction systems for use on vessels...
8A002.p.	Pumpjet propulsion systems...
8D001	“Software” specially designed for the “development” or “production” of equipment in 8A of this List.
8D002	Specific “software”...
8E001	“Technology” according to the General Technology Note for the “development” or “production” of equipment specified by 8A of this List.
8E002.a.	“Technology” for the “development”, “production”, repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction.

Category 9	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
9A011	Ramjet, scramjet or combined cycle engines...
9A104	Sounding rockets, capable of delivering at least a 500 kg payload to a range of at least 300 km. <i>N.B.: See also 9A004.</i>

Sensitive list of dual-use goods and technologies

316

Defence and Strategic Goods List

Compilation No. 6

Compilation date: 8/4/15

Registered: 10/4/15

Category 9	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
9A116	Reentry vehicles, usable in “missiles”, and equipment designed or modified therefor, as follows, except for reentry vehicles designed for non-weapon payloads: a. Reentry vehicles; b. Heat shields and components therefor fabricated of ceramic or ablative materials; c. Heat sinks and components therefor fabricated of light-weight, high heat capacity materials; d. Electronic equipment specially designed for reentry vehicles.
9A119	Individual rocket stages, usable in complete rocket systems or “unmanned aerial vehicles”, capable of delivering at least a 500 kg payload to a range of 300 km, other than those specified in 9A005 or 9A007.a. above
9B001.b.	Ceramic cores or shells.
9B115	Specially designed “production equipment” for the systems, sub-systems and components specified in 9A005, 9A007.a., 9A008.d., 9A105.a., 9A106.c., 9A108.c., 9A116 or 9A119 above.
9B116	Specially designed “production facilities” for the space launch vehicles specified in 9A004, or systems, sub-systems, and components specified in 9A005, 9A007.a., 9A008.d., 9A104, 9A105.a., 9A106.c., 9A108.c., 9A116 or 9A119 above.
9D001	“Software” specially designed or modified for the “development” of equipment or “technology”, specified by 9A, 9B or 9E003 of this List.
9D002	“Software” specially designed or modified for the “production” of equipment specified by 9A or 9B of this List.
9D004.a.	Other “software”... 2D or 3D...
9D004.c.	Other “software”...”Software” specially...
9D101	“Software” specially designed for the “use” of goods specified in 9B116 above.
9E001	“Technology” according to the General Technology Note...
9E002	“Technology” according to the General Technology Note...
9E003.a.1.	Other “technology”...Gas turbine blades...

Part 2 Dual-use list

Sensitive list of dual-use goods and technologies

Category 9	SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
9E003.a.2. to 5. and 9E003.a.8. & 9E003.h.	Other “technology”...
9E101	“Technology” according to the General Technology Note for the “development” or “production” of goods specified in 9A104, 9A105.a., 9A106.c., 9A108.c., 9A116 or 9A119 above.
9E102	“Technology” according to the General Technology Note for the “use” of space launch vehicles specified in 9A004, 9A005, 9A007.a., 9A008.d., 9A104, 9A105.a., 9A106.c., 9A108.c., 9A116, 9A119, 9B115, 9B116 or 9D101 above.

Very sensitive list of dual-use goods and technologies

Note: This List is a sub-set of the items contained in the Sensitive List. The items in this List are considered to be very sensitive, requiring extreme care in their transfer. General Export Licences are not available for the export of the following very sensitive goods.

N.B.: Where abbreviated entries are used, see List of Dual-Use Goods and Technologies for full details. Text that differs from that in the List of Dual-Use Goods and Technologies is *shaded*.

Category 0	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
<p>All of Category 0 of Part 2 is included in the Very Sensitive List</p> <p><i>N.B.</i> For 0C003 and 0C004, only if for use in a “nuclear reactor” (within 0A001.a.).</p>	

Category 1	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
1A002.a.	“Composite” structures or laminates consisting of an organic “matrix” and materials specified by 1C010.c. or 1C010.d.
1B226	<p>Electromagnetic isotope separators designed for, or equipped with, single or multiple ion sources capable of providing a total ion beam current of 50 mA or greater.</p> <p><i>Note:</i> 1B226 includes separators:</p> <ol style="list-style-type: none"> a. Capable of enriching stable isotopes; b. With the ion sources and collectors both in the magnetic field and those configurations in which they are external to the field.
1B231	<p>Tritium facilities or plants, and equipment therefor, as follows:</p> <ol style="list-style-type: none"> a. Facilities or plants for the production, recovery, extraction, concentration, or handling of tritium; b. Equipment for tritium facilities or plants, as follows: <ol style="list-style-type: none"> 1. Hydrogen or helium refrigeration units capable of cooling to 23 K (-250°C) or less, with heat removal capacity greater than 150 W; 2. Hydrogen isotope storage or purification systems using metal hydrides as the storage or purification medium.

Part 2 Dual-use list

Very sensitive list of dual-use goods and technologies

Category 1	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
1B233	<p>Lithium isotope separation facilities or plants, and equipment therefor, as follows:</p> <ol style="list-style-type: none"> Facilities or plants for the separation of lithium isotopes; Equipment for the separation of lithium isotopes, as follows: <ol style="list-style-type: none"> Packed liquid-liquid exchange columns specially designed for lithium amalgams; Mercury or lithium amalgam pumps; Lithium amalgam electrolysis cells; Evaporators for concentrated lithium hydroxide solution. Ion exchange systems specially designed for lithium isotope separation, and specially designed component parts therefor; Chemical exchange systems (employing crown ethers, cryptands, or lariat ethers) specially designed for lithium isotope separation, and specially designed component parts therefor.
1C001	Materials specially designed for use as absorbers of electromagnetic waves...
1C012	Materials as follows...
1C233	<p>Lithium enriched in the lithium-6 (⁶Li) isotope to greater than its natural isotopic abundance, and products or devices containing enriched lithium, as follows: elemental lithium, alloys, compounds, mixtures containing lithium, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><i>Note: 1C233 does not control thermoluminescent dosimeters.</i></p> <p><i>Technical Note:</i></p> <p><i>The natural isotopic abundance of lithium-6 is approximately 6.5 weight per cent (7.5 atom per cent).</i></p>
1C235	<p>Tritium, tritium compounds, mixtures containing tritium in which the ratio of tritium to hydrogen atoms exceeds 1 part in 1000, and products or devices containing any of the foregoing.</p> <p><i>Note: 1C235 does not control a product or device containing less than 1.48×10^3 GBq (40 Ci) of tritium.</i></p>
1C351.d.4.	Ricin
1C351.d.5.	Saxitoxin
1E001	<p>“Technology” according to the General Technology Note for the “development” or “production” of equipment and materials specified by 1A002 or 1C of this List.</p>

Category 1	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
1E201	“Technology” according to the General Technology Note for the “use” of goods specified in 1B226, 1B231, 1B233, 1C233 or 1C235.
Category 2	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
	None
Category 3	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
3A228	Switching devices, as follows: <ul style="list-style-type: none"> a. Cold-cathode tubes, whether gas filled or not, operating similarly to a spark gap, having all of the following characteristics: <ul style="list-style-type: none"> 1. Containing three or more electrodes; 2. Anode peak voltage rating of 2.5 kV or more; 3. Anode peak current rating of 100 A or more; and 4. Anode delay time of 10 µs or less; <p><i>Note: 3A228 includes gas krytron tubes and vacuum spraytron tubes.</i></p>
	<ul style="list-style-type: none"> b. Triggered spark-gaps having both of the following characteristics: <ul style="list-style-type: none"> 1. An anode delay time of 15 µs or less; and 2. Rated for a peak current of 500 A or more.
3A231	Neutron generator systems, including tubes, having both of the following characteristics: <ul style="list-style-type: none"> a. Designed for operation without an external vacuum system; and b. Utilising electrostatic acceleration to induce a tritium-deuterium nuclear reaction.
3E201	“Technology” according to the General Technology Note for the “use” of equipment specified in 3A228.a., 3A228.b. or 3A231.
Category 4	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
	None
Category 5	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES

Part 2 Dual-use list

Very sensitive list of dual-use goods and technologies

Category 5 VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES	
Part 1	
5A001.b.5.	Digitally controlled radio receivers...
5A001.h.	Counter Improvised Explosive Device (IED) equipment and related equipment...
5D001.a.	“Software” specially designed for the “development” or “production” of equipment, functions or features specified by Category 5, Part 1 of this List.
5E001.a.	“Technology” according to the General Technology Note for the “development” or “production” of equipment, functions, features or “software” specified by Category 5, Part 1 of this List.
Part 2	None

Category 6 VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES	
6A001.a.1.b.1.	Object detection or location systems, having a sound pressure level exceeding 210 dB (reference 1 µPa at 1 m) and an operating frequency in the band from 30 Hz to 2 kHz.
6A001.a.2.a.1.	Hydrophones...Incorporating...
6A001.a.2.a.2.	Hydrophones...Incorporating flexible assemblies...
6A001.a.2.a.3.	Hydrophones...Having any...
6A001.a.2.a.5.	Hydrophones...Designed to operate ...
6A001.a.2.a.6.	Hydrophones...Designed for...
6A001.a.2.b.	Towed acoustic hydrophone arrays...
6A001.a.2.c.	Processing equipment, specially designed for real time application with towed acoustic hydrophone arrays, having “user accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;

Category 6	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
6A001.a.2.e.	Bottom or bay cable systems having any of the following: <ol style="list-style-type: none"> 1. Incorporating hydrophones... or 2. Incorporating multiplexed hydrophone group signal modules ...
6A001.a.2.f.	Processing equipment, specially designed for real time application with bottom or bay cable systems, having “user accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;
6A002.a.1.c.	“Space-qualified” solid-state detectors...
6A008.1.3.	Not used
6A203	High-speed cameras and imaging devices and components therefor, other than those specified in 6A003, as follows... <ol style="list-style-type: none"> a. Mechanical rotating mirror cameras, as follows, and specially designed components therefor: <ol style="list-style-type: none"> 1. Framing cameras with recording rates greater than 225,000 frames per second; 2. Streak cameras with writing speeds greater than 0.5 mm per microsecond; <p><i>Note: In 6A203.a. components of such cameras include their synchronizing electronics units and rotor assemblies consisting of turbines, mirrors and bearings.</i></p>
6A225	Velocity interferometers for measuring velocities exceeding 1 km/s during time intervals of less than 10 microseconds. <p><i>Note: 6A225 includes velocity interferometers such as VISARs (Velocity interferometer systems for any reflector) and DLIs (Doppler laser interferometers).</i></p>
6A226	Pressure sensors, as follows: <ol style="list-style-type: none"> a. Manganin gauges for pressures greater than 10 GPa; b. Quartz pressure transducers for pressures greater than 10 GPa.
6B008	Pulse radar cross-section...
6D001	“Software” specially designed for the “development” or “production” of equipment specified by 6A008, or 6B8 of this List.
6D003.a.	“Software”, as follows: ...

Part 2 Dual-use list

Very sensitive list of dual-use goods and technologies

Category 6	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
6E001	“Technology” according to the General Technology Note for the “development” of equipment or “software” specified by 6A, 6B, or 6D of this List.
6E002	“Technology” according to the General Technology Note for the “production” of equipment specified by 6A or 6B of this List.

Category 7	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
7D003.a.	“Software” specially designed or modified to...
7D003.b.	“Source code” for...

Category 8	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
8A001.b.	Manned, untethered submersible vehicles...
8A001.d.	Unmanned, untethered submersible vehicles...
8A002.o.3.b.	Active noise reduction or cancellation systems...
8D001	“Software” specially designed for the “development” or “production” of equipment specified by 8A of this List.
8E001	“Technology” according to the General Technology Note for the “development” or “production” of equipment specified by 8A of this List.

Category 9	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
9A011	Ramjet, scramjet or combined cycle engines...
9D001	“Software” specially designed or modified for the “development” of equipment or “technology” specified by 9A or 9E003 of this List.
9D002	“Software” specially designed or modified for the “production” of equipment specified by 9A of this List.

Category 9	VERY SENSITIVE LIST OF DUAL-USE GOODS AND TECHNOLOGIES
9E001	“Technology” according to the General Technology Note for the “development” of equipment or “software” specified by 9A011 or 9D of this List.
9E002	“Technology” according to the General Technology Note for the “production” of equipment specified by 9A011 of this List.
9E003.a.1.	Other “technology” ... Gas turbine blades...
9E003.a.3.a.	“Technology” “required” for ... Components manufactured from... Organic “composite” materials designed to operate above 588 K (315°C).

Part 3—Index

This index is for guidance only and is not part of the control text.

>>1<<

1-(2-nitrotriazolo)-2-dinitromethylene hydrazine

see NTNMH

1,1'-diacetyl ferrocene (CAS 1273-94-5)..... ML8.f.4.o

1,1R,1S-trimesoyl-tris(2-ethylaziridine) (HX-868, BITA)(CAS 7722-73-8)..... ML8.f.17

1,1,3,3,3-pentafluoro-2-(trifluoromethyl)-1-propene..... 1C450.a.2

1,1,3-trinitroazetidine

see TNAZ

1,1-diamino-2,2-dinitroethylene

see DADE

1,2,3-tris[1,2-bis(difluoroamino)ethoxy] propane

see TVOPA

1,2,4-butanetriol

see 1,2,4-trihydroxybutane

1,2,4-trihydroxybutane (CAS 3068-00-6)..... ML8.g.8

1,2-bis (2-chloroethylthio) ethane (CAS 3563-36-8)..... ML7.b.2

1,3,3-trinitroazetidine

see TNAZ

1,3,5,7-tetraacetyl-1,3,5,7-tetraaza cyclo-octane

see TAT

1,3,5,7-tetranitro-1,3,5,7-tetraza-cyclooctane

see HMX and derivatives

1,3,5-trichlorobenzene (CAS 108-70-3)..... ML8.g.7

1,3,5-trinitro-1,3,5-triaza-cyclohexane

see RDX and derivatives

1,3-bis (2-chloroethylthio)-n-propane (CAS 63905-10-2)..... ML7.b.2

1,3-dinitro-1,3-diazetidine

see DNAD

1,4,5,8-tetraazadecalin (CAS 5409-42-7)..... ML8.g.6

1,4,5,8-tetranitro-1,4,5,8-tetraazadecalin

see TNAD

1,4,5,8-tetranitro-pyridazino[4,5-d]pyridazine

see TNP

1,4-bis (2-chloroethylthio)-n-butane (CAS 142868-93-7)..... ML7.b.2

1,4-dihydrazine nitrate

see 3,6-dihydrazino tetrazine nitrate

1,4-dinitrodifurazanopiperazine

see DDFP

1,5-bis (2-chloroethylthio)-n-pentane (CAS 142868-94-8)..... ML7.b.2

10-chloro-5,10-dihydrophenarsazine (CAS 578-94-9)..... 1A004.a.4, ML7.d.5

1-amino-3,5-dinitro-1,2,4-triazole

see ADNT

1-fluoro-2,4-dinitroimidazole

see FDIA	
1-methyl-2-pyrrolidinone	ML8
1-N-(2-nitrotriazolo) 3,5-dinitrotriazole	
see NTDNT	
1-N-(2-nitrotriazolo)-4-nitrotetrazole	
see NTNT	
1-picryl-2,4,5-trinitroimidazole	
see PTIA	
1-picryl-3,5-dinitrotriazole	
see PDNT	
>>=====<<	
>>2<<	
2-(5-cyanotetrazolato) penta amine-cobalt (III) perchlorate	
see CP	
2,2-dinitropropanol	ML8
2,4,5-trichlorophenoxyacetic acid	
see Agent Orange	
2,4,6,8-tetranitro-2,4,6,8-tetraazabicyclo [3,3,0]-octanone-3	
see K-55	
2,4,6-trinitro-2,4,6-triazacyclohexanone	
see RDX and derivatives	
2,4,6-trinitroresorcinol	ML8
2,4,6-trinitrotoluene	ML8
2,4-dichlorophenoxyacetic acid	
see Agent Orange	
2,4-dinitroimidazole	
see DNI	
2,6-bis(picrylamino)-3,5-dinitropyridine	
see PYX	
2,6-diamino-3,5-dinitropyrazine-1-oxide	
see DDPO	
2-chloro-1-phenylethanone (CAS 532-27-4)	1A004.a.4, ML7.d.3
2-chloroethanol (CAS 107-07-3)	1C350
2-chloroethylchloromethylsulphide (CAS 2625-76-5)	ML7.b.2
2-chlorophenyl methylene propanedinitrile	1A004.a.4, ML7.d.2
2-chlorovinylchloroarsine (CAS 541-25-3)	ML7.b.2
2-hydroxyethylhydrazine nitrate	1C111.a.4
2-NDPA	
see 2-nitrodiphenylamine	
2-nitrodiphenylamine	1C111.c.3, ML8
2-nitroimino-5-nitro-hexahydro-1,3,5-triazine	
see NNHT	
2-nitrotriazole 5-dinitramide	
see NTDNA	
2-oxo-4,6-dinitroamino-s-triazine	
see DNAM	
2-propenolato-1 methyl, n-propanolatomethyl butanolato-1, tris[dioctyl] pyrophosphate	
see titanium, titanium alloys and titanium compounds	

>>=====<<	
>>3<<	
3,3,7,7-tetrakis(difluoroamine) octahydro-1,5-dinitro-1,5-diazocine	
see TEDDZ	
3,3-diamino-2,2,4,4,6,6-hexanitrobiphenyl	
see DIPAM	
3,3-dinitro-5,5-bi-1,2,4-triazole	
see DBT	
3,6-dihydrazino tetrazine nitrate	1C111.a.4
3-difluoroaminomethyl-3-azidomethyl oxetane	
see FAMAO	
3-hydroxy-1-methylpiperidine (CAS 3554-74-3)	1C350
3-nitrazo-1,5-pentane diisocyanate (CAS 7406-61-9)	ML8.f.14
3-nitro-1,2,4-triazol-5-one	
see NTO	
3-quinuclidinol (CAS 1619-34-7)	1C350
3-quinuclidinyl benzilate (CAS 6581-06-2)	ML7.b.3
3-quinuclidone (CAS 3731-38-2)	1C350
>>=====<<	
>>4<<	
4-amino-3,5-dihydrazino-1,2,4-triazole dinitramide	
see ADHTDN	
4-hydroxybenzoic acid	1C008.b.2
4-NDPA	
see 4-nitrodiphenylamine	
4-nitrodiphenylamine	ML8
>>=====<<	
>>5<<	
5,7-diamino-4,6-dinitrobenzofurazane-1-oxide	
see CL-14	
5-azido-2-nitrotriazole	ML8.a.32
>>=====<<	
>>6<<	
6-hydroxy-2 naphthoic acid, in thermoplastic liquid crystal copolymers	1C008.b.2
>>=====<<	
>>7<<	
7-amino-4,6-dinitrobenzofurazane-1-oxide	
see ADNBF	
>>=====<<	
>>A<<	
ablative liners	9A106
abradable materials, coating technology	2E003
abrin	1C351.d.12
absolute reflectance measurement equipment	
see reflectance measuring equipment	
absorbers of electromagnetic waves	
see electromagnetic equipment	
absorption and distillation columns	

see distillation and absorption columns	
accelerometers	7A001, 7A101, 7A103, 7B103
accessories, for non-military firearms	ML904
acetyl ferrocene (CAS 1271-55-2)	ML8.f.4.o, 1C111.c.6
acoustic systems, equipment and components	
see also underwater operations equipment	
.....	6A001
acoustic beacons	6A001.a.1
acoustic projectors	6A001.a.1
acoustic vibration test equipment	9B006
acoustic wave equipment	3A001
acoustic-optic signal processing equipment	3A001.c.3
bulk acoustic wave equipment	3A001.c.2
diver deterrent acoustic systems	6A001.c
environmental chambers	9B106
hydrophones	6A001.a.2, 6A001.a.2, 6D003.a.2
marine acoustic systems	6A001
noise reduction systems	8A002, 8E002
sonar navigation systems	6A001.a.2, 7A008
surface acoustic wave equipment	3A001.c.1
actinides, crucibles resistant to	2A225
Actinium 225 and 227	
see radionuclides	
active flight control system systems and software	
see flight control systems	
active magnetic bearing systems	
see bearings	
active pulsed Doppler missile warning sensors	ML4
actively cooled mirrors	
see optical mirrors	
adamsite	
see 10-chloro-5,10-dihydrophenarsazine	
adaptive optics	ML19, 6A004
ADCS	
see analogue-to-digital converters	
additives to fuels, explosives and propellants	ML8
adducted polymer ferrocene derivatives	ML8.f.4
ADHTDN (CAS 1614-08-0)	ML8.a.32
adjustable flow path geometry systems	9E003.a.10
ADN (CAS 140456-78-6)	ML8.d.1
ADNBF (CAS 97096-78-1)	ML8.a.1
ADNT	ML8.a.32
advanced persistent threat (APT)	
see intrusion software	
aerodynamic isotope separation systems	
see isotope separation plants, systems, equipment and components	
aerodynamic test facilities	

see wind tunnels	
aero-engines and components	
see also gas turbine engines	
fan turbine control systems.....	9E003.a.10
for military use	ML10
for missiles	9A105
for unmanned airborne vehicles	9A012.b.12
gas turbine engines	9A001
jet combustion regulation equipment	9A118
pulse jet engines	9A111
superplastic forming and diffusion bonding tools	1B003
turbofan engines	9A101, 9A102
turbojet engines	9A101
turboprop engines	9A102
aerosol challenge testing chambers.....	2B352
aerosol generating units	9A350
aflatoxins	1C351.d.11
African horse sickness virus	1C352.a.17
African swine fever virus	1C352.a.1
Agent Orange.....	ML7.b.4
agitators for use in reaction vessels.....	2B350
AHRS	
see attitude control equipment	
air conditioning units, designed to filter toxic agents.....	ML7.f.1
air data systems.....	7D003.d.6, 7E004.a.2
air guns	
see also firearms and firearm components	
.....	ML905
air independent power systems	8A002, ML9.b.4
air traffic control software.....	6D003.d.1
airborne altimeters	7A006
airborne vehicles, equipment and components	
see aircraft and aircraft components	
aircraft and aircraft components	
see also aero-engines and components	
see also navigation systems, equipment and components	
see also unmanned airborne vehicles, systems and components	
.....	1B232
equipment for the production of	1B001
for military use	ML10
global navigation satellite systems	7A105
made from fluorinated compounds.....	1A001
missile protection systems	ML4
navigation software	7D003
superplastic forming and diffusion bonding tools	1B003
aircraft engines	
see aero-engines and components	
aircraft fuels	

see fuels and propellants and related equipment	
aircraft simulators	
see simulators and simulator components	
airfoil-to-disk combination joining equipment	9B004, 9E003.a.6
Al--	
see aluminium, aluminium compounds and aluminium alloys	
alane (CAS 7784-21-6)	ML8.c.2
alexandrite lasers	6A005
alkyl phosphonyl difluorides	ML7.c.1
alkylated salts, as toxic agents	ML7.b.1, ML7.c.2
alkylphenylene ethers and thio-ethers	1C006.b.1
all wheel drive utility vehicles	
see also land vehicles and components	
.....	ML6
alloys	
see also name of metal, e.g. aluminium	
.....	1C002
equipment for the production of	1B002
allylhydrazine, as propellant	1C111.a.4
alpha-bromobenzeneacetonitrile (CAS 5798-79-8)	1A004.a.4, ML7.d.1
alpha-emitting radionuclides	1C236
altimeters	7A006, 7A106
aluminium, aluminium compounds and aluminium alloys	
alloys	1C002.b.4, 1C002.c.1, 1C202, 2E003.b.2
Al-Si-polyester coating technology	2E003
alumina fibres	1B001.d.4, 1C010
aluminides	1C002, 2E003
aluminium hydride.....	ML8.c.2
aluminium oxides	1E.c.1
conversion equipment.....	1B001.d.4
fibres made from Al ₂ O ₃	1C007.f.1
spherical powdered fuel.....	1C111.a.1, ML8.c.8
substrate materials	3C003, 3C005, 3C006
superplastic forming and diffusion bonding tools for.....	1B003
valves containing.....	2A226
amalgam electrolysis cells	
see electrolytic cells	
aminodinitrobenzofuroxan	
see ADNBF	
amiton (CAS 78-53-5)	1C450.a.1
AMMO (CAS 90683-29-7)	ML8.e.1
ammonia	
see nitrogen and nitrogen compounds	
ammonia--hydrogen exchange plants (crackers)	
see also distillation and absorption columns	
.....	0B004.a.2, 0B004.b.3, 0B004.b.5

ammunition and components	
see also explosives and explosive devices	
see also firearms and firearm components	
for non-military firearms	ML902
for smooth-bore weapons	ML3
land vehicles for transportation of	ML6
amorphous alloy strips	1C003
amphibious vehicles	ML6
amplifiers, microwave	
see microwave equipment and components	
amplifiers, solid state amplifiers	3A001.b.4
analogue computers, ruggedised	4A101
analogue instrumentation tape recorders	
see recording equipment	
analogue-to-digital converters	3A001.a.2, 3A001.a.5, 3A003, 4A003
analysers	
see network analysers	
see signal processing equipment	
Andes virus	1C351.a.1
anechoic chambers	9B106
angular accelerometers	7A001
angular measuring instruments	
see dimensional inspection and measuring systems	
angular rate sensors	7A002
angular--linear inspection equipment (hemishells)	
see dimensional inspection and measuring systems	
animal pathogens	1C352
anisotropic plasma dry etching equipment	3B001
anti-friction bearings and bearing systems	2A001
antimony compounds, substrate materials containing	3C003, 3C004
anti-tank weapons	ML2
AP (CAS 7790-98-9)	ML8.d.2
approach parachutes	ML10.h.6
aramid fibres and filamentary materials	1C210
arc remelt furnaces	2B227
argon arc light systems, for underwater use	8A002.g.2
argon ion lasers	6A205
armour	
see protective and decontamination clothing and equipment	
armoured plate	ML13
armoured vehicles and related equipment	
see also land vehicles and components	
.....	ML6
arms	
see firearms and firearm components	
aromatic polyamide fibre technology	1E
aromatic polyamide-imides	1C008.a.2, 1C008.a.3
aromatic polyetherimides	1C008.a.4

array processors	
see also signal processing equipment	
	4A003
arsenic compounds	
arsenic trichloride (CAS 7784-34-1)	1C350
substrate materials for integrated circuits	3C003, 3C004
aspheric optical elements	6A004
asymmetric algorithm encryption equipment	5A002.a.1
ATC software	
see air traffic control software	
atomic frequency standards	3A002
atomic vapour laser isotope separation equipment	
see isotope separation plants, systems, equipment and components	
attitude control equipment	
see also navigation systems, equipment and components	
	7A116
Aujeszkys disease virus	
see herpes virus	
authentication equipment	
see also cryptographic equipment	
	ML11
automated command and control systems	ML11
automatic loading multi-chamber central wafer handling systems	3B001
automatic pilots	7A103
automatic target tracking equipment	6A008
automatic weapons	ML1
autonomous programmable airborne vehicles	
see unmanned airborne vehicles, systems and components	
autonomous submersible vehicles	
see unmanned submersible vehicles	
avian influenza virus	1C352.a.2
avionics EMP/EMI protection technology	
see electromagnetic equipment	
avionics systems	
see aircraft and aircraft components	
see navigation systems, equipment and components	
AVLIS	
see isotope separation plants, systems, equipment and components	
azides and azide complexes	ML8
azido groups, compounds containing	ML8.e.6
azidomethylmethyloxetane and its polymers	
see AMMO	
>>=====<<	
>>B<<	
Bacillus anthracis	1C351.c.1
bacterial cultures	1C351, 1C354
baffles, for rotor tubes	0B001.b.5
balancing machines	2B119

ball and solid roller bearings	
see also bearings	
.....	2A001
ballistic protection materials and components	ML13, ML6
BAMO (CAS 17607-20-4)	ML8.e.2
band-pass filters	
see tunable band-pass filters	
base-ventilated propeller systems	8A002.o.2
basic copper salicylate (CAS 62320-94-9)	ML8.f.1
batch mixers with vacuum capabilities	1B117
bathymetric survey systems	6A001.a.1
batteries (electrical)	
see cells and batteries (electrical)	
bay cable systems	6A001.a.2, 6D003.a.4
BCMO (CAS 142173-26-0)	ML8.g.1
BDNPA (CAS 5108-69-0)	ML8.e.3
BDNPF (CAS 5917-61-3)	ML8.e.4
BDNTA	ML8.a.32
beam steering mirrors	6A004.a.4
bearings	
active magnetic bearing systems	2A001
anti-friction bearings and bearing systems	2A001
ball bearings	2A001
magnetic bearings	2A001, 8A002.o.3
magnetic suspension bearings	0B001.b.7
pivot-cup assembly bearings	0B001.b.8
radial ball bearings	2A101
silent bearings	ML9
solid roller bearings	2A001
bellows seal valves	2A226
for aerodynamic separation equipment	0B001.d.6
for gas centrifuges	0B001.b.13
for gaseous diffusion separators	0B001.c.6
bellows, for rotor tube support	0B001.b.4
bellows-forming mandrels and dies	
see rotor assemblies for gas centrifuges	
Bellows-sealed scroll-type compressors and vacuum pumps	2B233
benzoic acid (CAS 76-93-7)	1C350
benzyl bromide	ML7
benzyl iodide	ML7
beryllium, beryllium alloys and beryllium compounds	1C230
as powder fuel.....	ML8.c.5
as propellant	1C111.a.2.b
coating technology.....	2E003
substrate blanks of	6C004
BHEGA (CAS 17409-41-5)	ML8.f.2
binary precursors to CW agents	
see chemical warfare agents and precursors	

binders (chemical)	ML8
biocatalysts	ML22.b.5, ML7.i.1
biological warfare agents	
see also toxicological agents	
animal pathogens	1C352
bacterial cultures	1C351, 1C354
cell cultures	ML22.b.4, ML7, ML7.i.2
containment and handling facilities	2B352
fungi	1C351, 1C354
handling equipment	2B352
human pathogens	1C351
mycoplasmas	1C352
pathogens, zoonoses and toxins	1C351
plant pathogens	1C354
protective clothing and equipment against	1A004.a.1, 1A004.b.1
sensors and detectors for	1A004.c.1
software for determining effects of	ML21.b.3
technology for development and production of	ML22.b.3
virus cultures	1C351, 1C354, ML7.i.2
biopolymer technology	ML22.b.4
bioreactors	
see fermenters for pathogenic cultures	
biphenylene, in thermoplastic liquid crystal copolymers	1C008.b.1
bis (2,2-dinitropropyl)acetal	
see BDNPA	
bis (2,2-dinitropropyl)formal	
see BDNPF	
bis (2-chloroethyl) ethylamine (CAS 538-07-8)	ML7.b.2
bis (2-chloroethyl) methylamine (CAS 51-75-2)	ML7.b.2
bis (2-chloroethyl) sulphide (CAS 505-60-2)	ML7.b.2
bis (2-chloroethylthio) methane (CAS 63869-13-6)	ML7.b.2
bis (2-chloroethylthioethyl) ether (CAS 63918-89-8)	ML7.b.2
bis (2-chloroethylthiomethyl) ether (CAS 63918-90-1)	ML7.b.2
bis (2-chlorovinyl) chloroarsine (CAS 40334-69-8)	ML7.b.2
bis (2-fluoro-2,2-dinitroethyl) formaldehyde	
see FEFO	
bis (2-hydroxyethyl) glycolamide	
see BHEGA	
bis (2-methyl aziridinyl) 2-(2-hydroxypropanoxy) propylamino phosphine oxide	
see BOBBA 8	
bis (2-methyl aziridinyl) methylamino phosphine oxide (CAS 85068-72-0)	
see methyl BAPO	
bisazidomethyloxetane	
see BAMO	
bischloromethyloxetane	
see BCMO	
bis-dinitrotriazole amine	
see BDNTA	

bismaleimides	1C008.a.1
bismuth, high-purity	1C229
black powder	ML8
black-out lighting for vehicles	ML6
bladders made from fluoroelastomers	1A001
blades for turbine engines see gas turbine engines	
blast initiation systems see detonation equipment	
blindness, systems designed to cause	ML19
blowers and compressors	1B232
for aerodynamic separation equipment.....	0B001.d.3
for gaseous diffusion separators	0B001.c.3
for hydrogen sulphide gas circulation	0B004.b.2
for molecular laser isotope separation equipment	0B001.h.3
bluetongue virus	1C352.a.3
BNCP (CAS 117412-28-9)	ML8.a.2
BNNII	ML8.a.16
BNO (CAS 9003-18-3)	ML8.f.3
boats, military see marine vessels, equipment and components	
BOBBA 8	ML8.f.11
body armour see also protective and decontamination clothing and equipment	1A005, ML13
bomb disposal equipment see also explosives and explosive devices	1A006
bombing computers	ML5
bomblets see submunitions	
bombs see also detonation equipment see also explosives and explosive devices	ML4
borides of titanium see titanium, titanium alloys and titanium compounds	
boron and boron compounds	1C011
as propellants	1C111.a.2.d
boron nitrides.....	1E.c.2, 2E003
in fibrous form.....	1C010
in powder fuel.....	ML8.c.5
isotope enriched.....	1C225
boron equivalence	0C004
bottom cable systems	6A001.a.2, 6D003.a.1, 6D003.a.2, 6D003.a.3, 6D003.a.4
botulinum toxins	1C351.d.1
Brayton cycle engines, for underwater use	8A002.j.1
breathing equipment	

for high altitude parachutists	ML10.h.8
for use in military aircraft.....	ML10
full and half suits or hoods	2B352.f.1
gas masks and components.....	1A004
self-contained diving apparatus	8A002, ML17
bremsstrahlung accelerators	3A003
bridges and bridge laying vehicles	ML17
bromine and bromine compounds	
see also alpha-bromobenzeneacetonitrile	
bromoacetone	ML7
bromomethylethylketone	ML7
Brucella abortus.....	1C351.c.2
Brucella melitensis.....	1C351.c.3
Brucella suis	1C351.c.4
brush seals for gas turbine engines	9B003
BTAT (Bis(2,2,2-trinitroethyl)-3,6-diaminotetrazine).....	ML8.a.38
BTTN (CAS 6659-60-5).....	ML8.e.5
bulk acoustic wave equipment	
see acoustic systems, equipment and components	
bullet cups	ML3
bullet proof and resistant materials and clothing	
see protective and decontamination clothing and equipment	
bullet-proof tyre casings.....	ML6
buoyant electric conducting cable	ML4
Burkholderia mallei.....	1C351.c.11
Burkholderia pseudomallei.....	1C351.c.12
Burkholderia solanacearum	
see Ralstonia solanacearum	
butacene (CAS 125856-62-4)	ML8.f.4
butadienenitrileoxide	
see BNO	
butanetrioltrinitrate	
see BTTN	
butyl 2-chloro-4-fluorophenoxyacetate.....	ML7.b.4
BZ	
see 3-quinuclidinyl benzilate	
>>=====<<	
>>C<<	
C3I (command, communications, control and intelligence) software.....	ML21.b.4
CA	
see alpha-bromobenzeneacetonitrile	
cables	
see also communications systems	
see also optical fibre, equipment and accessories	
with intrusion detection capabilities	5A002.a.8
cadmium, cadmium alloys and cadmium compounds	
cadmium telluride	6C002.b.2
cadmium zinc telluride	6C002, 6C002.b.1

calcium and calcium compounds

calcium fluoride.....	2A225.a.2
calcium zirconate.....	2A225.a.2
high-purity.....	1C227

Californium 253

see radionuclides

camera systems, camera equipment, and camera components

see also optical components and equipment

.....	6A003, 6A203
electron tube cameras	6A203.c
electronic cameras	6A003.a.4, 6A003.a.5
framing cameras	6A203.a.1, 6A203.b
high speed cameras.....	6A003.a.1, 6A003.a.2
imaging cameras.....	6A003, ML15
instrumentation cameras.....	6A003
low-light-level television camera tubes.....	ML15
mechanical high speed cameras.....	6A003.a.2
plug-ins for instrumentation cameras	6A003.a.6
pyroelectric television camera tubes.....	ML15
radiation hardened	6A204
scanning cameras.....	6A003.b.2
streak cameras	6A003.a.3, 6A203.a
underwater cameras.....	8A002
video cameras	6A003.b.1, 6A203, 8A002.d.1
with focal plane arrays.....	6A003.b.4
with solid state sensors	6A003.b.5, 6A203.c

cannons, large calibre.....ML2**capacitors** 3A001.e.2, 3A201**carbides, coating technology.....** 2E003**carbines**

see also firearms and firearm components

.....ML1**carbon dioxide lasers.....** 6A205**carbon fibre and filamentary materials**

see also fibrous and filamentary materials

..... 1A002, 1C010, 1C010.e.2, 1C210**carbon graphite materials**

see graphite

carbon monoxide lasers..... 6A005.d.3**carbon--carbon materials**

see also pyrolysed materials and pyrolysis equipment

..... 1A102, 1C102

coating technology..... 2E003

for liquid rocket propulsion systems

one-piece thrust chambers and exit cones

carbonyl chloride

see phosgene (carbonyl chloride)

carbonyl dichloride..... 1C450.a.4

carboranes	ML8.c.3
carboxy/carboxyl-terminated polybutadiene	1C111.b.1
cargo parachutes see also parachutes	
.....	ML10.h.2
cartridge links see also ammunition and components	
.....	ML3
CAS 100-15-2 see N-methyl-P-nitroaniline	
CAS 10025-67-9 see sulphur compounds	
CAS 10025-87-3 see phosphorus and phosphorus compounds	
CAS 10026-13-8 see phosphorus and phosphorus compounds	
CAS 100-37-8 see diethylaminoethanol	
CAS 10102-03-1 see dinitrogen pentoxide	
CAS 10102-44-0 see nitrogen dioxide	
CAS 102-71-6 see triethanolamine	
CAS 103850-22-2 see neopentyl[diallyl]oxy, tri[dioctyl]phosphato-titanate	
CAS 10544-72-6 see dinitrogen tetroxide	
CAS 10544-73-7 see dinitrogen trioxide	
CAS 10545-99-0 see sulphur compounds	
CAS 1066-50-8 see ethyl phosphonyl dichloride	
CAS 107-07-3 see 2-chloroethanol	
CAS 108-18-9 see di-isopropylamine	
CAS 108-70-3 see 1,3,5-trichlorobenzene	
CAS 110438-25-0 see neopentyl[diallyl]oxy, tri[dioctyl]phosphato-titanate	
CAS 111-22-8 see triethylene glycol dinitrate	
CAS 111-48-8 see thiodiglycol	
CAS 115029-35-1 see RDX and derivatives	

- CAS 116-17-6**
see triisopropyl phosphite
- CAS 117412-28-9**
see BNCP
- CAS 117907-74-1**
see CL-14
- CAS 119-27-7**
see DNAN (2,4-dinitroanisole)
- CAS 12036-31-6**
see lead and lead compounds
- CAS 12069-32-8**
see boron and boron compounds
- CAS 12024-11-2**
see gallium selenide
- CAS 121-45-9**
see trimethyl phosphite
- CAS 121-82-4**
see RDX and derivatives
- CAS 122-52-1**
see triethyl phosphite
- CAS 124-40-3**
see dimethylamine
- CAS 124782-15-6**
see HBIW
- CAS 125735-38-8**
see dinitroazetidine-T-butyl salt
- CAS 125856-62-4**
see butacene
- CAS 1271-55-2**
see acetyl ferrocene
- CAS 1273 89 8**
see ethyl ferrocene
- CAS 1273-94-5**
see 1,1'-diacetyl ferrocene
- CAS 1273-97-8**
see diethyl ferrocene
- CAS 1274-00-6**
see pentyl ferrocene
- CAS 1274-08-4**
see dibutyl ferrocene
- CAS 217464-38-5**
see GUDN (Guanylurea dinitramide)
- CAS 130256-72-3**
see K-55
- CAS 130400-13-4**
see NNHT
- CAS 1313-82-2**
see sodium and sodium compounds
-

CAS 1314-80-3	
see triethanolamine	
CAS 1333-83-1	
see sodium and sodium compounds	
CAS 13465-08-2	
see HAN	
CAS 135285-90-4	
see CL-20	
CAS 135877-16-6	
see TNAD	
CAS 139-87-7	
see ethyldiethanolamine	
CAS 140456-78-6	
see ADN	
CAS 142173-26-0	
see BCMO	
CAS 142868-93-7	
see 1,4-bis (2-chloroethylthio)-N-butane	
CAS 142868-94-8	
see 1,5-bis (2-chloroethylthio)-N-pentane	
CAS 143178-24-9	
see GAP	
CAS 143-33-9	
see sodium and sodium compounds	
CAS 143850-71-9	
see hexanitroadamantane	
CAS 14450-60-3	
see lead and lead compounds	
CAS 1445-76-7	
see O-isopropyl methylphosphonochloridate	
CAS 1498-40-4	
see ethyl phosphinyl dichloride	
CAS 151-50-8	
see potassium and potassium compounds	
.....	1C350
CAS 15588-62-2	
see HAP	
CAS 15715-41-0	
see diethyl methylphosphonite	
CAS 15748-73-9	
see lead and lead compounds	
CAS 1614-08-0	
see ADHTDN	
CAS 1619-34-7	
see 3-quinuclidinol	
CAS 1630-08-6	
see DATB	
CAS 16142-89-5	

-
- see Thallium arsenic selenide
- CAS 16893-85-9**
see sodium and sodium compounds
- CAS 17003-79-1**
see FEFO
- CAS 17096-47-8**
see NENAs
- CAS 17215-44-0**
see DIPAM
- CAS 17409-41-5**
see BHEGA
- CAS 17607-20-4**
see BAMO
- CAS 17702-41-9**
see decaborane
- CAS 18433-84-6**
see pentaboranes
- CAS 19136-34-6**
see lead and lead compounds
- CAS 194486-77-6**
see DDPO
- CAS 19624-22-7**
see pentaboranes
- CAS 19899-80-0**
see DNAM
- CAS 20062-22-0**
see HNS
- CAS 20773-28-8**
see dicyclopentyl ferrocene
see HNF
- CAS 20936-32-7**
see lead and lead compounds
- CAS 229176-04-9**
see TNP
- CAS 2404-03-7**
see diethyl-N,N-dimethylphosphoramidate
- CAS 2465-65-8**
see O,O-diethyl phosphorothioate
- CAS 25243-36-1**
see TACOT
- CAS 257-07-8**
see dibenz-(B,F)-1,4-oxazephine
- CAS 2625-76-5**
see 2-chloroethylchloromethylsulphide
- CAS 2691-41-0**
see HMX and derivatives
- CAS 2698-41-1**
see 2-chlorophenyl methylene propanedinitrile
-

-
- CAS 27814-48-8**
see PGN
- CAS 27978-54-7**
see hydrazine and hydrazine compounds
- CAS 298-06-6**
see O,O-diethyl phosphorodithioate
- CAS 30003-46-4**
see DBT
- CAS 302-01-2**
see hydrazine and hydrazine compounds
- CAS 3058-38-6**
see TATB
- CAS 3068-00-6**
see 1,2,4-trihydroxybutane
- CAS 31904-29-7**
see N-butyl-ferrocene
- CAS 3554-74-3**
see 3-hydroxy-1-methylpiperidine
- CAS 3563-36-8**
see 1,2-bis (2-chloroethylthio) ethane
- CAS 37206-42-1**
see catocene
- CAS 3731-38-2**
see 3-quinuclidone
- CAS 376-90-9**
see FPF-1
- CAS 37836-27-4**
see hydrazine and hydrazine compounds
- CAS 38082-89-2**
see PYX
- CAS 382-21-8**
see PFIB
- CAS 3982-91-0**
see thiophosphoryl chloride
- CAS 4000-16-2**
see TAGN
- CAS 40334-69-8**
see bis (2-chlorovinyl) chloroarsine
- CAS 41378-98-7**
see TAT
- CAS 4261-68-1**
see N,N-diisopropyl-(beta)-aminoethyl chloride hydrochloride
- CAS 430-78-4**
see ethyl phosphinyl difluoride
- CAS 464-07-3**
see pinacolyl alcohol
- CAS 479-45-8**
see tetryl
-

CAS 505-60-2

see bis (2-chloroethyl) sulphide

CAS 506-59-2

see dimethylamine hydrochloride

CAS 506-77-4

see cyanogen chloride

CAS 5108-69-0

see BDNPA

CAS 51-75-2

see bis (2-chloroethyl) methylamine

CAS 5213-49-0

see DNI

CAS 5299-64-9

see N-nonanoylmorpholine

CAS 53159-39-0

see TVOPA

CAS 532-27-4

see 2-chloro-1-phenylethanone

see phenylacetyl chloride

CAS 538-07-8

see bis (2-chloroethyl) ethylamine

CAS 540-73-8

see symmetrical dimethyl hydrazine

CAS 5409-42-7

see 1,4,5,8-tetraazadecalin

CAS 541-25-3

see 2-chlorovinylchloroarsine

CAS 55510-03-7

see TNGU

CAS 55510-04-8

see DINGU

CAS 555-77-1

see tris (2-chloroethyl) amine

CAS 55-63-0

see nitroglycerin

CAS 556-88-7

see nitroguanidine

CAS 57-14-7

see unsymmetrical dimethyl hydrazine

CAS 57-39-6

see MAPO and derivatives

CAS 57856-11-8

see O-ethyl-2-di-isopropylaminoethyl methylphosphonite

CAS 578-94-9

see 10-chloro-5,10-dihydrophenarsazine

CAS 5798-79-8

see alpha-bromobenzeneacetonitrile

-
- CAS 5842-07-9**
see N,N-diisopropyl-(beta)-aminoethane thiol
- CAS 5917-61-3**
see BDNPF
- CAS 59400-80-5**
see Potassium titanyl arsenate
- CAS 603-33-8**
see TPB
- CAS 60-34-4**
see monomethyl hydrazine
- CAS 6163-75-3**
see dimethyl ethylphosphonate
- CAS 62320-94-9**
see basic copper salicylate
- CAS 637-39-8**
see triethanolamine hydrochloride
- CAS 63869-13-6**
see bis (2-chloroethylthio) methane
- CAS 63905-10-2**
see 1,3-bis (2-chloroethylthio)-N-propane
- CAS 63918-89-8**
see bis (2-chloroethylthioethyl) ether
- CAS 63918-90-1**
see bis (2-chloroethylthiomethyl) ether
- CAS 6581-06-2**
see 3-quinuclidinyl benzilate
- CAS 6659-60-5**
see BTTN
- CAS 676-83-5**
see methyl phosphinyl dichloride
- CAS 676-97-1**
see methyl phosphonyl dichloride
- CAS 676-98-2**
see methylphosphonothioic dichloride
- CAS 676-99-3**
see methyl phosphonyl difluoride
see phosgene (carbonyl chloride)
- CAS 677-43-0**
see N,N-dimethyl phosphoramidic dichloride
- CAS 683-08-9**
see diethyl methylphosphonate
- CAS 68411-07-4**
see lead and lead compounds
- CAS 68412-45-3**
see TEPAN
- CAS 68412-46-4**
see TEPANOL
- CAS 693-21-0**
-

- see diethylene glycol dinitrate
 - CAS 70247-32-4**
 - see CP
 - CAS 70890-46-9**
 - see DNBT
 - CAS 7406-61-9**
 - see 3-nitroazido-1,5-pentane diisocyanate
 - CAS 74-90-8**
 - see hydrogen and hydrogen compounds
 - CAS 753-59-3**
 - see methyl phosphinyl difluoride
 - CAS 75393-84-9**
 - see NTDNA
 - CAS 75-55-8**
 - see propyleneimine (2-methylaziridine)
 - CAS 756-79-6**
 - see dimethyl methylphosphonate
 - CAS 75-97-8**
 - see pinacolone
 - CAS 76-06-2**
 - see chloropicrin
 - CAS 762-04-9**
 - see diethyl phosphite
 - CAS 7664-39-3**
 - see hydrogen and hydrogen compounds
 - CAS 7681-49-4**
 - see sodium and sodium compounds
 - CAS 76-89-1**
 - see methyl benzilate
 - CAS 76-93-7**
 - see benzoic acid
 - CAS 7719-09-7**
 - see thionyl chloride
 - CAS 7719-12-2**
 - see phosphorus and phosphorus compounds
 - CAS 7722-73-8**
 - see 1,1R,1S-trimesoyl-tris(2-ethylaziridine) (HX-868, BITA)
 - CAS 77-81-6**
 - see tabun
 - CAS 7784-21-6**
 - see alane
 - CAS 7784-34-1**
 - see arsenic compounds
 - CAS 7789-23-3**
 - see potassium and potassium compounds
 - CAS 7789-29-9**
 - see potassium and potassium compounds
 - CAS 7790-98-9**
-

see AP	
CAS 78246-06-7	
see DNAD	
CAS 78-38-6	
see diethyl ethylphosphonate	
CAS 78-53-5	
see amiton	
see O,O-diethyl S-[2-(diethylamino)ethyl] phosphorothiolate	
CAS 78644-90-3	
see DAAzF	
CAS 79-37-8	1C350
CAS 82486-82-6	
see NENAs	
CAS 82486-83-7	
see NENAs	
CAS 84051-81-0	
see poly-NMMO	
CAS 85068-72-0	
see bis (2-methyl aziridiny) methylamino phosphine oxide	
CAS 85068-73-1	
see NENAs	
CAS 85954-06-9	
see NENAs	
CAS 868-85-9	
see dimethyl phosphite	
CAS 9003-18-3	
see BNO	
CAS 90591-48-3	
see TEPB (Tris (ethoxyphenyl) bismuth)	
CAS 90683-29-7	
see AMMO	
CAS 932-64-9	
see NTO	
CAS 93894-59-8	
see dihexyl ferrocene	
CAS 96-79-7	
see N,N-diisopropyl-(beta)-aminoethyl chloride	
CAS 96-80-0	
see N,N-diisopropyl-(beta)-amino ethanol	
CAS 97096-78-1	
see ADNBF	
CAS 97645-24-4	
see TNAZ	
CAS 993-13-5	
see methylphosphonic acid	
caseless ammunition, weapons using	ML1
casting and remelt furnaces	
see furnaces	

castings	ML16, ML901, ML902
catalytic burners, for deuterium compound production	0B004.b.7
cathodes for microwave equipment	
see also vacuum tubes and valves (electronic)	
.....	3A001.b.1
cathodic arc discharge equipment	2B005, 2E003
catocene (CAS 37206-42-1)	ML8.f.4
cell cultures	
biopolymer technology	ML7
for use against chemical warfare agents	ML7.i.2
technology for development and production of	ML22.b.4
cell-interconnect-coverglass assemblies	3A001.e.4
cells and batteries (electrical)	
see also power supplies	
.....	3A102
fuel cell power systems	8A002.j.3
primary high energy cells and batteries	3A001.e.1
secondary cells and batteries	3A001.e.1
thermal batteries	3A102
cellular mobile phone equipment	
see also communications systems	
.....	5A002
centralites	ML8
centrifugal balancing machines	2B219
centrifugal balancing machines for rotor components	
see rotor assemblies for gas centrifuges	
centrifugal fixtures for gyro bearings	
see gyros, gyro components and gyro equipment	
centrifugal separators and decanters	2B352
centrifugal testing apparatus	ML18
centrifuges, with slip rings	2B122
ceramic materials	
see also composite material components and structures	
.....	1C007, 1C107
ceramic--ceramic composite materials	1C007
coating technology	2E003
for gas turbine manufacture	9B001
for radomes	1C107
in electromagnetic wave absorbers	1C001
in engine systems	9E003.f.1
in fibrous form	1C010
in incinerators	2B350.i.2
in pumps	2B350.i.2
machine tools for removing	2B001
machine tools for working	2B123
technology for the production of	1E.c.4
wet-spinning equipment	1B001.d.3, 1B101.c.3
cerium sulphide, crucibles coated with	2A225.a.2

certification software for information security software	
see information security systems	
charges, explosive	
see explosives and explosive devices	
Chapare virus	1C351.a.2
chemical exchange isotope separation equipment	
see isotope separation plants, systems, equipment and components	
chemical incinerators	2B350
chemical lasers	6A005.d.5
chemical manufacturing facilities, equipment and components	2B350
chemical propulsion systems, kinetic energy weapons	ML12
chemical storage tanks and containers	2B350
for military use	ML17
in liquid rocket propulsion systems	9A120
resistant to nitric acid	0B006
chemical toxic agents	
see toxicological agents	
chemical vapour deposition equipment	1B001.d.2, 2B005
furnaces	2B105
metal organic CVD reactors	3B001.a.2
physical vapour deposition technology	2E003
pulsating	2B005.a.1
technology for	2E003
chemical warfare agents and precursors	
see also toxicological agents	
.....	ML7
defoliants	ML7.b.4
expression vectors for use against chemical warfare agents	ML7.i.2
incapacitating agents	ML7.b.3
nerve agents	ML7.b.1
nitrogen mustards	ML7.b.2
precursors	1C350, 1C450
protective and decontamination clothing and equipment	1A004.a.3, 1A004.b.3, ML7
sensor and detector equipment	1A004.c.3, ML7
software for determining effects of	ML21.b.3
sulphur compounds	1C350, ML7.b.2
tabun	ML7.b.1
technology for development and production of	ML22.b.3
vesicant agents	ML7.b.2
virus cultures for use against	ML7.i.2
Chikungunya virus	1C351.a.3
Chlamydia psittaci	
see Chlamydophila psittaci	
Chlamydophila psittaci	1C351.c.5
chlorine and chlorine compounds	
see also O-isopropyl methylphosphonochloridate	
.....	ML7
chlorates	ML8.c.7

chlorine trifluoride.....	1C238, ML8.d.3
chloro acetone.....	ML7
chlorofluorocarbons.....	1C006.a.2
chloropicrin	1C450.a.7, ML7
chloropicrin (CAS 76-06-2).....	ML7
Choclo virus	1C351.a.4
cholera toxin.....	1C351.d.13
cholinesterase-inhibiting activity detection	2B351
chromates	ML8.c.7
chromium, chemical handling equipment made with	2B350
chromosomes	
see genetic elements	
CICs	
see cell-interconnect-coverglass assemblies	
cinema recording cameras	
see video cameras	
cis-bis (5-nitrotetrazolato) tetra amine-cobalt (III) perchlorate	
see BNCP	
Cl--	
see chlorine and chlorine compounds	
CL-14 (CAS 117907-74-1).....	ML8.a.3
CL-20 (CAS 135285-90-4).....	ML8.a.4
Clavibacter michiganensis subsp. Sepedonicus	1C354.b.4
clicker dies, for composite materials.....	1B101
clips	ML1
closed circuit diving apparatus	
see breathing equipment	
see underwater operations equipment	
Clostridium argentinense.....	1C351.c.7
Clostridium baratii.....	1C351.c.8
Clostridium botulinum.....	1C351.c.6
Clostridium botulinum Type G	
see Clostridium argentinense	
Clostridium butyricum	1C351.c.9
Clostridium perfringens epsilon.....	1C351.c.17
Clostridium perfringens toxins	1C351.d.2
clothing and materials	
see protective and decontamination clothing and equipment	
CN	
see 2-chloro-1-phenylethanone	
CNTD	
see controlled nucleation thermal deposition equipment	
coating and processing equipment	
see surface coating and processing materials and equipment	
Coccidioides immitis.....	1C351.e.1
Coccidioides posadasii.....	1C351.e.2
Cochliobolus miyabeanus	1C354.c.2
coherent optical transmission and detection equipment.....	5E001.c.2

cold boxes	
see distillation and absorption columns	
cold traps and desublimers for UF₆ removal	
see also uranium metal, uranium alloys, and uranium compounds	
.....	0B001.d.7, 0B002
cold-cathode tubes	3A228
Colletotrichum coffeanum var. virulans	1C354.c.1
Colletotrichum kahawae	
see Colletotrichum coffeanum var. virulans	
colour centre lasers	6A005
columbium	
see niobium and niobium alloys	
combat aircraft	
see also aircraft and aircraft components	
.....	ML10
combat parachutes	
see parachutes	
combatant vessels and components	
see also marine vessels, equipment and components	
see also submersible vessels, equipment and components	
.....	ML9
combined cycle engines and components	9A011
combustion regulation equipment	9A118
combustors, technology for development and production of	9E003.a.2
command, communications, control and intelligence software	
see C3I (command, communications, control and intelligence) software	
comminution, alloys made by	1C002.c.2
communications systems	
see radio equipment and components	
see telecommunications systems, equipment, components and accessories	
see underwater operations equipment	
compasses, gyroscopic	
see gyros, gyro components and gyro equipment	
compensation systems	6A006
complex programmable logic equipment	
see field programmable gates, logic arrays and interconnects	
composite material components and structures	
see also ceramic materials	
.....	1A002, 1C007, 9C110
coating technology.....	2E003
equipment for the production of	1B001, 1B201, 2B123
fibrous and filamentary materials in	1C010
flexible piezoelectric composites.....	6A001.a.2
for gas turbine engines.....	9E003.a.3
for space launch vehicles	9A110
mirrors constructed from	6A004.a.3, 6A004.c.4
software for the production of	1D002
space-qualified.....	9A010

superconductive composite conductors	1C005
tools for removing	2B001
tubular	1A202
compound acoustic mounts	8A002.o.3
compound rotary tables	2B008
compound semiconductor photocathodes, for imaging equipment	ML15
compound substrates	
see substrate materials for integrated circuits	
compressors	
see blowers and compressors	
computer controlled tools	
see numerically controlled machine tools	
computer-aided-design systems, software for	7D003
computers, computer assemblies and computer components	
see also software	
bombing computers	ML5
for monitoring furnaces	2B227
for underwater use	8A002
neural computers	4A004
optical computers	4A004
radiation hardened	4A001.a.2
ruggedised	4A001.a.1, 4A101
systolic array computers	4A004
temperature-rated	4A001.a.1
condensers	
see heat exchangers and condensers	
Congo-Crimean haemorrhagic fever virus	1C351.a.5
connection equipment for computers	4A003
connectors, optical fibre	
see optical fibre, equipment and accessories	
conotoxin	1C351.d.3
construction equipment, for military use	ML17
contactors	
see switching equipment	
containers, chemical	
see chemical storage tanks and containers	
containment facilities, biological warfare agents	2B352
continuous mixers	1B118, ML18
continuous nitrators	ML18
continuous output accelerometers	7A101
continuous-flow fermenters	
see fermenters for pathogenic cultures	
contrarotating propeller systems	8A002.o.1
control law compensation technology	7E004.b.2
controllable-pitch propellers	
see propellers and propfans	
controlled atmosphere melting and casting furnaces	
see furnaces	

controlled nucleation thermal deposition equipment	2B005.a.1
convection current converters, manufacturing equipment	ML18
conversion plant and equipment for uranium	
see uranium metal, uranium alloys, and uranium compounds	
conversion tower internals	0B004.b.4
converters (microwave)	3A001.b.7
convertors (electrical)	
see frequency changers and generators	
cooling equipment for molten uranium	
see uranium metal, uranium alloys, and uranium compounds	
cooling systems	
see also cryogenic equipment, accessories and components	
for imaging equipment	ML15
for isotope separation equipment.....	0B001.h.5
for nuclear reactors	0A001
for tritium facilities and plants	1B231.b.1
optical mirrors with	6A005.e.1
co-ordinate measuring machines	2B006
copper, copper alloys and copper compounds	
copper salicylate	ML8.f.1
coprocessors	
see digital signal processors and coprocessors	
cordless telephone equipment	5A002
correlation--velocity sonar log equipment	
see sonar navigation systems	
corrosion-resistant materials	0B002
Corynebacterium michiganensis subsp. sepedonicum	
see Clavibacter michiganensis subsp. Sepedonicus	
Corynebacterium sepedonicum	
see Clavibacter michiganensis subsp. Sepedonicus	
counter-current solvent extractors for nuclear fuel reprocessing	0B006
countermeasure and counter countermeasure equipment	ML15
electronic	ML11
for directed energy weapons.....	ML19
for negative hydrogen ion beams.....	ML19
coupled cavity tubes	3A001.b.1
couplers	
see optical fibre, equipment and accessories	
Coxiella burnetii	1C351.c.19
CP (CAS 70247-32-4)	ML8.a.5
CR	
see dibenz-(b,f)-1,4-oxazepine	
critically safe tanks for nuclear fuel reprocessing	0B006
cross flow filtration equipment and components	2B352
crossed-field amplifier tubes	3A001.b.1
crucibles	
actinide resistant	2A225
for liquid uranium handling systems	0B001.g.2

cryogenic distillation towers and cold boxes	
see absorption and distillation columns	
cryogenic equipment, accessories and components	
see also cooling systems	
.....	ML20
for aerodynamic separation equipment.....	0B001.d.7
for isotope separation equipment.....	0B001.h.5
for liquid rocket propulsion systems	9A006
for optical sensors.....	6A002
hydrogen-cryogenic distillation columns	1B228
steam sterilisable freeze drying equipment	2B352
cryptographic equipment	5A002.a.1, 5A002.b, ML11
CS	
see [(2-chlorophenyl) methylene] propanedinitrile	
CTPB	
see carboxy-terminated polybutadiene	
cultivation chambers	2B352.b.2
cultures of microorganisms	
see bacterial cultures	
see fungi	
see virus cultures	
Curium 240, 241, 242, 243 and 244	
see radionuclides	
current injectors	ML19
custom integrated circuits	
see integrated circuits	
cutting machines	1B101, ML18
CVD	
see chemical vapour deposition equipment	
CW agents	
see chemical warfare agents and precursors	
cyanginosin	
see microcystin	
cianoethylated polyamines	ML8.f.20, ML8.f.21
cyanogen bromide	ML7
cyanogen chloride	ML7
cyanogen chloride (CAS 506-77-4)	1C450.a.5
cyclonite	
see RDX and derivatives	
cyclotetramethylenetetranitramine	
see HMX and derivatives	
cyclotrimethylenetrinitramine	
see RDX and derivatives	
cylinder components using ceramic materials	9E003.f.1
>>=====<<	
>>D<<	
DAAOF	ML8.a.12
DAAzF (CAS 78644-90-3)	ML8.a.12

DACs	
see digital-to-analogue converters	
DADE	ML8.a.6
DADN (1,5-diacetyl-3,7-dinitro-1, 3, 5, 7-tetraaza-cyclooctane)	ML.g.9, ML8.a.13
damage assessment systems	ML12, ML19
damage tolerant systems	
see fault tolerant equipment	
damping equipment (electromagnetic)	5A002.a.4
damping fluids	
see lubricating materials	
data acquisition and processing systems	
see also computers, computer assemblies and computer components	
see also sensors and detectors	
see also signal processing equipment	
for aerospace design and testing	9B005
for gas turbine manufacture	9B002
data fusion equipment, weapon control systems	ML5
data processing security equipment, using ciphering processes	ML11
data-based reference navigation equipment	7A003, 7D003.b.3, 7E004.a.6
DATB (CAS 1630-08-6)	ML8.a.7
DBRN	
see data-based reference navigation equipment	
DBT (CAS 30003-46-4)	ML8.a.32
DDFP	ML8.a.8
DDPO (CAS 194486-77-6)	ML8.a.9
decaborane (CAS 17702-41-9)	ML8.c.3
decanters	
see centrifugal separators and decanters	
decontamination equipment	ML7
decoying equipment	
see also explosives and explosive devices	
decryption equipment and software	
see cryptographic equipment	
deep water fording vehicles	
see amphibious vehicles	
deep-hole drilling machines	
see drilling machines	
defoliants	
see chemical warfare agents and precursors	
deformable mirrors	6A004.a.1
DEGDN	
see diethylene glycol dinitrate	
DEHN	
see diethylhydrazine nitrate	
dehydration presses	ML18
demolition equipment	
see also explosives and explosive devices	
.....	ML4

dengue fever virus	1C351.a.3
depleted uranium	
see uranium metal, uranium alloys, and uranium compounds	
depth charges and components	
see also explosives and explosive devices	
.....	ML4
depth sounders	6A001.a.1
desublimers	
see cold traps and desublimers for UF ₆ removal	
detection and protection equipment	
see protective and decontamination clothing and equipment	
see sensors and detectors	
detonation equipment	
see also explosives and explosive devices	
.....	1A007
multipoint initiation systems	3A232
non-military	ML909
deuterium compounds	0C003
concentrators for	0B004.b.8
manufacturing equipment	0B004, 1A225, 1A226
deuterium fluoride lasers	6A005.d.5
DEW	
see directed energy weapon systems	
DF	
see methyl phosphonyl difluoride	
DHTN	
see 3,6-dihydrazino tetrazine nitrate	
diacetoxyscirpenol toxin	1C351.d.14
diagnostic equipment, laser beam systems	6A005.f.2
dialkyl [methyl, ethyl and propyl (normal and iso)] N,N-dialkyl [methyl, ethyl and propyl (normal and iso)]-phosphoramidates	1C450.b.3
diamino dinitrobenzofuroxan	
see CL-14	
diaminoazofurazan	
see DAAzF	
diaminoazoxyfurazan	
see DAAOF	
diaminohexanitrobiphenyl	
see DIPAM	
diaminotrinitrobenzene	
see DATB	
diamond materials	
coating technology	2E003
in optical equipment	6C004
substrate materials for integrated circuits	3E003
diaphragm pumps	
see pumps	
diaphragms, made from fluoroelastomers	1A001

dibenz-(B,F)-1,4-oxazepine (CAS 257-07-8)	1A004.a.4, ML7.d.4
dibromotetrafluoroethane, in damping and flotation fluids	1C006.c.1
dibutyl ferrocene (CAS 1274 08 4)	ML8.f.4.m, 1C111.c.6
dicyclohexyl ferrocene	ML8.f.4.j, 1C111.c.6
dicyclopentyl ferrocene (CAS 20773 28 8)	ML8.f.4.i, 1C111.c.6
dicyclohexyl ferrocene	1C111.c.6
dicyclopentyl ferrocene (CAS 20773-28-8)	1C111.c.6
dielectric layers, coating technology	2E003
dies	
see also rotor assemblies for gas centrifuges	
for bellows.....	2B228
for isostatic presses.....	2B204
for superplastic forming and diffusion bonding	1B003
for the production of composite structures	1B101
diesel engines	
for submersible vessels.....	8A002.j.2, ML9.b.1
non-magnetic	ML9.b.3
technology for development and production of.....	9E003
diethyl ethylphosphonate (CAS 78-38-6)	1C350
diethyl ferrocene (CAS 1273-97-8)	ML8.f.4.k, 1C111.c.6
diethyl methylphosphonate (CAS 683-08-9)	1C350
diethyl methylphosphonite (CAS 15715-41-0)	1C350
diethyl phosphite (CAS 762-04-9)	1C350
diethylaminoethanol (CAS 100-37-8)	1C350
diethyldiphenyl urea	ML8
diethylene glycol dinitrate (CAS 693-21-0)	1C111.c.5
diethylhydrazine nitrate	1C111.a.4
diethyl-N,N-dimethylphosphoramidate (CAS 2404-03-7)	1C350
differential analysers	4A101
diffusion bonding technology	1B003, 2E003, 9E003.a.7
difluoroaminated analogs of HMX	ML8.a.13
difluoroamine	ML8, ML8.e.6
digital array processors and differential analysers	
see digital signal processors and coprocessors	
digital cellular radio equipment	
see telecommunications systems, equipment, components and accessories	
digital computers	
see computers, computer assemblies and computer components	
digital controllers, vibration test systems	2B116
digital demodulators	ML11
digital flight controls	
see flight control systems	
digital integrated circuits	
see integrated circuits	
digital radio equipment	
see radio equipment and components	
digital recording equipment	
see recording equipment	

digital signal processors and coprocessors	
see signal processing equipment	
digital troposcatter-radio communications transmission equipment	ML11
digital video magnetic tape recorders	
see recording equipment	
digital-to-analogue converters	3A001.a.2, 3A001.a.5
digitisers, waveform	
see waveform digitisers	
dihexyl ferrocene (CAS 93894 59 8)	ML8.f.4.n, 1C111.c.6
diimido oxalic acid dihydrazine, as propellant	1C111.a.4
di-isopropylamine (CAS 108-18-9)	1C350
dimensional inspection and measuring systems	2B006, 6B007, 6B008
dimethyl ethylphosphonate (CAS 6163-75-3)	1C350
dimethyl methylphosphonate (CAS 756-79-6)	1C350
dimethyl phosphite (CAS 868-85-9)	1C350
dimethylamine (CAS 124-40-3)	1C350
dimethylamine hydrochloride (CAS 506-59-2)	1C350
dimethylhydrazinium azide, as propellant	1C111.a.4
dimethyldiphenyl urea	ML8
DINGU (CAS 55510-04-8)	
see DNGU	
dinitroazetidine-t-butyl salt (CAS 125735-38-8)	ML8.g.2
dinitrobistriazole	
see DNBT	
dinitrogen pentoxide (CAS 10102-03-1)	1C111.a.3
dinitrogen tetroxide (CAS 10544-72-6)	1C111.a.3
dinitrogen trioxide (CAS 10544-73-7)	1C111.a.3
dinitroglycoluril	
see DINGU	
diethylmaleate	ML8
DIPAM (CAS 17215-44-0)	ML8.a.10
diphenyl methylphosphonate	1C450.b.1
diphosgene	ML7
dipicramide	
see DIPAM	
dipropyl ferrocene	ML8.f.4.l, 1C111.c.6
direct current power supplies	
see power supplies	
direct current propulsion motors and thrusters	8A002.a.2
direct view imaging equipment	6A002
direct writing equipment for mask and semiconductor making	3B001.f.3
direct-acting hydraulic pressing technology	2E003
direct-bonded motors	9A007
directed energy weapon systems	ML19
direction finding systems	
see navigation systems, equipment and components	
directional solidification casting equipment	9B001, 9D004
discharging equipment, explosive	

see explosives and explosive devices	
disruptors for explosives disposal	1A006
dissolvers for nuclear fuel reprocessing	0B006
distillation and absorption columns	2B350
divert propulsion (lateral acceleration) systems	ML12
diving apparatus, articles and components	
see breathing equipment	
see underwater operations equipment	
DM	
see 10-chloro-5,10-dihydrophenarsazine	
DMP	
see dimethyl phosphite	
DNAD (CAS 78246-06-7)	ML8.d.4
DNAM (CAS 19899-80-0)	ML8.a.31
DNAN (2,4-dinitroanisole) (CAS 119-27-7)	ML8.a.35
DNBT (CAS 70890-46-9)	ML8.a.32
DNGU	ML8.a.11
DNI (CAS 5213-49-0)	ML8.a.16
Dobrava-Belgrade virus	1C351.a.7
Dobrava virus	1C351.a.31
Doppler navigation radar equipment	6A008, 6A108
Doppler-velocity cable log equipment	6A001.a.2
Dothidella ulei	
see Microcyclus ulei	
drag parachutes	
see also parachutes	
.....	ML10.h.3
drilling machines	2B001, 9E003
drogue parachutes	
see also parachutes	
.....	ML10.h.3
drones	
see unmanned airborne vehicles, systems and components	
dye lasers	6A005, 6A205
>>=====<<	
>>E<<	
eastern equine encephalitis virus	1C351.a.8
EB detonators	
see exploding bridge detonators	
Ebola virus	1C351.a.5
EB-PVD	
see electron beam equipment	
EBW detonators	
see exploding bridge wire detonators	
EDDN	
see ethylenediaminedinitrate	
EEPROMS	
see electrical erasable programmable read-only memories	

EFI detonators	
see exploding foil detonators	
Einsteinium 253 and 254	
see radionuclides	
elastomer modified cast double base propellants	ML8.b.5
electric actuators, technology for development and production of	7E004.a.5
electric detonators, explosive	
see detonation equipment	
electric engines	
see also engines and engine components	
for marine vessels	8A002.o.2
for submersible vehicles	ML9.b.2
electrical erasable programmable read-only memories	3A001.a.2
electrochemical machining	9E003
electrochemical reduction cells	0B001.e.4
electrolytic cells	
for fluorine production	1B225
for lithium isotope separation	1B233.b.3
electromagnetic equipment	
see also computers, computer assemblies and computer components	
see also integrated circuits	
see also microwave equipment and components	
see also radio equipment and components	
see also sensors and detectors	
see also signature reduction equipment and materials	
.....	ML11
damping equipment	5A002.a.4
electric field sensors	6D003.b.1
electrical discharge machines	2B001, 9E003
electrically triggered shutters	ML15
electrically triggered thyristors	3A001
electroburst equipment	1B102
electron sensing equipment	6A002.a.2
flight control systems	7A116
for military use	ML11
for surveillance and monitoring	ML11
gradiometers	6A006
hair type absorbers	1C001
in electric engines	8A002.o.2, ML9.b.2
interference protection technology	7E102
isotope separation equipment	0B001, 0B001.a.9, 0B001.j.4, 1B226
magnetic bearings	0B001.b.7, 2A001, 8A002.o.3
magnetic field sensors	6D003.b.1
magnetic metals	1C003
magnetic propulsion systems	ML22
magnetometers	6A006, 6D003.b.2
nuclear precession magnetometers	6A006.a.2
power supplies for	0B001.j.6

propulsion systems	ML12
pulse protection technology	7E102, ML17
software for	2D002
three axis magnetic heading sensors	7A103
wave absorbers	1C001
with superconductive components	3A001.e.3, 3A201
electron beam equipment	
see also semiconductor manufacturing equipment	
.....	0B001.g.1, 2B005, 2B227, 2E003, 5A001.b.1
electron bombardment mass spectrometers	0B002.g.3, 3A233
electronic assemblies	3A001
for boosting processing performance	4A003
for feedback capability	2B006
for reentry vehicles	9A116
software for development of	4D001
superconductive materials in	3A001
technology for	4E001
electronic cameras	6A003.a.5
electronic computers and related equipment	
see computers, computer assemblies and computer components	
electronic framing cameras	6A003.a.4
electronic imaging systems, for underwater use	8A002
electronic vacuum tubes and valves	
see vacuum tubes and valves (electronic)	
electronically steerable phased array antennae	5A001, 6A008, 6D003.d.2
electro-optical integrated circuits	3A001.a.2, 3A001.a.6
electrorheological finishing tools	2B002
electrothermal propulsion systems	ML12
EMCDB propellants	
see elastomer modified cast double base propellants	
EMP/EMI protection technology	
see electromagnetic equipment	
encrypted GPS	
see global navigation satellite systems	
encryption equipment and software	
see cryptographic equipment	
end caps, for rotor tubes	0B001.b.6
end-effectors	
see robot systems	
energetic materials	ML8, ML8.e.6, ML908
energetic particle beam finishing tools	2B002
energy storage equipment	
see also capacitors	
see also cells and batteries (electrical)	
see also superconductive materials and equipment	
for directed energy weapons	ML19
energy weapons systems	
see directed energy weapon systems	

engines and engine components

see also aero-engines and components
 see also diesel engines
 see also gas turbine engines
 see also marine engines
 see also rocket propulsion systems

.....	ML9
Brayton cycle engines.....	8A002.j.1
combined cycle engines and components.....	9A011
cylinder components using ceramic materials.....	9E003.f.1
direct-bonded motors.....	9A007
filament-wound composite motor cases.....	9A008
pulse jet engines.....	9A111
pumpjet propulsion systems.....	8A002
ramjet engines and components.....	9A011
Rankine cycle engines.....	8A002.j.1
reciprocating engines.....	ML10
ring-shaped motor stators.....	0B001.b.10
scramjet engines.....	9A011
Stirling cycle engines.....	8A002.j.4
superconductive propulsion engines.....	8A002.o.2

enriched uranium

see uranium metal, uranium alloys, and uranium compounds

enrichment plants

see isotope separation plants, systems, equipment and components

enterohaemorrhagic Escherichia coli (EHEC)

see Shiga toxin producing Escherichia coli (STEC)

environmental chambers.....	9B106
-----------------------------	-------

epitaxial growth equipment

see also semiconductor manufacturing equipment

.....	3B001
epoxy resin impregnated carbon materials.....	1A002, 1C010

equine morbillivirus

see Hendra virus

erbium oxide, crucibles coated with.....	2A225.a.2
--	-----------

ERF

see electrorheological finishing tools

errocene derivatives.....	ML8.f.4
---------------------------	---------

escape equipment, for use in military aircraft.....	ML10, ML10.h.4
---	----------------

Escherichia coli

see Shiga toxin producing Escherichia coli (STEC)

ethyl ferrocene (CAS 1273-89-8).....	ML8.f.4.o, 1C111.c.6
ethyl ferrocene.....	1C111.c.6
ethyl iodoacetate.....	ML7
ethyl phosphinyl dichloride (CAS 1498-40-4).....	1C350
ethyl phosphinyl difluoride (CAS 430-78-4).....	1C350
ethyl phosphonyl dichloride (CAS 1066-50-8).....	1C3500
ethyl unsymmetrical diphenylurea	

see ethyl-N,N-diphenylurea	
ethyldiethanolamine (CAS 139-87-7)	1C350
ethylene dihydrazine, as propellant	1C111.a.4
ethylenediaminedinitrate	ML8
ethylhexylacrylate	ML8
ethyl-N,N-diphenylurea	ML8
ethyl-phosphonothioic dichloride	1C450.b.1
ETTs	
see electromagnetic equipment	
evaporators	
see isotope separation plants, systems, equipment and components	
excimer lasers	6A005, 6A005.d.4
exploding bridge detonators	1A007.b.1
exploding bridge wire detonators	1A007.b.2
exploding foil detonators	1A007.b.4
explosive detonator firing sets	1A007
explosives and explosive devices	
see also detonation equipment	
see also fuels and propellants and related equipment	
see also pyrotechnics, pyrotechnic equipment and components	
.....	1C239, ML8, ML8.a.33
containing energetic materials	ML910
disposal equipment	1A006
for military use	ML4
incendiary munitions	ML8.c.6
robot systems for handling	2B007, 2B207
expression vectors for use against CW agents	ML7.i.2
>>=====<<	
>>F<<	
FADEC (full authority digital electronic engine control) software	
see full authority digital electronic controls	
FAMAO	ML8.e.7
fan turbine control systems	9E003.a.10
fast Fourier transform processors	3A001.a.2, 3A001.a.12
fast reacting ion-exchange resins	
see isotope separation plants, systems, equipment and components	
fast switching modules and assemblies	
see switching equipment	
fast-exchange liquid-liquid separators	0B001.e.1, 0B001.e.2
fault tolerant equipment	
computers	4A003
gas turbine engines	9E003.a.8
software for	7D003.d.4, 9D003
technology for development and production of	7E004.b.3
FDIA	ML8.a.16
Fe--	
see iron, iron alloys and iron compounds	
feed autoclaves	0B002

feed preparation systems	0B001.e.5
FEFO (CAS 17003-79-1)	ML8.e.8
fermenters for pathogenic cultures	2B352.b
ferries	ML17
ferrocene and ferrocene derivatives	1C111.c.6, ML8.f.4
ferrosilicon, in pumps	2B350.i.2
fibre ‘lasers’, in optical components	6A005
fibre optic cable	
see optical fibre, equipment and accessories	
fibrous and filamentary materials	
see also graphite	
.....	1C010, 1C210
aromatic polyamide fibres	1E
components made from	1A002
equipment for the production of	1B001
in the form of tubes	1A202
inorganic	1C010
field engineer equipment, for military use	ML17
field generators, for military use	ML17
field programmable gates, logic arrays and interconnects	3A001.a.7
field test equipment, weapon control systems	ML5
filament winding equipment and software	1B001, 1B101, 1B201
filamentary materials	
see fibrous and filamentary materials	
filament-wound composite motor cases	9A008
filling equipment, remotely controlled and operated	
see remotely operated equipment	
film processing equipment	
see also camera systems, camera equipment, and camera components	
.....	ML15
filters	
see Kalman filtering software	
see tunable band-pass filters	
fingers for surface effect vessels	8A002
finishing machines	
see machine tool equipment, components and assemblies	
fire bombs and components	
see incendiary munitions, fuels for use in	
fire control and warning equipment and related systems	
see weapons control systems	
firearms and firearm components	
see also ammunition and components	
see also smooth-bore weapons	
.....	ML1
high velocity kinetic energy weapon systems	ML12
non-military	ML901
technology for development and production of	ML22.b.2
training equipment	ML14

firing sets	
see detonation equipment	
first generation image intensifier tubes	
see image processing and enhancement equipment	
flame throwers	ML2, ML8.c.6
flares for aircraft missile protection	ML4
flash memories	3A001.a.2
flash suppressors	ML1, ML904
flash x-ray generators	3A201
flexible piezoelectric composites in hydrophones	6A001.a.2
flexible rotor centrifugal balancing machines	
see rotor assemblies for gas centrifuges	
flight control systems	7E104
fluid injection thrust vector control systems	9A008
fly-by-light control systems	7D003.d.3, 7E004.c.1
fly-by-wire control systems	7D003.d.3, 7E004.c.1
for unmanned airborne vehicles	ML10.c.3
full authority digital electronic engine controls	9D003
hydraulic	7A116
integrated flight instrument systems	7A103, 7D003.d.2
optical sensor array technology	7E004.a.6
software for	7D003.d.1
space-qualified	7A116
technology for	7E004
total control systems	7E004.b.5
flightweight dewars, for liquid rocket propulsion systems	9A006
flotation fluids	
see lubricating materials	
flow-environments	
simulators and components for	9B005
software for	9D004
transducers for testing	9B008
flow-forming machines	
see also machine tool equipment, components and assemblies	
.....	2B009, 2B109, 2B209
fluid energy mills	1B119, ML18
fluid injection thrust vector control systems	9A008
fluid jet finishing tools	2B002
fluorine and fluorine compounds	ML8.d.3
as propellants	1C111.a.3
components made from	1A001
electrolysis cells for the production of	1B225
fluorinated polyimides	1C009
fluorinated silicone fluids	1C006.b.2
fluorinating equipment	0B001.h.4
fluoroelastomers	1A001, 1E
fluorophosphate glass	6C004
fluoropolymers	2B350

in cooling fluids.....	1C006, 1C006.d.1, 1C006.d.4
unprocessed	1C009
fluxgate technology	6A006.a.3
fly cutting machines	2B001.b.4
fly-by-light and fly-by-wire control systems	7D003.d.3, 7E004.c.1
foam structures	6A004.a.3, 8C001
focal plane arrays	6A002.a.3, 6A002.c.2
imaging cameras with.....	6A003.b.4
space qualified.....	6A002
fogging systems	9A350
fonofos	1C450.b.1
foot and mouth disease virus	1C352.a.4
forgings	ML16, ML901, ML902
FOX7	
see DADE	
FPF-1 (CAS 376-90-9)	ML8.e.9
FPF-3	ML8.e.10
FPG/LAs	
see field programmable gates, logic arrays and interconnects	
framing cameras	
see also camera systems, camera equipment, and camera components	
.....	6A203.a.1, 6A203.b.1, 6A203.b.3
framing tubes	1C351.c.10
Francisella tularensis	1C351.c.7
freeze drying equipment	
see cryogenic equipment, accessories and components	
frequency agility radar technology (frequency hopping)	5A001.b.3, 5A002.a.5, ML11
frequency analysers	
see signal processing equipment	
frequency changers and generators	3A225
frequency extenders, mixers and converters	
see microwave equipment and components	
frequency mask trigger	
see signal processing equipment	
frequency signal generators	
see signal processing equipment	
frequency standards	
see atomic frequency standards	
frequency synthesisers	3A001.b.11
fuel cell air independent power systems	
see air independent power systems	
fuel cell power systems, for underwater use	
see cells and batteries (electrical)	
fuels and propellants and related equipment	1C111, ML8
bonding systems	9A008
equipment for the production of	1B115
for aircraft.....	ML8.c.1
for directed energy weapons.....	ML19

for nuclear reactors	0B005, 0B006
fuel injection systems	9E003.f.3
liquid propellant charges	ML2
metal powder fuels	1B102, 1C111.a.2, ML18, ML8.c.5
pressure refuellers	ML10
propellant injectors	9A006
remotely operated shredding equipment	0B006
storage systems	9A006, 9A120
thickeners for	ML8.c.6
UN classified	ML8.b.1, ML8.b.2
full authority digital electronic controls	9D003, 9E003.a.9
full face masks	
see gas masks	
fully automatic smooth-bore weapons	ML1
functional testing equipment for integrated circuits	
see integrated circuits	
fungi	1C351, 1C354
furazans	ML8.a.12
furnaces	
arc remelt furnaces	2B227
casting furnaces	2B227
controlled atmosphere induction furnaces and components	2B226, 2B227
electron beam melting furnaces	2B227
monitoring systems	2B227
plasma furnaces	2B227
power supplies for	2B226
fused silica, in optical materials	6C004
fuze setting equipment for smooth-bore weapons	ML3
>>=====<<	
>>G<<	
Ga--	
see gallium and gallium compounds	
GA (tabun)	
see tabun	
Gadolinium 148	
see radionuclides	
Galileo navigation system	
see global navigation satellite systems	
gallium and gallium compounds	
in photocathodes	6A002.a.2
substrate materials for integrated circuits	3C001, 3C005, 3C006
Gallium selenide	6C004.b.5
gamma-chloroacetophenone	
see 2-chloro-1-phenylethanone	
see phenylacetyl chloride	
GAP (CAS 143178-24-9)	ML8.e.11
gas atomisation, alloys made by	1C002.c.2
gas blowers	

see blowers and compressors	
gas centrifuges and components	
see also isotope separation plants, systems, equipment and components	
see also rotor assemblies for gas centrifuges	
.....	0B001, 2B228
gas generators	9E003.a.10, ML2
gas guns	2B232, 9B005, ML12
gas krytron tubes	3A228
gas masks and components	1A004
gas monitoring systems	
see toxicological agents	
gas tunnels	9B005
gas turbine engines	
see also aero-engines and components	
see also engines and engine components	
see also rotor assemblies for gas centrifuges	
blade manufacturing equipment	9B001
clearance control software	9D004
components of	9A003
fault tolerant	9E003.a.8
manufacturing equipment	9B002, 9B003, 9B004, 9B009
rotor technology	9E003
software for design, manufacturing and operation	9D004
technology for development and production	9E003
tip shroud castings	9B001, 9E003.a.4, 9E003.a.5
vanes for	9B001, 9E003.a.4, 9E003.a.5
gaseous diffusion barriers and housings	0B001.c.1, 0B001.c.2, 0C005
gaseous diffusion separators	
see isotope separation plants, systems, equipment and components	
gases, toxic	
see chemical warfare agents and precursors	
see riot control agents	
gaskets, made from fluoroelastomers	1A001
gate silicon intensifier target videcon tubes	6A203.b.4
gate turn-off thyristors	3A001
GB	
see sarin	
GD	
see soman	
GDMS	
see glow discharge mass spectrometers	
gear manufacturing machine tools	2B003
genetic elements	1C353
genetically modified organisms	
see also biological warfare agents	
.....	1C353
genomes	
see genetic elements	

germanium substrate materials for integrated circuits	3C001
gimbals for optical control equipment	6A004.d.3
glass and glass-based materials	
see also fibrous and filamentary materials	
see also optical fibre, equipment and accessories	
see also silicon and silicon compounds	
chemical handling equipment made with	2B350
coating technology	2E003
fibrous and filamentary materials	1C210
in optical materials	6C004
radiation shielding windows	1A227
glass lasers	6A005.d.6, 6A205
global navigation satellite systems	7A003, 7A005
jamming equipment	ML11
receiving equipment	7A105
software using	7D003.b.2
GLONASS	
see global navigation satellite systems	
glow discharge mass spectrometers	3A233
glyceroltrinitrate	ML8
glycidylazide polymer	
see GAP	
GNSS	
see global navigation satellite systems	
goat pox virus	1C352.a.5
GPS (global positioning system) equipment and components	
see global navigation satellite systems	
graphite	2B350.d.3, 2B350.e.4
controlled materials	1C107
distillation and absorption columns made with	2B350.e.4
heat exchangers and condensers made with	2B350.d.3
nuclear grade	0C004
gravimeters	
see gravity meters and components	
gravity gradiometers, components and software	6A007, 6A107, 6D003
gravity meters and components	6A007, 6A107, 6B007, 6D003
grenades and components	
see also explosives and explosive devices	
.....	ML4
grinding machines	
see also gear manufacturing machine tools	
.....	2B001, 2B123
ground control equipment	
see flight control systems	
see launch and launch support equipment	
ground vehicles	
see land vehicles and components	
GTOs	

see gate turn-off thyristors	
Guanarito virus	1C351.a.10
guanidine nitrate	1C011
GUDN (Guanylurea dinitramide) FOX-12 (CAS 217464-38-5)	ML8.a.37
guidance equipment	
see navigation systems, equipment and components	
guidance sets for missiles	7A117, 7D103
guns and components	
see also cannons, large calibre	
see also firearms and firearm components	
see also smooth-bore weapons	
.....	ML2
armed vehicles	ML6
gun laying equipment	ML5
gun mountings	ML1
high-velocity gun systems	2B232
gyros, gyro components and gyro equipment	7A002, 7A103, 7B003
calibration equipment	7B002
for missiles	7A102
gyro-astro compasses.....	7A004, 7A104
gyrostabilisers.....	7A103
>>=====<<	
>>H<<	
hafnium, hafnium alloys and hafnium compounds	1C231
crucibles coated with	2A225.a.2
hafnium fluoride	6C004
in particle form	1C011
hair type absorbers	1C001
HAN (CAS 13465-08-2)	ML8.d.5
Hantaan virus	1C351.a.6
HAP (CAS 15588-62-2)	ML8.d.6
harmonic mixers	3A001.b.7
HBIW (CAS 124782-15-6)	ML8.g.3
HBTs	
see hetero-bipolar transistor technology	
He3	
see helium-3, mixtures and products containing	
heading sensors	
see also hydrophones	
see also navigation systems, equipment and components	
see also sensors and detectors	
.....	6A001.a.2
head-up displays	7D003.d.7, 7E004.a.3
heat exchangers and condensers	2B350
for aerodynamic separation equipment.....	0B001.d.4, 0B001.d.7
for gaseous diffusion separators	0B001.c.5
for molecular laser separation equipment.....	0B001.h.5
for nuclear reactors	0A001

heat shield and heat sink components	9A116
heat-rated equipment	
see temperature-rated equipment	
heavy water	
see deuterium compounds	
HEHN	
see 2-hydroxyethylhydrazine nitrate	
helicopters	
power transmission systems	9E003
rotor blades for	7E004.c.3
technology for.....	7E004
helium-3, mixtures and products containing	1C232
helix tubes.....	3A001.b.1
helmets	
see protective and decontamination clothing and equipment	
Helminthosporium oryzae	
see Cochliobolus miyabeanus	
hematite	
see iron, iron alloys and iron compounds	
hemishell inspection tools.....	2B206
hemostats	
see fermenters for pathogenic cultures	
HEMTs	
see high electron mobility transistor technology	
Hendra virus	1C351.a.29
Herpes virus	1C352.a.6
hetero-bipolar transistor technology	3E003
hetero-epitaxial materials	3C001
hetero-structure semiconductor technology.....	3E003
hexabenzylhexaazaisowurtzitane	
see HBIW	
hexahydro-1,3,5-trinitro-1,3,5-triazine	
see RDX and derivatives	
hexanitroadamantane (CAS 143850-71-9)	
see HNAD	
hexanitrodiphenylamine	ML8
hexanitrohexaazaisowurtzitane	
see CL-20	
hexanitrostilbene	
see HNS	
hexogen	
see RDX and derivatives	
hexogene	
see RDX and derivatives	
high explosives	
see explosives and explosive devices	
High explosive containment devices.....	3A234
high-altitude equipment, robot systems.....	2B007

high-current pulse generators	3A229
high-electron mobility transistor technology	3E003
high-energy equipment	3A001
high-energy fuels	
see aircraft fuels	
see fuels and propellants and related equipment	
high-energy storage capacitors	
see capacitors	
high-power direct current power supplies	3A226, 3A227
high-power electron beam guns	
see electron beam equipment	
high-pressure thrust chambers and nozzles	
see rocket propulsion systems	
high-pressure turbo pumps	9A006
high-speed cameras	
see camera systems, camera equipment, and camera components	
high-speed pulse generators	
see pulse generators	
high-velocity gun systems	
see firearms and firearm components	
HMX and derivatives (CAS 2691-41-0)	ML8.a.13
HN1/2/3	
see nitrogen and nitrogen compounds	
HNAD	ML8.a.14
HNF (CAS 20773-28-8)	ML8.d.7
HNIW	
see CL-20	
HNS (CAS 20062-22-0)	ML8.a.15
hog cholera virus	
see swine fever virus	
holding and storage vessels	
see chemical storage tanks and containers	
hollow cylinder centrifugal balancing machines	
see rotor assemblies for gas centrifuges	
hollow fan blades	9E003.a.11
homing seeker systems	ML12
honing machines	
see machine tool equipment, components and assemblies	
hot embossing tools	3B001.f.2
hot isostatic densification technology	2E003
hot isostatic presses	2B004, 2B104, 2B204
hot melt prepeg production equipment	1B001
hot-shot tunnels	9B005
housings for isotope separation equipment	0B001.d.5, 0B001.g.4, 0B001.i.6, 0B001.j.3
hovercraft	
see surface-effect vehicles	
howitzers	ML2
HT-2 toxin	1C351.d.16

HTPB	1C111.b.2, ML8.e.12
hub assemblies for marine power transmission systems	8A002.o.2
hull penetrators and connectors	8A002, ML9
human pathogens	1C351
hybrid computers	4A101
hybrid inertial navigation systems	7A003
hybrid integrated circuits	3A001
hybrid rocket propulsion systems see rocket propulsion systems	
hydraulic flight control systems	7A116
hydraulic fluids	1C006
hydraulic stretch-forming machine technology	2E003
hydrazine and hydrazine compounds (CAS 37836-27-4, CAS 302-01-2, CAS 27978-54-7)	1C111.a.4, ML8
hydrides, substrate materials for integrated circuits	3C004
hydrocarbon fuels see fuels and propellants and related equipment	
hydrofoil vessels and components	8A001, 8A002
hydrogen and hydrogen compounds see also deuterium compounds see also tritium	
hydrogen cyanide (hydrocyanic acid, CAS 74-90-8)	1C450.a.6, ML7
hydrogen fluoride (CAS 7664-39-3)	1C350
water-hydrogen sulphide exchange plants	0B004.a.1, 0B004.b.1, 1B229
hydrogen cryogenic distillation columns	1B228
hydrogen fluoride lasers	6A005.d.5
hydrogen isotope storage and purification systems see isotope separation plants, systems, equipment and components	
hydrophones see also sensors and detectors see also underwater operations equipment	
.....	6A001.a.2, 6D003.a.1, 6D003.a.2
hydroxyl terminated polybutadiene see HTPB	
hydroxylammonium nitrate see HAN	
hydroxylammonium perchlorate see HAP	
hydroxy-terminated polybutadiene see HTPB	
>>=====<<	
>>I<<	
ICPMS see inductively coupled plasma mass spectrometers	
IEDs see improvised explosive devices	
IGCTs see integrated gate commutated thyristors	

igniters	
see detonation equipment	
image processing and enhancement equipment	4A003, ML15
for underwater use	8A002.d.1
image intensifiers	6A002.a.2, 6A002.c.1, 6A003.b.3, ML15
infrared imaging equipment	ML15
solid-state imaging equipment	6A003.b.5, 6A203.b.4
imaging cameras	
see also camera systems, camera equipment, and camera components	
	6A003
imaging sensor equipment	
see sensors and detectors	
imidazoles	ML8.a.16
impellers for use in reaction vessels	2B350
imprint lithography equipment	3B001, 3B001.f.1, 3B001.f.2, 3C002
improvised explosive devices	ML4
incapacitating agents	
see chemical warfare agents and precursors	
incendiary munitions, fuels for use in	ML8.c.6
incinerators for destroying chemicals	2B350
independent air power systems	
see air independent power systems	
indicator heads for balancing machines	2B119
indium substrate materials	3C001, 3C003
induction coil magnetometers	
see also electromagnetic equipment	
	6A006.a.4
induction furnaces	
see furnaces	
inductively coupled plasma mass spectrometers	3A233
inertial navigation systems, equipment and components	
see also navigation systems, equipment and components	
	7A003, 7D002, 7E004.a.4
inflatable membrane finishing tools	2B002
information security systems	
see also cryptographic equipment	
see also jamming equipment	
see also non-cryptographic information systems	
	4D003, 5A002
infrared absorption analysers	0B004.b.6
infrared imaging equipment	ML15
infrared sensors and detectors	
see also sensors and detectors	
	6A002.a.3
inhibited red fuming nitric acid	1C111.a.3
initiation systems	
see detonation equipment	
inorganic fibres and filamentary materials	

see fibrous and filamentary materials	
inorganic overlays	
see surface coating and processing materials and equipment	
INS	
see inertial navigation systems, equipment and components	
inspection equipment	
see test, inspection and production equipment	
inspection equipment for hemishells	
see dimensional inspection and measuring systems	
instruction generators for machine tools	
see machine tool equipment, components and assemblies	
instrumentation cameras	6A003
insulation in rockets	9A008, 9C108
integrated circuits	
see also semiconductor manufacturing equipment	
see also substrate materials for integrated circuits	
.....	3A001
electro-optical	3A001.a.2, 3A001.a.6
monolithic	3A001, 3A001.b.2
neural network integrated circuits	3A001.a.9
optical integrated circuits	3A001, 3A001.a.6
radiation hardened	3A001.a.1
storage integrated circuits	3A001.a.4
integrated flight instrument systems	
see flight control systems	
integrated gate commutated thyristors	3A001
integrated navigation systems	
see also navigation systems, equipment and components	
.....	7A103, 7D102
interconnect equipment	
see computers, computer assemblies and computer components	
interferometers	2B006.b.1, 6A225
interlacing machines	1B001
interstage connectors	9A121
interstages, usable in missiles	9A117
intrinsic magnetic gradiometers	
see electromagnetic equipment	
intrinsically conductive polymers	1C001
intrusion software	4A005, 4D004, 4E001.c
inverters (electrical)	
see frequency changers and generators	
iodo acetone	ML7
ion exchange separators	
see also isotope separation plants, systems, equipment and components	
.....	0B001, 0B001.a.5, 0B006, 1B233
ion implantation equipment	2B005, 2E003, 3B001
ion plating technology	2B005, 2E003
ion sources	

see mass spectrometers and ion sources	
IRFNA	
see inhibited red fuming nitric acid	
iron, iron alloys and iron compounds	
see also steels	
as powder fuels	ML8.c.5
ferrocene carboxylic acids	ML8.f.4
ferrocene derivatives	1C111.c.6
ferrosilicon, in pumps	2B350.i.2
superfine iron oxide	ML8.f.19
isolators for biological agents	2B352.f.2
isostatic presses	
see hot isostatic presses	
isotope separation plants, systems, equipment and components	0B001.a.3
aerodynamic separators	0B001
atomic vapour laser separators	0B001.a.6
chemical exchange separators	0B001.a.4, 1B233.d
electromagnetic components	0B001.j.4, 0B001.j.6
fast reacting ion-exchange resins	0B001.f.1
for lithium isotope separation	1B233.b.4
gas centrifuge separators	0B001.a.1
gaseous diffusion separators	0B001.a.2
hydrogen isotope storage and purification systems	1A225, 1B231.b.2
ion exchange separators	0B001.a.5, 0B006, 1B233.c
liquefaction stations	0B002
lithium separation	1B233, 1C233
molecular laser isotope separation equipment	0B001, 0B001.a.7
plasma separators	0B001, 0B001.a.8
product and tails collector systems	0B001.g.3, 0B001.h.2, 0B001.i.5, 0B002
separation nozzle units	0B001.d.1, 0B001.d.7
supersonic expansion nozzles	0B001.h.1
using corrosion-resistant materials	0B002
vortex tubes	0B001.d.1, 0B001.d.2, 0B001.d.7
>>=====<<<	
>>J<<<	
jamming and interception equipment	
see also explosives and explosive devices	
for global navigation satellite systems	ML11
for telecommunications systems	5A001
Japanese encephalitis virus	1C351.a.20
jet engines and components	
see aero-engines and components	
jig boring machines	2B001.b.3
Joule–Thomson self-regulating minicoolers	6A002.d.2
Junin virus	1C351.a.14
>>=====<<<	
>>K<<<	
K-55 (CAS 130256-72-3)	ML8.a.13

K-6	
see RDX and derivatives	
Kalman filtering software	7D102
Kerr cells	6A203.b.4
keto-bicyclic HMX	
see K-55	
keto-RDX	
see RDX and derivatives	
key precursors to chemical warfare agents	
see chemical warfare agents and precursors	
keyloader equipment	
see also cryptographic equipment	
.....	ML11
KR3538	
see titanium, titanium alloys and titanium compounds	
krytron tubes	3A228
vacuum tubes and valves (electronic).....	3A228
Kyasanur Forest virus	1C351.a.21
>>=====<<	
>>L<<	
Laguna Negra virus	1C351.a.16
laminates	
see composite material components and structures	
land vehicles and components	ML6
bridges and bridge laying vehicles	ML17
launch vehicles	9A110, 9B116
mobile repair shops and related equipment	ML17
recovery vehicles	ML10.h.5
remotely operated bomb disposal units	1A006
surface-effect vehicles	8A001
landing deceleration parachutes	
see also parachutes	
.....	ML10.h.6
laser beam systems	6A005, 6A205
coating and processing equipment.....	2E003
diagnostic equipment.....	6A005.f.2
for communications	5E001.b.2, 5E001.c.2
for directed energy weapons.....	ML19
for isotope separation	0B001
for light detection and ranging equipment (LIDAR).....	6A008
for measuring instruments and systems.....	2B006
for submersible vehicles	8A002.d.2
for underwater communications	5A001.b.1
for vapour deposition systems	2B005.c.1
in radar systems	6A008, 6A108
laser microphones	6A005.g
laser stacks.....	6A005.d.1.d
protective military	ML17

pulsed lasers	ML19
ring laser gyros	7B002
super high-powered	6E003
synthetic crystalline host material	6C005
Lassa fever virus	1C351.a.8
launch and launch support equipment	9A115
for kinetic energy weapons	ML12
for unmanned airborne vehicles	ML10.c.2
launch vehicles	9A010, 9A110, 9A115, 9B116
projectile launchers	ML2
software for	9D103, 9D105
technology for	9E012
laying equipment	
see explosives and explosive devices	
LAX-112 (3,6-diamino-1,2,4,5-tetrazine-1,4-dioxide)	ML8.a.38
lead and lead compounds	ML8, ML8.f.5
lewisites	ML7.b.2
libraries	
see parametric technical databases (libraries)	
LICA 12	
see neopentyl[diallyl]oxy, tri[dioctyl]phosphato-titanate	
LIDAR	
see light detection and ranging equipment (LIDAR)	
lift fans for surface effect vessels	8A002
light detection and ranging equipment (LIDAR)	6A008
light gas gun systems	
see gas guns	
light triggering thyristors	3A001
lighter than air vehicles	
see aircraft and aircraft components	
lighting systems, for underwater use	8A002
linear accelerometers	7A001, 7A101
linear and angular displacement measuring instruments	
see dimensional inspection and measuring systems	
linear focal plane arrays	
see focal plane arrays	
linear position feedback units	
see also sensors and detectors	
.....	2B008
linear voltage differential transformer systems	2B006.b.1
liquefaction stations	0B002
liquid fuels and propellants	
see fuels and propellants and related equipment	
liquid lasers	6A005
liquid metal handling systems	
see also crucibles	
.....	0B001.i.4
liquid oxidisers	

see oxidisers	
liquid oxygen converters	ML10
liquid rocket propulsion systems	
see rocket propulsion systems	
liquid uranium handling systems	
see uranium metal, uranium alloys, and uranium compounds	
lithium isotope separation facilities	
see isotope separation plants, systems, equipment and components	
lithography equipment, for wafer processing	3B001
LNF	
see butyl 2-chloro-4-fluorophenoxyacetate	
location and object detection systems	
see sensors and detectors	
see underwater operations equipment	
logic processors and assemblies	
see also field programmable gates, logic arrays and interconnects	
.....	4A003
Louping ill virus	1C351.a.22
low-light-level television camera tubes	ML15
LTTs	
see light triggering thyristors	
lubricating materials	1C006
Lujo virus	1C351.a.19
lumpy skin disease virus	1C352.a.16
lymphocytic choriomeningitis virus	1C351.a.9
lyssa virus	
see Rabies virus and all other members of the Lyssavirus genus	
>>=====<<	
>>M<<	
machine guns and machine pistols	
see also firearms and firearm components	
.....	ML1
machine tool equipment, components and assemblies	
see also numerically controlled machine tools	
see also rotor assemblies for gas centrifuges	
assemblies and units	2B008
for removing materials	2B001
for superplastic forming and diffusion bonding	1B003
for the production of composite structures	1B101
numerically controlled	2B001
Machupo virus	1C351.a.21
magazines (ammunition)	
see ammunition and components	
Magnaporthe grisea	1C354.c.6
magnesium, magnesium alloys and magnesium compounds	1C002.b.5, 1C002.c.1
as propellant	1C111.a.2.c
high-purity	1C228
in particle form	1C011

in powder fuel.....	ML8.c.5
magnesium oxide.....	2A225.a.2
magnetic equipment	
see electromagnetic equipment	
magnetorheological finishing tools.....	2B002
magnetostrictive alloys.....	1C003
mandrels	
for bellows.....	2B228
for composite structures.....	1B101
for filament winding machines.....	1B201
for forming rotors.....	2B209
manganin gauges.....	6A226
manipulative equipment	
for nuclear reactors.....	0A001
for underwater use.....	8A002
manned submersible vehicles	
see submersible vessels, equipment and components	
manufacturing equipment	
see machine tool equipment, components and assemblies	
MAPO and derivatives (CAS 57-39-6).....	ML8.f.11
maraging steels.....	1C116, 1C216
Marburg virus.....	1C351.a.11
marine acoustic systems	
see acoustic systems, equipment and components	
marine engines	
see propellers and propfans	
marine vessels, equipment and components	
see also propellers and propfans	
see also submersible vessels, equipment and components	
.....	8A
acoustic systems, equipment and components.....	6A001
amphibious vehicles.....	ML6
ferries.....	ML17
marine engines.....	8A002.o.2, 9A002
pumpjet propulsion systems.....	8A002
stabilisers for.....	8A002
masks (facial)	
see protective and decontamination clothing and equipment	
masks for integrated circuits	
see semiconductor manufacturing equipment	
mass spectrometers and ion sources.....	3A233
in isotope separators.....	0B001.j.2, 0B002, 0B002.g.2, 0B002.g.4, 1B226
microfluorination ion sources.....	3A233
materials, for aerospace design and testing.....	9C
McAIX, coating technology.....	2E003
MCTs	
see MOS controlled thyristors	
measuring instruments and systems	

see dimensional inspection and measuring systems	
see sensors and detectors	
mechanical alloying, alloys made by	1C002.c.2
mechanical cameras	
see camera systems, camera equipment, and camera components	
melt extraction and spinning, alloys made by	1C002.c.2, 1C002.d.3
melting and casting furnaces	
see furnaces	
mercury amalgam pumps	1B233.b.2
mercury cadmium telluride	6C002.b.3
metal alloys	
see alloys	
metal coated fibre preforms	
see fibrous and filamentary materials	
metal organic chemical vapour deposition reactors	
see chemical vapour deposition equipment	
metal powder fuels	ML8.c.5
as propellants	1C111.a.2
manufacturing equipment	1B102, ML18
metal vessels for nuclear reactors	0A001
metal working process tools, die and fixture technology	
see machine tool equipment, components and assemblies	
metallurgical melting and casting furnaces	
see furnaces	
metals	
see also name of metal, e.g. aluminium	
in particle form	1C011
machine tools for removing	2B001
methyl BAPO	ML8.f.12
methyl benzilate (CAS 76-89-1)	1C350
methyl phosphinyl dichloride (CAS 676-83-5)	1C350
methyl phosphinyl difluoride (CAS 753-59-3)	1C350
methyl phosphonyl dichloride (CAS 676-97-1)	1C350
methyl phosphonyl difluoride (CAS 676-99-3)	1C350, ML7.c.1
methyl unsymmetrical diphenylurea	
see methyl-N,N-diphenylurea	
methyldiethanolamine	1C450.b.8
methylethyldiphenyl urea	ML8
methylhydrazine nitrate	1C111.a.4
methyl-N,N-diphenylurea	ML8
methylphosphonic acid (CAS 993-13-5)	1C350, 1C450.b.1
methylphosphonothioic dichloride (CAS 676-98-2)	1C350
methyl-substituted phenylene	8.b.1
MHN	
see methylhydrazine nitrate	
micro contact printing tools	3B001.f.2
microbolometers	6A002.a.3
microchannel plates	6A002.a.2, ML15

Microcycclus ulei	1C354.c.3
microcystin	1C351.d.10
Micro-firing units	3A229.c
microfluorination ion sources	3A233
microorganism cultures	
see bacterial cultures	
see biological warfare agents	
see fungi	
see virus cultures	
microprocessor, microcontroller and microcomputer microcircuits	
.....	3A001.a.2, 3A001.a.3, 3E003
microwave equipment and components	0B001.i.1, 3A001, 3A002
military vehicles	
see land vehicles and components	
milling machines	2B001, 2B123
minelets	
see submunitions	
mines (explosive) and components	
see also explosives and explosive devices	
.....	ML4
missiles, missile equipment and missile components	
see also launch and launch support equipment	
see also rockets, rocket equipment and components	
.....	ML4
accelerometers for	7A101, 7A103
combustion regulation equipment	9A118
components usable in	9A108
control systems	5A101
for military use	ML4
guidance sets.....	7A117, 7D103
navigation systems.....	7A102, 7A103
precision tracking systems for	6A108
propulsion systems and components	9A101, 9A105, 9A106, 9A109, 9A111
radar cross-section measurement systems and components	6B108
reentry vehicles usable with	9A116
software for.....	6D103
staging mechanisms.....	9A117
thermal batteries	3A102
wind tunnels for.....	9B105
mission-abort assessment systems	
see damage assessment systems	
MMICs	
see monolithic integrated circuits	
mobile gas liquefying equipment	ML4
mobile repair shops and related equipment	ML17
MOCVD equipment	
see chemical vapour deposition equipment	
modeccin	1C351.d.17

models (simulations)	
see simulators and simulator components	
see software	
modular electrical pulse generators	3A229
molecular laser isotopic separation plant	
see isotope separation plants, systems, equipment and components	
molecular pumps	0B001.b.9
molybdenum and molybdenum alloys	
coating technology	2E003
in fibrous form	1C010
spherical particles of	1C117
MON	
see nitrogen and nitrogen compounds	
monitoring systems	
see sensors and detectors	
see surveillance systems	
monkey pox virus	1C351.a.12
monolithic integrated circuits	3A001, 3A001.b.2
monolithic mirrors	6A004.a.2
monomers	ML8
monomethyl hydrazine (CAS 60-34-4)	1C111.a.4, ML8.c.4
monospectral imaging sensors	6A002
mortars	ML2
MOS controlled thyristors	3A001
motion simulators	
see also simulators and simulator components	
.....	2B120
motors and motor components	
see engines and engine components	
moulds	
for isostatic presses	2B204
for superplastic forming and diffusion bonding	1B003
for the production of composite structures	1B101
movable nozzle control systems	
see rocket propulsion systems	
MPA	
see N-nonanoylmorpholine	
MPMs	
see microwave equipment and components	
MRF	
see magnetorheological finishing tools	
multichip integrated circuits	3A001
multidirectional, multidimensional weaving machines	1B001
multi-element detector arrays	
see sensors and detectors	
multi-layer masks for integrated circuits	
see semiconductor manufacturing equipment	
multilevel security capability equipment	

see information security systems	
multimode optical fibre and cables, high tensile strength	
see optical fibre, equipment and accessories	
multiple domed combustors, technology for development and production of....	9E003.a.1
multiple-seal pumps.....	2B350
multipoint initiation systems	
see detonation equipment	
multisensor mission management systems, technology for	7E004.b.6
multispectral imaging sensors	6A002
multistage light gas guns	
see gas guns	
multi-walled piping.....	2B350
Murray Valley encephalitis virus.....	1C351.a.23
mustard gas	
see chemical warfare agents and precursors	
see nitrogen and nitrogen compounds	
Mycoplasma capricolum subsp. Capripneumoniae	1C352.b.2
Mycoplasma mycoides subsp. Mycoides.....	1C352.b.1
mycoplasmas	1C352
>>=====<<	
>>N<<	
N-(2-nitrotriazolo)-2,4-dinitroimidazole	
see NTDNIA	
N,N diallylhydrazine, as propellant	1C111.a.4
N,N-dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-ols and corresponding protonated salts	1C450.b.5
N,N-dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-thiols and corresponding protonated salts	1C450.b.6
N,N-dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethyl-2-chlorides and corresponding protonated salts	1C450.b.4
N,N-dialkyl [methyl, ethyl or propyl (normal or iso)] phosphoramidic dihalides	1C450.b.2
N,N-diisopropyl-(beta)-amino ethanol (CAS 96-80-0).....	1C350
N,N-diisopropyl-(beta)-aminoethane thiol (CAS 5842-07-9).....	1C350
N,N-diisopropyl-(beta)-aminoethyl chloride (CAS 96-79-7).....	1C350
N,N-diisopropyl-(beta)-aminoethyl chloride hydrochloride (CAS 4261-68-1).....	1C350
N,N-dimethyl phosphoramidic dichloride (CAS 677-43-0).....	1C350
N,N-dimethylaminophosphoryl dichloride	
see diethyl methylphosphonate	
N,N-diphenylurea	ML8
nanocrystalline alloy strips	1C003
nano-imprint lithography tools	3B001.f.2
naphthalene.....	1C008.b.1
natural uranium	
see uranium metal, uranium alloys, and uranium compounds	
naval vessels	
see marine vessels, equipment and components	
see submersible vessels, equipment and components	

navigation systems, equipment and components

see also global navigation satellite systems

see also sensors and detectors

.....	7A, 7A105
acoustic underwater systems	6A001.a.1
avionics systems	7D003
data-based reference navigation equipment	7A003, 7D003.b.3, 7E004.a.6
direction finding systems.....	5A001, 7A115, 7D003.d.5, 7E004.a.1
electronic	ML11
for helicopters.....	7E004.c.2
for missiles	7A117, 7D103
for submersible vehicles	8A002
for unmanned airborne vehicles	9A012.b.2
global navigation satellite systems	7A003
inertial navigation systems	7A003, 7E004.a.4
integrated navigation systems.....	7A103
ocean salvage systems	8A001
passive coherent location systems	5A001
passive direction finding systems	7A115
piloting systems for parachuted loads	ML10
production facilities for	7B002, 7B003, 7B103
software for.....	7D002
sonar navigation systems	6A001.a.2, 7A008
terrain contour mapping equipment.....	6A108
True North determination equipment	7A003, 7A003.c.1

NBC detection systems

see nuclear, biological and chemical detection systems

N-butyl-ferrocene (CAS 31904-29-7)	ML8.f.4
---	----------------

NDT

see non-destructive test equipment

negative hydrogen ion beam current injectors	ML19
---	-------------

NENAs (CAS 85954-06-9, CAS 85068-73-1, CAS 85068-73-1, CAS 82486-83-7, CAS 82486-82-6, CAS 17096-47-8)	ML8.e.14
---	-----------------

neodymium lasers	6A205
-------------------------------	--------------

neopentyl[diallyl]oxy, tri[dioctyl]phosphato-titanate (CAS 110438-25-0, CAS 103850-22-2)	ML8.f.15
---	-----------------

neptunium-237	1C012
----------------------------	--------------

nerve agents

see chemical warfare agents and precursors

nets for submersible vessels and torpedoes

see submersible vessels, equipment and components

network analysers.....	3A002
-------------------------------	--------------

neural computers, assemblies and components	4A004
--	--------------

neural network integrated circuits.....	3A001.a.9
--	------------------

neutron detection and measuring instruments, for nuclear reactors	0A001
--	--------------

neutron generator systems.....	3A231
---------------------------------------	--------------

Newcastle disease virus	1C352.a.9
--------------------------------------	------------------

NG

see nitroglycerin	
nickel, nickel alloys and nickel compounds	1C002.b.1
chemical handling equipment made with	2B350
nickel aluminides	1C002.a.1
nickel--graphite coating technology	2E003
porous nickel metal	1C240
powdered	1C240
qualified for turbine engines	1C002.c.1
niobium and niobium alloys	1C002.b.2, 1C002.c.1, 2B350
Nipah virus	1C351.a.25
nitrate groups, compounds containing	ML8.e.6
nitrateethylnitramine compounds	
see NENAs	
nitraza groups, compounds containing	ML8.e.6
nitric acid, liquid oxidisers containing	ML8.d.10
nitrided niobium-titanium-tungsten alloy	2A225.a.2
nitro groups, compounds containing	ML8.e.6
nitrocellulose	ML8
nitrogen and nitrogen compounds	
see also ADN	
see also ammonia-hydrogen exchange plants (crackers)	
see also AP	
see also NTAT	
ammonium bifluoride	1C350
ammonium picrate	ML8
mixed oxides of nitrogen	1C111.a.3
nitrogen dioxide (CAS 10102-44-0)	1C111.a.3
nitrogen mustards	ML7.b.2
nitrogen trifluoride	ML8.d.3
nitroglycerin (CAS 55-63-0)	ML8
nitroguanidine (CAS 556-88-7)	1C011, ML8
nitrostarch	ML8
N-methyl-P-nitroaniline (CAS 100-15-2)	ML8.f.13
NNHT (CAS 130400-13-4)	ML8.a.31
N-nonanoylmorpholine (CAS 5299-64-9)	1A004.a.4, ML7.d.6
noble metal modified aluminides, coating technology	2E003
noise reduction systems	
for marine vessels	8A002, 8A002.o.3
for underwater use	8A002
propellers and propfans	8E002
non-composite ceramic materials	
see ceramic materials	
non-contact type measuring systems	2B006.b.1
non-cryptographic information systems	5A002.a.7
non-destructive test equipment	9B007
non-fluorinated polymeric substances	1A003, 1C008
non-linear optical materials	
see optical components and equipment	

non-magnetic diesel engines, for military use	ML9.b.3
non-planar absorbers	
see electromagnetic equipment	
non-tunable lasers	
see laser beam systems	
nozzles for aerodynamic isotope separation	
see isotope separation plants, systems, equipment and components	
nozzles for pyrolytic deposition	
see pyrolysed materials and pyrolysis equipment	
nozzles for rocket propulsion systems	
see also rocket propulsion systems	
.....	9A008
control systems	9E003.a.10
usable in missiles.....	9A106, 9A108
N-pyrrolidinone	ML8
NQ	
see nitroguanidine	
NTAT	ML8.a.25
NTDNA (CAS 75393-84-9).....	ML8.a.32
NTDNIA	ML8.a.16
NTDNT	ML8.a.32
NTNMH.....	ML8.a.17
NTNT	ML8.a.25
NTO (CAS 932-64-9)	ML8.a.18
nuclear precession magnetometers	6A006.a.2
nuclear reactors and reactor components	0A, 0A001
control systems	0A001
for military use	ML17
fuels and propellants for	0B005, 0B006
metallic heat sources.....	1C012
pressure vessels and tubes	0A001
nuclear, biological and chemical detection systems.....	1A004
nucleic acid sequences	
see genetic elements	
numerically controlled machine tools	2B001
co-ordinate measuring machines	2B006
dimensional inspection machines, instruments and systems	2B206
for gear production	2B003
for optical finishing	2B002
software for.....	2D002
spin-and flow-forming machines.....	2B009, 2B109, 2B209
technology for operating.....	2E003
>>=====<<	
>>O<<	
O,O-diethyl phosphorodithioate (CAS 298-06-6)	1C350
O,O-diethyl phosphorothioate (CAS 2465-65-8).....	1C350
O,O-diethyl S-[2-(diethylamino)ethyl] phosphorothiolate (CAS 78-53-5).....	1C450.a.1
O-alkyl alkyl-phosphonofluoridates	ML7.b.1

O-alkyl N,N-dialkyl phosphoramidocyanidates	ML7.b.1
O-alkyl O-2-dialkyl aminoethyl alkyl phosphonites	ML7.c.2
O-alkyl-aminoethyl alkyl phosphonothiolates	ML7.b.1
object detection and location systems see also sensors and detectors	
.....	6A001.a.1
ocean salvage systems	8A001
O-Chlorobenzylidenemalononitrile see [(2-chlorophenyl) methylene] propanedinitrile	
octahydro-1,3,5,7-tetranitro-1,3,5,7-tetrazine see HMX and derivatives	
octahydro-2,5-bis(nitroimino)imidazo [4,5-d]imidazole see BNNII	
octogen see HMX and derivatives	
octogene see HMX and derivatives	
O-ethyl s-2-diisopropylaminoethyl methyl phosphonothiolate see VX	
O-ethyl s-phenyl ethylphosphonothiolothionate see fonofos	
O-ethyl O-2-di-isopropylaminoethyl methylphosphonite (CAS 57856 11 8)	ML7.c.2
O-ethyl-N,N-dimethylphosphoramidocyanidate see tabun	
O-isopropyl methylphosphonochloridate (CAS 1445-76-7)	ML7.c.3
O-isopropyl methylphosphonofluoridate see sarin	
Omsk haemorrhagic fever virus	1C351.a.24
on board weapon control systems see weapons control systems	
on-line control systems for aerospace design and testing.....	9B005
for gas turbine manufacture.....	9B002
ONTA see NTO	
operating systems software see software	
O-pinacolyl methylphosphonochloridate	ML7.c.4
O-pinacolyl methylphosphonofluoridate see soman	
optical (infrared) tracking (range) radars see radar systems and components	
optical components and equipment see also optical fibre, equipment and accessories see also optical mirrors see also sensors and detectors	
.....	6A002, 6A004
coherent optical transmission and detection equipment	5E001.c.2

for measurement and testing.....	6B004
Kerr cells	6A203.b.4
non-linear optical materials	6C004
optical computers.....	4A004
optical control equipment.....	6A004
optical detectors and sensors	6C002
optical integrated circuits	3A001
optical switching technology and software	5B001.b.3, 5E001.c.3
optically pumped technology	6A006.a.2
Pockel cells.....	6A203.b.4
projection telescopes	6A005.f.4
optical fibre, equipment and accessories	5A001
gyro coil winders	7B003
hull penetrators and connectors	8A002, ML9
image inverters	ML15
in hydrophones	6A001.a.2
magnetometers.....	6A006.a.4, 6A006.a.5
sensitive	6A002.d.3
optical finishing machine tools	2B002
optical mirrors	6A004
beam steering mirrors	6A004.a.4
calibration equipment	7B002
with cooling systems	6A005.e.1
optical surface coating and treatment technology	
see surface coating and processing materials and equipment	
organic materials	
see also composite material components and structures	
explosives	ML8.a.34
fibrous and filamentary materials	1C010, 1C010.e.2
matrix materials.....	1A002
organo--inorganic compounds.....	3C003
organo--metallic coupling agents	ML8.f.15
Oropouche virus	1C351.a.25, 1C351.a.26
oscilloscope	3A002.a.7
ovens for UF₆ isotope separation equipment.....	0B002
overlay coatings	
see surface coating and processing materials and equipment	
over-the-wall manipulators.....	2B225
oxidisers	1C111.a.3, ML8
oxygen and oxygen compounds	
liquid oxygen converters	ML10
mixed oxides of nitrogen	1C111.a.3
oxalyl chloride	1C350
oxide coating technology.....	2E003
oxygen iodine lasers	6A005.d.5
>>=====<<	
>>P<<	
pack cementation	2E003

packed liquid--liquid exchange columns	1B233.b.1
paints	
see surface coating and processing materials and equipment	
parachutes	ML10
paragliders	ML10.h.3
para-hydrogen Raman shifters	6A205
Parallel mechanism machine tools	2B001.b.2.d
parametric technical databases (libraries)	1E, ML17
particle beam systems for directed energy weapons	ML19
particulate metal fuels	
see fuels and propellants and related equipment	
see metals	
passive coherent location systems	5A001
passive direction finding systems	7A115
passive sensors, in aircraft missile protection systems	ML4
pathogens	
see animal pathogens	
see human pathogens	
see plant pathogens	
PBAA	
see polybutadiene-acrylic acid	
PBAN	
see polybutadiene-acrylic acid-acrylonitrile	
PCLs	
see passive coherent location systems	
PDNT	ML8.a.32
pellicular macro-reticulated resins	0B001.f.1
pentaboranes (CAS 19624-22-7, CAS 18433-84-6)	ML8.c.3
pentaerythritoltetranitrate	ML8
pentyl ferrocene (CAS 1274-00-6)	1C111.c.6
perchlorates composited with high energy fuels	ML8.c.7
perfluoroaliphatic-ethers	1C006.d.1
perfluoropolyalkylether-triazines	1C006.d.1
permanent magnet electric engines	8A002.o.2
personal radiation monitoring dosimeters, sensors and detectors for	1A004
personalised smart card systems	5A002
peste des petits ruminants virus	1C352.a.10
PETN	
see pentaerythritoltetranitrate	
PFIB (CAS 382-21-8)	1C450.a.2
PG/LAs (programmable gate/logic arrays)	
see field programmable gates, logic arrays and interconnects	
PGN (CAS 27814-48-8)	ML8.e.15
phase conjugators	ML19
phase measuring equipment	
see signal processing equipment	
phased-array systems	
see also optical mirrors	

see also radar systems and components	
.....	6A004.d.4, 6A005.f.2
phenarsazine chloride	
see 10-chloro-5,10-dihydrophenarsazine	
phenolic resin impregnated carbon materials	1C010
phenyl substituted phenylene	1C008.b.1
phenylacetyl chloride (CAS 532-27-4)	
see 2-chloro-1-phenylethanone	
phenylene and phenylene compounds	1C006.b.1, 1C008.b.1
phosgene (carbonyl chloride) (CAS 676-99-3)	1C450.a.3, ML7
phosphorus and phosphorus compounds	
see also methyl-phosphonic acid	
phosphate glass.....	6C004
phosphor bronze mesh packings.....	1A226
phosphorus oxychloride (CAS 10025-87-3).....	1C350
phosphorus pentachloride (CAS 10026-13-8)	1C350
phosphorus trichloride (CAS 7719-12-2)	1C350
substrate materials for integrated circuits	3C003, 3C004
photocathodes	6A002.a.2
photoconductive arrays	
see focal plane arrays	
photographic equipment	
see camera systems, camera equipment, and camera components	
see film processing equipment	
photomultiplier tubes	6A202
photovoltaic arrays	
see focal plane arrays	
physical vapour deposition technology	2E003
piezoelectric polymers and copolymers	1A001, 6A001.a.2
piloting systems for parachuted loads	
see also navigation systems, equipment and components	
.....	ML10
pinacolone (CAS 75-97-8)	1C350
pinacolyl alcohol (CAS 464-07-3)	1C350
pingers	6A001.a.1
piping and header systems for UF₆ isotope separation equipment	0B002
pistols	
see also firearms and firearm components	
.....	ML1
pistons, using ceramic materials	9E003.f.1
pitch-impregnated fibres	
see preforms and prepegs	
pivot-cup assembly bearings	0B001.b.8
planar absorbers	1C001
plant pathogens	1C354
plasma equipment and components	
arc tunnels.....	9B005
CVD equipment.....	2B005.a.1, 3B001

furnaces	2B227
isotope separation equipment	0B001.a.8
metal powder generators.....	1B102
plasma separation process	0B001
propulsion systems	ML12
spraying equipment	2B005, 2E003
plasmids	
see genetic elements	
plasticisers	ML8
platinized catalysts	1A225
platinum coating technology	2E003
plug-ins for instrumentation cameras	6A003.a.6
Plutonium 236 and 238	
see radionuclides	
plutonium and plutonium compounds and isotopes	1C012
conversion plant and equipment	0B006
pneumatic tyre casings	ML6
Pockel cells	6A203.b.4
Polonium 208, 209 and 210	
see radionuclides	
poly nitratomethylmethyloxetane	
see poly-NIMMO	
poly phenylene-vinylene, intrinsically conductive polymers based on	1C001
poly(epichlorohydrin)	ML8.e.13
poly(epichlorohydrindiol)	ML8.e.13
poly(nitratomethyl oxirane)	
see PGN	
poly[3-nitratomethyl-3-methyloxetane]	
see poly-NMMO	
poly-2,2,3,3,4,4-hexafluoropentane-1,5-diol formal	
see FPF-1	
poly-2,4,4,5,5,6-heptafluoro-2-tri-fluoromethyl-3-oxaheptane-1,7-diol formal	
see FPF-3	
polyaniline, intrinsically conductive polymers based on	1C001
polyarylene ketones, in thermoplastic liquid crystal copolymers	1C008
polyarylene sulphides, in thermoplastic liquid crystal copolymers	1C008
polybenzothiazoles, technology for the production of	1E
polybenzoxazoles, technology for the production of	1E
polybiphenylenethersulphone	1C008
polybromotrifluoroethylene	1C006.c.3
polybutadiene--acrylic acid	1C111.b.3
polybutadiene--acrylic acid--acrylonitrile	1C111.b.4
polycarbosilazanes	1C007.e.3
polychlorotrifluoroethylene	1C006.c.2
polycyanodifluoroaminoethyleneoxide	ML8.f.16
polydiorganosilanes	1C007.e.1
polyetherimides	1C010.d.1
polyfunctional aziridine amides	ML8.f.17

polyglycidyl nitrate	
see PGN	
poly-GLYN	
see PGN	
polymeric substances	1C111, ML8, ML8.e.6
coating technology.....	2E003
fibre conversion equipment	1B001.d.1, 1B101.c.1
non-fluorinated	1A003, 1C008
poly-NIMMO (CAS 84051-81-0)	ML8.e.16
polynitrocubanes	ML8.a.19
polynitroorthocarbonates	ML8.e.17
poly-NMMO (CAS 84051-81-0)	
see poly-NIMMO	
polypyrrole, polymers based on	1C001
polysilazanes	1C007.e.2
polytetrahydrofuran polyethylene glycol	1C111.b.5
polythiophene, polymers based on	1C001
porcine enterovirus type 9	1C352.a.11
porcine herpes virus	
see herpes virus	
porous macro-reticulated resins	0B001.f.1
porous nickel metal	
see nickel , nickel alloys and nickel compounds	
positioning equipment	
see navigation systems, equipment and components	
positioning tables	2B121
potassium and potassium compounds	1C350
potassium amide catalyst pumps	1B230
potassium nitrate.....	ML8
potassium titanyl arsenate.....	6C004.b.1
potato andean latent tymovirus	1C354.a.1
potato spindle tuber viroid	1C354.a.2
powdered metal fuels	
see fuels and propellants and related equipment	
see metals	
power amplifiers, microwave equipment	3A001.b.8
power generating equipment, for directed energy weapons	ML19
power supplies	
air independent power systems.....	8A002, ML9.b.4
for induction furnaces.....	2B226
for isotope separation	0B001.j.5
high-power direct current	3A226, 3A227
power transmission systems	
see also engines and engine components	
for helicopters.....	9E003
for marine vessels	8A002
for tilt rotor/wing aircraft.....	9E003
praseodymium-doped fluoride fibre amplifiers	5E001.c.2

precision mandrels	
see mandrels	
precision tracking systems	
see tracking systems	
precursor materials	
see also chemical warfare agents and precursors	
see also explosives and explosive devices	
see also fuels and propellants and related equipment	
for composite materials	1C007
preforms and prepegs	
see also fibrous and filamentary materials	
.....	1C210
made from fibrous and filamentary materials.....	1C010
production facilities	1B001, 1B101
resin impregnated fibre prepegs	9C110
pressure refuellers	
see also fuels and propellants and related equipment	
.....	ML10
pressure regulation technology	
see also sensors and detectors	
.....	1E103, 2B230, 6A226
pressure suits	
see protective and decontamination clothing and equipment	
pre-swirl and post-swirl systems	8A002.o.1
primary high energy cells and batteries	
see cells and batteries (electrical)	
primer anvils	ML3
probing (test) systems, semiconductor equipment	
see semiconductor manufacturing equipment	
process systems	
for aerodynamic separation equipment.....	0B001.d.7
for molecular laser isotope separation equipment	0B001.h.5
for nuclear fuel reprocessing	0B006
processors, digital	
see signal processing equipment	
product and tails collector systems for isotope separation equipment	0B001.g.3,
0B001.h.2, 0B001.i.5, 0B002	
profilometers	7B002
programmable gate and logic arrays	
see field programmable gates, logic arrays and interconnects	
projectile launchers	
see launch and launch support equipment	
projection telescopes.....	6A005.f.4
propellants	
see fuels and propellants and related equipment	
propellers and propfans	
for marine vessels	8A002
software for.....	8D002

technology for.....	8E002, 9E003.b.2
ventilated propeller systems	8A002.o.2
propelling nozzles	
see nozzles for rocket propulsion systems	
propulsion systems and components	
see engines and engine components	
see fuels and propellants and related equipment	
see propellers and propfans	
see rocket propulsion systems	
propulsive substances	
see fuels and propellants and related equipment	
propyl ferrocene (CAS 1273-89-8)	1C111.c.6
propyleneimine (2-methylaziridine) (CAS 75-55-8)	ML8.f.18
protective and decontamination clothing and equipment	
see also breathing equipment	
.....	1A004
against chemical warfare agents	ML7
armoured plate	ML13
ballistic protection materials and components.....	ML13, ML6
body armour	1A005, ML13
for high altitude parachutists	ML10.h.8
full and half suits	2B352.f.1
helmets.....	ML10, ML13
hoods	2B352.f.1
masks	ML10
protonated salts, as toxic agents	ML7.b.1, ML7.c.2
proximity focused image intensifier tubes.....	6A203.b.4
Pseudomonas campestris pv. Oryzae	
see Xanthomonas oryzae pv. Oryzae	
Pseudomonas mallei	
see Pseudomonas mallei	
see Pseudomonas pseudomallei	
Pseudomonas solanacearum	
see Ralstonia solanacearum	
PTIA	ML8.a.16
Puccinia glumarum	
see Puccinia striiformis	
Puccinia graminis	1C354.c.4
Puccinia striiformis	1C354.c.5
pulsating chemical vapour deposition production equipment	
see chemical vapour deposition equipment	
pulse compression equipment.....	6A008
pulse generators	
see also detonation equipment	
.....	3A229, 3A230
pulse jet engines	
see aero-engines and components	

pulse liquid rocket engines	
see rocket propulsion systems	
pulse radar cross-section measurement systems and components	
see radar systems and components	
pulsed electron accelerators	3A201
pulsed laser systems	6A005, 6A205, ML19
pulsers	
see modular electrical pulse generators	
pumpjet propulsion systems	8A002
pumps	
ceramic materials in.....	2B350.i.2
ferrosilicon in.....	2B350.i.2
for isotope separation equipment.....	0B002
for potassium amide	1B230
for rocket propulsion systems.....	9A006
mercury amalgam pumps	1B233.b.2
molecular	0B001.b.9
multiple-seal pumps.....	2B350
optically pumped technology	6A006.a.2
pumpjet propulsion systems	8A002
seal-less pumps.....	2B350
stage pumps	0B004.b.4
vacuum pumps.....	0B002, 2B231
Puumala virus	1C351.a.31
PVD	
see physical vapour deposition technology	
Pyricularia spp.	
see Magnaporthe grisea	
pyroelectric television camera tubes	ML15
pyrolised materials and pyrolysis equipment	
see also carbon--carbon materials	
equipment and process controls.....	2B117
graphites	1C107
nozzles for	1B116
technology for the production of	1E104
pyrophoric metal alkyls and aryls	ML8
pyrotechnics, pyrotechnic equipment and components	ML2, ML4, ML8
PYX (CAS 38082-89-2)	ML8.a.20
PZO	
see DDPO	
>>=====<<	
>>Q<<	
QAM	
see quadrature-amplitude-modulation equipment	
QL	
see O-ethyl-2-di-isopropylaminoethyl methylphosphonite	
Q-switched lasers	
see laser beam systems	

quadrature-amplitude-modulation equipment	5B001.b.4, 5E001.c.4
quantum cryptography systems	5A002.a.9
quantum well equipment	3E003
quartz pressure transducers	
see also sensors and detectors	
.....	6A226
>>=====<<	
>>R<<	
Ra-226	
see radium alloys and compounds	
Rabies virus and all other members of the Lyssavirus genus	1C352.a.8
radar systems and components	6A008
Doppler navigation equipment	6A008, 6A108
electronically steerable phased array antennae.....	5A001, 6D003.d.2
for missiles	6B108
frequency agility technology	5A001.b.3, ML11
laser beam systems	6A108
pulsed cross-section measurement systems	6B007, 6B008
radiation hardened	6A102
range instrumentation radars	6A108.b.2
sidelooking airborne radar	6A008
signal processing equipment in	6A008
signature reduction equipment and materials	1C101
space-qualified.....	6A008, 6A108
synthetic aperture radar	6A008
temperature-rated.....	6A102
radiation hardened equipment	
computers	4A001.a.2
design technology	7E102
integrated circuits	3A001.a.1
radar systems	6A102
robot systems	2B007
shielding windows	1A227
telecommunications systems	5A001
video cameras	6A204
radiation sensors	
see sensors and detectors	
radio equipment and components	5A001.b.2
digital cellular radio equipment	5E001.b.3
digital demodulators	ML11
digital troposcatter-radio	ML11
digitally controlled receivers	5A001.b.5
for directed energy weapons.....	ML19
quadrature-amplitude-modulation equipment	5B001.b.4, 5E001.c.4
radio-frequency signal analysers	3A002
radiotelephones for civil use.....	5A002
receivers.....	5A002
spread spectrum equipment	5A001.b.3, 5A002.a.5, 5E001.b.4

radio frequency ion excitation coils	0B001.i.2
radioactive materials	
adapted for use in war.....	ML7
protective clothing and equipment against	1A004.a.2, 1A004.b.2
sensors and detectors	1A004.c.2
radiographic equipment.....	1B001.f.1
radionuclides.....	1C236
radiotelephones for civil use	5A002
Radium 223	
see radionuclides	
radium alloys and compounds.....	1C237
radome design and production software	6D003.d.2
Ralstonia solanacearum	1C354.b.5
Raman shift lasers	
see laser beam systems	
ramjet engines	
see also aero-engines and components	
.....	9A011
range instrumentation radars	6A108.b.2
range-finding systems	
see target acquisition systems	
range-gated illuminators, for submersible vehicles.....	8A002.d.2
Rankine cycle engines, for underwater use.....	8A002.j.1
rapid beam slew capability equipment	ML19
rate tables	
see motion simulators	
RDX and derivatives (CAS 121-82-4, CAS 115029-35-1)	ML8.a.21
reaction vessels and reactors (chemical).....	2B350
reactor fuels	
see fuels and propellants and related equipment	
see nuclear reactors and reactor components	
reactors	
see nuclear reactors and reactor components	
real-time control systems	
see flight control systems	
rebreathing apparatus	
see breathing equipment	
receivers, chemical	
see chemical storage tanks and containers	
receivers, microwave	
see microwave equipment and components	
receivers, radio	
see radio equipment and components	
rechargeable batteries and cells	
see cells and batteries (electrical)	
reciprocating engines	
see also engines and engine components	
.....	ML10

recoilless rifles	
see also firearms and firearm components	
	ML2
recorders, imaging equipment	ML15
recording equipment	3A002
analogue instrumentation magnetic tape recorders	3A002.a.1
digital data recorders	3A002.a.6
digital instrumentation magnetic tape data recorders	3A002.a.4
digital magnetic tape data recorders	3A002.a.2
digital video magnetic tape recorders	3A002.a.2
recovery parachutes	ML10.h.5
recovery vehicles and related equipment	ML10.h.5, ML6
reentry vehicles	9A116
re-entry vehicles	
see also spacecraft	
reflectance measuring equipment	6B004
reflectivity reducing materials and treatments	
see signature reduction equipment and materials	
reflectometers	7B102
reflectors	
see optical mirrors	
refractory ceramics, wet-spinning equipment	1B001.d.3, 1B101.c.3
refractory metals, coating technology	2E003
refrigeration units	
see cooling systems	
see cryogenic equipment, accessories and components	
refuellers for aircraft	ML10
reinforced composite materials	
see composite material components and structures	
reinforcement fibres, production facilities	1B001
remotely operated equipment	
see also unmanned airborne vehicles, systems and components	
see also unmanned submersible vehicles	
bomb disposal equipment	1A006
refuelling equipment	2B350
remote manipulators	2B225
resaturated pyrolised materials	
see carbon-carbon materials	
see pyrolised materials and pyrolysis equipment	
resin impregnated fibre preregs	
see preforms and prepegs	
resist materials	
see also semiconductor manufacturing equipment	
	3C002
reticles	
see semiconductor manufacturing equipment	

revolvers	
see also firearms and firearm components	
.....	ML1
Rhenium and rhenium alloys	1C241
ricin	1C351.d.4
Rickettsia prowazecki	1C351.c.20
Rickettsiae	
see Bacteria	
rifles	
see also firearms and firearm components	
.....	ML1
Rift Valley fever virus	1C351.a.13
rinderpest virus	1C352.a.12
ring laser gyros	
see gyros, gyro components and gyro equipment	
rings, for rotor tube support	0B001.b.4
ring-shaped motor stators	0B001.b.10
riot control agents	
see also chemical warfare agents and precursors	
see also toxicological agents	
protective and decontamination clothing and equipment	1A004.a.4
robot systems	2B007, 2B207, 8A002, ML17
Rocio virus	1C351.a.27
rocket propulsion systems	
carbon-carbon materials in	9A006
control systems	9A106
hybrid systems	9A009, 9A109
liquid-propellant	9A005, 9A006, 9A105, 9A106
motor cases	9A108
nozzles for	9A008, 9A106, 9A108, 9E003.a.10
pulsed.....	9A010
solid-propellant.....	9A107
tanks for.....	9A120
test benches and stands for	9B117
thrust chambers.....	9A006
rockets, rocket equipment and components	
see also flight control systems	
see also launch and launch support equipment	
see also rocket propulsion systems	
see also spacecraft	
.....	ML4
individual stages	9A119
insulation for.....	9C108
non-destructive test equipment	9B007
pyrolised materials.....	1C102
separation mechanisms.....	9A117
sounding rockets	1A102, 9A104, 9D103, 9D105
staging mechanisms.....	9A117

roller bearings	
see bearings	
rollers, for composite materials	1B101
rotary atomisation, alloys made by	1C002.c.2
rotary input type shaft absolute position encoders	3A001, 3A001.e.4
rotary position feedback units	2B008
rotary shaft seals for aerodynamic separation	0B001.d.4
rotary shaft seals for gaseous diffusion separators	0B001.c.4
rotating bands	ML3
rotational accelerometers	7A001
rotor assemblies for gas centrifuges	0B001.b.2, 0B001.b.3, 2B228
rotor blades for gas turbine engines	
see gas turbine engines	
rotor blades for helicopters	7E004.c.3
ROVs and RPVs	
see unmanned airborne vehicles, systems and components	
ruggedised equipment	
computers and components	4A101
telecommunications systems	5A001
Russian Spring--Summer encephalitis virus	
see Tick-borne encephalitis virus	
>>=====<<	
>>S<<	
S20 and S25 photocathodes	
see photocathodes	
Sabia virus	1C351.a.31
safety cabinets for biological agents	2B352.f.2
safety equipment	
see protective and decontamination clothing and equipment	
salicylates	ML8.f.1, ML8.f.9
Salmonella typhi	1C351.c.13
salvage systems	
see ocean salvage systems	
sarin	ML7.b.1
satellite technology	
see also spacecraft	
.....	5E001.b.1
saxitoxin	1C351.d.5
scanning cameras and systems	
see also camera systems, camera equipment, and camera components	
.....	6A003.b.2
scatterometers	7B002
scene mapping and correlation equipment	6A108
scoops for gas centrifuges	0B001.b.12
scramjet engines	
see also aero-engines and components	
.....	9A011
screw extruders	ML18

SCRs	
see silicon controlled rectifiers	
seal-less pumps	2B350
seals	
for surface effect vessels	8A002
made from fluoroelastomers	1A001
secondary batteries and cells	
see cells and batteries (electrical)	
security equipment	
see information security systems	
segmented mirrors for space assembly	
see optical mirrors	
self-contained diving apparatus	8A002, ML17
self-propelled guns and related equipment	
see land vehicles and components	
semi-automatic smooth-bore weapons	ML1
semi-closed diving apparatus	
see underwater operations equipment	
semiconductor lasers	6A005.d.1, 6A005.d.2
semiconductor manufacturing equipment	
see also integrated circuits	
.....	3B001, 3B002
sensors and detectors	
see also image processing and enhancement equipment	
see also radar systems and components	
explosives detection equipment	1A004.d
fabrication technology	6E003.a.1
for chemical warfare agents.....	ML7
for security-related equipment and systems	5B002
hydrophones	6A001.a.2, 6D003.a.2
imaging sensors	6A002, 6A108
linear position feedback units	2B008
nuclear, biological and chemical detection systems	1A004, ML7
object detection and location systems	6A001.a.1
optical sensors and detectors	6C002
sensor window materials	2E003
solid state detectors.....	6A002.c.3
Seoul virus	1C351.a.32
separation mechanisms for rockets	
see rockets, rocket equipment and components	
separation nozzles and tubes	
see isotope separation plants, systems, equipment and components	
separator module housings, for plasma separation equipment	0B001.i.6
separators for isotopes	
see isotope separation plants, systems, equipment and components	
separators, biological	
see centrifugal separators and decanters	
servo valves	7A116, 9A106

sesquimustard	
see chemical warfare agents and precursors	
S-FIL	
see step and flash imprint lithography tools	
shaker units	2B116, 9B106
sheep pox virus	1C352.a.13
shielding systems	
see also protective and decontamination clothing and equipment	
see also radiation hardened equipment	
see also signature reduction equipment and materials	
see also temperature-rated equipment	
design technology	7E102
shielding windows	1A227
Shiga toxin	1C351.d.6
Shiga toxin producing Escherichia coli (STEC)	1C351.c.18, 1C353
Shiga-like ribosome inactivating proteins	1C351.d.9
Shigella dysenteriae	1C351.c.14
ship positioning systems	
see navigation systems, equipment and components	
shock tubes and tunnels	9B005
shotguns	
see firearms and firearm components	
SHPL	
see super high-powered laser system components	
shrink fit machines	2B228
Si--	
see silicon and silicon compounds	
sidelooking airborne radar	6A008
sights and sighting equipment	ML1, ML2, ML5, ML904
signal processing equipment	4A003
array processors	4A003
digital technology	3E002
for towed hydrophones	6A001.a.2
frequency signal generators	3A002
in radar systems and components	6A008
in radio devices	5A001.b.6
signal analysers	3A002
underwater cable systems	6A001.a.2
wavefront measuring equipment	6A005.f.1
signature reduction equipment and materials	1C101, ML2
for military use	ML17
for underwater use	8A002.d.2
software for	1D101
silencers	ML1
silent bearings	
see bearings	
silicon and silicon compounds	
see also glass and glass-based materials	

see also silicon carbides	
fibres made from.....	1C007.c.1
fluorinated silicone fluids.....	1C006.b.2
fused silica in optical materials	6C004
Si-Al-O-N.....	1C007.c.1
silicide coating technology	2E003
silicon controlled rectifiers	3A001
silicon nitrides technology.....	1E.c.4
silicon oxide technology.....	1E.c.1
silicon-on-sapphire integrated circuits.....	3A001
substrate materials for integrated circuits.....	3C001, 3C005, 3C006, 3E003
silicon carbides.....	1C007.c.1
ceramic materials reinforced with	1C107
coating technology.....	2E003
heat exchangers and condensers made with	2B350.d.9
substrate materials for integrated circuits.....	3C001, 6C004
technology for the production of.....	1E.c.3
silicon intensifier target videcon tubes.....	6A203.b.4
silicon microcircuits	
see microprocessor, microcontroller and microcomputer microcircuits	
silver gallium selenide	6C004.b.2
silylated resists	3C002
simple programmable logic equipment	
see field programmable gates, logic arrays and interconnects	
simulants.....	1A004
simulators and simulator components	
environmental chambers.....	9B106
for flow environments	9B005
for gas turbine design and modelling	9D004
for integrated circuit manufacture	3D001
for military use	ML14
for nuclear reactors	ML17
motion simulators	2B120
of space launch and flight.....	4A102
software for.....	ML21.b.2
simultaneous initiation arrangements and systems	
see detonation equipment	
Sin nombre virus.....	1C351.a.33
single crystal casting equipment.....	9B001, 9D004
single mode optical fibre and cable	
see optical fibre, equipment and accessories	
single point diamond cutting tool inserts	
see machine tool equipment, components and assemblies	
single-convolution bellows	2B228
SIT vidicon tubes	
see silicon intensifier target videcon tubes	
skimming acoustic wave equipment.....	3A001.c.1
skirts for surface effect vessels	8A002

slapper detonators	1A007.b.3
slurry deposition equipment.....	2E003
slurry propellant control systems.....	9A106
slush hydrogen storage and transfer systems.....	9A006
small arms	
see firearms and firearm components	
small waterplane area vessels	8A001
smart card systems	5A002
smoke projectors and generators	ML2, ML4
smooth-bore weapons	
see also firearms and firearm components	
.....	ML1, ML2, ML901
sodium and sodium compounds	1C350
sodium lasers	
see laser beam systems	
software	0D, 1D, 2D001, 2D101, 2D201, 2D202, ML21
aerospace design and testing software.....	9D
air navigation software	7D003
air traffic control software	6D003.d.1
C3I software	ML21.b.4
clearance control software	9D004
composite material manufacturing software.....	1D002
design software	6D003.d.2, 7D003, 8D002
diver detection software	6D003.a.5, 6D003.f
expert systems software.....	2E003, 7D003, 7E004.b.6
filament winding equipment software	1B001, 1B201
flight control software	7D003.d.1
flow modelling software.....	9D004
for computer development and use.....	4D001
for determining biochemical effects	ML21.b.3
for electromagnetic equipment	2D002
for electronics development	4D001
for fault tolerant equipment	7D003.d.4, 9D003
for marine vessels	8D001
gas turbine design software	9D004
gravity gradiometer software.....	6A007, 6A107, 6D003
integrated circuit manufacturing software	3D001, 3D004, 3D101
Kalman filtering software.....	7D102
machine tool software.....	2D002
military software.....	ML21.b.1
missile software.....	6D103
navigation software	7D, 7D002, 7D003.b.2, 7D102
operating system software	4D003
optical switching software	5B001.b.3, 5E001.c.3
security-related	5D002
sensor and detector software	6D
signature reduction software.....	1D101
simulator software	ML21.b.2

sounding rocket software.....	9D103, 9D105
space launch software.....	9D103, 9D105
space-qualified equipment software.....	7D103
technological development software.....	3E101
technology for the development of.....	1E102, 1E203, 2E003, 3E101, 3E102
towed hydrophone software.....	6D003, 6D003.a.1, 6D003.a.2
unmanned airborne vehicle software.....	9D004
vapour deposition systems software.....	2B005.c.2
weapons systems software.....	ML21.b.1
solar cells and arrays	3A001.e.4
solenoids	3A001.e.3, 3A201
solid propellant rocket engines	
see rocket propulsion systems	
solid roller bearings	
see bearings	
solid state amplifiers	
see microwave equipment and components	
solid state cameras	
see camera systems, camera equipment, and camera components	
solid state detectors	6A002.c.3
solid state imaging equipment	
see image processing and enhancement equipment	
solid state joining equipment, tools, dies and fixtures	
see machine tool equipment, components and assemblies	
solid state lasers	
see laser beam systems	
solid state switching equipment	
see switching equipment	
solidification systems for UF₆ isotope separation equipment	0B002
solidtrons	3A001
soman	ML7.b.1
sonar navigation systems	6A001.a, 7A008
sonar signal processing equipment	
see signal processing equipment	
SORGUYL	
see TNGU	
sounding rockets	
see also rockets, rocket equipment and components	
.....	9A104
pyrolised components.....	1A102
software for.....	9D103, 9D105
source code	
see software	
South American haemorrhagic fever	1C351.a.30
space launch equipment	
see launch and launch support equipment	
spacecraft	
see also launch and launch support equipment	

see also rockets, rocket equipment and components	
see also space-qualified equipment	
.....	9A004
computer systems for.....	4A101
pyrolised components.....	1A102, 1C102
radar systems and components.....	6A108
reentry vehicles.....	9A116
solar cells and arrays for.....	3A001.e.4
vacuum tube components.....	3A001.b.1
space-qualified equipment	9A010
altimeters.....	7A106
cryocoolers.....	6A002.d.1
flight control systems.....	7A116
focal plane arrays.....	6A002
global navigation satellite systems.....	7A105
imaging sensors.....	6A002.b.2
negative hydrogen ion beams.....	ML19
optical control equipment.....	6A004.d.2
optical system components.....	6A002.a.1, 6A004
radar systems and components.....	6A008
software for.....	7D103
spectrum analysers	
see signal processing equipment	
spectrum frequency stabilisers	0B001.h.6
spherical aluminium powder	
see aluminium, aluminium compounds and aluminium alloys	
spindle assemblies	
see machine tool equipment, components and assemblies	
spin-forming machines	2B009, 2B109, 2B209
splat quenching, alloys made by	1C002.c.2, 1C002.d.3
spray booms	9A350
spray cooling thermal management systems	3A003
spraying systems for aircraft	9A350
spread spectrum equipment	5A001.b.3, 5A002.a.5, 5E001.b.4
sprytron vacuum tubes	3A228
sputter deposition equipment	2B005, 2E003
SQUID technology	6A006.a.1
SR 12	
see ADN	
SRAMS	
see static random-access memories	
St Louis encephalitis virus	1C351.a.28
stabilisers (chemical)	
see explosives and explosive devices	
stabilisers for marine vessels	8A002
stage pumps for conversion towers	0B004.b.4
staging mechanisms for rockets	
see rockets, rocket equipment and components	

Staphylococcus aureus toxins	1C351.d.7
star trackers	
see gyro-astro compasses	
start gyros and gyro components	
see gyros, gyro components and gyro equipment	
static random-access memories	
see also computers, computer assemblies and computer components	
.....	3A001.a.2
stators, ring shaped	
see engines and engine components	
stealth technology	
see damping equipment (electromagnetic)	
see surface coating and processing materials and equipment	
steam sterilisable freeze drying equipment	2B352
steels	
coating technology.....	2E003
maraging steels	1C116, 1C216
titanium-stabilised duplex stainless steel.....	1C118
step and flash imprint lithography tools.....	3B001.f.2
still cameras	
see camera systems, camera equipment, and camera components	
Stirling cycle engines	
see also engines and engine components	
.....	8A002.j.4
storage tanks for chemicals	
see chemical storage tanks and containers	
strap down/gimbal gyros and gyro components	
see gyros, gyro components and gyro equipment	
streak cameras	
see also camera systems, camera equipment, and camera components	
.....	6A003.a.3, 6A203.a
striplines, low inductance.....	3A235
stroboscopic light systems, for underwater use	8A002.g.1
styphnic acid	
see 2,4,6-trinitroresorcinol	
subcavitating hydrofoils	
see hydrofoil vessels	
submarine nets	
see also underwater operations equipment	
.....	ML9
submarines	
see submersible vessels, equipment and components	
submersible vessels, equipment and components	
see also marine vessels, equipment and components	
see also propellers and propfans	
see also underwater operations equipment	
.....	8A001, 8A002
pressure vessels	8A002.a.1

propulsion systems and components for	ML9
umbilical cables	8A002.a.3
unmanned	8A001
submunitions	ML3
substrate materials for integrated circuits	3C001, 3C002, 3C005, 3C006, 3E003
sulphur compounds (CAS 10545-99-0, CAS 10545-99-0)	
sulphur dichloride	1C350
sulphur monochloride	1C350
sulphur mustards	ML7.b.2
super high-powered laser system components	6A005, 6E003
superalloys	2E003
supercavitating hydrofoils	
see hydrofoil vessels and components	
supercavitating propellers	
see also propellers and propfans	
.....	8A002.o.1
superconductive materials and equipment	ML20
in electromagnets and solenoids	3A001.e.3
in electronic components	3A001
propulsion engines	8A002.o.2
solenoidal electromagnets	3A201
SQUID technology	6A006.a.1
superconductive composite conductors	1C005
technology for the production of	3E003
superfine iron oxide	ML8.f.19
superlattice equipment technology	3E003
superplastic forming technology	1B003, 2E003
supersonic expansion nozzles	0B001.h.1
super-ventilated propellers	
see propellers and propfans	
surface acoustic wave equipment	
see acoustic systems, equipment and components	
surface coating and processing materials and equipment	
see also signature reduction equipment and materials	
.....	1B101, 2B005
coatings for signature reduction	1C101
for composite materials	1B101
for inorganic overlays	2B005
McrAlX coating technology	2E003
optical surface coating and treatment technology	6E003.a.1
surface irregularity measuring equipment	2B006
surface vessels and components	
see marine vessels, equipment and components	
surface-effect vehicles	
see also marine vessels, equipment and components	
.....	8A001, 8A002
surveillance systems	
see information security systems	

see sensors and detectors	
see telecommunications systems, equipment, components and accessories	
sweeping equipment	
see explosives and explosive devices	
see sensors and detectors	
swimming apparatus	
see breathing equipment	
see underwater operations equipment	
swine fever virus	1C352.a.7
swine vesicular disease virus	
see Porcine enterovirus type 9	
switching equipment	3A001, 3A228, 5B001
symmetric algorithm encryption equipment	5A002.a.1
symmetrical dimethyl hydrazine (CAS 540-73-8)	ML8.c.4
syntactic foam, for underwater use	8C001
synthetic crystalline laser host material	6C005
synthetic silahydrocarbon oils	1C006.a.1
systolic array computers	4A004
>>=====<<	
>>T<<	
T-2 toxin	1C351.d.15
T4	
see RDX and derivatives	
tabun (CAS 77-81-6)	ML7.b.1
TACOT (CAS 25243-36-1)	ML8.a.32
TAGN (CAS 4000-16-2)	ML8.a.22
TAIW	ML8.g.4
tangential inlet flow-driven cylindrical and conical tubes	
see vortex tubes	
tank destroyers	
see land vehicles and components	
tank transporters	
see land vehicles and components	
tanks (vehicles) and related equipment/components	
see also land vehicles and components	
.....	ML6
tanks for chemical storage	
see chemical storage tanks and containers	
tantalum and tantalum compounds	
chemical handling equipment made with	2B350
crucibles coated with	2A225
tape-laying machines	1B001
target acquisition systems	ML12, ML19, ML5
target damage assessment	
see damage assessment systems	
TAT (CAS 41378-98-7)	ML8.g.5
TATB (CAS 3058-38-6)	ML8.a.23
TCSEC capability	

see trusted computer system evaluation criteria capability	
TEA	
see triethylaluminium	
tear gases and related equipment and materials	
see chemical warfare agents and precursors	
see riot control agents	
technical military databases libraries, parametric	
see parametric technical databases (libraries)	
technology	1E, 2E001, 2E002
for aerospace design and testing.....	9E
for computer development and use.....	4E001
for development, production and use of controlled items	0E, ML22
for flight control	7E004.b.5
for integrated circuit manufacture	3E001, 3E002
for marine vessels	8E
for metal-working processes.....	2E003
for navigation systems, equipment and components	7E001, 7E101
for numerical control units	2E003
for pressure regulation	1E103
for security-related equipment and systems	5E002
for sensors and detectors	6E
for software development and use.....	3E101
for telecommunications systems.....	5E001
TEDDZ	ML8.a.24
TEGDN	
see triethylene glycol dinitrate	
telecommunications systems, equipment, components and accessories	
see also radio equipment and components	
.....	5A001
telemetering and telecontrol equipment	
see also sensors and detectors	
.....	5A101
television systems and equipment	
see also video cameras	
.....	5A002, 8A002.d.1
tellurium, in optical sensors	6C002
temperature-rated equipment	
computer systems	4A001.a.1
radar systems	6A102
robot systems.....	ML17
telecommunications systems	5A001.a.3
TEMPEST type equipment	
see information security systems	
see surveillance systems	
tension stretchers for composite materials	
see also optical fibre, equipment and accessories	
.....	1B101
TPB (triphenyl bismuth) (CAS 603-33-8)	ML8.f.22

TEPB (Tris (ethoxyphenyl) bismuth) (CAS 90591-48-3)	ML8.f.23
TEPAN (CAS 68412-45-3)	ML8.f.20
TEPANOL (CAS 68412-46-4)	ML8.f.21
TE-PVD	
see thermal-evaporation physical vapour deposition technology	
terephthalic acid	1C008.b.2
terrain contour mapping equipment	6A108
tertiary-butyl substituted phenylene	1C008.b.1
teschen disease virus	1C352.a.14
test tape for recording equipment	3A002
test, inspection and production equipment	
for aerospace and propulsion systems	9B
for composite materials	1B001
for controlled products	ML18
for directed energy weapons.....	ML19
for marine vessels and equipment	8B
for materials processing.....	2B
for navigation and avionics systems	7B
for security-related equipment and systems	5B002
for semiconductor production.....	3B002
for sensors and lasers.....	6B
for telecommunications and security systems	5B1
test benches and stands	9B117
tetraacetyldibenzylhexaazaisowurtzitane	
see TAIW	
tetraethylenepentaamineacrylonitrile	
see TEPAN	
tetraethylenepentaamineacrylonitrileglycidol	
see TEPANOL	
tetramethylhydrazine	1C111.a.4
tetranitrobenzotriazolobenzotriazole	
see TACOT	
tetranitroglycoluril	
see TNGU	
tetranitronaphthalene	ML8
tetranitrosemiglycouril	
see K-55	
tetrazoles	ML8.a.25
tetrodotoxin	1C351.d.8
tetryl (CAS 479-45-8)	ML8.a.26
TEX (4,10-Dinitro-2,6,8,12-tetraoxa-4,10-diazaisowurtzitane)	ML8.a.36
thallium arsenic selenide	6C004.b.3
thermal batteries	3A102
thermal evaporation physical vapour deposition technology	2E003
thermal imaging equipment	
see infrared imaging equipment	
thermal ionisation mass spectrometers	3A233
thermal sensors	

see infrared sensors and detectors	
thermal-rated equipment	
see temperature-rated equipment	
thermoplastic liquid crystal copolymers	1C008
thermoset resin impregnated continuous materials	1C210
thickeners	
see fuels and propellants and related equipment	
thiodiglycol (CAS 111-48-8)	1C350
thionyl chloride (CAS 7719-09-7)	1C350
thiophosphoryl chloride (CAS 3982-91-0)	1C350
Thorium 227 and 228	
see radionuclides	
three axis magnetic heading sensors	7A103
through-the-wall manipulators	2B225
thrust chambers for rocket propulsion systems	9A006
thrust vector control sub-systems	9A106, 9A108
thulium--YAG lasers	6A005
thulium--YSGG lasers	6A005
thyristors	3A001
tick-borne encephalitis virus	1C351.a.14
tilt rotor and tilt wing aircraft	
see also aircraft and aircraft components	
.....	9E003
tilting spindles	2B008
TIMS	
see thermal ionisation mass spectrometers	
tip shroud castings	9B001, 9E003.a.4, 9E003.a.5
tip-tilt mirrors	
see beam steering mirrors	
titanium, titanium alloys and titanium compounds	1C002.b.3, 1C002.c.1, 1C202
borides of titanium.....	1C007, 1C007, 1C007, 1C007
chemical handling equipment made with	2B350
coating technology for	2E003
diffusion bonding technology for	2E003.b.2
superplastic technology	1B003, 2E003.b.2
titanium aluminides	1C002.a.2
titanium subhydride	ML8.c.9
titanium tetrachloride (titanium IV) compounds	ML8.f.15
titanium-doped sapphire	6C005
titanium--sapphire lasers	6A005
titanium-stabilised duplex stainless steel	1C118
with uranium.....	1C004
TMA	
see trimethylaluminium	
TMETN	
see trimethylolethane trinitrate	
TMP	
see trimethyl phosphite	

TNAD (CAS 135877-16-6)	ML8.a.27
TNAZ (CAS 97645-24-4)	ML8.a.28
TNGU (CAS 55510-03-7)	ML8.a.29
TNP (CAS 229176-04-9)	ML8.a.30
TNT	
see 2,4,6-trinitrotoluene	
tools	
see machine tool equipment, components and assemblies	
torpedoes, components and equipment	
see also explosives and explosive devices	
see also underwater operations equipment	
.....	ML4
torpedo nets	ML9
towed acoustic hydrophone arrays	
see hydrophones	
tow-placement machines	1B001
toxicological agents	
see also biological warfare agents	
see also chemical warfare agents and precursors	
see also protective and decontamination clothing and equipment	
.....	1C351, 1C450, ML7
monitoring systems for	2B351
precursor materials	1C350
riot control agents	ML7
TPB (CAS 603-33-8)	ML8.f.22
TPEG	
see polytetrahydrofuran polyethylene glycol	
tracking systems	
see also navigation systems, equipment and components	
see also radar systems and components	
automatic	6A008
for directed energy weapons	ML19
for kinetic energy weapons	ML12
for missiles	6A108
trailers	
see also land vehicles and components	
.....	ML6
training equipment	ML14
trajectory technology	
see rocket propulsion systems	
transceivers	
see radio equipment and components	
transducers	
see also sensors and detectors	
.....	6A001.a.1, 9B008
transfer lasers	6A005.d.5
transient recorders	
see waveform digitisers	

transistors for microwave equipment	3A001.b.3
transmitters	
see radio equipment and components	
transposons	
see genetic elements	
travelling wave tubes	3A001.b.1
tray exchange towers	
see isotope separation plants, systems, equipment and components	
triaminoguanidinenitrate	
see TAGN	
triaminotrinitrobenzene	
see TATB	
triazines	ML8.a.31
triazoles	ML8.a.32
trichloronitromethane	1C450.a.7
triethanolamine (CAS 102-71-6)	1C350
triethanolamine hydrochloride (CAS 637-39-8)	1C350
triethyl phosphite (CAS 122-52-1)	1C350
triethylaluminium	ML8
triethylene glycol dinitrate (CAS 111-22-8)	1C111.c.2, ML8
triggered spark-gaps	3A228
triisopropyl phosphite (CAS 116-17-6)	1C350
trimethyl phosphite (CAS 121-45-9)	1C350
trimethylaluminium	ML8
trimethylhydrazine	1C111.a.4
trimethylolethane trinitrate	1C111.c.4
trinitroanisol	ML8
trinitroglycerine	ML8
trinitronaphthalene	ML8
trinitrophenylmethylnitramine	
see tetryl	
trinitroxylene	ML8
triol	ML8.e.13
triphenyl bismuth	
see TPB	
tris (2-chloroethyl) amine (CAS 555-77-1)	ML7.b.2, ML7.c.3
tris vinox propane adduct	
see TVOPA	
tris-1-(2-methyl)aziridinyl phosphine oxide	
see MAPO and derivatives	
tritium	1B231, 1C235
True North determination equipment	7A003, 7A003.c.1
trusted computer system evaluation criteria capability	
see computers, computer assemblies and computer components	
tumblers	ML18
tunable band-pass filters	3A001.b.5
tunable lasers	
see also laser beam systems	

.....	6A005, 6A205
tungsten, tungsten alloys and tungsten compounds	
coating technology.....	2E003
spherical particles of.....	1C117
tungsten carbide.....	1C226
tungsten in solid form.....	1C117
with uranium.....	1C004
turbine engines	
see gas turbine engines	
turbocharger systems technology.....	9E003.f.2
turboexpanders and turboexpander compressors.....	1B232
turbofan, turbojet and turboprop engines	
see also aero-engines and components	
.....	9A101, 9A102
turning machines	2B001
TV cameras	
see video cameras	
TVOPA (CAS 53159-39-0).....	ML8.e.18
two dimensional focal plane arrays	
see focal plane arrays	
tyres, bullet-proof	ML6
>>=====<<	
>>U<<	
UAVs	
see unmanned airborne vehicles, systems and components	
UF₆	
see uranium metal, uranium alloys, and uranium compounds	
ultrasonic testing machines, for defect inspection	1B001.f.2
ultra-wideband modulation equipment.....	5A001.b.4
umbilical cables for rockets	9A121
umbilical cables for submersible vessels.....	8A002.a.3
UN class 1.1 solid propellants	ML8.b.1
UN class 1.3 solid propellants	ML8.b.2
underwater operations equipment	
see also acoustic systems, equipment and components	
see also submersible vessels, equipment and components	
.....	8A002.j.1
acoustic location systems	6A001.a.1
air independent power systems.....	8A002, ML9.b.4
bathymetric survey systems.....	6A001.a.1
countermeasure equipment.....	ML11
detection equipment.....	ML9
electric field sensors	6A006
electromagnetic receivers	6A006.e
laser beam systems	5A001.b.1
navigation systems.....	6A001.a.1, 7A008
optical fibre equipment.....	5A001.c.2
self-contained diving apparatus.....	8A002, ML17

signal processing equipment.....	6A001.a.2
syntactic foam.....	8C001
untethered communications systems	5A001.b.1
underwater vessels	
see submersible vessels, equipment and components	
unmanned airborne vehicles, systems and components	
see also aircraft and aircraft components	
.....	9A012, ML10
autonomous programmable	ML10.c.1
combustion regulation equipment	9A118
flight control systems	7E004.b.4, 7E004.b.5
production facilities	9B010
pulse jet engines for.....	9A111
remotely piloted air vehicles	ML10.c.1
software for.....	9D004
turboprop engines for	9A102
unmanned launchers	
see launch and launch support equipment	
unmanned submersible vehicles	8A001
unprocessed fluorinated compounds	1C009
unsymmetrical dimethyl hydrazine (CAS 57-14-7)	ML8.c.4
unsymmetrical dimethylhydrazine nitrate	1C111.a.4
unsymmetrical diphenylurea	
see N,N-diphenylurea	
Uranium 230 and 232	
see radionuclides	
uranium metal, uranium alloys, and uranium compounds	1C004
conversion plant and equipment	0B003
isotope separation equipment	0B001
>>=====<<	
>>V<<	
vacuum atomisation, alloys made by	1C002.c.2
vacuum furnaces	
see furnaces	
vacuum headers	0B002
vacuum housings.....	0B001.j.3
vacuum manifolds.....	0B002
vacuum microelectronic equipment	
see microprocessor, microcontroller and microcomputer microcircuits	
vacuum pumps.....	0B002, 2B231
vacuum tubes and valves (electronic)	3A001.b.1, 3A228, 3E003
valves (electronic)	
see vacuum tubes and valves (electronic)	
valves (mechanical).....	2A226
bellows seal valves	2A226
containing aluminium.....	2A226
for handling chemicals	2B350
servo valves	7A116, 9A106

with fluoroelastomers	1A001
vanes for gas turbine engines	
see also gas turbine engines	
.....	9B001, 9E003.a.4, 9E003.a.5
vapour deposition equipment	1B101.c.2
Variola virus	1C351.a.15
vector processors and assemblies	3E002, 4A003
vectors (genetic)	
see genetic elements	
vehicles	
see aircraft and aircraft components	
see land vehicles and components	
see marine vessels, equipment and components	
see spacecraft	
see submersible vessels, equipment and components	
velocity interferometers	6A225
Venezuelan equine encephalitis virus	1C351.a.37
ventilated full and half (protective clothing) suits	
see protective and decontamination clothing and equipment	
ventilated propellers	
see propellers and propfans	
verotoxin producing E. coli (VTEC)	
see Shiga toxin producing Escherichia coli (STEC)	
verotoxin producing strains	1C353
verotoxin ribosome inactivating proteins	1C351.d.9
vesicant agents	ML7.b.2
vesicular stomatitis virus	1C352.a.15
vessels of war	
see marine vessels, equipment and components	
see submersible vessels, equipment and components	
vibration test systems, equipment and components	2B116, 9B006
Vibrio cholerae	1C351.c.15
videcon tubes	6A203.b.4
video cameras	
see also camera systems, camera equipment, and camera components	
.....	6A203
for underwater use	8A002.d.1
with solid state sensors	6A003.b.1
vinylidene fluoride materials	1A001, 1C009
virus cultures	
see also animal pathogens	
see also human pathogens	
see also plant pathogens	
.....	1C351, ML7.i.2
VISARS	
see velocity interferometers	
viscum album lectin 1	1C351.d.19
vision systems	

see image processing and enhancement equipment	
volkensin	1C351.d.18
vortex tubes	
see isotope separation plants, systems, equipment and components	
VX	ML7.b.1
>>=====<<	
>>W<<	
wafers and wafer handling equipment	
see semiconductor manufacturing equipment	
warships	
see marine vessels, equipment and components	
water jet cutting machines	
see machine tool equipment, components and assemblies	
water tunnels	8B001
water-hydrogen sulphide exchange plants	0B004.a.1, 0B004.b.1, 1B229
water-screw propeller systems	
see propellers and propfans	
waveform digitisers	3A002.a.5
wavelength division multiplexing technology	
see coherent optical transmission and detection equipment	
wax pattern preparation equipment	
see ceramic materials	
weapon sights	
see sights and sighting equipment	
weapons	
see ammunition and components	
see firearms and firearm components	
see missiles	
see smooth-bore weapons	
.....	0
weapons control systems	ML21.b.1, ML5
weaving machines, multidimensional	1B001
western equine encephalitis virus	1C351.a.17
wet-spinning equipment	
see ceramic materials	
white pox	1C351.a.18
wide-swath bathymetric survey systems	
see bathymetric survey systems	
wind tunnels	9B005, 9B105, 9E003.b.1
windows for nuclear radiation shielding	
see radiation hardened equipment	
work stations	
see computers, computer assemblies and computer components	
>>=====<<	
>>X<<	
Xanthomonas spp.	1C354.b.1
xenon flash-lamp drivers	3A229
X-ray equipment	

see radiographic equipment	
xylyl bromide	ML7
>>=====<<	
>>Y<<	
yellow fever virus	1C351.a.39
Yersinia pestis	1C351.c.16
yttrium oxide, crucibles coated with	2A225.a.2
>>=====<<	
>>Z<<	
zinc and zinc compounds	
zinc selenide	6A004, 6C004
zinc sulphide	6A004, 6C004
Zinc germanium phosphide	6C004.b.4
zirconium and zirconium compounds	1C234
as propellants	1C111.a.2.a
chemical handling equipment made with	2B350
in particle form	1C011
in powder fuel	ML8.c.5
zirconium dioxide (zirconia)	2E003
zirconium fluoride	6C004
zirconium oxides	1E.c.1, 2A225.a.2
zirconium tubes for nuclear reactors	0A001
zoonoses	
see also animal pathogens	
.....	1C351

Endnotes

Endnote 1—About the endnotes

The endnotes provide information about this compilation and the compiled law.

The following endnotes are included in every compilation:

Endnote 1—About the endnotes

Endnote 2—Abbreviation key

Endnote 3—Legislation history

Endnote 4—Amendment history

Endnotes about misdescribed amendments and other matters are included in a compilation only as necessary.

Abbreviation key—Endnote 2

The abbreviation key sets out abbreviations that may be used in the endnotes.

Legislation history and amendment history—Endnotes 3 and 4

Amending laws are annotated in the legislation history and amendment history.

The legislation history in endnote 3 provides information about each law that has amended (or will amend) the compiled law. The information includes commencement details for amending laws and details of any application, saving or transitional provisions that are not included in this compilation.

The amendment history in endnote 4 provides information about amendments at the provision (generally section or equivalent) level. It also includes information about any provision of the compiled law that has been repealed in accordance with a provision of the law.

Misdescribed amendments

A misdescribed amendment is an amendment that does not accurately describe the amendment to be made. If, despite the misdescription, the amendment can be given effect as intended, the amendment is incorporated into the compiled law and the abbreviation “(md)” added to the details of the amendment included in the amendment history.

If a misdescribed amendment cannot be given effect as intended, the amendment is set out in the endnotes.

Endnotes

Endnote 2—Abbreviation key

Endnote 2—Abbreviation key

A = Act	orig = original
ad = added or inserted	par = paragraph(s)/subparagraph(s) /sub-subparagraph(s)
am = amended	pres = present
amdt = amendment	prev = previous
c = clause(s)	(prev...) = previously
C[x] = Compilation No. x	Pt = Part(s)
Ch = Chapter(s)	r = regulation(s)/rule(s)
def = definition(s)	Reg = Regulation/Regulations
Dict = Dictionary	reloc = relocated
disallowed = disallowed by Parliament	renum = renumbered
Div = Division(s)	rep = repealed
exp = expires/expired or ceases/ceased to have effect	rs = repealed and substituted
F = Federal Register of Legislative Instruments	s = section(s)/subsection(s)
gaz = gazette	Sch = Schedule(s)
LI = Legislative Instrument	Sdiv = Subdivision(s)
LIA = <i>Legislative Instruments Act 2003</i>	SLI = Select Legislative Instrument
(md) = misdescribed amendment	SR = Statutory Rules
mod = modified/modification	Sub-Ch = Sub-Chapter(s)
No. = Number(s)	SubPt = Subpart(s)
o = order(s)	<u>underlining</u> = whole or part not commenced or to be commenced
Ord = Ordinance	

Endnote 3—Legislation history

Endnote 3—Legislation history

Name	FRLI registration	Commencement	Application, saving and transitional provisions
Defence and Strategic Goods List - November 1996	2 Dec 2008 (F2008B00287)	1 Nov 1996	
Defence and Strategic Goods List Amendment 2006	16 Oct 2006 (F2006L03230)	17 Oct 2006 (s 2)	
Defence and Strategic Goods List Amendment 2007	20 Nov 2007 (F2007L04380)	21 Nov 2007 (s 2)	
Defence and Strategic Goods List Amendment 2010	3 May 2010 (F2010L01084)	4 May 2010 (s 2)	
Defence and Strategic Goods List Amendment 2011 (No. 1)	13 Oct 2011 (F2011L02061)	14 Oct 2011 (s 2)	
Defence and Strategic Goods List Amendment 2012 (No. 1)	4 Dec 2012 (F2012L02318)	5 Dec 2012 (s 2)	
Defence and Strategic Goods List Amendment Instrument 2015	7 Apr 2015 (F2015L00499)	8 Apr 2015 (s 2)	

Endnotes

Endnote 4—Amendment history

Endnote 4—Amendment history

Provision affected	How affected
Defence and Strategic Goods List	rs F2006L03230; F2007L04380; F2010L01084; F2011L02061; F2015L00499
Part 1	
ML2.c	rs 2012 No 1
ML4.b	rs 2012 No 1
ML6.b	rs 2012 No 1
ML7.b.1	rs 2012 No 1
ML7.g	am 2012 No 1
ML7.i	rs 2012 No 1
ML8	am 2012 No 1
ML10	rs 2012 No 1
ML13	rs 2012 No 1
ML15	am 2012 No 1
ML16	rs 2012 No 1
ML19	rs 2012 No 1
Part 2	
Category 1	
1A001	rs 2012 No 1
1A002	am 2012 No 1
1A004	am 2012 No 1
1B001.c	am 2012 No 1
1B001.g	ad 2012 No 1
1C001.a	am 2012 No 1
1C002.b	rs 2012 No 1
1C006.c	rs 2012 No 1
1C008	am 2012 No 1
1C008.a.2	rs 2012 No 1
1C008.b.1	rs 2012 No 1
1C008.b.2	rs 2012 No 1
1C008.b	rs 2012 No 1
1C010.b	rs 2012 No 1
1C010.e	rs 2012 No 1
1C011.b	rs 2012 No 1
1C011.d	am 2012 No 1
1C111.a.4.h	rs 2012 No 1
1C111.a.4.n	rs 2012 No 1
1C111.a.5	ad 2012 No 1
1C111.c.6.h	rs 2012 No 1
1C111.c.6.l	rs 2012 No 1
1C111.c.6.o	rs 2012 No 1
1C117	rs 2012 No 1
1C230	rs 2012 No 1
1C351.a	rs 2012 No 1

Endnote 4—Amendment history

Provision affected	How affected
Category 2	
2A001.....	rs 2012 No 1
2A101.....	ad 2012 No 1
2B	am 2012 No 1
2B005.d.2.....	am 2012 No 1
2B005.g.....	am 2012 No 1
2B006.a.....	rs 2012 No 1
2B201.a.....	rs 2012 No 1
2B201.a.1.....	rs 2012 No 1
2B206.....	rs 2012 No 1
2B350.j.....	rs 2012 No 1
2B351.....	rs 2012 No 1
2B006.a.....	rs 2012 No 1
2E003.f.....	rs 2012 No 1
Category 3	
3A001.a.4.....	rep 2012 No 1
3A001.a.5.a.....	rs 2012 No 1
3A001.a.5.b.....	rs 2012 No 1
3A001.b.2.....	rs 2012 No 1
3A001.b.3.....	rs 2012 No 1
3A001.b.4.....	rs 2012 No 1
3A001.b.11.....	ad 2012 No 1
3A002.b.....	rep 2012 No 1
3A002.c.....	rs 2012 No 1
3A002.d.4.....	rs 2012 No 1
3A228.c.....	rs 2012 No 1
3B001.d.....	rs 2012 No 1
3B001.e.....	rs 2012 No 1
3B001.f.....	rs 2012 No 1
3E001.....	rs 2012 No 1
Category 4	
4A001.....	rs 2012 No 1
4A003.a.....	rs 2012 No 1
4A003.b.....	rs 2012 No 1
4D001	rs 2012 No 1
4D002	rs 2012 No 1
4D003	rs 2012 No 1
4E001.....	rs 2012 No 1
Category 5	
Part 1	
	am 2012 No 1
5A001.c.....	rs 2012 No 1
5A001.h.....	rs 2012 No 1
5B001.b.1.....	rep 2012 No 1
5B001.b.3.....	rep 2012 No 1
5D001.d.1	rep 2012 No 1
5D001.d.3	rep 2012 No 1

Endnotes

Endnote 4—Amendment history

Provision affected	How affected
5E001.c.....	rs 2012 No 1
5E001.c.1.....	rs 2012 No 1
5E001.c.3.....	rs 2012 No 1
5E001.d.....	rs 2012 No 1
Part 2	am 2012 No 1
5A002.a.9.....	am 2012 No 1
5A002.a.9.b.....	ad 2012 No 1
5A002.b.....	ad 2012 No 1
5D002	rs 2012 No 1
5E002.....	rs 2012 No 1
Category 6	
6A001.....	rs 2012 No 1
6A002.b.....	rs 2012 No 1
6A002.c.....	rs 2012 No 1
6A002.d.....	rs 2012 No 1
6A002.e.....	rs 2012 No 1
6A003.....	am 2012 No 1
6A003.b.2.....	rs 2012 No 1
6A003.b.4.....	am 2012 No 1
6A005.c.1.....	rs 2012 No 1
6A005.d.....	rs 2012 No 1
6A005.e.....	rs 2012 No 1
6A005.g.....	ad 2012 No 1
6A006.e.....	ad 2012 No 1
6A008.....	am 2012 No 1
6A008.f.....	am 2012 No. 1
6A008.l.....	am 2012 No 1
6D003	rs 2012 No 1
6E003.a.....	rs 2012 No 1
Category 7	
7A001.a.3.....	am 2012 No 1
7A002.....	rs 2012 No 1
7A003.d.....	rs 2012 No 1
7A005.....	rs 2012 No 1
7B001.....	rs 2012 No 1
7E004.a.4.....	rs 2012 No 1
7E004.b.6.....	rs 2012 No 1
Category 8	
8A002.f.....	rs 2012 No 1
8A002.i.....	rs 2012 No 1
8A002.o.3.....	rs 2012 No 1
8A002.p.....	rs 2012 No 1
8A002.q.....	rs 2012 No 1
8A002.r	ad 2012 No 1
Category 9	
9A001.a.....	rs 2012 No 1
9A003.....	rs 2012 No 1

Endnote 4—Amendment history

Provision affected	How affected
9A109.....	rs 2012 No 1
9B002.....	rs 2012 No 1
9B116.....	rs 2012 No 1
9D003	rs 2012 No 1
9E003.a.8.....	rs 2012 No 1
9E003.a.9.....	rs 2012 No 1
9E003.a.10.....	rs 2012 No 1
9E003.h.....	ad 2012 No 1
9E003.i.....	ad 2012 No 1
9E102.....	rs 2012 No 1
Sensitive List of Dual-Use Goods and Technologies	
Category 1	
1A007.....	rep 2012 No 1
Category 5	
5A001.h.....	ad 2012 No 1
Category 6	
6A001.a.1.b.....	rs 2012 No 1
6°001.a.2.a.1.....	
Renumbered	2012 No 1
6A001.a.2.a.1	
6°001.a.2.a.2.....	
Renumbered	2012 No 1
6A001.a.2.a.2	
6°001.a.2.a.3.....	
Renumbered	2012 No 1
6A001.a.2.a.3	
6°001.a.2.a.5.....	
Renumbered	2012 No 1
6A001.a.2.a.5	
6A003.b.4.....	rs 2012 No 1
6A006.e.....	ad 2012 No 1
Category 9	
9A004.....	rep 2012 No 1
9A005.....	rep 2012 No 1
9A007.a.....	rep 2012 No 1
9A008.d.....	rep 2012 No 1
Very Sensitive List of Dual-Use Goods and Technologies	
Category 5	
5A001.h.....	rs 2012 No 1
Index	
Index.....	am 2012 No 1